

fixLOCK Self-Tapping Screw, 2.4 mm

Thread dia.	2.4 mm
Head dia.	3.5 mm
Core dia.	1.7 mm
Lengths	6.0 – 40.0 mm
Drill bit used	2.0 mm

(Item Code: 770)



fixLOCK Self-Tapping Screw, 2.7 mm

(Item Code: 771)



Thread dia.	2.7 mm
Head dia.	3.5 mm
Core dia.	2.0 mm
Lengths	6.0 – 50.0 mm
Drill bit used	2.0 mm

fixLOCK Self-Tapping Screw, 3.5 mm

(Item Code: 765)

Thread dia.	3.5 mm
Head dia.	5.0 mm
Core dia.	2.8 mm
Lengths	10 – 80 mm
Drill bit used	2.8 mm



fixLOCK Cancellous Screw,
3.5 mm- Fully Threaded

(Item Code: 769)



Thread dia.	3.5 mm
Head dia.	6.0 mm
Core dia.	1.8 mm
Lengths	25 – 60 mm
Drill bit used	2.8 mm

All the screws are available in stainless steel & titanium.
For Titanium, please affix 'T' after code number.



GOS1439S	fixLOCK Instrument Set - Small	
BTD1130.25.180	Drill Bit 2.5, Length 180 mm	1
BTD1130.27.100	Drill Bit 2.7, Length 100 mm	1
BTD1130.35.200	Drill Bit 3.5, Length 200 mm	1
C-ILBS736.20	Locking Drill Bit (Q.C) 2.0 mm	2
C-ILBS736.28	Locking Drill Bit (Q.C) 2.8 mm, Length 165 mm	2
IBS700.03	Counter Sink 3.5 mm	1
C-IBS762.35	Bone Tap (Q.C) 3.5 mm	1
C-IBS762.40	Bone Tap (Q.C) Cancellous 4 mm	1
IBS765	Quick Coupling Handle	1
IBS723.20	Triple Drill Guide 2 mm	1
IBS720.25	Insert Drill Sleeve 2.5 mm	1
ILBS716.35	Locking Drill Sleeve for Locking Screw 3.5 mm	2
ILBS716.27	Locking Drill Sleeve for Locking Screw 2.7 mm	2
SH.25	Small Screw Holder	1
ILBS786.35	Torque screwdriver for small screws (3.5 mm)	1
ILBS746.25	Hexagonal screw Driver Shaft for screws 2.7 mm to 4.0 mm	1
ILBS747.25	Hexagonal screw Driver for screws 2.7 mm to 4.0 mm	1
IBS709	Depth Gauge 3.5 mm	1
REH1053	Sharp Hook	1
IBS753	Screw Holding Forceps	1
ILBS737	Universal Drill Guide 2.7 mm, for drill bit 2.0 mm & 2.7 mm	1
ILBS737	Universal Drill Guide 3.5 mm, for drill bit 2.5 mm & 3.5 mm	
REH1064.08.160	Hohman Retractor 8 mm	1
REH1064.15.160	Hohman Retractor Broad Shank, width 15 mm, Length 160 mm	1
REH1068.06S	Periosteal Elevator with Fibre Handle 6 mm	1
BHF1247.14	Reduction Forceps Serrated 140mm (R.Lock)	2
BHF1246.19	Self Centering Bone Holding Forceps, Speed Lock Length 190 mm	1
ILBS738	Push Pull Reduction Device	1
IBP630.01	Plate Bender small	1
ILBS739-S	Threaded Plate Holder Small	1
IPW952	Wire Bending Plier	1
AGC1439S	Graphic Container Aluminium	1