

TECHNICAL DATA SHEET



Type no.	625 23
Article no.	010625230100
Standards	DIN EN 50342-1, 50342-4
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	125 Ah (K20)
Cold start current	720 A (EN)
Dimensions and weights	
Box	NATO 6TN
Length max.	280mm
Width max.	267mm
Box height max.	213mm
Total height max.	230mm
Battery weight	Ca. 34,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	36
Pallet ID	Euro pallet
Items per layer	12
Features	
Base hold-down	B00
Layout	2
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Performance identification	W3-C2-V2-E1
Maintenance ¹⁾	
Water consumption	W3
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 5 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,4 V



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!