

## PRODUCT SPECIFICATION

### office paper **Tecnis Copier**

Issued 03.02.2020 (\*)

<i>Lp.</i>	<i>Parameter</i>	<i>Unit</i>	<i>Value</i>	<i>Method</i>
1.	<b>Basis weight</b> (grammage)	g/m <sup>2</sup>	80 ± 3,0	PN- EN-ISO 536
2.	<b>Moisture</b>	%	3,6 – 5,0	PN-EN- ISO 287
3.	<b>Caliper</b>	µm	104 ± 3	PN-EN ISO 534
4.	<b>CIE whiteness</b>		146± 3	PN-ISO 11475
5.	<b>Brightness D65</b>	%	105 ± 2	ISO 2470-2 :2008
6.	<b>Opacity</b>	%	92 +2/-1	ISO 2471
7	<b>Bendtsen Roughness</b>	cm <sup>3</sup> /min	220± 60	ISO 8791-2

Conditioning Rh = 50 ± 2 ; Temp = 23 ± 1 according to PN-EN 20187-2000

**Tecnis Copier** paper produced by International Paper - Kwidzyn sp. z o.o. is made from own manufactured Elementary Chlorine Free kraft pulp. Manufacturing process is carried out in neutral environment. Precipitated calcium carbonate used as a filler ensures appropriate alkaline reserve requisite to meet PN-EN ISO 9706:2001 standard „Information and documentation - Paper for documents - Requirements for permanence”.

**Tecnis Copier** paper is delivered in formats : **A4** (210 x 297 mm) and **A3** (420 x 297 mm)

(\*) Valid for one year or until further notice