

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1727240260343 din 25.09.2024

Obiectul achiziției: Achiziția de Microfoane și seturi de portavoce pentru instituțiile din subordinea Direcției Cultură a Primăriei Mun.Chisinau

| Denumirea bunurilor/serviciilor | Denumirea modelului bunului/serviciului | Țara de origine | Producătorul | Specificarea tehnică deplină solicitată de către autoritatea contractantă | Specificarea tehnică deplină propusă de către ofertant | Standarde de referință |
|--|---|-----------------|--------------|---|---|------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Allen & Heath M-SQ-WAVES3-A | M-SQ-WAVES3-A | China | Allen&Heath | 64 × 64 Channel Interface Usable with 96 kHz or 48 kHz Can be integrated via Waves Plugin Server or Waves Native Multi-channel recording / playback 2 Ports with redundant and switch modes Internal Control Network Bridge Lockable Ethercon connector Available since October 2018 Item number 449259 Sales Unit 1 piece(s) Extension Card for Allen & Heath Type Waves Sound Garantie 36 luni | 64 × 64 Channel Interface Usable with 96 kHz or 48 kHz Can be integrated via Waves Plugin Server or Waves Native Multi-channel recording / playback 2 Ports with redundant and switch modes Internal Control Network Bridge Lockable Ethercon connector Available since October 2018 Item number 449259 Sales Unit 1 piece(s) Extension Card for Allen & Heath Type Waves Sound Garantie 36 luni | |
| Allen & Heath SQ Slink | SQ-Slink | China | Allen&Heath | Audio Network Expansion Card For installation in Allen & Heath SQ mixing consoles Extends the mixer by a SLink output with a maximum of 128x128 channels and 48 / 96kHz operation Note: The built-in SLink port and the then additional SLink Option Card port are operated independently of each other and can work in 3 different modes: dSnake / ME, DX or GigaACE | Audio Network Expansion Card For installation in Allen & Heath SQ mixing consoles Extends the mixer by a SLink output with a maximum of 128x128 channels and 48 / 96kHz operation Note: The built-in SLink port and the then additional SLink Option Card port are operated independently of each other and can work in 3 different modes: dSnake / ME, DX or GigaACE | |

| | | | | | | |
|--|---------------------------|----------|------------|--|--|--|
| | | | | Available since October 2018 Sales Unit 1 piece(s) Extension Card for Allen & Heath Type SQ Garantie 36 luni | Available since October 2018 Sales Unit 1 piece(s) Extension Card for Allen & Heath Type SQ Garantie 36 luni | |
| Thon Case for Allen & Heath SQ6 | Case for A&H SQ6 | Germania | Thon | Mixer Case For Allen & Heath SQ6 Material: 7 mm plywood 30 x 30mm Aluminium edges Foam padding 4 Spring-loaded butterfly latches 4 Folding handles 4 Steel ball corners 4 Steel ball corners with integrated L-corner 15 cm Cable duct External dimensions (W x D x H): 710 x 705 x 285 mm Weight: 12.8 kg Colour: Phenol Brown Available since December 2017 Sales Unit 1 piece(s) made for Allen & Heath Type: Case Material: 7 mm Plywood Wheels: No Dockhouse: No Colour: Phenol/Alu Weight: 12,8 kg External Width: 710 mm External Depth: 705 mm External Height: 285 mm Garantie 36 luni | Mixer Case For Allen & Heath SQ6 Material: 7 mm plywood 30 x 30mm Aluminium edges Foam padding 4 Spring-loaded butterfly latches 4 Folding handles 4 Steel ball corners 4 Steel ball corners with integrated L-corner 15 cm Cable duct External dimensions (W x D x H): 710 x 705 x 285 mm Weight: 12.8 kg Colour: Phenol Brown Available since December 2017 Sales Unit 1 piece(s) made for Allen & Heath Type: Case Material: 7 mm Plywood Wheels: No Dockhouse: No Colour: Phenol/Alu Weight: 12,8 kg External Width: 710 mm External Depth: 705 mm External Height: 285 mm Garantie 36 luni | |
| Sennheiser ew IEM G4 Twin A1-Band | ew IEM G4 Twin A1-Band | Germania | Sennheiser | In Ear System Evolution Wireless Series Consisting of 2x UHF Bodypack receiver (EK IEM G4), 9.5" transmitter (SR IEM G4) and 2x IE4 earphones Frequency range A1 band: 470 - 516 MHz Stereo- / Focus- / Mono - Mode Up to 1680 frequencies in 42 MHz switching bandwidth 20 Channel banks each with up to 16 presets | In Ear System Evolution Wireless Series Consisting of 2x UHF Bodypack receiver (EK IEM G4), 9.5" transmitter (SR IEM G4) and 2x IE4 earphones Frequency range A1 band: 470 - 516 MHz Stereo- / Focus- / Mono - Mode Up to 1680 frequencies in 42 MHz switching bandwidth 20 Channel banks each with up to 16 presets | |

| | | | | | | |
|-------------------------------------|-------------------|----------|------------|---|---|--|
| | | | | <p>Up to 16 compatible channels Frequency range: 25 - 15,000 Hz Frequency transmission via infrared interface Pocket receiver with charging contacts for optional BA 2015 rechargeable battery (NiMH) (battery not included) Pilot tone Auto tune to find free frequencies Audio Gain includes 60 dB 4-Digit battery indicator on the transmitter and receiver HDX compander OLED display with NF level and channel display 3.5 mm jack for earphones Adjustable limiter Switchable transmission power 10/30/50 mW WSM support (Ethernet interface for frequency management) Adjustable 6.3 mm headphone jack on the transmitter 1 BNC antenna jack 2 x Jack/XLR female balanced combo jack inputs Power supply 10.5 - 16 V DC Including power supply unit NT 2-3 CW, 2 earphones IE 4, 4 x 1.5 V batteries and rack kit GA 3 for 19" installation Available since: May 2018 Sales Unit: 1 piece(s) Switchable Frequencies: Yes Mono/Stereo: Stereo Limiter: Yes Incl. Earpieces: Yes Focus, Mixed, Dual Mono: Yes Frequency from: 470 MHz Frequency to: 516 MHz Garantie 36 luni</p> | <p>Up to 16 compatible channels Frequency range: 25 - 15,000 Hz Frequency transmission via infrared interface Pocket receiver with charging contacts for optional BA 2015 rechargeable battery (NiMH) (battery not included) Pilot tone Auto tune to find free frequencies Audio Gain includes 60 dB 4-Digit battery indicator on the transmitter and receiver HDX compander OLED display with NF level and channel display 3.5 mm jack for earphones Adjustable limiter Switchable transmission power 10/30/50 mW WSM support (Ethernet interface for frequency management) Adjustable 6.3 mm headphone jack on the transmitter 1 BNC antenna jack 2 x Jack/XLR female balanced combo jack inputs Power supply 10.5 - 16 V DC Including power supply unit NT 2-3 CW, 2 earphones IE 4, 4 x 1.5 V batteries and rack kit GA 3 for 19" installation Available since: May 2018 Sales Unit: 1 piece(s) Switchable Frequencies: Yes Mono/Stereo: Stereo Limiter: Yes Incl. Earpieces: Yes Focus, Mixed, Dual Mono: Yes Frequency from: 470 MHz Frequency to: 516 MHz Garantie 36 luni</p> | |
| Sennheiser EK IEM G4 A1-Band | EK IEM G4 A1-Band | Germania | Sennheiser | <p>In-ear bodypack receiver Evolution Wireless Series Frequency range: A1-band, 470-516 MHz Charging contacts for optional BA 2015 (NiMH) rechargeable battery (battery is not included, must be purchased separately) Pilot tone 4-Digit battery indicator LCD display with RF / AF level- and channel display 3.5 mm Jack input for earphones</p> | <p>In-ear bodypack receiver Evolution Wireless Series Frequency range: A1-band, 470-516 MHz Charging contacts for optional BA 2015 (NiMH) rechargeable battery (battery is not included, must be purchased separately) Pilot tone 4-Digit battery indicator LCD display with RF / AF level- and channel display 3.5 mm Jack input for earphones</p> | |

| | | | | | | |
|---|-----------------------|----------|------------|--|--|--|
| | | | | Adjustable limiter Operates with 2x 1.5 V batteries or rechargeable battery Includes IE4 earphones Available since March 2019 Item number 436956 Sales Unit 1 piece(s) Incl. Earpieces Yes Type Receiver Frequency Range 407 MHz – 516 MHz Garantie 36 luni | Adjustable limiter Operates with 2x 1.5 V batteries or rechargeable battery Includes IE4 earphones Available since March 2019 Item number 436956 Sales Unit 1 piece(s) Incl. Earpieces Yes Type Receiver Frequency Range 470 MHz – 516 MHz Garantie 36 luni | |
| Sennheiser AC41 Antenna Combiner | AC41 Antenna Combiner | Slovakia | Sennheiser | Active antenna combiner for ew G4 Up to 4 IEM transmitters Compatible with SR IEM G4, SR 300 IEM G3, SR 2000 IEM and SR 2050 IEM Type: 9.5", / 1 U Includes power supply NT 3-1 and 4x BNC cable Available since: May 2018 Sales Unit: 1 piece(s) Device type: Combiner Device type: Active Frequency range up to - Frequency range from 470 MHz – 870 MHz Width: 212 mm Height: 43 mm Depth: 168 mm Weight: 1,5 kg Garantie 36 luni | Active antenna combiner for ew G4 Up to 4 IEM transmitters Compatible with SR IEM G4, SR 300 IEM G3, SR 2000 IEM and SR 2050 IEM Type: 9.5", / 1 U Includes power supply NT 3-1 and 4x BNC cable Available since: May 2018 Sales Unit: 1 piece(s) Device type: Combiner Device type: Active Frequency range up to - Frequency range from 470 MHz – 870 MHz Width: 212 mm Height: 43 mm Depth: 168 mm Weight: 1,5 kg Garantie 36 luni | |
| Sennheiser GZL RG 8x - 10m | GZL RG 8x - 10m | Germania | Sennheiser | BNC Cable Low damping With ultra-low resistance 50 Ohm For connecting remote antennae Length: 10 m Available since: October 2002 Item number: 152574 Sales Unit: 1 piece(s) Application: Antenna Input connector: BNC male Output connector: BNC male Length In cm: 10,00 m Connection: BNC | BNC Cable Low damping With ultra-low resistance 50 Ohm For connecting remote antennae Length: 10 m Available since: October 2002 Item number: 152574 Sales Unit: 1 piece(s) Application: Antenna Input connector: BNC male Output connector: BNC male Length In cm: 10,00 m Connection: BNC | |

| | | | | | | |
|--|--------------------------------|----------|------------|--|--|--|
| | | | | Cable type: RG213 Length: 10 m | Cable type: RG213 Length: 10 m | |
| Sennheiser ADP UHF 470-1075 MHz | ADP UHF 470- 1075 MHz | China | Sennheiser | Passive External Directional Antenna UHF range: 470 Hz - 1075 MHz BNC connection 3/8" and 5/8" thread for microphone stands Available since: June 2021 Item number: 519465 Sales Unit: 1 piece(s) Type: Directional antenna Frequency range up to - Frequency range from 470 MHz – 1075 MHz Connection: BNC Connection 3/8": Yes 5/8" Connection: Yes Antenne type: Passive | Passive External Directional Antenna UHF range: 470 Hz - 1075 MHz BNC connection 3/8" and 5/8" thread for microphone stands Available since: June 2021 Item number: 519465 Sales Unit: 1 piece(s) Type: Directional antenna Frequency range up to - Frequency range from 470 MHz – 1075 MHz Connection: BNC Connection 3/8": Yes 5/8" Connection: Yes Antenne type: Passive | |
| SKB Roto-Molded 4U Shallow Rack | Roto-Molded 4U Shallow Rack | China | SKB | Double Door Rack Installation depth: 27.18 cm 4 Butterfly latches Dimensions: 56.9 x 23.1 x 41.2 cm Weight: 5.81 kg Colour: Black Available since: June 2014 Item number: 342315 Sales Unit: 1 piece(s) Formfactor: 19" Construction Type: Double-Door Vertical Height Units: 4 U Internal Depht [mm]: 270 mm Horizontal Height Units: 0 U with display stand: No Rack rail at the back: Yes Service flap: No With Wheels: No Trolley: No Shock Mount: No Clasps: Butterfly Material: Plastic Colour: Black Weight:5,8 kg | Double Door Rack Installation depth: 27.18 cm 4 Butterfly latches Dimensions: 56.9 x 23.1 x 41.2 cm Weight: 5.81 kg Colour: Black Available since: June 2014 Item number: 342315 Sales Unit: 1 piece(s) Formfactor: 19" Construction Type: Double-Door Vertical Height Units: 4 U Internal Depht [mm]: 270 mm Horizontal Height Units: 0 U with display stand: No Rack rail at the back: Yes Service flap: No With Wheels: No Trolley: No Shock Mount: No Clasps: Butterfly Material: Plastic Colour: Black Weight:5,8 kg | |
| Thon Inlaycase BK Univ | Inlaycase BK Univ | Germania | Thon | Custom-Made Case for Inlay System For the Thon Inlay System Material: 7 mm coated plywood 22 x 22 mm Aluminium edges 2 Small butterfly latches 1 Suitcase handle 2 Locking hinges 8 Steel ball corners | Custom-Made Case for Inlay System For the Thon Inlay System Material: 7 mm coated plywood 22 x 22 mm Aluminium edges 2 Small butterfly latches 1 Suitcase handle 2 Locking hinges 8 Steel ball corners | |

| | | | | | | |
|----------------------------------|----------------------|----------|------|--|--|--|
| | | | | <p>Convolved foam in the lid Internal dimensions (W x D x H): 405 x 375 x 60 mm External dimensions (W x D x H): Approximately 445 x 415 x 130 mm Weight: Approximately 4.6 kg Colour: Black Milled foam inlay Suitable for 2 U rack with pullout drawers or Thon inlay system case For 12 pockettransmitters Foam in two colours black/ red Accessory compartment Milled compartment for handheld transmitter (W x D x H): approx. 118 x 31 x 50 mm Dimensions (WxDxH): 405 x 375 x 60 mm Available since: September 2018 Item number: 449284 Sales Unit: 1 piece(s) suitable for: Bodypacks 12x Material: 7 mm Plywood Wheels: No IP Class: No Colour: Black Weight: 4,8 kg External Width: 445 mm External Depth: 415 mm External Height:130 mm</p> | <p>Convolved foam in the lid Internal dimensions (W x D x H): 405 x 375 x 60 mm External dimensions (W x D x H): Approximately 445 x 415 x 130 mm Weight: Approximately 4.6 kg Colour: Black Milled foam inlay Suitable for 2 U rack with pullout drawers or Thon inlay system case For 12 pockettransmitters Foam in two colours black/ red Accessory compartment Milled compartment for handheld transmitter (W x D x H): approx. 118 x 31 x 50 mm Dimensions (WxDxH): 405 x 375 x 60 mm Available since: September 2018 Item number: 449284 Sales Unit: 1 piece(s) suitable for: Bodypacks 12x Material: 7 mm Plywood Wheels: No IP Class: No Colour: Black Weight: 4,8 kg External Width: 445 mm External Depth: 415 mm External Height:130 mm</p> | |
| Thon Rack Drawer 2U short | Rack Drawer 2U short | Germania | Thon | <p>Rack Drawer 2 U Installation depth of rack drawer: 210 mm Material: Metal Black powder-coated Robust castor guide Inner dimensions (W x D x H): 404 x 210 x 74 mm Construction: 19" / 2 U Weight: 3.4 kg Available since: November 2017 Item number: 417809 Sales Unit: 1 piece(s) Type: 19" Height in Rack Units: 2 U Depth: 210 mm Lock: No Material: Steel Weight:3,4 kg</p> | <p>Rack Drawer 2 U Installation depth of rack drawer: 210 mm Material: Metal Black powder-coated Robust castor guide Inner dimensions (W x D x H): 404 x 210 x 74 mm Construction: 19" / 2 U Weight: 3.4 kg Available since: November 2017 Item number: 417809 Sales Unit: 1 piece(s) Type: 19" Height in Rack Units: 2 U Depth: 210 mm Lock: No Material: Steel Weight:3,4 kg</p> | |

| | | | | | | |
|--|--------------------------------------|----------|------|---|---|--|
| Thon Case A&H Stagebox AB/DT/DX 168 | Case A&H Stagebox AB/DT/DX 168 | Germania | Thon | Transport Case Suitable for one A&H Stagebox AB168, DT168 and DX168 Made of plywood coated 25 x 25 mm Aluminium edge 1 Medium-sized butterfly latch V4 1 Medium folding handle 2 Locking hinges 8 Medium ball corners Foam padding Exterior dimensions (W x D x H): approx. 325 x 255 x 515 mm Weight: approx. 4.8 kg Colour: Black Available since: October 2020 Item number: 504877 Sales Unit: 1 piece(s) Profondită interna: 255 mm Locks And Catches: 1x Fluturaş Strap Handles: No Flip Handles: 1 Material: 6,8 mm Plywood Wheels: No Weight: 4,8 kg Speacial Features / Options: None External Width [mm]: 325 mm: External Depht [mm]: 255 mm External Heigh [mm]: 515 mm | Transport Case Suitable for one A&H Stagebox AB168, DT168 and DX168 Made of plywood coated 25 x 25 mm Aluminium edge 1 Medium-sized butterfly latch V4 1 Medium folding handle 2 Locking hinges 8 Medium ball corners Foam padding Exterior dimensions (W x D x H): approx. 325 x 255 x 515 mm Weight: approx. 4.8 kg Colour: Black Available since: October 2020 Item number: 504877 Sales Unit: 1 piece(s) Profondită interna: 255 mm Locks And Catches: 1x Fluturaş Strap Handles: No Flip Handles: 1 Material: 6,8 mm Plywood Wheels: No Weight: 4,8 kg Speacial Features / Options: None External Width [mm]: 325 mm: External Depht [mm]: 255 mm External Heigh [mm]: 515 mm | |
|--|--------------------------------------|----------|------|---|---|--|

Semnat: Semnat electronic, Numele, Prenumele: Carabut Vladislav, În calitate de: Director

Ofertantul: SC “Muzic-Prod” S.R.L.

Adresa: Moldova, Chisinau, Durl esti, str-la II Vovinteni 15