


Overview


HP Z2 G9 SFF Workstation Desktop PC



Front View

1. Power button
2. HDD Activity LED & Power button LED
3. Universal audio jack (with CTIA & OMTP headset support)
4. (2) USB-A 10Gbps port (1 charge port supports up to 5V/2.1A)
5. (2) USB-A 10Gbps port
6. (1) USB-C® 20Gbps port (charge supports up to 5V/3A)
7. Media Card Reader 4.0 (optional)
8. Slim ODD bay
9. Shared internal/external 3.5" bay

Overview




Rear View (Full Height Graphics Enabled Chassis)

- | | |
|---|--|
| <ol style="list-style-type: none"> 1. Audio line out 2. (2) DisplayPort 1.4 ports 3. Flex I/O module: choose one from the following: (1) DisplayPort 1.4, (1) HDMI 2.0b, (1) VGA, 1 Dual USB-A 5Gbps, 1 USB-C® 10Gbps (Power Delivery 15W, Alt Mode DisplayPort), (1) 2nd 1GbE LAN, (1) 1Gbps Fiber LC LAN, (1) Thunderbolt 3 with USB4 Type-C® 40Gbps port (cabled to PCIe AIC) 4. (2) USB-A 480Mbps ports | <ol style="list-style-type: none"> 5. (3) USB-A 5Gbps ports (1) USB-A 480Mbps port 6. WLAN Antenna (optional) <ol style="list-style-type: none"> a. Internal b. External 7. 2nd serial port (optional) 8. (1) 1GbE LAN 9. Release latch 10. Power connector |
|---|--|

NOTE: Onboard display support DP1.4/HBR2. Flex I/O module display support DP1.4/HBR3. All resolutions support up to 5120x3200 24bpp @60Hz.

Overview



Rear View (Standard Chassis) - shown with rear jet black back cover option

- | | |
|---|--|
| 1. Audio line out | 5. (3) USB-A 5Gbps ports (1) USB-A 480Mbps port |
| 2. (2) DisplayPort 1.4 ports | 6. WLAN Antenna (optional) |
| | a. Internal |
| | b. External |
| 3. Flex I/O module: choose one from the following: | 7. 2nd serial port (optional) |
| (1) DisplayPort 1.4, (1) HDMI 2.0b, (1) VGA, (1) Dual USB-A | 8. (1) 1GbE LAN |
| 5Gbps port, (1) USB-C® 10Gbps port (Power Delivery 15W, | 9. Release latch |
| Alt Mode DisplayPort), (1) 2nd 1GbE LAN, (1) 1Gbps Fiber LC | 10. Power connector |
| LAN, (1) Thunderbolt 3** USB4 Type-C® 40Gbps port (cabled | |
| to PCIe AIC) | |
| 4. (2) USB-B 480Mbps ports | 11. Rear jet black GS Mark Cover option (Not shown on the image) |

NOTE: Onboard Display support DP1.4/HBR2. Flex I/O module Display support DP1.4/HBR3. Resolution all support up to 5120x3200 24bpp @60Hz.

**Thunderbolt only supported on PCI-E slot3

Overview

| | |
|--------------------------|--|
| Form Factor | Small Form Factor |
| Base Unit Options | Standard Half Height Graphics Base Unit Full Height Graphics Base Unit |
| Operating Systems | <p>Preinstalled:</p> <ul style="list-style-type: none">• Windows 11 Pro - HP recommends Windows 11 Pro²• Windows 11 Home - HP recommends Windows 11 Pro²• Windows 10 Pro (available through downgrade rights from Windows 11 Pro)^{1,2,3}• Linux[®]-ready⁵• Ubuntu[®]^{4,5}<ul style="list-style-type: none">o Intel 12th generation processors will support and preinstall Ubuntu 20.02 and 20.04.o Intel 13th generation processors support and preinstall Ubuntu 22.04 LTS <p>Web-supported only:</p> <ul style="list-style-type: none">• Windows 10 Enterprise 64² <p>Supported Version:</p> <ul style="list-style-type: none">• HP tested Windows 10, versions 20H2, 21H1 and 21H2 on this platform. For testing information on newer versions of Windows 10, please see: https://support.hp.com/document/c05195282.• Red Hat[®] Enterprise Linux[®] Workstation 8⁵• SUSE Linux[®] Enterprise Desktop 15⁵• Ubuntu[®]^{4,5}<ul style="list-style-type: none">o Intel 12th generation processors will support and preinstall Ubuntu 20.02 and 20.04.o Intel 13th generation processors support and preinstall Ubuntu 22.04 LTS |

¹ Device comes with Windows 10 and a free Windows 11 upgrade or may be preloaded with Windows 11. Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see Windows 11 Specifications).

² Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

³This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

⁴ Not all features are available in all editions or versions of Ubuntu. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS to take full advantage of Ubuntu functionality. Ubuntu may be automatically updated. ISP fees may apply, and additional requirements may apply over time for updates.

⁵For detailed Linux[®] OS/hardware support information, see: http://www.hp.com/support/linux_hardware_matrix

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows[®] 8 or Windows 7 operating system on products configured with Intel[®] and AMD[®] 7th generation and forward processors or provide any Windows[®] 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

Processors Overview^{1,2,3,4,5}

Intel 13th Generation Processors:

Overview

Intel® Core™ i5-13400 (2.5GHz P-Core base frequency, 1.8GHz E-Core base frequency, up to 3.3GHz E-Core Max Turbo frequency, up to 4.6 GHz P-core Max Turbo frequency, 20MB L3 cache, 6 P-cores and 4 E-cores, 16 threads)

Intel® Core™ i5-13500 (2.5GHz P-Core base frequency, 1.8GHz E-Core base frequency, up to 3.5GHz E-Core Max Turbo frequency, up to 4.8 GHz P-core Max Turbo frequency, 24MB L3 cache, 6 P-cores and 8 E-cores, 20 threads)

Intel® Core™ i5-13600 (2.7GHz P-Core base frequency, 2GHz E-Core base frequency, up to 3.7GHz E-Core Max Turbo frequency, up to 5 GHz P-core Max Turbo frequency, 24MB L3 cache, 6 P-cores and 8 E-cores, 20 threads)

Intel® Core™ i5-13600K (3.5GHz P-Core base frequency, 2.6GHz E-Core base frequency, up to 3.9GHz E-Core Max Turbo frequency, up to 5.1 GHz P-core Max Turbo frequency, 24MB L3 cache, 6 P-cores and 8 E-cores, 20 threads)

Intel® Core™ i7-13700 (2.1GHz P-Core base frequency, 1.5GHz E-Core base frequency, up to 4.1GHz E-Core base frequency, up to 5.1GHz E-Core base frequency, 30MB L3 cache, 8 P-cores and 8 E-cores, 24 threads)

Intel® Core™ i7-13700K (3.4GHz P-Core base frequency, 2.5GHz E-Core base frequency, up to 4.2GHz E-Core Max Turbo frequency, up to 5.3 GHz P-core Max Turbo frequency, 30MB L3 cache, 8 P-cores and 8 E-cores, 24 threads)

Intel® Core™ i9-13900 (2GHz P-Core base frequency, 1.5GHz E-Core base frequency, up to 4.2GHz E-Core Max Turbo frequency, up to 5.2 GHz P-core Max Turbo frequency, 36MB L3 cache, 8 P-cores and 16 E-cores, 32 threads)

Intel® Core™ i9-13900K (3GHz P-Core base frequency, 2.2GHz E-Core base frequency, up to 4.3GHz E-Core Max Turbo frequency, up to 5.4 GHz P-core Max Turbo frequency, 36MB L3 cache, 8 P-cores and 16 E-cores, 32 threads)

Intel 12th Generation Processors:

Intel® Core™ i9-12900K (2.4GHz E-core base frequency, 3.2GHz P-core base frequency, up to 3.9 GHz E-core Max Turbo frequency, up to 5.1 GHz P-core Max Turbo frequency, 30MB L3 cache, 8 P-cores and 8 E-cores, 24 threads)

Intel® Core™ i9-12900 (1.8GHz E-core base frequency, 5.0 GHz P-core base frequency, up to 3.8 GHz E-core Max Turbo frequency up to 5.0 GHz P-core Max Turbo frequency, 30MB L3 cache, 8 P-cores and 8 E-cores, 24 threads)

Intel® Core™ i7-12700K (2.7 GHz E-core base frequency, 3.6 GHz P-core base frequency, up to 3.8 GHz E-core Max Turbo frequency, up to 4.9 GHz P-core Max Turbo frequency, 25MB L3 cache, 8 P-cores and 4 E-cores, 20 threads)

Intel® Core™ i7-12700 (1.6 GHz E-core base frequency, 2.1 GHz P-core base frequency, up to 3.6 GHz E-core Max Turbo frequency, up to 4.8 GHz P-core Max Turbo frequency, 25MB L3 cache, 8 P-cores and 4 E-cores, 20 threads)

Intel® Core™ i5-12600K (2.8 GHz E-core base frequency, 3.7 GHz P-core base frequency, up to 3.6 GHz E-core Max Turbo frequency, up to 4.9 GHz P-core Max Turbo frequency, 20MB L3 cache, 6 P-cores and 4 E-cores, 16 threads)

Intel® Core™ i5-12600 (3.3 GHz P-core base frequency, up to 4.8 GHz P-core Max Turbo frequency, 18MB L3 cache, 6 P-cores and 0 E-cores, 12 threads)

Intel® Core™ i5-12500 (3.0 GHz P-core base frequency, up to 4.6 GHz P-core Max Turbo frequency, 18MB L3 cache, 6 P-cores and 0-E-cores, 12 threads)

Intel® Core™ i5-12400 (2.5 GHz P-core base frequency, up to 4.4 GHz P-core Max Turbo frequency, 18MB L3 cache, 6 P-cores and 0-E cores, 12 threads)

Intel® Core™ i3-12300 (3.5 GHz P-core base frequency, up to 4.4 GHz P-core Max Turbo frequency, 12MB, 4 P-cores. 8 threads)

Intel® Core™ i3-12100 (3.3 GHz P-core base frequency, up to 4.3 GHz P-core Max Turbo frequency, 12MB, 4 P-cores. 8 threads)

¹ Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

² Intel Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

³ Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

⁴ Memory will run at 4400 speed (MT/s) if there is one DIMM per channel. 2 DIMMS per channel will run 4000 speed

Overview

(MT/s). DIMMs must be the same, either 8GB or 16GB DIMMs. 32GB DIMMs run at 3200 MT/s.

⁵ Error Correction Memory

Color Black

Convertibility The SFF can either be placed flat on the desktop or made to stand on the desk with the optional tower stand.

| Expansion Slots (see system board section for more details) ¹ | Standard Base Unit with Half Height PCIe | Full Height Graphics PCIe Base Unit |
|---|--|--|
| | Slot 1: PCIe Gen4 x16 Slot 2: PCIe Gen3 x4 Slot 3: PCIe Gen3 x4 - with x16 Connector Slot 4: PCIe Gen3 x1 | Slot 1: PCIe Gen4 x16 ¹ Slot 2: PCIe Gen4 x8 (with x16 connector) ¹ ¹ When slot 2 is configured with a PCIe card, slot 1 will automatically downgrade to PCIe x8 electrical |

Expansion Bays (see storage section for more details)

(1) Shared internal/external 3.5" bay
NOTE: This shared bay is supported only with Core i7 / i9 processors.
(1) Internal 3.5" bay
(1) Internal 3.5" bay (optional in Standard SFF. Not Available with Full Height Graphics Base Unit)
(1) Dedicated 9.5mm slim optical disk drive bay

Front I/O 2 Type-A SuperSpeed USB 10Gbps signaling rate port (1 charge port supports up to 5V/2.1A), 2 Type-A SuperSpeed USB 10Gbps signaling rate port, 1 Type-C SuperSpeed® USB 20Gbps signaling rate port (charge supports up to 5V/3A), 1 SD card reader (optional), 1 universal audio jack

Internal I/O (1) USB 480Mbps header for SD card reader
(1) serial port available with header
(1) serial and PS/2 available with header

Rear I/O (2) DisplayPort 1.4 [3], (1) Audio Line out, (1) 1GbE LAN, (3) USB-A 480Mbps ports, (3) USB-A 5Gbps ports, (1) serial (optional), (1) Flex I/O port (VGA, HDMI 2.0b, DisplayPort 1.4, USB-C® 10Gbps port (Power Delivery 15W, Alt Mode Display Port), Dual USB-A 5Gbps port, 2nd 1GbE LAN, (1) Thunderbolt 3 with USB4 Type-C® 40Gbps (cabled to PCIe AIC), (1) 1Gbps Fiber LC NIC

Optional I/O Flex IO* - choose one of the following options: (1) DisplayPort™ 1.4, (1) HDMI 2.0b, (1) VGA, (1) 2nd 1GbE LAN, (1) 1Gbps Fiber LC NIC, (1) Dual USB-A 5Gbps port, (1) USB® 10Gbps port (15W USB Power Delivery, Alt Mode DisplayPort™), (1) Thunderbolt™ 3 with USB4 Type-C® 40Gbps port (cabled to PCIe® AIC); Front - (1) SD card reader; Rear - (1) serial; (1) SD 4.0 card reader

* Flex IO port and one PCIe slot will be occupied when Thunderbolt is installed. Thunderbolt will be available in Q2, 2022 (1st refresh).

Interfaces Supported SD card reader (optional)

On-board RAID Support SATA and NVME RAID 0 Striped Array
SATA RAID and NVME RAID 1 Mirror Array

Overview

| | |
|---|--|
| Chassis Dimensions (H x W x D) | H: 3.95" [100mm] W: 15.1" [384mm] D: 12.1" [308mm] (Standard desktop orientation) |
| Packaged Dimensions | H: 20.4" (514mm) W: 7.83" (199mm) D: 19.29" (490mm) |
| Weight | Exact weights depend upon configuration (System weight only). Starting at 5.0kg (11.1lbs.) |
| Temperature | Operating: 5° to 35° C (40° to 95° F) Above 1524 m (5,000 feet) altitude, the maximum operating temperature is reduced by 1° C (1.8° F) for every 305 m (1,000 feet) increase in elevation Non-operating: -40° to 60° C (-40° to 140° F) Maximum rate of change: 10°C/hr |
| Humidity | Operating: 10% to 85% RH, non-condensing, 35° C maximum wet bulb Non-operating: 10% to 90% RH, non-condensing, 35° C maximum wet bulb |
| Maximum Altitude (non-pressurized) | Operating (with Rotational Hard Drives): 3,048 m (10,000 feet) Operating (with only Solid-State Drives): 5,000 m (16,404 feet) Non-operating: 12,192 m (40,000 feet) Maximum operating temperature is reduced as altitude increases. See Temperature for details. |
| Power Supply | <p>260W PSU: only available with standard half height graphics base unit 260W wide-ranging, active Power Factor Correction, 92% Efficiency. LiteOn 260W PSU Efficiency Report Chicony 260W PSU Efficiency Report AcBel 260W PSU Efficiency Report</p> <p>450W PSU: only available with standard half height graphics base unit 450W wide-ranging, active Power Factor Correction, 90% Efficiency. https://www.plugloadsolutions.com/80PlusPowerSuppliesDetail.aspx?id=0&type=2 LiteOn 450W PSU Efficiency Report</p> <p>550W PSU: only available with full height graphics base unit 550W wide-ranging, active Power Factor Correction, 92% Efficiency. LiteOn550W PSU Efficiency Report AcBel 550W PSU Efficiency Report</p> |
| Backup Devices | For a complete listing of compatible DAT tape drives, LTO tape drives and RDX Removable Disk Backup System offerings, please visit http://www.hp.com/go/connect |
| Chipset | Intel® W680 chipset |
| Memory | 4 DIMM slots, supporting up to 128GB ECC/non-ECC, DDR5 unbuffered DIMM memory. Speed depending on the system configuration. See Supported Components / Memory Section for details. |

Supported Components

| Storage / Hard Drives* | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|---|--------------------|------------|------------------------|---------------|
| SATA Hard Drives¹ | | | | |
| 500GB SATA 7200 rpm 6Gb/s 3.5" HDD | Y | Y | LQ036AA | 1 |
| 1TB SATA 7200 rpm 6Gb/s 3.5" HDD | Y | Y | LQ037AA | 1 |
| 2TB SATA 7200 rpm 6Gb/s 3.5" HDD | Y | Y | QB576AA | 1 |
| 1TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Y | Y | W0R10AA | 1 |
| 2TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Y | Y | 2Z274AA | 1 |
| 4TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Y | Y | K4T76AA | 1 |
| 8TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Y | Y | 2Z273AA | 1 |
| 12TB 7200 RPM SATA-6G 3.5in Enterprise HDD | Y | Y | 5S461AA | 1 |
| 500GB SATA 7.2K SED SFF HDD | Y | Y | D8N29AA | 1 |
| PCIe Solid State Drives | | | | |
| HP ZTurbo 512GB PCIe-Gen 4x4 TLC Z2 SSDKit | Y | Y | 201G0AA | |
| HP ZTurbo 512GB PCIe-Gen 4x4 SED Z2 SSDKit | Y | Y | 201F9AA | |
| HP ZTurbo 1TB PCIe-Gen 4x4 TLC Z2 SSDKit | Y | Y | 201F5AA | |
| HP ZTurbo 2TB PCIe-Gen 4x4 TLC Z2 SSDKit | Y | Y | 201F8AA | |
| HP Z Turbo Drive 1TB 2280 PCIe-4x4 SED OPAL2 TLC Z2 Kit SSD | Y | Y | 223A3AA | |
| HP Z Turbo Drive 2TB 2280 PCIe-4x4 SED OPAL2 TLC Z2 Kit SSD | Y | Y | 223A4AA | |
| Z Turbo 4TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 Z2 Kit SSD | Y | Y | 5S498AA | |
| HP 256GB PCIe NVMe TLC M.2 Z2 G9 TWR/SFF SSD | Y | Y | | |
| HP 500GB PCIe NVMe TLC M.2 Z2 G9 TWR/SFF SSD | Y | Y | | |
| HP 1TB PCIe NVMe TLC M.2 Z2 G9 TWR/SFF SSD | Y | Y | | |
| HP 256GB 2280 PCIe-4x4 NVMe Value M.2 Z2 Kit SSD | Y | Y | 4M9Z1AA | |
| HP 512GB 2280 PCIe-4x4 NVMe Value M.2 Z2 Kit SSD | Y | Y | 4M9Z2AA | |
| HP 1TB 2280 PCIe-4x4 NVMe Value M.2 Z2 Kit SSD | Y | Y | 4M9Z3AA | |
| HP Z Turbo 4TB 2280 PCIe-4x4 TLC M.2 Z2 Kit SSD | Y | Y | 5S492AA | |
| HP Z Turbo 2TB PCIe-4x4 TLC SSD Module | Y | Y | 38T75AA | |
| HP Z Turbo 1TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD Module | Y | Y | 38T76AA | |
| HP Z Turbo 1TB PCIe-4x4 TLC SSD Module | Y | Y | 38T77AA | |
| HP Z Turbo 2TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD Module | Y | Y | 38T79AA | |
| HP Z Turbo 512GB PCIe-4x4 TLC SSD Module | Y | Y | 38T80AA | |
| HP Z Turbo 512GB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD Module | Y | Y | 38T81AA | |
| HP Z Turbo 4TB 2280 PCIe-4x4 TLC M.2 SSD Module | Y | Y | 5S496AA | |
| HP Z Turbo 4TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD Module | Y | Y | 5S497AA | |

NOTE 1: HDD option kits also require purchase of separate cable kit (available Sept 2022). This option kit includes necessary components to install the HDD options in an internal or external bay.
HP Z2 SFF HDD Cable Kit 6Z9U5AA. This is only needed when HDD is purchased as AMO.

Supported Components

*For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of sy disk (for Windows) is reserved for system recovery software.

| Graphics | Factory Configured | Option Kit | Option Kit Part Number | Supported # of cards | Support Note: |
|--|--------------------|------------|------------------------|----------------------|---------------|
| Graphics Cable Adapters | | | | | |
| HP DisplayPort To HDMI True 4k Adapter | Y | Y | 2JA63AA | | |
| HP Single miniDP-to-DP Adapter Cable | Y | Y | 2MY05AA | | |
| HP DisplayPort To DVI-D Adapter | Y | Y | FH973AA/A6 | | |
| HP DisplayPort To VGA Adapter | Y | Y | AS615AA/AT | | |
| HP DisplayPort To VGA Adapter | Y | Y | AS615A6 | | |
| HP DisplayPort To VGA Adapter | Y | Y | F7W97AA | | |
| HP USB-C to DisplayPort Adapter | Y | Y | 4SH08AA | | |
| HP USB-C to HDMI Adapter | Y | Y | 4SH07AA | | |
| HP USB-C to VGA Adapter | Y | Y | 4SH06AA | | |
| Entry 3D Graphics | | | | | |
| NVIDIA® T400 2 GB Graphics | Y | Y | 340K8AA | 2 | 1 |
| NVIDIA® T400 4 GB Graphics | Y | Y | 5Z7E0AA/AT | 2 | |
| NVIDIA® T600 4 GB Graphics | Y | Y | 340K9AA | 2 | 1 |
| AMD Radeon RX 6400 4 GB DH DP+HDMI Graphics | Y | Y | 6Q3U4AA | 1 | |
| AMD Radeon Pro WX 3200 4GB (4)mDP GFX, w/2 mDP-to-DP adapters | Y | Y | 6YT68AA | 1 | |
| Mid-range 3D Graphics | | | | | |
| NVIDIA® T1000 4 GB Graphics | Y | Y | | 2 | |
| NVIDIA® T1000 8 GB Graphics | Y | Y | 5Z7D8AA/AT | 2 | |
| NVIDIA Long-Life T1000E 8 GB 4mDP Graphics | Y | Y | 6V9V4AA/AT | 2 | |
| NVIDIA® RTX™ A2000 6 GB 4mDP Graphics | Y | Y | 340L0AA | 1 | 3 |
| NVIDIA® RTX™ A2000 12GB Graphics* | Y | Y | 5Z7D9AA/AT | 1 | 3 |
| NVIDIA Long-Life RTX A2000E 12 GB 4mDP Graphics | Y | Y | 6V9V5AA/AT | 1 | |
| AMD Radeon™ Pro W6600 Graphics (8GB GDDR6 dedicated) * | Y | Y | 340K5AA | 1 | |
| High-end 3D Graphics | | | | | |
| AMD Radeon™ RX 6700 XT Graphics (12 GB GDDR6 dedicated) * | Y | N | | 1 | 2 |
| NVIDIA® RTX™ A4000 16 GB Graphics* | Y | Y | 20X24AA/AT | 1 | 2, 3 |
| NVIDIA Long-Life RTX A4000E 16 GB 4DP Graphics | Y | Y | 6H7J7AA | 1 | 2, 3 |
| Note 1: NVIDIA® T400 (2 GB GDDR6 dedicated) and NVIDIA® T600 (4 GB GDDR6 dedicated) may go End of Life in 2022. | | | | | |
| Note 2: Full Height Graphics (eg. NV A4000, AMD 6700) are only supported by Full Height Chassis/550W PSU) | | | | | |
| Note 3: Double wide card consumes 2 PCIe slots | | | | | |

Supported Components

| Memory | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|---------------------------------------|--------------------|------------|------------------------|---------------|
| HP 8GB (1x8GB) DDR5-4800 UDIMM NECC | Y | Y | 4M9X9AA | 2, 3 |
| HP 16GB (1x16GB) DDR5-4800 UDIMM NECC | Y | Y | 4M9Y0AA | 2, 3 |
| HP 16GB (1x16GB) DDR5-4800 UDIMM ECC | Y | Y | 4M9Y1AA | 1, 2, 3 |
| HP 32GB (1x32GB) DDR5-4800 UDIMM NECC | Y | Y | 4M9Y2AA | 2, 3 |
| HP 32GB (1x32GB) DDR5- 4800 UDIMM ECC | Y | Y | 4M9Y3AA | 1, 2, ,3 |

NOTE 1: See Processor Overview section for processors that support ECC Memory.

NOTE 2: Two channels of DDR5 memory are supported. To realize full performance one DIMM must be inserted into each channel.

NOTE 3: Though the memory modules can run up to 4800MHz, the current platform will support the maximum memory speed of 4400MHz.

The system speed will be determined by these key factors:

| Module Configuration | Description of configuration | Max Memory Speed (Actual Memory speed is dependent on CPU) |
|---------------------------------------|--|--|
| Single 8, 16 or 32GB DIMM per channel | Configurations that contain only one or two DIMM modules with DIMMs only in the black slots | 4400MHz |
| Two 8 or 16GB DIMMs in a channel | Configurations with 3 or 4 DIMMs installed in a system. Memory DIMMs must all be of the same size. | 4000MHz |
| Two 32GB DIMMs in a channel | Configurations with 3 or 4 32GB DIMMs installed in a system | 3600MHz |

| Optical and Removable Storage | Factory Configured | Option Kit | Option Kit Part Number | Support Note |
|--|--------------------|------------|------------------------|--------------|
| HP DP25 Removable 2.5" HDD Frame/Carrier | N | Y | W3J84AA | |
| HP DP25 2.5 in HDD Spare Carrier | N | Y | W3J85AA | |
| HP Z2 SFF DVD-Writer 9.5mm Slim ODD | Y | Y | 4L5J9AA | 1 |
| HP Z2 SFF DVD-ROM 9.5mm Slim ODD | Y | Y | 4L5J8AA | 1 |
| HP CRU QX118 3.5 in Front Removable Frame/Carrier | Y | N | | |
| HP CRU QX328 3.5 in Front Removable Frame/Carrier | Y | Y | 4N012AA | 2, 3 |
| HP CRU Secure High Performance Storage Module with 2TB M.2 SSD | Y | Y | 56Q87AA | 4 |
| HP CRU Secure High Performance Storage Module with 1TB M.2 SSD | Y | Y | 56Q88AA | 4 |
| HP CRU Secure High Performance Storage Module with 512GB M.2 SSD | Y | Y | 56Q89AA | 4 |

NOTE 1: Duplication of copyrighted material is strictly prohibited. Actual speeds may vary. Double Layer media compatibility will widely vary with some home DVD players and DVD-ROM drives. Note that DVD-RAM cannot read or write to 2.6GB Single Sided/5.2 Double Sided-Version 1.0 Media.

NOTE 2: HP CRU QX328 3.5 in Front Removable Frame/Carrier is only compatible with Intel core i7 and core i9 processors

NOTE 3: Requires separate purchase of HP CRU SHIP Storage Module(s).

NOTE 4: HP CRU Secure High Performance Storage (SHIPS) Module Kit contains select M.2 SSD for install into a factory configured or after market option front removable storage carrier (HP CRU QX328 Frame/Carrier).

Supported Components

| Networking and Communications | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|--|--------------------|------------|------------------------|---------------|
| Integrated Intel® I219LM PCIe GbE Controller (Intel® vPro® with Intel® AMT 16.0) | Y | N | | 2 |
| HP 1GbE LAN Flex Port 2020 | Y | Y | 141J6AA/AT | 3 |
| HP Flex 1GbE Fiber LC Single Port | Y | Y | 20J15AA | 3 |
| Intel Ethernet I350-T4 4-Port 1Gb NIC* | N | Y | W8X25AA | 3 |
| Intel X550 10GBASE-T Dual Port NIC | Y | Y | 1QL46AA | |
| Intel Ethernet Network Adapter I225-T1 | Y | Y | 406L9AA | |
| Intel Wi-Fi 6E AX211 BT 5.3 wireless card M.2 non-vPro ^{1,**} | Y | N | | 1 |
| Allied Telesis AT-2911T/2-901 Dual Port 1GbE NIC | Y | Y | 6E3Y9AA/AT | |
| NVIDIA Mellanox ConnectX-6 DX Dual Port 10/25GbE SFP28 NIC | Y | Y | 436M8AA | |

*Intel I350-T4 4-port GbE NIC is an After Market Option only.

**Intel AX211 must be configured at time of purchase. Not available as an After Market Option.

NOTE 1: Intel AX211 with external antenna support WIFI 6E. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. The integrated network connection is required to support Intel® vPro® Technology.

NOTE 2: If AMT is provisioned, then network teaming with the integrated LAN port is not possible.

NOTE 3: "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required

| Racking and Physical Security | Factory Configured | Option Kit | Option Kit Part Number |
|-------------------------------------|--------------------|------------|------------------------|
| HP Keyed Cable Lock | N | Y | T1A62AA |
| HP Master Keyed Cable Lock 10mm | N | Y | T1A63AA |
| HP Business PC Security Lock V3 Kit | N | Y | 3XJ17AA |

Supported Components

Input Devices

| | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| HP 320K Wired Keyboard | Y | Y | 9SR37AA |
| HP 455 Programmable Wireless Keyboard | Y | Y | 4R177AA |
| HP 975 USB+BT Dual-Mode Wireless Keyboard | Y | Y | 3Z726AA |
| HP 655 Wireless Keyboard and Mouse Combo | Y | Y | 4R009AA |
| HP 125 Wired Keyboard | Y | Y | 266C9AA |
| HP Wired Desktop 320MK Mouse and Keyboard | Y | Y | 9SR36AA |
| HP Wired 320M Mouse | Y | Y | 9VA80AA |
| HP 128 Laser Wired Mouse | Y | Y | 265D9AA |
| HP 125 Wired Mouse | Y | Y | 265A9AA |
| HP Creator 935 Black Wireless Mouse | Y | Y | 1D0K8AA |
| HyperX Cloud MIX Wireless GAM HEADSET | N | Y | 4P5K9AA |
| HyperX Cloud Core BLK GAM HEADSET | N | Y | 4P4F2AA |
| HyperX Cloud Flight - Wireless Gaming Headset (Black-Red) (HX-HSCF-BK/AM) | N | Y | 4P5L4AA |
| HyperX Cloud Stinger Core GAM HEADSET PC | N | Y | 4P4F4AA |
| HyperX SoloCast - USB Microphone (Black) (HMIS1X-XX-BK/G) | N | Y | 4P5P8AA |

Flexport Options

| | Factory Configured | Option Kit | Option Kit Part Number |
|--------------------------------------|--------------------|------------|------------------------|
| HP DP Flex Port 2020 | Y | Y | 141J7AA/AT |
| HP 1GbE LAN Flex Port 2020 | Y | Y | 141J6AA/AT |
| HP Flex 1GbE Fiber LC Single Port | Y | Y | 20J15AA |
| HP Dual USB-A 3.2 Gen1 Flex 2020 | Y | Y | 141J8AA/AT |
| HP HDMI Flex Port | Y | Y | 69D47AA/AT |
| HP USB-C 3.2 Gen2 Alt Flex Port 2020 | Y | Y | 141K6AA/AT |
| HP VGA Flex Port 2020 | Y | Y | 141K7AA/AT |

Miscellaneous

| | Factory Configured | Option Kit | Option Kit Part Number |
|--|--------------------|------------|------------------------|
| HP Z2 Internal Serial Port and PS/2 Port | Y | Y | 141K9AA/AT |
| HP Z2 Power Cord Kit | Y | Y | 1N1D5AA |
| HP Z2 2nd serial port adapter | Y | Y | 141K8AA/AT |
| HP PCIe x1 Parallel Port Card | Y | Y | N1M40AA |
| HP Z2 SFF Dust Filter | Y | Y | 4N002AA |
| HP Z2 SFF Dust Filter and Bezel | Y | Y | 4N003AA |
| HP Z2 SFF HDD Cable Kit | N | Y | 6Z9U5AA |
| HP Anyware Integrated Remote System Controller | Y | Y | 7K6D9AA |
| HP Anyware Remote System Controller Main Board Adapter | Y | Y | 7K6D8AA |
| HP Anyware Remote System Controller | Y | Y | 7K6D7AA |

Supported Components

| Software | Factory | | Support Notes |
|---|------------|------------|---------------|
| | Configured | Option Kit | |
| HP Performance Advisor | Y | N | 1 |
| HP PC Hardware Diagnostics UEFI (Windows OS only) | Y | N | 2 |
| HP PC Hardware Diagnostics Windows | | N | 3 |
| HP Wolf Security | Y | N | |
| HP Notifications | Y | N | |
| HP Desktop Support Utility | Y | N | |
| HP Documentation | Y | N | |
| HP Image Assistant | N | N | |
| HP Support Assistant | N | N | |
| myHP | Y | N | |
| HP Easy Clean | Y | N | |
| Kingsoft WPS Office | Y | N | 4 |
| My Office | Y | N | 5 |
| Adobe Substance 3D Collection Plan | N | Y | 6 |
| WSL2/Ubuntu Data Science Stack | Y | N | 7 |

Note 1: Supports, and preinstalled with Windows 10 only. Also available as a free download from <http://www.hp.com/go/performanceadvisor>

Note 2: Windows OS only

Note 3: Not available in Russia

Note 4: Only available in China

Note 5: Only available in Russia

Note 6: Not available in China

Note 7: Optional Software

Operating Systems

Windows 11 Pro - HP recommends Windows 11 Pro²

Windows 11 Home - HP recommends Windows 11 Pro²

Windows 10 Pro (available through downgrade rights from Windows 11 Pro)^{1,2,3}

Linux[®]-ready⁵

Ubuntu[®]^{4,5}

- o Intel 12th generation processors will support and preinstall Ubuntu 20.02 and 20.04.
- o Intel 13th generation processors support and preinstall Ubuntu 22.04 LTS

¹ Device comes with Windows 10 and a free Windows 11 upgrade or may be preloaded with Windows 11. Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see Windows 11 Specifications).

² Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

³This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

⁴ Not all features are available in all editions or versions of Ubuntu. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS to take full advantage of Ubuntu functionality.

Supported Components

Ubuntu may be automatically updated. ISP fees may apply and additional requirements may apply over time for updates.

⁵For detailed Linux® OS/hardware support information, see:

http://www.hp.com/support/linux_hardware_matrix

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

HP BIOS

Key features of the HP BIOS include:

- Deployment and manageability - HP BIOS provides several technologies that help integrate the HP Z2 G9 SFF Workstation Desktop PC into the enterprise, such as PXE, remote recovery, remote configuration, remote control, and BIOS (F10) Setup support for 15 languages.
- Network firmware updates - Update your BIOS via the cloud or standardize on a BIOS version hosted on an Enterprise network.
- Stability - HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- Class 3 UEFI specification version 2.7
- Absolute Persistence agent - For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management - The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Workstation computer in any enterprise environment.
- Acoustic performance - Industry leading acoustic emissions across the range of operating conditions.
- Serviceability - HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery - HP BIOS provides numerous ways to upgrade HP Workstation computers, including BIOS updates from within Windows (HP Firmware Update and Recovery), Capsule update, HP Client Manager, and fail-safe recovery. In addition, the HP BIOS Configuration Utility enables replication of BIOS settings within Windows while the Replicated Setup feature provides the same capability within BIOS (F10) Setup. The BIOS Configuration Utility is available from the HP support website.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery.

Additional HP BIOS Features:

- Power-On password - Helps prevent an unauthorized user from powering on the system.
- Administrator password - Also known as the BIOS Setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS cannot be updated and changes cannot be made to BIOS settings using BIOS Setup or under the OS.
- S4/S5 Maximum Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 0.5W in S4/S5 (when turned off). When S4/S5 Maximum Power Savings feature is enabled below features are turned off:

-Power to expansion connectors / slots

Supported Components

-Most Wake events other than power buttons and WOL (Wake on LAN supported by embedded Lan controller under S4/S5 Maximum Power Saving Enabled)

-USB charging ports

HP Sure Start Gen7

- BIOS Integrity checking - Sure Start protection ensures that only trusted BIOS code is executed and not rootkits, viruses and malware. Verification is done upon boot up, shutdown and while the system is on.
- Sure Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability. Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability.
- Protecting beyond BIOS - Integrity checking and repair is extended to other data that should be protected such as network configuration parameters, platform specific information (i.e. system IDs), secure boot credentials, and other code the system needs to boot.
- Audit enabled - System Audit via Sure Start Event Logs capture data such as incident, repair date and time for troubleshooting and investigating.

NOTE: HP Sure Start Gen7 is available on HP Workstation products equipped with Intel® 12th generation processors.

SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

Software

HP Support Assistant¹⁴
HP Image Assistant
HP Desktop Support Utility
HP Documentation
HP Notifications
HP PC Hardware Diagnostics UEFI
HP PC Hardware Diagnostics Windows
HP Performance Advisor¹
myHP
HP Easy Clean²⁰
WSL/Ubuntu Data Science Stack
HP Privacy Settings
Touchpoint Customizer for Commercial

Manageability Features

HP Driver Packs²
HP UWP Pack
HP System Software Manager (SSM)
HP Manageability Integration Kit Gen4³
HP Smart Support⁵
HP Client Catalog (download)
HP Image Assistant (download)
HP Cloud Recovery
HP Client Management Script Library (download)
HP BIOSphere Gen6¹³

Client Security Software

HP Client Security Suite Gen7⁴ including: (including Credential Manager, HP Password Manager⁶, HP Spare Key)
HP Power On Authentication

Supported Components

Microsoft Defender⁷

Security Management

HP Secure Erase¹⁶

HP Wolf Pro Security Edition (optional)¹⁸

HP Wolf Security for Business²² Includes:

HP Sure Click¹¹

HP Sure Sense¹²

HP Sure Run Gen5⁹

HP Sure Recover Gen4¹⁰

HP Sure Start Gen7⁸

HP Tamper Lock

HP Sure Admin¹⁷

HP Client Security Manager Gen 7⁴

¹ HP Performance Advisor Software - HP Performance Advisor is ready to help you get the most out of your HP Workstation from day one-and every day after. Learn more or download at: <http://hp.com/PerformanceAdvisor>

² HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

³ HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>

⁴ HP Client Security Manager Gen7 requires Windows and is available on the select HP PCs.

⁵ HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or can be downloaded. For more information about how to enable HP Smart Support or for download, please visit <http://www.hp.com/smart-support>.

⁶ HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.

⁷ Microsoft Defender Opt in and internet connection required for updates.

⁸ HP Sure Start Gen 7 is available on select HP PCs and workstations. See product specifications for availability.

⁹ HP Sure Run Gen5 is available on select Windows 11 based HP Pro, Elite and Workstation PCs with select Intel® or AMD processors.

¹⁰ HP Sure Recover Gen4 is available on select HP PCs and requires Windows 10 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi only available on PCs with Intel Wi-Fi Module

¹¹ HP Sure Click requires Windows 10 Pro or higher or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.

¹² HP Sure Sense requires Windows 11 Pro or Enterprise and supports Microsoft Internet Explorer, Google Chrome™, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode, when Microsoft Office or Adobe Acrobat are installed.

¹³ HP BIOSphere Gen6 features may vary depending on the platform and configurations.

¹⁴ HP Support Assistant requires Windows and Internet access.

¹⁶ Secure Erase - For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clearing, restoring, and sanitizing magnetic media." HP Secure Erase does not support platforms with Intel® Optane.

¹⁷ HP Sure Admin requires Windows 11, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

¹⁸ HP Wolf Pro Security Edition is available preloaded on select SKUs and, depending on the HP product purchased, includes a paid 1-year or 3-year license. The HP Wolf Pro Security Edition software is licensed under the license terms of the HP Wolf Security Software - End-User license Agreement (EULA) that can be found at: https://support.hp.com/us-en/document/ish_3875769-3873014-16 as that EULA is modified by the following: "7. Term. Unless otherwise terminated earlier pursuant to the terms contained in this EULA, the license for the HP Wolf Pro Security Edition (HP Sure Sense Pro and HP Sure Click Pro) is effective upon activation and will continue for either a twelve (12) month or thirty-six (36) month license term ("Initial Term"). At the end of the Initial Term you may either (a) purchase a renewal license for the HP Wolf Pro Security Edition from HP.com, HP Sales or an HP Channel Partner, or (b) continue using the standard versions of HP Sure Click and HP Sure Sense at no additional cost with no future software updates or HP Support.

²⁰ HP Easy Clean requires Windows 10 RS3 and higher and will disable the keyboard, touchscreen, and clickpad only. Ports are not disabled. See user guide for cleaning instructions.

²² HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro,

Supported Components

Elite, RPOS and Workstation products. See product details for included security features

System Technical Specifications

System Board

System Board Form Factor Customized PCB 231.04 x 301.24 mm (9.213X11.86inches)

Processor Socket Single LGA-1700

CPU Bus Speed DMI

Chipset Intel® PCH W680

Super I/O Controller Nuvoton SIO21

Memory Expansion Slots 4 DDR5 memory slots

Memory Type Supported DDR5, UDIMM (Unbuffered), ECC& non-ECC

Memory Modes Non-Interleaved for single channel. Interleaved when both channels are populated.

Memory Speed Supported 3600MT/s to 4400MT/s DDR5, dependent on memory configuration¹

¹Though the memory modules can run up to 4800MHz, the current platform will only be able to support maximum memory speed of 4400MHz.

The system speed will be determined by a number of key factors:

| Module Configuration | Description of configuration | Max Memory Speed (Actual Memory speed is dependent on CPU) |
|---------------------------------------|--|--|
| Single 8, 16 or 32GB DIMM per channel | Configurations that contain only one or two DIMM modules with DIMMs only in the black slots | 4400MHz |
| Two 8 or 16GB DIMMs in a channel | Configurations with 3 or 4 DIMMs installed in a system. Memory DIMMs must all be of the same size. | 4000MHz |
| Two 32GB DIMMs in a channel | Configurations with 3 or 4 32GB DIMMs installed in a system | 3600MHz |

Memory Protection ECC available on data

Maximum Memory 128GB

Memory Configuration (Supported) 8GB, 16GB and 32GB non-ECC, 16GB and 32GB ECC unbuffered DIMMs are supported. ECC and non-ECC memory DIMMs cannot be mixed in the same system

NOTE: Maximum memory capacities assume 64-bit operating systems, such as Genuine Windows® 11 Professional 64 bit, Red Hat Linux 64-bit. 32-bit Windows Operating Systems support up to 4 GB.

PCI Express Connectors

| Standard Base Unit with Half Height PCIe | Full Height Graphics PCIe Base Unit |
|--|--|
| Slot 1: PCIe Gen4 x16 Slot 2: PCIe Gen3 x4 Slot 3: PCIe Gen3 x4 - with x16 Connector Slot 4: PCIe Gen3 x1 | Slot 1: PCIe Gen4 x16 ¹ Slot 2: PCIe Gen4 x8 (with x16 connector) ¹ |

(1) M.2 2280 Storage (PCIe Gen4 x4)

(1) M.2 2280 Storage (PCIe Gen4 x4)

(1) M.2 2280 Storage (PCIe Gen4 x4)

¹When slot 2 is configured with a PCIe card, slot 1 will automatically downgrade to PCIe x8 electrical

System Technical Specifications

(1) M.2 2230 WLAN (PCIe Gen3 x1+ Intel CNVi)

NOTE: The PCIe Gen 4 x16 slot is meant for HP qualified cards, configured or after market. HP does not provide warranty support for 3rd party cards.

| | | |
|---|---|--|
| Supported Interfaces | SATA | Integrated (4) Serial ATA interfaces (6Gb/s SATA). |
| | Serial Attached SCSI | None |
| | Integrated Graphics | Intel® UHD Graphics 730 (on Core i5-12400/i3-12300/i3-12100) processor; Intel® UHD Graphics 770 (on Core i5/i7/i9 processors); Based on Unified Memory Architecture (UMA) - a region of system memory reserved and dedicated to the graphics display. Support for Microsoft DirectX 12, OpenGL 4.6 and OpenCL 3.0 on Intel® UHD Graphics 730/770; Based on Unified Memory Architecture (UMA) - a region of system memory reserved and dedicated to the graphics display. |
| | Network Controller | 2 DP 1.4 graphics ports integrated in motherboard; Supports up to three simultaneous displays across DisplayPort*/HDMI*/DVI outputs. Max. resolution supported on onboard DP 1.4/HBR2 ports: 4096x2304 @ 60Hz, 24bpp Max. resolution supported on FlexIO DP 1.4/HBR3 port: 5120x3200 @ 60Hz, 24bpp Integrated Ethernet PHY Connection I219LM. Management capabilities: Wake-on-LAN, PXE 2.1 and AMT 16 |
| | External SATA (eSATA) | None |
| | IDE connector | None |
| | Floppy connector | None |
| | Serial | 1 internal header (requires optional Serial Port and PS/2 Combo Kit with bracket) |
| | 2nd Serial | 1 internal header (requires optional Serial Port Adapter Kit) |
| | Connector(s) | Front |
| Rear | | 3 High-speed USB 480Mbps signaling rate port; 3 Type-A SuperSpeed USB 5Gbps signaling rate port; Flex I/O option: 1 SuperSpeed USB Type-C® 10Gbps signaling rate (Power Delivery 15W, Mode DisplayPort); 1 Dual SuperSpeed USB Type-A 5Gbps signaling rate port |
| Internal | | 1 High-speed USB 480Mbps signaling rate header for SD Card Reader |
| HD Integrated Audio | Realtek ALC3252 | |
| Flash ROM | Yes | |
| CPU Fan Header | Yes | |
| Memory Fan Header | None | |
| Chassis Fan Header | 1 Rear System Chassis Fan Header, 1 Graphic chassis Fan Header. | |
| Front PCI Fan Header | None | |
| Front Control Panel/Speaker Header | Yes | |
| CMOS Battery Holder - Lithium | Yes | |
| Integrated Trusted Platform Module | Integrated TPM 2.0 (Infineon SLB9672) Convertible to FIPS 140-2 Certified mode through firmware v15.21 | |

System Technical Specifications

Power Supply Headers Yes

Power Switch, Power LED & Hard Drive LED Header Yes

Clear Password Jumper None

Keyboard/Mouse USB or PS/2 Mouse (option)

Power Supply 260W EPA92, 450W EPA90 and 550W EPA92

¹Maximum memory capacities assume 64-bit operating systems, such as Genuine Windows® 10 Professional 64 bit, Red Hat Linux 64-bit Windows Operating Systems support up to 4 GB.

²M.2 storage supports compatible devices up to 80mm

PROCESSORS

| Name | Ghz P-Core Base Frequency | Ghz E-Core Base Frequency | Up to X P-Core Max Turbo Freq | Up to x GHz E-Core Max Turbo Frequency | L3 Cache (MB) | P-Cores | E-Cores | Total Cores | Process or Threads | Memory Speed (MT/s) (DDR5) ⁴ | ECC Memory Supported ⁵ | Integrated Graphics | Featuring Intel® vPro® Technology ³ | TDP (W) | Max Turbo Frequency (GHz) ² |
|--|---------------------------|---------------------------|-------------------------------|--|---------------|---------|---------|-------------|--------------------|---|-----------------------------------|-------------------------|--|---------|--|
| Intel 13th Generation Processors | | | | | | | | | | | | | | | |
| Intel® Core™ i9-13900K | 3 | 2.20 | 5.4 | 4.3 | 36 | 8 | 16 | 24 | 32 | 5600 | Y | Intel® UHD Graphics 770 | Y | 125 | 5.8 |
| Intel® Core™ i9-13900 | 2 | 1.50 | 5.2 | 4.2 | 36 | 8 | 16 | 24 | 32 | 5600 | Y | Intel® UHD Graphics 770 | Y | 65 | 5.6 |
| Intel® Core™ i7-13700K | 3.4 | 2.50 | 5.3 | 4.2 | 30 | 8 | 8 | 16 | 24 | 5600 | Y | Intel® UHD Graphics 770 | Y | 125 | 5.8 |
| Intel® Core™ i7-13700 | 2.1 | 1.50 | 5.1 | 4.10 | 30 | 8 | 8 | 16 | 24 | 5600 | Y | Intel® UHD Graphics 770 | Y | 65 | 5.2 |
| Intel® Core™ i5-13600K | 3.5 | 2.60 | 5.1 | 3.9 | 24 | 6 | 8 | 14 | 20 | 5600 | Y | Intel® UHD Graphics 770 | Y | 65 | 5.1 |
| Intel® Core™ i5-13600 | 2.7 | 2.00 | 5.0 | 3.7 | 24 | 6 | 8 | 14 | 20 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 5.0 |
| Intel® Core™ i5-13500 | 2.5 | 1.80 | 4.8 | 3.5 | 24 | 6 | 8 | 14 | 20 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 4.8 |
| Intel® Core™ i5-13400 | 2.5 | 1.80 | 4.6 | 3.3 | 20 | 6 | 4 | 10 | 16 | 4800 | N | Intel® UHD Graphics 730 | N/A | 65 | 4.6 |
| Intel 12th Generation Processors | | | | | | | | | | | | | | | |
| Intel® Core™ i9-12900K | 3.2 | 2.4 | 5.1 | 3.9 | 30 | 8 | 8 | 16 | 24 | 4800 | Y | Intel® UHD Graphics 770 | Y | 125 | 5.2 |
| Intel® Core™ i9-12900 | 5 | 1.8 | 5.0 | 3.8 | 30 | 8 | 8 | 16 | 24 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 5.1 |
| Intel® Core™ i7-12700K | 3.6 | 2.7 | 4.9 | 3.8 | 25 | 8 | 4 | 12 | 20 | 4800 | Y | Intel® UHD Graphics 770 | Y | 125 | 5.0 |

System Technical Specifications

| | | | | | | | | | | | | | | | |
|------------------------|-----|-----|-----|-----|----|---|---|----|----|------|---|-------------------------|-----|-----|-----|
| Intel® Core™ i7-12700 | 2.1 | 1.6 | 4.8 | 3.6 | 25 | 8 | 4 | 12 | 20 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 4.9 |
| Intel® Core™ i5-12600K | 3.7 | 2.8 | 4.9 | 3.6 | 20 | 6 | 4 | 10 | 16 | 4800 | Y | Intel® UHD Graphics 770 | Y | 125 | 4.9 |
| Intel® Core™ i5-12600 | 3.3 | N/A | 4.8 | N/A | 18 | 6 | 0 | 6 | 12 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 4.8 |
| Intel® Core™ i5-12500 | 3 | N/A | 4.6 | N/A | 18 | 6 | 0 | 6 | 12 | 4800 | Y | Intel® UHD Graphics 770 | Y | 65 | 4.6 |
| Intel® Core™ i5-12400 | 2.5 | N/A | 4.4 | N/A | 18 | 6 | 0 | 6 | 12 | 4800 | N | Intel® UHD Graphics 730 | N/A | 65 | 4.4 |
| Intel® Core™ i3-12300 | 3.5 | N/A | 4.4 | N/A | 12 | 4 | 0 | 4 | 8 | 4800 | N | Intel® UHD Graphics 730 | N/A | 60 | 4.4 |
| Intel® Core™ i3-12100 | 3.3 | N/A | 4.3 | N/A | 12 | 4 | 0 | 4 | 8 | 4800 | N | Intel® UHD Graphics 730 | N/A | 60 | 4.3 |

¹ Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

² Intel Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

³ Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

⁴ Memory will run at 4400 speed (MT/s) if there is one DIMM per channel. 2 DIMMS per channel will run 4000 speed (MT/s). DIMMs must be the same, either 8GB or 16GB DIMMs. 32GB DIMMs run at 3200 MT/s.

⁵ Error Correction Memory

System Technical Specifications

System Configurations

| | | | | | | | |
|---|-----------------------------|-----------------------------|--------------|-------------|--------------|-------------|--------------|
| <i>HP Z2 G9 SFF Workstation Desktop PC Configuration #1</i> | Processor Info | Core i5-12500,6C 3.0G 65W | | | | | |
| | Memory Info | 2 x 8G DDR5 4800 UDIMM NECC | | | | | |
| | Graphics Info | NVIDIA T400 4GB | | | | | |
| | Disks/Optical/Floppy | 512GB SSD Z Turbo | | | | | |
| | PSU | 260W | | | | | |
| | Other | NA | | | | | |
| Energy Consumption (Watts) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 16.907 | | 16.195 | | 16.452 | |
| | Windows short Idle (S0) | 17.323 | | 17.742 | | 17.245 | |
| | Windows Busy Typ(S0) | 165.717 | | 168.913 | | 164.628 | |
| | Windows Busy Max (S0) | 187.903 | | 183.393 | | 186.965 | |
| | Sleep (S3) | 1.001 | 0.991 | 1.033 | 1.001 | 0.991 | 1.033 |
| | Off (S5) | 0.657 | 0.631 | 0.672 | 0.657 | 0.631 | 0.672 |
| | Zero Power Mode (ErP) | 0.229 | | 0.237 | | 0.224 | |
| | Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Enabled | LAN Enabled | LAN Enabled |
| Windows long Idle (S0) | | 57.687 | | 55.257 | | 56.134 | |
| Windows short Idle (S0) | | 59.106 | | 60.536 | | 58.84 | |
| Windows Busy Typ(S0) | | 565.426 | | 576.331 | | 561.711 | |
| Windows Busy Max (S0) | | 641.125 | | 625.737 | | 637.925 | |
| Sleep (S3) | | 3.415 | 3.381 | 3.525 | 3.415 | 3.381 | 3.525 |
| Off (S5) | | 2.242 | 2.153 | 2.293 | 2.242 | 2.153 | 2.293 |
| Zero Power Mode (ErP) | | 0.781 | | 0.809 | | 0.764 | |

| | | | | | | | |
|---|-----------------------------|-----------------------------|--------------|-------------|--------------|-------------|--------------|
| <i>HP Z2 G9 SFF Workstation Desktop PC Configuration #2</i> | Processor Info | Core i7-12700,12C 2.1G 65W | | | | | |
| | Memory Info | 2 x 8G DDR5 4800 UDIMM NECC | | | | | |
| | Graphics Info | NVIDIA T1000 8GB | | | | | |
| | Disks/Optical/Floppy | 512GB SSD Z Turbo | | | | | |
| | PSU | 450W | | | | | |
| | Other | NA | | | | | |
| Energy Consumption (Watts) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 19.136 | | 19.335 | | 19.211 | |
| | Windows short Idle (S0) | 20.404 | | 21.197 | | 20.32 | |
| | Windows Busy Typ(S0) | 245.533 | | 239.257 | | 242.62 | |
| | Windows Busy Max (S0) | 268.903 | | 247.683 | | 266.482 | |
| | Sleep (S3) | 1.132 | 1.101 | 1.211 | 1.132 | 1.101 | 1.211 |
| | Off (S5) | 0.735 | 0.722 | 0.744 | 0.735 | 0.722 | 0.744 |
| | Zero Power Mode (ErP) | 0.265 | | 0.268 | | 0.252 | |
| | Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Enabled | LAN Enabled | LAN Enabled |
| Windows long Idle (S0) | | 65.292 | | 65.971 | | 65.548 | |
| Windows short Idle (S0) | | 69.618 | | 72.324 | | 69.332 | |
| Windows Busy Typ(S0) | | 837.759 | | 816.345 | | 827.819 | |
| Windows Busy Max (S0) | | 917.497 | | 845.094 | | 909.237 | |
| Sleep (S3) | | 3.862 | 3.757 | 4.132 | 3.862 | 3.757 | 4.132 |
| Off (S5) | | 2.508 | 2.463 | 2.539 | 2.508 | 2.463 | 2.539 |
| Zero Power Mode (ErP) | | 0.904 | | 0.914 | | 0.86 | |

System Technical Specifications

| | | | | | | | |
|---|-------------------------|--|--------------|----------------|--------------|----------------|--------------|
| HP Z2 G9 SFF Workstation Desktop PC Configuration #3 | | Processor Info Core i7-12700K,12C 3.6G 125W | | | | | |
| | | Memory Info 2 x 16G DDR5 4800 UDIMM ECC | | | | | |
| | | Graphics Info NVIDIA RTX A2000 | | | | | |
| | | Disks/Optical/Floppy 512GB SSD Z Turbo | | | | | |
| | | PSU 450W | | | | | |
| | | Other NA | | | | | |
| Energy Consumption (Watts) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 21.043 | | 20.428 | | 20.228 | |
| | Windows short Idle (S0) | 23.125 | | 22.638 | | 22.444 | |
| | Windows Busy Typ(S0) | 258.063 | | 253.127 | | 256.521 | |
| | Windows Busy Max (S0) | 274.25 | | 263.977 | | 268.45 | |
| | Sleep (S3) | 1.302 | 1.221 | 1.411 | 1.302 | 1.221 | 1.411 |
| | Off (S5) | 0.705 | 0.691 | 0.725 | 0.705 | 0.691 | 0.725 |
| | Zero Power Mode (ErP) | 0.238 | | 0.242 | | 0.239 | |
| Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 71.799 | | 69.700 | | 69.018 | |
| | Windows short Idle (S0) | 78.903 | | 77.241 | | 76.579 | |
| | Windows Busy Typ(S0) | 880.511 | | 863.669 | | 875.25 | |
| | Windows Busy Max (S0) | 935.741 | | 900.69 | | 915.951 | |
| | Sleep (S3) | 4.442 | 4.166 | 4.814 | 4.442 | 4.166 | 4.814 |
| | Off (S5) | 2.405 | 2.358 | 2.474 | 2.405 | 2.358 | 2.474 |
| | Zero Power Mode (ErP) | 0.812 | | 0.826 | | 0.815 | |

| | | | | | | | |
|---|-------------------------|--|--------------|----------------|--------------|----------------|--------------|
| HP Z2 G9 SFF Workstation Desktop PC Configuration #4 | | Processor Info Core i7-12700K,12C 3.6G 125W | | | | | |
| | | Memory Info 4 x 16G DDR5 4800 UDIMM NECC | | | | | |
| | | Graphics Info NVIDIA RTX A2000 | | | | | |
| | | Disks/Optical/Floppy 1T SSD Z Turbo | | | | | |
| | | PSU 550W | | | | | |
| | | Other NA | | | | | |
| Energy Consumption (Watts) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 16.118 | | 16.525 | | 16.022 | |
| | Windows short Idle (S0) | 17.591 | | 17.935 | | 17.485 | |
| | Windows Busy Typ(S0) | 166.23 | | 166.157 | | 165.652 | |
| | Windows Busy Max (S0) | 215.6 | | 214.207 | | 213.633 | |
| | Sleep (S3) | 1.023 | 0.968 | 1.215 | 1.023 | 0.968 | 1.215 |
| | Off (S5) | 0.654 | 0.642 | 0.678 | 0.654 | 0.642 | 0.678 |
| | Zero Power Mode (ErP) | 0.248 | | 0.252 | | 0.248 | |
| Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 54.995 | | 56.383 | | 54.667 | |
| | Windows short Idle (S0) | 60.020 | | 61.194 | | 59.659 | |
| | Windows Busy Typ(S0) | 567.177 | | 566.928 | | 565.205 | |
| | Windows Busy Max (S0) | 735.627 | | 730.874 | | 728.916 | |
| | Sleep (S3) | 3.491 | 3.303 | 4.146 | 3.491 | 3.303 | 4.146 |
| | Off (S5) | 2.231 | 2.191 | 2.313 | 2.231 | 2.191 | 2.313 |
| | Zero Power Mode (ErP) | 0.846 | | 0.86 | | 0.846 | |

System Technical Specifications

| | | | | | | | |
|---|-----------------------------|-------------------------------|--------------|-------------|--------------|-------------|--------------|
| HP Z2 G9 SFF Workstation Desktop PC Configuration #5 | Processor Info | Core i9-12900K, 16C 3.2G 125W | | | | | |
| | Memory Info | 4 x 32G DDR5 4800 UDIMM ECC | | | | | |
| | Graphics Info | NVIDIA RTX A4000 | | | | | |
| | Disks/Optical/Floppy | 1T SSD Z Turbo | | | | | |
| | PSU | 550W | | | | | |
| | Other | NA | | | | | |
| Energy Consumption (Watts) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 32.725 | | 32.709 | | 32.711 | |
| | Windows short Idle (S0) | 33.525 | | 35.083 | | 33.432 | |
| | Windows Busy Typ(S0) | 392.633 | | 392.11 | | 390.621 | |
| | Windows Busy Max (S0) | 419.361 | | 406.324 | | 414.845 | |
| | Sleep (S3) | 1.929 | 1.862 | 2.142 | 1.929 | 1.862 | 2.142 |
| | Off (S5) | 0.776 | 0.749 | 0.825 | 0.776 | 0.749 | 0.825 |
| | Zero Power Mode (ErP) | 0.213 | | 0.219 | | 0.208 | |
| Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC | |
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows long Idle (S0) | 111.658 | | 111.603 | | 111.61 | |
| | Windows short Idle (S0) | 114.387 | | 119.703 | | 114.07 | |
| | Windows Busy Typ(S0) | 1339.664 | | 1337.879 | | 1332.799 | |
| | Windows Busy Max (S0) | 1430.86 | | 1386.377 | | 1415.451 | |
| | Sleep (S3) | 6.582 | 6.353 | 7.309 | 6.582 | 6.353 | 7.309 |
| | Off (S5) | 2.648 | 2.556 | 2.815 | 2.648 | 2.556 | 2.815 |
| | Zero Power Mode (ErP) | 0.727 | | 0.747 | | 0.71 | |
| NOTE: The Power Supply Efficiency report may be found at the following links: https://www.plugloadolutions.com/80PlusPowerSuppliesDetail.aspx?id=0&type=2 | | | | | | | |

Declared Noise Emissions

| | | | |
|--|-----------------------------|--|--|
| System Configuration (Entry level, Lowprofile) | Processor Info | Intel® CPU Core i5-12400 6C LGA 2.50G 18 MB 65W (Intel - Alder Lake-S) | |
| | Memory Info | 1* 32GB 4800 SK hynix memory | |
| | Graphics Info | Intel® UHD | |
| | Disks/Optical/Floppy | 1*2TB Samsung M.2 | |
| | Power Supply | LITE-ON 450W | |

| | | | |
|---|---|---------------------------------|---|
| Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296) | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
| | Idle | 3.1 | 15.2 |
| | Hard drive Operating (Drive Random Seek) | 3.4 | 23.9 |
| | Hard drive Operating (Active mode) | 3.05 | 14.8 |

| | | | |
|--|-----------------------------|---|--|
| System Configuration (Mid-level, Lowprofile) | Processor Info | Intel® CPU Core i9-12900 16C LGA 2.40G 30 MB 65W ECC (Intel - Alder Lake-S) | |
| | Memory Info | 4* 32GB 4800 SK hynix memory | |
| | Graphics Info | NVIDIA® T1000 | |
| | Disks/Optical/Floppy | 2*WD 2TB 7200RPM SATA HDD; 3*2TB Samsung M.2 | |
| | Power Supply | LITE-ON 450W | |

System Technical Specifications

| Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296) | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
|--|---|-----------------------------|---|
| | Idle | 3.35 | 23.4 |
| | Hard drive Operating (Drive Random Seek) | 3.48 | 24.9 |
| | Hard drive Operating (Active mode) | 4.34 | 30.5 |

| System Configuration (High-end, Lowprofile) | Processor Info | Intel® Core i9-12900K 16C 3.20G LGA 30 MB 125W ECC (Intel - Alder Lake-S) |
|--|----------------------|---|
| | Memory Info | 4* 32GB 4800 SK hynix memory |
| | Graphics Info | NVIDIA® T1000 |
| | Disks/Optical/Floppy | 2*WD 2TB 7200RPM SATA HDD; 3*2TB Samsung M.2 |
| | Power Supply | LITE-ON 450W |

| Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296) | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
|--|---|-----------------------------|---|
| | Idle | 3.37 | 23.1 |
| | Hard drive Operating (Drive Random Seek) | 3.45 | 24.7 |
| | Hard drive Operating (Active mode) | 4.35 | 33.0 |

| System Configuration (Entry level, Riser) | Processor Info | Intel® Core i5-12400 6C LGA 2.50G 18 MB 65W (Intel - Alder Lake-S) |
|--|----------------------|--|
| | Memory Info | 1* 32GB 4800 SK hynix memory |
| | Graphics Info | Intel® UHD |
| | Disks/Optical/Floppy | 1*2TB Samsung M.2 |
| | Power Supply | Liteon 550W EPA92 |

| Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296) | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
|--|---|-----------------------------|---|
| | Idle | 3.01 | 12.0 |
| | Hard drive Operating (Drive Random Seek) | 3.37 | 23.1 |
| | Hard drive Operating (Active mode) | 3.09 | 15.5 |

System Technical Specifications

| | | |
|-----------------------------------|-------------------------|--|
| Environmental Requirements | Temperature | Operating: 5° to 35° C (40° to 95° F) Non-operating: -40° to 60° C (-40° to 140° F) Maximum rate of change: 10°C/hr |
| | Humidity | Operating: 10% to 85% RH, non-condensing, 35° C maximum wet bulb Non-operating: 10% to 90% RH, non-condensing, 35° C maximum wet bulb |
| | Maximum Altitude | Operating (with Rotational Hard Drives): 3,048 m (10,000 feet) Operating (with only Solid-State Drives): 5,000 m (16,404 feet) Non-operating: 12,192 m (40,000 feet) Maximum operating temperature is reduced as altitude increases. See Cooling for details. |
| | Dynamic | Shock Operating: ?-sine: 40g, 2-3ms (~62 cm/sec) Non-operating: ?-sine: 160 cm/s, 2-3ms (~105g) square: 422 cm/s, 20g |
| | Cooling | Vibration Operating random: 0.5g (rms), 5-300 Hz, up to 0.0025g ² /Hz Non-operating random: 2.0g (rms), 5-500 Hz, up to 0.0150 g ² /Hz Above 1524 m (5,000 feet) altitude, the maximum operating temperature is reduced by 1° C (1.8° F) for every 305 m (1,000 feet) increase in elevation, up to 3048 m (10,000 feet) |
| | NOTE: | System enduring or operating beyond the environmental requirement range not recommended and may compromise system reliability permanently. |

Physical Security and Serviceability

| | |
|--|---|
| Access Panel | Tool-less Includes support information |
| Optical Drive | Tool-less, except for Screw-In carrier |
| Hard Drives | Tool-less, except for internal/external bay |
| Expansion Cards | Tool-less |
| Processor Socket | Tool-less, except for the processor heatsink |
| Blue User Touch Points | Yes, on tool-less internal chassis mechanisms |
| Color-coordinated Cables and Connectors | Yes |
| Memory | Tool-less |
| System Board | Screw-In |
| Padlock Support | Yes (optional): Locks side cover and secures chassis from theft 0.22-in diameter padlock loop at rear of system |
| Cable Lock Support | Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system |
| Universal Chassis Clamp Lock Support | Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable Threaded feature at rear of system |

System Technical Specifications

| | |
|--|--|
| Solenoid Lock and Hood Sensor | Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor detects when the access panel has been removed. |
| Keyboard/Mouse/Video Cable Lock | No |
| CPUs and Heatsinks | A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less. |
| Internal Speaker | Yes |
| Power Supply Fans | 70mm x 70mm x 25mm 4-wire PWM (non-serviceable) |
| Access Panel Key Lock | No |
| Integrated Chassis Handles | No |
| Power Supply | Requires T15 Torx or flat blade screwdriver |
| PCI Card Retention | Yes, rear (all), middle (optional), front (none) |

Service, Support, and Warranty

On-site Warranty and Service¹: Three-years, limited warranty and service offering delivers on-site, next business-day² service for parts and labor and includes free telephone support³ 8am - 5pm. Global coverage² ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering. 24/7 operation will not void the HP warranty. Storage devices are not covered under warranty for 24/7 operation except for Enterprise class HDDs.

NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.

NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24x7 support service may not be available in some countries.

HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at:

<http://www.hp.com/go/lookuptool>. Service levels and response times for HP Care Packs may vary depending on your geographic location.

System Technical Specifications

Certification and Compliance

Environmental Sustainability questions concerning:

- Ecolabels (EPEAT, TCO, etc.)
- ENERGY STAR, California Energy Commission (CEC)
- Compliance with Environmental legislation (EU ErP, China CECP, EU RoHS and other countries)
- Supply Chain Social Environmental Responsibility (SER) (conflict minerals; human rights, etc.)
- Product specific environmental features (material content, packaging content, recycled content, etc.)
- China Energy Label (CEL)

Please contact sustainability@hp.com

For country specific Regulatory Compliance approval documents or Regulatory and Safety questions concerning:

- Declarations of Conformity (for self-service, go to https://www.hp.com/uk-en/certifications/technical/regulations-certificates.html?jumpid=ex_r135_uk/en/any/corp/hpuk-mu_chev/certificates)
- GS Certificates
- Product Safety Certificates (UL, CB, BIS, etc.)
- EMC Certificates, Declarations of Conformity, or Certificates of Conformity (CE, FCC, ICES, etc.)
- CCC Certificates
- Ergonomics

Please contact techregshelp@hp.com

BIOS

| | |
|---|--|
| BIOS 64-bit Services | BIOS supports 64-bit Operating systems only. |
| PCI 3.0 Support | Full BIOS support for PCI Express through industry standard interfaces. |
| ATAPI | ATAPI Removable Media Device BIOS Specification Version 1.0. |
| BBS | BIOS Boot Specification v1.01.(Not Support) |
| WMI Support | WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications. |
| BIOS Boot Spec 1.01+ | Provides more control over how and from what devices the workstation will boot. |
| BIOS Power On | Users can define a specific date and time for the system to power on. |
| ROM Based Computer Setup Utility (F10) | Review and customize system configuration settings controlled by the BIOS. |
| System/Emergency ROM Flash Recovery with Video | Recovers system BIOS in corrupted Flash ROM. |
| Replicated Setup | Saves BIOS settings to USB flash device in human readable file (HpSetup.txt). BiosConfigurationUtility.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup). |
| SMBIOS | System Management BIOS Reference Specification, Version 3.4 External BIOS simulator found at: http://csrmsl.itcs.hp.com/ |
| Boot Control | Disables the ability to boot from removable media on supported devices. |
| Memory Change Alert | Alerts management console if memory is removed or changed. |
| Thermal Alert | Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none">• NORMAL - normal temperature ranges.• ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown.• SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs. |
| Remote ROM Flash | Provides secure, fail-safe ROM image management from a central network console. |

System Technical Specifications

| | |
|---|--|
| ACPI (Advanced Configuration and Power Management Interface) | Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 6.0 for full compatibility with 64-bit operating systems. |
| Ownership Tag | A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen. |
| Remote Wakeup/Remote Shutdown | System administrators can power on, restart, and power off a client computer from a remote location. |
| Instantly Available PC (Suspend to RAM - ACPI sleep state S3) | Allows for very low power consumption with quick resume time. |
| Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server) | Allows a new or existing system to boot over the network and download software, including the operating system. |
| ROM revision levels | Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS and WMI) so that management SW applications can use and report this information. |
| System board revision level | Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified. |
| Start-up Diagnostics (Power-on Self-Test) | Assesses system health at boot time with selectable levels of testing. |
| Auto Setup when new hardware installed | System automatically detects addition of new hardware. |
| Keyboard-less Operation | The system can be booted without a keyboard. |
| Localized ROM Setup | Common BIOS image supports System Configuration Utility (F10 Setup) menus in 14 languages with local keyboard mappings. |
| Asset Tag | The user or MIS to set a unique tag string in non-volatile memory. |
| Per-slot Control | Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually. |
| Adaptive Cooling | Control parameters are set according to detected hardware configuration for optimal acoustics. |
| Pre-boot Diagnostics | (Pre-video) critical errors are reported via beeps and blinks on the power LED. |
| UEFI Specification | |
| Revision | 2.7 |
| ACPI | Advanced Configuration and Power Management Interface, Version 6.0 |
| ATA (IDE) | ATA Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b |
| CD Boot | "El Torito" Bootable CD-ROM Format Specification Version 1.0 |
| EDD | Enhanced Disk Drive Specification Version 1.1 BIOS Enhanced Disk Drive Specification Version 3.0(Not support) |
| EHCI | Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0 |
| PCI | PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0, Draft .7 |
| PCI Express | PCI Express Base Specification, Revision 2.0 PCI Express Base Specification, Revision 3.0 PCI Express Base Specification, Revision 4.0 |
| PMM | POST Memory Manager Specification, Version 1.01(Not support) |
| SATA | Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Serial ATA Specification, Revision 2.5 Serial ATA 6 Gb/s: Serial ATA Specification, Revision 3.0 |
| SPD | JEDEC JESD300-5 |

System Technical Specifications

| | |
|---------------|---|
| TPM | Trusted Computing Group TPM Specification Version 2.0 (Infineon SLB 9670). Common Criteria EAL4+ certified. FIPS 140-2 Certification TCG TPM Certified products list: http://www.trustedcomputinggroup.org/certification/tpm-certified-products/ |
| UHCI | Universal Host Controller Interface Design Guide, Revision 1.1 |
| USB | Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification Universal Serial Bus Revision 3.1 Specification |
| SMBIOS | System Management BIOS Reference Specification, Version 3.2 External BIOS simulator found at: http://csrsml.itcs.hp.com/ |

Social and Environmental Responsibility

Eco-Label Certifications & Declarations This product is low halogen except for power cords, cables, and peripherals. Service parts obtained after purchase may not be Low Halogen.
This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- This product is low halogen except for power cords, cables, and peripherals. Service parts obtained after purchase may not be Low Halogen.
- IT ECO declaration
- US ENERGY STAR®
- US Federal Energy Management Program (FEMP)
- EPEAT® Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.
- TCO Certified
- China Energy Conservation Program (CECP)
- China State Environmental Protection Administration (SEPA)
- Taiwan Green Mark
- Korea Eco-label
- Japan PC Green label*

Sustainable Impact Specifications

- Ocean-bound plastic in System FAN, CPU FAN and Speaker
- 45% post-consumer recycled plastic
- Low halogen
- Outside Box and corrugated cushions are 100% sustainably sourced and recyclable
- Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable
- Bulk packaging available

System Configuration The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook"?

Energy Consumption (in accordance with US ENERGY STAR® test method)

| | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 50Hz |
|------------------------------|--------------|--------------|--------------|
| Normal Operation (Sort idle) | 45.62 W | 45.60 W | 45.63 W |
| Normal Operation (Long idle) | 41.46 W | 41.62 W | 41.57 W |
| Sleep | 2.34 W | 2.34 W | 2.39 W |

System Technical Specifications

| | | | |
|-----|--------|--------|--------|
| Off | 0.89 W | 0.91 W | 0.90 W |
|-----|--------|--------|--------|

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

| Heat Dissipation* | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 50Hz |
|-------------------------------|--------------|--------------|--------------|
| Normal Operation (Short idle) | 156 BTU/hr | 156 BTU/hr | 156.1 BTU/hr |
| Normal Operation (Long idle) | 141.8 BTU/hr | 142.3 BTU/hr | 142.2 BTU/hr |
| Sleep | 8 BTU/hr | 8 BTU/hr | 8.2 BTU/hr |
| Off | 3 BTU/hr | 3.1 BTU/hr | 3.1 BTU/hr |

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise

Emissions

(in accordance with ISO 7779 and ISO 9296)

| | Sound Power (L _{WAd} , bels) | Sound Pressure (L _{pAm} , decibels) |
|----------------------------------|--|---|
| Typically Configured - Idle | 3.37 | 23.1 |
| Fixed Disk - Random writes | 3.45 | 24.7 |
| Optical Drive - Sequential reads | 4.35 | 33.0 |

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the

Spare parts are available throughout the warranty period and or for up to "5"? years after the end of production.

Batteries

This battery in this product complies with EU Directive 2006/66/EC

Battery size: CR2032 (coin cell)

Battery type: Lithium Metal

The battery in this product does not contain:

- Mercury greater than 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 40 ppm by weight

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.

System Technical Specifications

- This product is 93.5% recycle-able when properly disposed of at end of life.

| | | | |
|----------------------------|------------------|---|--------|
| Packaging Materials | External: | PAPER/Corrugated | 1204 g |
| | | PAPER/Molded Pulp | 722 g |
| | Internal: | PLASTIC/Polyethylene low density - LDPE | 40 g |

The plastic packaging material contains at least 0.0% recycled content.

The corrugated paper packaging materials contains at least 35% recycled content.

RoHS Compliance

HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.

We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances-including PVC, BFRs, and certain phthalates-in future RoHS legislation that pertains to electrical and electronics products.

We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.

To obtain a copy of the HP RoHS Compliance Statement, see [HP RoHS position statement](#).

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Bis(2-Ethylhexyl) phthalate (DEHP)
- Benzyl butyl phthalate (BBP)
- Dibutyl phthalate (DBP)
- Diisobutyl phthalate (DIBP)
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.

System Technical Specifications

- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

HP, Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842>

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

footnotes

- Percentage of ocean-bound plastic contained in each component varies by product
- Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.
- External power supplies, WWAN modules, power cords, cables and peripherals excluded.
- 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.
- Fiber cushions made from 100% recycled wood fiber and organic materials.

Technical Specifications - Hard Drives

| | | | | | |
|---|---|--|-----------------------------------|----------------|--|
| SATA Hard Drives for HP Workstations | 500GB SATA 7200 rpm 6Gb/s 3.5" HDD | Capacity | 500GB | | |
| | | Protocol | SATA | | |
| | | Form Factor | 3.5" | | |
| | | Controller | AHCI | | |
| | | Height | 1 in; 2.54 cm | | |
| | | Width | Media Diameter | 3.5 in; 8.9 cm | |
| | | | Physical Size | 4 in; 10.17 cm | |
| | | Interface | Serial ATA (6.0Gb/s), NCQ enabled | | |
| | | Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | | |
| | | Buffer | 32MB | | |
| | | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 2 ms * | |
| | | | Average | 11 ms * | |
| | | | Full Stroke | 21 ms * | |
| | | Rotational Speed | 7,200 rpm | | |
| | | Logical Blocks | 976,773,168 | | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | | |
|------------------------------|---|--|-----------------------------------|----------------|--|
| | 1TB SATA 7200 rpm 6Gb/s 3.5" HDD | Capacity | 1TB | | |
| | | Protocol | SATA | | |
| | | Form Factor | 3.5" | | |
| | | Controller | AHCI | | |
| | | Height | 1 in; 2.54 cm | | |
| | | Width | Media Diameter | 3.5 in; 8.9 cm | |
| | | | Physical Size | 4 in; 10.17 cm | |
| | | Interface | Serial ATA (6.0Gb/s), NCQ enabled | | |
| | | Synchronous Transfer Rate (Maximum) | Up to 600 MB/s * | | |
| | | Buffer | 64MB | | |
| | | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 2 ms * | |
| | | | Average | 11 ms * | |
| | | | Full Stroke | 21 ms * | |
| | | Rotational Speed | 7,200 rpm | | |
| | | Logical Blocks | 1,953,525,168 | | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | |
|---|---|------------------------------------|----------------|
| 2TB SATA 7200 rpm 6Gb/s 3.5" HDD | Capacity | 2TB | |
| | Protocol | SATA | |
| | Form Factor | 3.5" | |
| | Controller | AHCI | |
| | Annualized Failure Rate (based on Rated POH) | <0.62% | |
| | Height | 1 in; 2.54 cm | |
| | Width | Media Diameter | 3.5 in; 8.9 cm |
| | | Physical Size | 4 in; 10.17 cm |
| | Interface | Serial ATA (6.0 Gb/s), NCQ Enabled | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| | Buffer | 64MB | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 2.0 ms * |
| | | Average | 11 ms * |
| | | Full Stroke | 21 ms * |
| Rotational Speed | 7,200 rpm | | |
| Logical Blocks | 3,907,029,168 | | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|---|------------------------------------|----------------|
| 1TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Capacity | 1TB | |
| | Height | 1 in; 2.54 cm | |
| | Protocol | SATA | |
| | Form Factor | 3.5" | |
| | Controller | AHCI | |
| | Reliability | 2.0M hours | |
| | Rated Power On Hours | 8760/yr | |
| | Annualized Failure Rate (based on Rated POH) | <0.62% | |
| | Width | Media Diameter | 3.5 in; 8.9 cm |
| | | Physical Size | 4 in; 10.17 cm |
| | Interface | Serial ATA (6.0 Gb/s), NCQ Enabled | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| | Buffer | 128MB | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.32ms* |
| | | Average | 7.45ms* |
| | | Full Stroke | 14.2ms* |
| | Rotational Speed | 7,200 rpm | |
| | Operating Temperature | 41° to 140° F (5° to 60° C) | |
| | Performance | Sequential Read | up to 226MB/s* |
| Sequential Write | | up to 226MB/s* | |

Technical Specifications - Hard Drives

Enterprise Class Features High Reliability

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | |
|--|---|---------------------------------|----------------|--|
| 2TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Capacity | 2TB | | |
| | Protocol | SATA | | |
| | Form Factor | 3.5" | | |
| | Controller | AHCI | | |
| | Reliability (MTBF) | 2.0M hours | | |
| | Rated Power On Hours | 8760/yr | | |
| | Annualized Failure Rate (based on Rated POH) | <0.62% | | |
| | Rated for 24/7/365 Operation | | | |
| | Physical Size (Height) | 1 in; 2.54 cm | | |
| | Physical Size (Width) | 4 in; 10.17 cm | | |
| | Media Diameter | 3.5 in; 8.9 cm | | |
| | Interface | Serial ATA (6Gb/s), NCQ enabled | | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s* | | |
| | Buffer | 128MB | | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7ms* | |
| | | Average | 8.5ms* | |
| | | Full Stroke | 15.7ms* | |
| | Rotational Speed | 7,200 rpm | | |
| | Operating Temperature | 41° to 131° F (5° to 55° C) | | |
| | Performance | Sequential Read | up to 226MB/s* | |
| Sequential Write | | up to 226MB/s* | | |
| Enterprise Class Features High Reliability | | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | | |
|--|---|---------------------------------|---------|--|
| 4TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Capacity | 4TB | | |
| | Protocol | SATA | | |
| | Form Factor | 3.5" | | |
| | Controller | AHCI | | |
| | Reliability | 2.0M hours | | |
| | Rated Power On Hours | 8760/yr | | |
| | Annualized Failure Rate (based on Rated POH) | <0.62% | | |
| | Rated for 24/7/365 Operation | | | |
| | Physical Size (Height) | 1 in; 2.54 cm | | |
| | Physical Size (Width) | 4 in; 10.17 cm | | |
| | Media Diameter | 3.5 in; 8.9 cm | | |
| | Physical Size | 4 in; 10.17 cm | | |
| | Interface | Serial ATA (6Gb/s), NCQ enabled | | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s* | | |
| | Buffer | 256MB | | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7ms* | |
| | | Average | 8.5ms* | |
| | | Full Stroke | 15.7ms* | |
| | Rotational Speed | 7,200 rpm | | |
| | Operating Temperature | 41° to 131° F (5° to 55° C) | | |
| Performance | Sequential Read | up to 226MB/s* | | |
| | Sequential Write | up to 226MB/s* | | |
| Enterprise Class Features | High Reliability | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | |
|--|---|-----------------------------------|----------------|--|
| 8TB SATA 7200 rpm 6Gb/s 3.5" HDD (Enterprise Class) | Capacity | 8TB | | |
| | Protocol | SATA | | |
| | Form Factor | 3.5" | | |
| | Controller | AHCI | | |
| | Reliability | 2.0M hours | | |
| | Width | Media Diameter | 3.5 in; 8.9 cm | |
| | | Physical Size | 4 in; 10.17 cm | |
| | Interface | Serial ATA (6.0Gb/s), NCQ enabled | | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s [1] | | |
| | Buffer | 256MB | | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7ms* | |
| | | Average | 8.5ms* | |
| | | Full Stroke | 15.7ms* | |
| | Rotational Speed | 7,200 rpm | | |

Technical Specifications - Hard Drives

| | | |
|----------------------------------|-----------------------------|----------------------------|
| Operating Temperature | 41° to 140° F (5° to 60° C) | |
| Performance | Sequential Read | up to 226MB/s ¹ |
| | Sequential Write | up to 226MB/s ¹ |
| Enterprise Class Features | High Reliability | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|-----------------------------------|------------------|
| 500GB SATA 7.2K SED 2.5" Capacity HDD | 500GB | |
| Protocol | SATA | |
| Form Factor | 2.5" | |
| Height | 0.275 in; 0.7 cm | |
| Width | Media Diameter | 2.5 in; 6.36 cm |
| | Physical Size | 2.75 in; 6.99 cm |
| Interface | Serial ATA (6.0Gb/s), NCQ enabled | |
| Synchronous Transfer Rate (Maximum) | Up to 600MB/s* | |
| Buffer | 64MB | |
| Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 1 ms* |
| | Average | 4.2ms* |
| | Full Stroke | 25ms (Typical)* |
| Rotational Speed | 7,200 rpm | |
| Operating Temperature | 32° to 131° F (0° to 60° C) | |
| Self-Encrypting Drive Support | Yes | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|------------------------------|-----------------------------------|
| HP Z Turbo Drv PCIe-4X4 512GB TLC PCIe SSD (Z2G9) | Capacity | 512GB |
| | Protocol | PCIe |
| | Form Factor | M.2 in native Slot on motherboard |
| | Controller | NVMe |
| | NAND Type | 3D TLC |
| | Endurance | 300TBW (TB Written) |
| | Reliability (MTBF) | 1.5M hours |
| | Interface | PCI Express 4.0 x4 electrical |
| | Operating Temperature | 32° to 178° F (0° to 81° C) |
| Performance | Sequential Read | 6400MB/s* |
| | Sequential Write | 3400MB/s* |
| | Random Read | 600K IOPS* |
| | Random Write | 600K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | |
|--|------------------------------|--|
| HP Z Turbo Drv PCIe-4X4 1TB TLC PCIe SSD (Z2G9) | Capacity | 1TB |
| | Protocol | PCIe |
| | Form Factor | M.2 in native Slot on motherboard |
| | Controller | NVMe |
| | NAND Type | 3D TLC |
| | Endurance | 400TBW (TB Written) |
| | Reliability | 1.5M Hours |
| | Interface | PCI Express 4.0 x4 electrical |
| | Operating Temperature | 32° to 178° F (0° to 81° C) |
| | Performance | Sequential Read 6500MB/s* Sequential Write 5000MB/s* Random Read 800K IOPS* Random Write 800K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|------------------------------|--|
| HP Z Turbo Drv PCIe-4X4 2TB TLC PCIe SSD (Z2G9) | Capacity | 2TB |
| | Protocol | PCIe |
| | Form Factor | M.2 in native Slot on motherboard |
| | Controller | NVMe |
| | NAND Type | 3D TLC |
| | Endurance | 500TBW (TB Written) |
| | Reliability | 1.5M Hours |
| | Interface | PCI Express 4.0 x4 electrical |
| | Operating Temperature | 32° to 178° F (0° to 81° C) |
| | Performance | Sequential Read 6500MB/s* Sequential Write 5000MB/s* Random Read 800K IOPS* Random Write 800K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | |
|---|------------------------------|-----------------------------------|------------|
| HP Z Turbo Drv PCIe-4X4 4TB TLC PCIe SSD | Capacity | 4TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 in native Slot on motherboard | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 600TBW (TB Written) | |
| | Reliability (MTBF) | 1.5M Hours | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 178° F (0° to 81° C) | |
| | Performance | Sequential Read | 6500MB/s* |
| | | Sequential Write | 5000MB/s* |
| | | Random Read | 700K IOPS* |
| | | Random Write | 700K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|--------------------------------------|-----------------------------------|------------|
| HP Z Turbo Drv PCIe Gen4x4 4TB TLC PCIe SED OPAL2 | Capacity | 4TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 in native Slot on motherboard | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 600TBW (TB Written) | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 178° F (0° to 81° C) | |
| | Performance | Sequential Read | 6500MB/s* |
| | | Sequential Write | 5000MB/s* |
| | | Random Read | 700K IOPS* |
| | | Random Write | 700K IOPS* |
| | Self-Encrypting Drive Support | OPAL2 | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | | |
|---|--------------------------------------|-----------------------------------|------------|--|
| HP Z Turbo Drv 512GB TLC PCIe SED OPAL2 (Z2G9) | Capacity | 512GB | | |
| | Protocol | PCIe | | |
| | Form Factor | M.2 in native Slot on motherboard | | |
| | Controller | NVMe | | |
| | NAND Type | 3D TLC | | |
| | Endurance | 300TBW (TB Written) | | |
| | Reliability | 1.5M Hours | | |
| | Interface | PCI Express 4.0 x4 electrical | | |
| | Operating Temperature | 32° to 178° F (0° to 81° C) | | |
| | Performance | Sequential Read | 6400MB/s* | |
| | | Sequential Write | 3400MB/s* | |
| | | Random Read | 600K IOPS* | |
| | | Random Write | 600K IOPS* | |
| | Self-Encrypting Drive Support | OPAL2 | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | |
|---|--------------------------------------|-----------------------------------|------------|--|
| HP Z Turbo Drv 1TB TLC PCIe SED OPAL2 (Z2G9) | Capacity | 1TB | | |
| | Protocol | PCIe | | |
| | Form Factor | M.2 in native Slot on motherboard | | |
| | Controller | NVMe | | |
| | NAND Type | 3D TLC | | |
| | Endurance | 400TBW (TB Written) | | |
| | Reliability | 1.5M Hours | | |
| | Interface | PCI Express 4.0 x4 electrical | | |
| | Operating Temperature | 32° to 178° F (0° to 81° C) | | |
| | Performance | Sequential Read | 6500MB/s* | |
| | | Sequential Write | 5000MB/s* | |
| | | Random Read | 800K IOPS* | |
| | | Random Write | 800K IOPS* | |
| | Self-Encrypting Drive Support | OPAL2 | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | |
|---|------------------------------|-----------------------------------|------------|
| HP Z Turbo Drv 2TB TLC PCIe SED OPAL2 (Z2G9) | Capacity | 2TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 in native Slot on motherboard | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 500TBW (TB Written) | |
| | Reliability | 1.5M Hours | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 178° F (0° to 81° C) | |
| | Performance | Sequential Read | 6500MB/s* |
| | | Sequential Write | 5000MB/s* |
| | | Random Read | 800K IOPS* |
| | | Random Write | 800K IOPS* |
| Self-Encrypting Drive Support | OPAL2 | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|------------------------------|-----------------------------------|
| 256GB 2280 PCIe-4x4 Value M.2 SSD | Capacity | 256GB |
| | Protocol | PCIe |
| | Form Factor | M.2 in native Slot on motherboard |
| | Controller | NVMe |
| | NAND Type | 3D TLC |
| | Endurance | 150TBW (TB Written) |
| | Reliability | 1.5M Hours |
| | Interface | PCI Express 4.0 x4 electrical |
| | Operating Temperature | 32° to 158° F (0° to 70° C) |
| | Performance | Sequential Read |
| Sequential Write | | 1400MB/s* |
| Random Read | | 200K IOPS* |
| Random Write | | 400K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Hard Drives

| | | | |
|--|------------------------------|-----------------------------------|------------|
| 512GB 2280 PCIe-4x4 Value M.2 SSD | Capacity | 512GB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 in native Slot on motherboard | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 300TBW (TB Written) | |
| | Reliability | 1.5M Hours | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | 3400MB/s* |
| | | Sequential Write | 2500MB/s* |
| | | Random Read | 380K IOPS* |
| | | Random Write | 430K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|------------------------------|-----------------------------------|------------|
| 1TB 2280 PCIe-4x4 Value M.2 SSD | Capacity | 1TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 in native Slot on motherboard | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 400TBW (TB Written) | |
| | Reliability | 1.5M Hours | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | 3400MB/s* |
| | | Sequential Write | 2500MB/s* |
| | | Random Read | 500K IOPS* |
| | | Random Write | 440K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Graphics

| | | |
|---|-----------------------------------|---|
| AMD Radeon™ Pro W6600 8GB Graphics | Form Factor | Single slot, full-height, 9.5" length |
| | Graphics Controller | Navi23 architecture Power: 122 Watts Cooling Solution: Active Fan Heatsink |
| | Bus Type | PCI Express 4.0 x8 |
| | Memory | 8GB GDDR6 Memory Memory Bandwidth: 224 GB/s Memory Interface: 128 bit |
| | Connectors | 4x DisplayPort™ 1.4 with DSC - HDR Ready - Supports Multi-Stream Transport (MST) |
| | Max simultaneous displays | @ 60Hz with HDR Enabled 4x @ 3840x2160px (4K) 4x @ 5120x2880px (5K) 1x @ 7680x4320px (8K) |
| | Shading Architecture | DirectX 12 Shader Model 6.5 |
| | Supported Graphics APIs | DirectX®12 Ultimate OpenGL® 4.6 OpenCL™ 2.1 Vulkan™ 1.2 |
| | Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |
| | | HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html |

| | | |
|----------------------------------|-----------------------------------|--|
| NVIDIA® T400 2GB Graphics | Form Factor | Single Slot, Low Profile (2.7" H x 6.1" L) |
| | Graphics Controller | Turing architecture Max Power: 30 Watts Cooling Solution: Active fan heatsink |
| | Bus Type | PCI Express 3.0 x16 |
| | Memory | 2GB GDDR6 Memory Memory Bandwidth: 80 GB/s Memory Interface: 64 bit |
| | Connectors | 3x mDP (Mini DisplayPort™) 1.4 Connectors |
| | Max simultaneous displays | - 3x 3840 x 2160 @ 120Hz - 3x 5120 x 2880 @ 60Hz - supports Multi-Stream Transport (MST) |
| | Shading Architecture | DirectX 12 Shader Model 5.1 |
| | Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| | Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |

Technical Specifications - Graphics

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

NVIDIA® T400 4GB Graphics

| | |
|-----------------------------------|--|
| Form Factor | Single Slot, Low Profile (2.7"? H x 6.1"? L) |
| Graphics Controller | Turing architecture Max Power: 30 Watts Cooling Solution: Active fan heatsink |
| Bus Type | PCI Express 3.0 x16 |
| Memory | 4GB GDDR6 Memory Memory Bandwidth: 80 GB/s Memory Interface: 64 bit |
| Connectors | 3x mDP (Mini DisplayPort™) 1.4 Connectors |
| Max simultaneous displays | - 3x 3840 x 2160 @ 120Hz - 3x 5120 x 2880 @ 60Hz - supports Multi-Stream Transport (MST) |
| Shading Architecture | DirectX 12 Shader Model 5.1 |
| Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

NVIDIA® T600 4GB Graphics

| | |
|----------------------------------|---|
| Form Factor | Single Slot, Low Profile (2.7"? H x 6.1"? L) |
| Graphics Controller | Turing architecture Max Power: 40 Watts Cooling Solution: Active fan heatsink |
| Bus Type | PCI Express 3.0 x16 |
| Memory | 4GB GDDR6 Memory Memory Bandwidth: 160 GB/s Memory Interface: 128 bit |
| Connectors | 4x mDP (Mini DisplayPort™) 1.4 Connectors |
| Max simultaneous displays | - 4x 3840 x 2160 @ 120Hz - 4x 5120 x 2880 @ 60Hz - 2x 7680 x 4320 @ 60Hz - supports Multi-Stream Transport (MST) |
| Shading Architecture | DirectX 12 Shader Model 5.1 |

Technical Specifications - Graphics

| | |
|-----------------------------------|---|
| Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |
| | HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html |

NVIDIA® T1000 4GB Graphics

| | |
|-----------------------------------|---|
| Form Factor | Single Slot, Low Profile (2.7"? H x 6.1"? L) |
| Graphics Controller | Turing architecture Max Power: 50 Watts Cooling Solution: Active fan heatsink |
| Bus Type | PCI Express 3.0 x16 |
| Memory | 4GB GDDR6 Memory Memory Bandwidth: 160 GB/s Memory Interface: 128 bit |
| Connectors | 4x mDP (Mini DisplayPort™) 1.4 Connectors |
| Max simultaneous displays | - 4x 3840 x 2160 @ 120Hz - 4x 5120 x 2880 @ 60Hz - 2x 7680 x 4320 @ 60Hz - supports Multi-Stream Transport (MST) |
| Shading Architecture | DirectX 12 Shader Model 5.1 |
| Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |
| | HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html |

Technical Specifications - Graphics

| | | |
|-----------------------------------|-----------------------------------|---|
| NVIDIA® T1000 8GB Graphics | Form Factor | Single Slot, Low Profile (2.7" H x 6.1" L) |
| | Graphics Controller | Turing architecture Max Power: 50 Watts Cooling Solution: Active fan heatsink |
| | Bus Type | PCI Express 3.0 x16 |
| | Memory | 8GB GDDR6 Memory Memory Bandwidth: 160 GB/s Memory Interface: 128 bit |
| | Connectors | 4x mDP (Mini DisplayPort™) 1.4 Connectors |
| | Max simultaneous displays | - 4x 3840 x 2160 @ 120Hz - 4x 5120 x 2880 @ 60Hz - 2x 7680 x 4320 @ 60Hz - supports Multi-Stream Transport (MST) |
| | Shading Architecture | DirectX 12 Shader Model 5.1 |
| | Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| | Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |
| | | HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html |

| | | |
|---|-----------------------------------|---|
| NVIDIA® RTX™ A2000 12GB Graphics | Form Factor | Low-Profile Double Slot (2.7" H x 6.1" L) |
| | Graphics Controller | Ampere architecture Power: 70 Watts Cooling: Active Fan Heatsink |
| | Bus Type | PCI Express 4.0 x16 |
| | Memory | 12GB GDDR6 memory Memory Bandwidth: 288 GB/s Memory Interface: 192 bit Support Error-correcting code (ECC) |
| | Connectors | 4x mDP (Mini DisplayPort™) 1.4 Connectors |
| | Max simultaneous displays | 4x 4096 x 2160 @ 120 Hz, 4x 5120 x 2880 @ 60 Hz 2x 7680 x 4320 @ 60 Hz |
| | Shading Architecture | Shader Model 6.5 |
| | Supported Graphics APIs | OpenGL 4.6 DirectX 12 Vulkan 1.2 API support includes: CUDA, OpenCL 1.2 |
| | Available Graphics Drivers | Windows 10 64-bit Windows 11 64-bit Linux® 64-bit (selected Enterprise distributions) |

Technical Specifications - Graphics

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

Technical Specifications - Optical and Removable Storage

HP 9.5mm Slim DVD Writer

| | | |
|---|---|---|
| Description | 9.5mm height, tray-load | |
| Mounting Orientation | Either horizontal or vertical | |
| Interface Type | SATA/ATAPI | |
| Dimensions (WxHxD) | 128 x 9.5 x 127mm | |
| Supported Media Types | DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW | |
| Disc Capacity | DVD-ROM | 8.5 GB DL or 4.7 GB standard |
| Access Times | Full Stroke DVD | < 200 ms (seek) |
| | Full Stroke CD | < 200 ms (seek) |
| Maximum Data Transfer Rates | CD ROM Read | CD-ROM, CD-R Up to 24X CD-RW Up to 24X |
| | DVD ROM Read | DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 8X DVD-ROM DL Up to 8X DVD+R Up to 8X DVD-R Up to 8X |
| Power | Source | SATA DC power receptacle |
| | DC Power Requirements | 5 VDC ± 5%-100 mV ripple p-p |
| | DC Current | 5 VDC -< 800 mA typical, <1600 mA maximum |
| Operating Environmental (all conditions non-condensing) | Temperature | 41° to 122° F (5° to 50° C) |
| | Relative Humidity | 10% to 80% |
| | Maximum Wet Bulb Temperature | 84° F (29° C) |
| Operating Systems Supported | Windows 10, Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Linux® | |
| | No driver is required for this device. Native support is provided by the operating system. | |
| Kit Contents | HP SATA DVD Writer drive, installation guide. | |
| Approvals | USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3, FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUVT | |

Technical Specifications - Optical and Removable Storage

| | | | | |
|------------------------------------|---|--|--|--|
| HP 9.5mm Slim DVD-ROM Drive | Description | 9.5mm height, tray-load | | |
| | Mounting Orientation | Either horizontal or vertical | | |
| | Interface Type | SATA / ATAPI | | |
| | Dimensions (WxHxD) | 128 x 9.5 x 127mm | | |
| | Disc Capacity | DVD-ROM | Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB | |
| | Access Times | DVD-ROM Single Layer | < 110 me (typical) | |
| | | CD-ROM Mode 1 | < 110 ms (typical) | |
| | | Full Stroke DVD | < 230 ms (typical) | |
| | | Full Stroke CD | < 220 ms (typical) | |
| | Power | Source | SATA DC power receptacle | |
| | | DC Power Requirements | 5 VDC ± 5%-100 mV ripple p-p | |
| | | DC Current | 5 VDC - <800mA typical, < 1600 mA maximum | |
| | Operating Environmental (all conditions non-condensing) | Temperature | 41° to 122° F (5° to 50° C) | |
| | | Relative Humidity | 10% to 80% | |
| | | Maximum Wet Bulb Temperature | 84° F (29° C) | |
| | Operating Systems Supported | Windows 10, Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Linux® | | |
| | Kit Contents | No driver is required for this device. Native support is provided by the operating system. | | |
| | Approvals | 9.5mm Slim DVD-ROM Drive, slim SATA data/power cable, installation guide USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3, FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUVT | | |

Technical Specifications - Optical and Removable Storage

| | | |
|--------------------------------|------------------------------------|---|
| HP SD Media Card Reader | Description | USB3.0-SD4.0 NOTE: actual throughput is USB2.0. |
| | Interface Type | <ul style="list-style-type: none">• Support USB 2.0 LPM function• Support USB 3.0 U1/U2/U3 Power saving mode• Support USB 3.0 LTM function. |
| | Dimensions (WxHxD) | Dedicated slot in front bezel (orderable option) |
| | Supported Media Types | <ol style="list-style-type: none">i. Secure Digital Card (SD)ii. Secure Digital Support up to 2TBiii. Secure Digital HC (SDHC)iv. Secure Digital XC (SDXC)v. Support SD UHS50 modevi. miniSD *1vii. miniSDHC*1viii. MicroSD*1ix. MicroSDHC*1x. MicroSDXC*1 <p>NOTE: "*1"? means Adapter Needed</p> |
| | Operating Systems Supported | <p>No driver is required for this device. Native support is provided by the operating system.</p> <p>Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See http://www.microsoft.com.</p> <p>See http://www.microsoft.com/windows/windows-7/ for details.</p> |

Technical Specifications - Networking and Communications

| | | |
|---|--------------------------------|---|
| Integrated Intel® I219LM PCIe GbE Controller (Intel® vPro® with Intel® AMT 16.0¹) | Connector | RJ-45 |
| | Cabling | Twisted pair up to 100m |
| | Controller | Intel® I219LM GbE platform LAN connect networking controller |
| | Memory | 3 KB Tx and 3KB Rx FIFO packet buffer memory |
| | Data Rates Supported | 10/100/1000 Mbps |
| | Compliance | 802.1as/1588, 802.1p, 802.1Q, 802.3, 802.3ab, 802.3az, 802.3i, 802.3u, 802.3z |
| | Bus Architecture | PCI Express and SMBus |
| | Data Transfer Mode | PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state) |
| | Power Requirement | Requires 3.3V (integrated regulators for core Vdc) |
| | Boot ROM Support | Yes |
| | Network Transfer Mode | Full-duplex; Half-duplex |
| | Network Transfer Rate | 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps |
| | Management Capabilities | vPro®, WOL, auto MDI crossover, PXE, Muti-port teaming, RSS, ACPI, Advanced cable diagnostic, loopback modes, AMT 16.0 support, Circuit Breaker, VLAN, Multicast Listener Discovery (MLD) |

¹Requires activation and a system with a corporate network connection, an Intel® AMT enabled chipset, and network hardware and software. For notebooks, Intel AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating, or powered off. Results dependent upon hardware, setup, and configuration. For more information, visit: <https://www.intel.com/content/www/us/en/architecture-and-technology/intel-active-management-technology.html>

| | | |
|-----------------------------------|------------------------------|---|
| HP 1-Port 1GbE Flex IO NIC | Connector | RJ-45 |
| | Cabling | 1GbE over Category 5e (or better) up to 100m |
| | Controller | Realtek RTL8153 |
| | Data Rates Supported | 10/100/1000 Mbps |
| | Compliance | 802.3 (LAN) 802.3u (100BASE-TX) 802.3ab (1000BASE-T) 802.3x (Ethernet Flow Control) 802.1Q (Virtual LAN) 802.3az (Energy Efficient Ethernet) |
| | Bus Architecture | USB |
| | Power Requirement | Requires 3.3V (integrated regulators for core Vdc) |
| | Boot ROM Support | Yes |
| | Network Transfer Mode | Full-duplex; Half-duplex |

Technical Specifications - Networking and Communications

| | |
|--|--|
| Network Transfer Rate | 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps |
| Operating Temperature | 32° to 131° F (0° to 55° C) |
| Dimensions (HxW) | 1.5 in x 1.5 in. x 0.75 in (3.81 cm x 3.81 cm x 1.9 cm) |
| Operating System Driver Support | Windows 11 Windows 10 Linux® |

| | | |
|--|---|--|
| Intel® X550-T2 2-Port 10GbE NIC | Connector | Dual-port RJ-45 |
| | Cabling | 10GbE: Cat6a (or better) up to 100m 5GbE and below: Cat5e (or better) up to 100m |
| | Controller | Intel® Ethernet Controller X550 |
| | Network Transfer Rates Supported | 10GbE, 5GbE, 2.5GbE, 1GbE, 100MbE |
| | Data Path Width | PCIe Gen3x4 |
| | Power Requirement | 11.2W (typical) 13.0 (Maximum) |
| | Operating Temperature | 32° to 131° F (0° to 55° C) |
| | Dimensions (HxW) | 5.1 x 2.7 in (without brackets) |
| | Operating System Driver Support | Windows 11 64-Bit Windows 10 64-bit Linux® |
| | Kit Contents | <ul style="list-style-type: none"> • Intel® X550-T2 2-Port 10GbE NIC with standard height bracket attached • Low-profile bracket • Product Literature |

| | | |
|---|---|---|
| NVIDIA Mellanox ConnectX-6 DX Dual Port 10/25GbE SFP28 NIC | Connector | Dual-port SFP28 |
| | Cabling | Transceiver with Multi-Mode Fiber OM3 or OM4) |
| | Controller | ConnectX-6 Dx |
| | Network Transfer Rates Supported | 1/10/25 GbE |
| | Data Path Width | PCIe Gen4x8 |
| | Power Requirement | 19.74W Maximum power available through SFP28 port: 2.5W (each port) |
| | Operating Temperature | 32° to 131° F (0° to 55° C) |
| | Dimensions (HxW) | 6.22in. x 2.67in (158mm x 68mm) |
| | Operating System Driver Support | Windows 11 64-Bit Windows 10 64-bit Linux® |
| | Kit Contents | <ul style="list-style-type: none"> • NVIDIA Mellanox ConnectX-6 SFP28 25GbE NIC with standard height bracket attached • Low-profile bracket • Product Literature |

Technical Specifications - Networking and Communications

NOTE: The NVIDIA Mellanox ConnectX-6 DX network adapter requires either a PCIeG4 x4 or PCIeG4 x8 slot (electrical connection) to have full performance with two 25GbE SFP28 transceivers installed in the network adapter. When the network adapter is installed in a PCIeG3 x4 slot, the performance will be limited when installing two 25GbE SFP28 transceivers or installing a 25GbE SFP28 transceiver plus a 10GbE SFP+ transceiver

| | | |
|--|------------------------------|---|
| NVIDIA Mellanox 25GbE SFP28 Transceiver | Operating Temperature | 32°F to 158°F (0°C to 70°C) |
| | Operating Humidity | 5% to 85%, noncondensing |
| | Dimensions (HxWxD) | 0.47 x 0.54 x 2.22 inches |
| | Kit Contents | NVIDIA Mellanox 25GbE SFP28 Transceiver |

| | | |
|--|------------------------------|---|
| NVIDIA Mellanox 10GbE SFP+ SR Transceiver | Operating Temperature | 32°F to 158°F (0°C to 70°C) |
| | Operating Humidity | 5% to 85%, noncondensing |
| | Dimensions (HxWxD) | 0.47 x 0.54 x 2.22 inches |
| | Kit Contents | NVIDIA Mellanox 10GbE SFP+ SR Transceiver |

| | | |
|---------------------------------------|---|---|
| Intel® I350-T4 4-Port 1GbE NIC | Connector | 4 RJ-45 |
| | Cabling | Cat5e (or better) up to 100m |
| | Controller | Intel® Ethernet I350 Controller |
| | Network Transfer Rates Supported | 1GbE, 100MbE, 10MbE |
| | Data Path Width | PCIe Gen2.1x4 |
| | Power Requirement | 5W (typical) |
| | Operating Temperature | 32° to 131° F (0° to 55° C) |
| | Dimensions (HxW) | 2.75 x 5.5 inches (without brackets) |
| | Operating System Driver Support | Windows 11 Windows 10 Linux® |
| | Kit Contents | <ul style="list-style-type: none"> • Intel® I350-T4 4-Port 1GbE NIC with standard height bracket attached • Low-profile bracket • Product Literature |

Technical Specifications - Networking and Communications

| | | |
|--|--|--|
| HP Flex 1GbE Fiber LC Single Port | Connector | Fiber |
| | Cabling | 1GbE over Category OM1 (or better) up to 100m |
| | Controller | Microchip LAN7801 |
| | Data Rates Supported | 100/1000 Mbps |
| | Compliance | IEEE 802.1p priority encoding/tagging (QoS, CoS) IEEE 802.1q VLAN tagging IEEE 802.3x flow control |
| | Bus Architecture | USB |
| | Power Requirement | Requires 3.3V (integrated regulators for core Vdc) |
| | Boot ROM Support | Yes |
| | Network Transfer Mode | Full-duplex; Half-duplex |
| | Network Transfer Rate | 100BASE-X (half-duplex) 100 Mbps 1000BASE-X (half-duplex) 1000 Mbps 1000BASE-X (full-duplex) 2000 Mbps |
| | Operating Temperature | 32° to 158° F (0°C to 70°C) |
| | calvin | 1.5 in x 1.7 in. x 0.75 in (3.84 cm x 4.3 cm x 1.9 cm) |
| | Operating System Driver Support | Windows 11 64-Bit Windows 10 64-bit Linux® |

| | | |
|---|---|---|
| Intel® I225-T1 1-Port 2.5GbE NIC | Connector | RJ-45 |
| | Cabling | Cat5e (or better) up to 85m |
| | Controller | Intel® Ethernet I225 Controller |
| | Network Transfer Rates Supported | 2.5GbE, 1GbE, 100MbE, 10MbE |
| | Data Path Width | PCIe Gen3.1x1 |
| | Power Requirement | 1.9W (typical) |
| | Operating Temperature | 32° to 158° F (0°C to 70°C) |
| | Dimensions (HxW) | 2.7 in x 2.57 in. (68.7mm x 65.3mm) |
| | Operating System Driver | Windows 11 64-Bit Windows 10 64-bit Linux® |
| | Kit Contents | <ul style="list-style-type: none"> • Intel® I225-T1 1-Port 2.5GbE NIC with standard height bracket attached • Low-profile bracket • Product Literature |

Technical Specifications - Networking and Communications

**Intel® Wi-Fi 6E* AX211
802.11ax, BT 5.3, M.2
With Internal Antenna**

| | |
|------------------------------|--|
| WLAN Standards | 802.11abgn+acR2+axR2(Pre-Standard) MIMO 2x2 High performance, low power dual band Pre-Standard-802.11ax R2 2x2, both with 160MHz channel support - Wi-Fi 6E |
| Antenna | 2x2 Dual- Band (internal) |
| Bluetooth Standards | 5.2 |
| Operating Temperature | 32° to 176° F (0° to 80° C) |
| Interface | M.2 CNVio2 |
| Dimensions | M.2 2230 |

NOTE: The AX211 with internal antenna only support WIFI 6

*Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

**Intel® Wi-Fi 6E* AX211
802.11ax, BT 5.3, M.2
With External Antenna**

| | |
|------------------------------|--|
| WLAN Standards | 802.11abgn+acR2+axR2(Pre-Standard) MIMO 2x2 High performance, low power dual band Pre-Standard-802.11ax R2 2x2, both with 160MHz channel support - Wi-Fi 6E |
| Antenna | 2x2 Dual- Band (External) |
| Bluetooth Standards | 5.2 |
| Operating Temperature | 32° to 176° F (0° to 80° C) |
| Interface | M.2 CNVio2 |
| Dimensions | M.2 2230 |

NOTE: The AX211 with external antenna support WIFI 6E

*Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.


Technical Specifications - Palletization

Palletization

Ocean Shipping uses a 20' x 40' x 40' container (490mm x 199mm x 516mm) with 4 layers; 2x6=12 pieces per layer for a total of 48 pieces per pallet


Air shipping uses 490mm x 199mm x 516mm carton with 2 layers; 2x6=12 pieces per layer for a total of 24 pieces per pallet.

Ocean Shipping 20' & 40' G & 40' H Container



Carton: 490*199*516 mm
2*6 = 12 pcs/layer
12*4 layer = 48 pcs/pallet

Air Shipping



Carton: 490*199*516 mm
2*6 = 12 pcs/layer
12*2 layer = 24 pcs/pallet

Container Loading

20' CONTAINER



For Sea Air: 12*4 layer = 48 pcs/20' Container

40'G CONTAINER



For Sea Air: 24*4 layer = 96 pcs/40'G Container

40'H CONTAINER



For Sea Air: 24*4 layer = 96 pcs/40'H Container

Summary of Changes

| Date of change: | Version History: | | Description of change: |
|------------------------|-------------------------|---------|---|
| March 8, 2022 | From v1 to v2 | Changed | Format |
| March 16, 2022 | From v2 to v3 | Changed | Social and Environmental Responsibility section |
| May 6, 2022 | From v3 to v4 | Changed | Processors, Graphics, Networking and Communications sections |
| May 19, 2022 | From v4 to v5 | Changed | Overview section in Packaged Dimensions subsection |
| June 1, 2022 | From v5 to v6 | Changed | Operating Systems and SATA Hard Drives sections |
| June 15, 2022 | From v6 to v7 | Changed | Networking and Communications section |
| July 1, 2022 | From v7 to v8 | Changed | Declared Noise Emissions section |
| August 1, 2022 | From v8 to v9 | Changed | Format pages 1-3, Overview section and Supported Components |
| August 4, 2022 | From v9 to v10 | Changed | Format |
| September 1, 2022 | From v10 to v11 | Changed | Graphics, Optical and Removable Storage Networking and Communications sections |
| October 1, 2022 | From v11 to v12 | Changed | Graphics, Networking and Communications sections |
| December 12, 2022 | From v12 to v13 | Changed | Format page 3 |
| January 1, 2023 | From v13 to v14 | Changed | Networking and Communications section |
| February 1, 2023 | From v14 to v15 | Added | AMD Radeon Pro WX 3200 4GB (4)mDP GFX, w/2 mDP-to-DP adapters to Graphics section |
| March 1, 2023 | From v15 to v16 | Changed | Manageability section |
| March 30, 2023 | From v16 to v17 | Changed | Processors section |
| April 1, 2023 | From v17 to v18 | Changed | Networking and Communications section |
| April 25, 2023 | From v18 to v19 | Changed | Social and Environmental Responsibility section |
| May 1, 2023 | From v19 to v20 | Changed | Miscellaneous section |
| June 1, 2023 | From v20 to v21 | Changed | Graphics, Social and Environmental Responsibility, Palletization sections |

title

© 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Intel Core, Pentium, Thunderbolt, vPro and Xeon are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ENERGY STAR® is a registered trademark owned by the U.S. Environmental Protection Agency. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. NVIDIA®, Quadro and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Red Hat® is a registered trademark of Red Hat, Inc. in the United States and other countries. Bluetooth is a trademark of its proprietor used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.