

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție	ocds-b3wdp1-MD-1741597159138
Obiectul achiziției:	Оргтехника для нужд подведомственных учреждений и примарии мун. Комрат

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Лот №1. Оргтехника для Примарии (ТВ студия)						
Minrray UV510E7 NDI Camera PTZ Full HD Zoom 20X NDI SDI HDMI set 3 cu controller Cadou	UV510E7	CN	Sony Group Corporation	1920x1080 60FPS, Unghi larg de vizualizare (3,3° tele - 54,7° wide). Senzor CMOS de inalta calitate de 1 / 2.8 inch Pan / TiltRotation ± 170 °, -30 ° ~ + 90 ° Viteza de control a panoului: 0,1 -60 ° / sec Viteza de control a inclinarii: 0,1-30 ° / sec Presetare panou de viteza: 60 ° / sec, inclinare: 30 ° / sec Numar presetat: 255 presetari (10 presetari ale telecomenzii) Dimensiune: 150mmX150mmX167.5mm Greutate 1,4KG	1920x1080 60FPS, Unghi larg de vizualizare (3,3° tele - 54,7° wide). Senzor CMOS de inalta calitate de 1 / 2.8 inch. Pan / TiltRotation ± 170 °, -30 ° ~ + 90 °. Viteza de control a panoului: 0,1 - 60 ° / sec. Viteza de control a inclinarii: 0,1-30 ° / sec. Presetare panou de viteza: 60 ° / sec, inclinare: 30 ° / sec. Numar presetat: 255 presetari (10 presetari ale telecomenzii). Dimensiune: 150mmX150mmX167.5mm. Greutate 1,4KG	
Blackmagic ATEM Mini Pro Switcher Video HDMI	SWATEMMINIBPR	AU	Blackmagic Design Pty Ltd	Available M/E Layers 5 M/E. Audio Mixing 2-Channel Mixing, Input Video Format HDMI (10-Bit 4:2:2 YUV) 1080p at 23.98/24/25/29.97/30/50/59.94/60 fps 1080i 50/59.94/60 fps 720p 50/59.94/60 fps Power Consumption 36 W	Available M/E Layers 5 M/E. Audio Mixing 2-Channel Mixing, Input Video Format HDMI (10-Bit 4:2:2 YUV), 1080p at 23.98/24/25/29.97/30/50/59.94/60 fps, 1080i 50/59.94/60 fps, 720p 50/59.94/60 fps. Power Consumption 36 W. Dimensions 9.35 x 4.07 x 1.38" / 23.75 x 10.34 x 3.51 cm. Weight 19.4 oz / 550 g	

				Dimensions 9.35 x 4.07 x 1.38" / 23.75 x 10.34 x 3.51 cm Weight 19.4 oz / 550 g	
Aputure Lantern 90	AP-LANTERN90	CN	Aputure	Interior Color - White (Translucent) Light Compatibility - Built-In Speed Ring with Bowens S Mount Dimensions - ø: 0.6 x H: 4.9' / ø: 18 x H: 150 cm (Closed) ø: 3 x H: 2.3' / ø: 90 x H: 70 cm (Open)	Interior Color - White (Translucent). Light Compatibility – Built-In Speed Ring with Bowens S Mount. Dimensions - ø: 0.6 x H: 4.9' / ø: 18 x H: 150 cm. (Closed) ø: 3 x H: 2.3' / ø: 90 x H: 70 cm (Open)
Aputure Light Dome III Softbox 89cm	AP-LIGHTDOMEIII	CN	Aputure	Interior Color - Silver Light Compatibility - Includes Speed Ring with Bowens S Mount Quick Open Type- Foldable Light Loss/Gain - 1.5-Stop Loss (with Diffuser and Baffle) 2.5-Stop Loss (with Diffuser and Baffle) Dimensions - ø: 35 x H: 23.6" / ø: 89 x H: 60 cm (Open) 34.6 x 7.1 x 2" / 88 x 18 x 5 cm (Closed) Weight - 4.9 lb / 2.2 kg	Interior Color – Silver Light. Compatibility - Includes Speed Ring with Bowens S Mount. Quick Open Type-Foldable. Light Loss/Gain - 1.5-Stop Loss (with Diffuser and Baffle), 2.5-Stop Loss (with Diffuser and Baffle). Dimensions - ø: 35 x H: 23.6" / ø: 89 x H: 60 cm (Open) 34.6 x 7.1 x 2" / 88 x 18 x 5 cm (Closed). Weight - 4.9 lb / 2.2 kg
Laptop Lenovo LOQ 3 15ARP9 Luna Gray	82V200L5UK	CN	Lenovo Group Limited	Display - 1920 x 1080 (144Hz) IPS, 15,6" Memory - RAM 24GB DDR5, SSD 512GB. Processor - AMD R7 7435HS (3.10 GHz - 4.55 GHz) Video Card - NVIDIA GeForce RTX 4050 (6GB) Bluetooth v5.1, USB 3.2 - 3x, WiFi 802.11ax, HDMI - 1x, RJ-45 - 1x, 3.5mm Jack - 1x, USB Type-C - 1x Dimensions - 359.86 x 258.7 x 23.9 mm Weight - 2.45kg	Display - 1920 x 1080 (144Hz) IPS, 15,6". Memory - RAM 24GB DDR5, SSD 512GB. Processor - AMD R7 7435HS (3.10 GHz - 4.55 GHz). Video Card - NVIDIA GeForce RTX 4050 (6GB). Bluetooth v5.1, USB 3.2 - 3x, WiFi 802.11ax, HDMI - 1x, RJ-45 - 1x, 3.5mm Jack 1x, USB Type-C – 1x. Dimensions - 359.86 x 258.7 x 23.9 mm. Weight - 2.45kg
Monitor Lenovo Think Vision T25D-10	61F3GAC6EU	CN	Lenovo Group Limited	Diagonala ecranului: 24 " Rezoluția Display-ului: 1920x1200 WUXGA Tip panou: IPS Rata maximă de reîmprospătare: 60 Hz Timp de răspuns: 4 ms D-Sub (VGA): 1x D-Sub	Diagonal – 25", Resolution 1920x1200 IPS 60Hz, luminosity 300 cd/mZ, Color ranges RGB 99%, Color depth 8 bits, HDMI – 1, DisplayPort – 1, 3.5mm jack – Yes. Wall mounting VESA 100x100, size 54.8 x 50.9 x 26 cm, Weight 5.5 kg

				Intrări HDMI: 2x HDMI 1.4 DisplayPort: 1x DP 1.2	
Amaran COB 200d S Daylight LED Monolight	AC200DS	CN	Aputure	Color Temperature - 5600K, CRI 96, TLCI 99, CQS 95 Photometrics - 110° at 5600K:732 fc / 7890 Lux at 3.3' / 1 m 87 fc / 945 Lux at 9.8' / 3 m 33 fc / 364 Lux at 16.4' / 5 m 26° at 5600K: 5183 fc / 55,800 Lux at 3.3' / 1 m (with Reflector) 532 fc / 5730 Lux at 9.8' / 3 m (with Reflector) 187 fc / 2021 Lux at 16.4' / 5 m (with Reflector) Front Accessory Mount - Bowens S Weight - 3.44 lb / 1.56 kg (Fixture)	Color Temperature - 5600K, CRI 96, TLCI 99, CQS 95. Photometrics - 110° at 5600K:732 fc / 7890 Lux at 3.3' / 1 m, 87 fc / 945 Lux at 9.8' / 3 m, 33 fc / 364 Lux at 16.4' / 5 m, 6° at 5600K: 5183 fc / 55,800 Lux at 3.3' / 1 m (with Reflector), 532 fc / 5730 Lux at 9.8' / 3 m (with Reflector), 187 fc / 2021 Lux at 16.4' / 5 m (with Reflector) Front Accessory Mount - Bowens S. Weight - 3.44 lb / 1.56 kg (Fixture)
SmallRig AD-01 Heavy-Duty Trepied cu Cap Fluid 186 cm	AD-01	CN	SmallRig	Camera Mounting - 1/4"-20 & 3/8"-16 Screws (Plate: 501 Type) Head Type - Fluid Head, Primary Material - Aluminum Load Capacity - 17.6 lb / 8 kg Maximum Working Height - 73.2" / 186 cm Minimum Working Height - 33.5" / 85 cm Closed Length - 35" / 88.9 cm Weight - 8.8 lb / 4 kg	Camera Mounting - 1/4"-20 & 3/8"-16 Screws (Plate: 501 Type). Head Type - Fluid Head, Primary Material - Aluminum. Load Capacity - 17.6 lb / 8 kg. Maximum Working Height - 73.2" / 186 cm. Minimum Working Height - 33.5" / 85 cm. Closed Length - 35" / 88.9 cm. Weight - 8.8 lb / 4 kg
Butterfly light Stativ (Stand) 3.7m Pro cu amortizare pneumatica pentru Lumini, Boom YS9020	YS9020	CN	Shenzhen Yongnuo Photographi c Equipment Co., Ltd..	Material: Robust metal construction (aluminum) Maximum Height: 370 cm. Minimum Height: 106 cm Sections: Telescopic, 4 sections (diameters: 40-25 mm)	Material: Robust metal construction (aluminum) Maximum Height: 370 cm Minimum Height: 106 cm Sections: Telescopic, 4 sections (diameters: 40-25)
Audio-Technica U851RbO Omnidirectional Condenser Boundary Microphone (Black)	U851RBO	JP	Audio-Technica Corporation	Element Type - Electret Condenser Controls - Low Cut/HPF Frequency Response - 20 Hz to 20 kHz Maximum SPL - 132 dB Cable Length - 25' / 7.62 m Weight - 8.92 oz / 253 g	Element Type - Electret Condenser Controls - Low Cut/HPF Frequency Response - 20 Hz to 20 kHz, Maximum SPL - 132 dB Cable Length - 25' / 7.62 m
Rode RodeCaster Pro II Integrated Audio Production Studio	RCP2	AU	Freedman Electronics Pty Ltd	Channels of I/O Analog: 4 Inputs / 4 Outputs uilt-In DSP - Yes Maximum Sampling Rate - 48 kHz / 24-Bit Number of Microphone Inputs - 4 Input Level Adjustment - 6x Fader Number of Headphone Mixes - 4x Assignable with Mix-Minus Dimensions - 12.2 x 10.7 x 3.3" / 30.9 x 27.3 x 8.3 cm Weight - 4.4 lb / 2.0 kg	Channels of I/O Analog: 4 Inputs / 4 Outputs built-In DSP - Yes, Maximum Sampling Rate - 48 kHz / 24-Bit Number of Microphone Inputs - 4, Input Level Adjustment - 6x Fader, Number of Headphone Mixes - 4x Weight - 2.0 kg
VSS-19L	VSS-19L	UA	Videosolutio n Group	Size: 18,5 in Mirror: Beam splitter: 30/70, ultra clear, anti-reflection coating Size: 450x480 mm (17,7x18,9 in)	Size: 18,5 in, Mirror: Beam splitter: 30/70, ultra clear, anti-reflection coating Size: 450x480 mm (17,7x18,9 in)

LILLIPUT FS7 Monitor	LILLIPUT FS7	CN	Zhangzhou Lilipu Electronic Technology Co., Ltd	7" 1920 x 1200 3G-SDI and HDMI Monitor, 500 cd/m ² Brightness Histogram / Aspect Markers / Peaking, Wide 7 to 24V Power Input Package Weight - 2.55 lb Box Dimensions (LxWxH) - 8.15 x 5.9 x 3.6"	7" 1920 x 1200 3G-SDI and HDMI Monitor, Wide 7 to 24V Power Input, 170° Viewing Angle, Histogram / Aspect Markers / Peaking, 500 cd/ m ² Brightness, Package Weight 2.55 lb	
Всего по лоту №1.						

Semnat: _____ Numele, Prenumele: Zapsa Andrei În calitate de: Administrator
Ofertantul: IM O-Video Grup SRL Adresa: or. Chisinau, str. Valea Trandafirilor nr. 20 of. 179