

TECHNICAL DATA

Mains voltage	90-240 V~ / 50-60 Hz	
Max absorbed power	300VA	
Power fuses	2 x T3.15AL, 250V (mains voltage 180-240 Vac) 2 x T6.3AL, 250V (mains voltage 90-130 Vac)	
Operative mode	Resistive / Capacitive	
Working frequencies	450 - 550 kHz	
Max Output Power	150 Watt @ 300 Ohm / 250 VA @ 500 Ohm	
Power Step	1 until 10 / 5 over 10	
Action/Pause Time	from 3 to 10 seconds / from 0 to 10 seconds	
Treatment time	from 1 to 60 min	
Electrical Safety class (IEC60601-1)	I BF	
Medical Device class (MDR 2017/745/UE)	IIB	
EMC environment	A	
Neutral Electrode type	F	
Dimensions (HxWxD)	170 x 315 x 390 mm	
Maximum current on reference load	650 mA (Heating factor 25 A ² s)	
Weight	5 kg	
Environmental characteristics	WORKING	STORAGE
Temperature	from +10 °C to +40 °C	from -10 °C to +50 °C
Moisture	from 30% to 75%	from 10% to 85%
Atmospheric pressure	from 70kPa to 106kPa	from 50kPa to 106kPa