

TECHNICAL PARAMETER

技术参数 Li-SOCl₂ Battery



类型 Type	国际型号 Shape	标准型号 Model	最大外形尺寸 (Ømm×mm) Max.Size	公称电压(V) Nominal Voltage	终止电压(V) Termination Voltage	容量 (mAh) Capacity	最大连续 工作电流(mA) Max. Constant current	重量(g) Weight
容量型 Bobbin type	/	ER10280	10.5×28.0	3.6	2	500	10	5
	AAA	ER10450	10.5×45.5	3.6	2	800	15	9.5
	1/2AA	ER14250	14.5×25.4	3.6	2	1200	25	11
	2/3AA	ER14335	14.5×33.5	3.6	2	1650	40	13
	AA	ER14505	14.5×50.5	3.6	2	2700	65	19
	2/3A	ER17335	17.0×33.5	3.6	2	2200	100	19
	/	ER17505	17.0×50.5	3.6	2	3500	100	28
	A	ER18505	18.5×50.5	3.6	2	4000	130	32
	C	ER26500	26.2×50.0	3.6	2	9000	180	55
	CC	ER261020	26.2×102.0	3.6	2	17000	200	100
	D	ER34615	34.0×61.5	3.6	2	19000	230	107

SMART METER SOLUTION

智能电表电源解决方案



产品优势 Product advantages

整体解决方案: 拥有锂/亚硫酰氯电池、ER+RHC、ER+LIC全系列解决方案
 市场应用验证: 超过12年市场应用验证
 保证安全可靠: 拥有UL、ATEX、国网认证
 产品核心优势: 脉冲电流大、长寿命、宽温范围(-40℃~+85℃)、安全可靠、低自放电率

Overall solution: A full range of solutions for lithium / thionyl chloride batteries, ER+RHC, and ER+LIC
 Market application: More than 12 years of market application

Guaranteed safe and reliable: With UL, ATEX, and State Grid certified

Product key advantages: Large pulse current, long life, wide temperature range (-40℃~+85℃), safe and reliable, low self-discharge rate

