

RG-EW300N 300 Mbps Wireless Smart Router

DATASHEET



/ Highlights

- Stable as always
- Four Mode supported: Router Mode, Repeater Mode, AP Mode, WISP Mode
- Easy setup
- Life-time free cloud management supported
- Easy management, easy life
- Three-year warranty

Highlight Features





Stable as Always

In a router, Flash and RAM are vital for storing and processing data, ensuring smooth and efficient network performance.

Memory

16 MB Flash

4 MB Flash

64 MB RAM

32 MB RAM

RG-EW300N

Traditional 300 Mbps Router



Router Mode

Create a private wireless network and connect devices to the Internet.





AP Mode

Add wireless capabilities to a wired network, extending the Wi-Fi coverage.





Repeater Mode

Extend the wireless signal to expand Wi-Fi coverage, eliminating dead zones.





WISP Mode

Connect to the ISP's wireless network and share the network connection with other devices.







RG-EW300N

Highlight Features

Good Helper for Your Family Management

Parental Control

Health Mode

Reyee Router App allows you to manage the internet access authority of the specified terminal, including the time limit, speed limit and black/white list setup



Good Helper for Your Family Management

Parental Control


Health Mode

The health mode limits the radiation exposure and blacks out the indicator lights for you to have a good sleep.




Easy Setup

Newbie-friendly configuration, connecting to the internet by a few clicks





Highlight Features



.

Specifications

| | Basic |
|---------------------------|---|
| Dimensions (W×D×H) | 180 mm × 120 mm × 27 mm (7.09 in. ×4.72 in. × 1.06 in. antennas not included) |
| Weight | 0.18 kg (packages not included) |
| Wi-Fi Standards | Wi-Fi 4 (802.11n) |
| MIMO | 2.4GHz, 2×2 MIMO |
| Max. Wi-Fi Speed | 2.4 GHz: 300 Mbps |
| Channel Width | 2.4 GHz: Auto/20/40 MHz |
| Antennas | 2 |
| Antennas Type | External Omnidirectional |
| Antennas Gain | 2.4 GHz: 5 dBi * |
| WAN Port | 1×10/100Base-T |
| LAN Ports | 3×10/100Base-T |
| Recommended Users | 8 |
| Max. Users | 16 |
| Power Supply | DC 5V/1.0A |
| Power Consumption | < 5 W |
| Operation Frequency Bands | 802.11b/g/n: 2.400 GHz to 2.483 GHz country-specific restrictions apply |
| Transmit Power | General: CE EIRP: ≤20dBm (2.4GHz) Myanmar: 2400~2483.5MHz ≤ 20dBm(EIRP) |
| Receive Sensitivity | 2.4 GHz:20MHz 802.11b: -98 dBm(1 Mbps) 802.11g: -94.5 dBm(6 Mbps), -77 dBm(54 Mbps) 802.11n: -94.5dBm(MCS0), -76 dBm(MCS7) |
| Operating Temperature | -10 °C to +40 °C (14 °F to 113 °F) |



| Basic | | | |
|-------------------------------|-------------------------|--|--|
| Operating Humidity | 5% to 95% Noncondensing | | |
| Certifications | CE | | |
| | Wireless | | |
| OFDMA | - | | |
| MU-MIMO | ✓ | | |
| BSS Coloring | - | | |
| Maximum Number of SSIDs | 3 | | |
| SSID Hiding | ✓ | | |
| Band Steering | - | | |
| Guest Wi-Fi | ✓ | | |
| WPA/WPA2 | ✓ | | |
| WPA3 | ✓ | | |
| Roaming | Layer 2 Roaming | | |
| Blacklist | ✓ | | |
| Reyee Mesh | - | | |
| Mesh Pairing by Hardware | - | | |
| Mesh Pairing by Mesh Button | - | | |
| Mesh Pairing by Eweb | - | | |
| Recommended Hop Count | - | | |
| Wi-Fi Optimization | - | | |
| QoS (WMM) | ~ | | |
| WPS | - | | |
| Transmission Power Adjustment | ~ | | |

Specifications

Static IP Assignment

Port-Based Flow Control

| | Hardware | |
|-----------------------------------|---|--|
| CPU | MT7628DAN | |
| Flash | 16 MB | |
| RAM/SDRAM | 64 MB | |
| Color | Black | |
| System LED Indicator | ✓ | |
| Reyee Mesh LED Indicator | NA | |
| Reyee Mesh Button | NA | |
| Power Button | - | |
| Reset Button | ✓ | |
| DC Connector Dimensions | Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm Length: 9.5 mm (Outer Diameter: 0.22 in. Inner Diameter: 0.08 in. Length: 0.37 in.) | |
| | WAN | |
| Static IP | ~ | |
| DHCP | ✓ | |
| PPPoE | ✓ | |
| Learning PPPoE Account & Password | ✓ | |
| VLAN Tagging | ~ | |
| LAN | | |
| DHCP Server | ~ | |
| Client List | ✓ | |

Specifications

| | Features | |
|------------------------------|---------------|--|
| TR069 | ✓ | |
| IPv6 | ✓ | |
| DDNS | ✓ | |
| IPTV | ✓ | |
| Alarm | ✓ | |
| Diagnosis | ✓ | |
| UPnP | ✓ | |
| ARP Binding | ✓ | |
| Port Mapping | ✓ | |
| DMZ Host | ✓ | |
| Rate Limitation of Terminals | ✓ | |
| Hardware Acceleration | ✓ | |
| MAC Address Cloning | ✓ | |
| Cloud Management | ✓ | |
| Repeater Mode | ✓ | |
| WISP Mode | ~ | |
| Security | | |
| PPTP VPN Server | - | |
| PPTP VPN Client | - | |
| L2TP VPN Client | - | |
| Parental Control | Time Schedule | |
| Protect TCP Flood Attacks | ✓ | |
| Protect ICMP Attacks | - | |
| Protect UDP Flood Attacks | - | |



| System | |
|-------------------------|---|
| Default Access/Password | 192.168.110.1 No Password Required by Default |
| URL Access | ✓ |
| Local Upgrade | ✓ |
| Online Upgrade | ✓ |
| APP Upgrade | ✓ |
| Syslog | ✓ |
| Backup | ✓ |
| Factory Reset | ✓ |
| Language | Chinese English Vietanmese Turkish Indonesian Thai traditioanl Chinese Spanish Russian Arabic Ukrainian Czech Italian |

Package Contents

| Package Information | RG-EW300N |
|---------------------|-----------|
| Wireless Router | 1 |
| Power Adapter | 1 |
| Quick Start Guide | 1 |
| Warranty Card | 1 |
| Cat5E UTP Cable | 1 |





Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global