

# 11.00R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(PSI)
SPX501	8.00	18PR	152/149	K	16.9	3550/3250	930
SPX508	8.00	18PR	152/149	K	17.9	3550/3250	930
SPX509	8.00	18PR	152/149	F	24.7	3550/3250	930
SP901	8.00	18PR	152/149	K	17.0	3550/3250	930
SP907	8.00	18PR	152/149	K	16.5	3550/3250	930
SP908	8.00	18PR	152/149	K	19.5	3550/3250	930
SP909	8.00	18PR	152/149	G	20.5	3550/3250	930
SP911	8.00	18PR	152/149	G	20.5	3550/3250	930
<b>SP912</b>	<b>8.00</b>	<b>18PR</b>	<b>152/149</b>	<b>K</b>	<b>20.0</b>	<b>3550/3250</b>	<b>930</b>
SP915	8.00	18PR	152/149	G	24.5	3550/3250	930
SP923	8.00	18PR	152/149	K	15.0	3550/3250	930
SP992	8.0	18PR	152/149	K	18.0	3550/3250	930
	8.0	20PR	153/150	K	18.0	3650/3350	970