

Battery System

AXE 30.0~60.0H-1HC-E1

- Adopt high -safety LFP battery
- Battery pack modular design, support 30 ~60kWh flexible expansion
- Support 1C continuous charge and discharge
- Battery pack compatible with 19 -inch cabinet installation
- Easy installation and maintenance
- Support multi-cabinet parallel operation



GROWATT

en.growatt.com

P O W E R
- I N G
T O M O R R O W

Datasheet	AXE 30.0H-1HC-E1	AXE 35.0H-1HC-E1	AXE 40.0H-1HC-E1	AXE 50.0H-1HC-E1	AXE 60.0H-1HC-E1
Control module	AXE 1000100-C1				
Number of control module	1				
Battery module	AXE 5.0H-E1 EU				
Battery module energy	5kWh				
Number of modules in series	6	7	8	10	12
Energy capacity	30kWh	35kWh	40kWh	50kWh	60kWh
Usable capacity	27kWh	31.5kWh	36kWh	45kWh	54kWh
Rated output power	30kW	35kW	40kW	50kW	60kW
Max. output power* ¹	30kW	35kW	40kW	50kW	60kW
Dimension (W/H/D)	600/2000/800mm				
Weight	≤0.48t	≤0.53t	≤0.58t	≤0.7t	≤0.8t
Nominal voltage	307.2V	358.4V	409.6V	512V	614.4V
Operating voltage range	278.4~340.8V	324.8~397.6V	371.2~454.4V	464~568V	556.8~681.6V
Nominal capacity	100Ah(@25°C)				
Battery type	Cobalt Free Lithium Iron Phosphate (LFP)				
Ingress protection	IP20				
Installation	Floor stand				
Operating temperature	-10~50°C				
Relative humidity	5% ~ 95%				
Cooling	Air-Cooling				
Warranty* ²	5 years				
Noise emission	<60dB				
Maximum elevation	≤2000m				
Control Module AXE 1000100-C1					
Dimension(W/H/D)	482/131/580mm				
Weight	≤15kg				
Communication port	CAN/RS485/USB				
Operating voltage range	120V-1000Vdc				
Maximum current	100A				
Monitoring parameters	SOC, System voltage, current, cell voltage,cell temperature, PCBA temperature				
Battery Module AXE 5.0H-E1 EU					
Nominal energy	5kWh				
Nominal voltage	51.2V				
Pack operating voltage/range	46.4~56.8V				
Battery module dimension (W/H/D)	482/131/580mm				
Battery module weight	≤47kg				
UN 38.3, IEC 62619, IEC 60730, IEC 62477, CE, RoHS, UKCA					

* 1 Depend on the max. battery charge/discharge power of the inverter.

* 2 Detailed warranty terms should be negotiated with Growatt in the warranty agreement.

* Nominal charge/discharge current and power derating will occur related to temperature and SOC.

SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. All specifications are subject to change without notice.

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Rechargeable Li-ion Battery system (Energy Storage System)
Name and address of the applicant	Shenzhen Growatt New Energy Co., Ltd. 4-13/F, Building A, Sino-German(Europe) Industrial Park Hangcheng Ave, Bao'an District, Shenzhen, Guangdong, P.R. China
Name and address of the manufacturer	Shenzhen Growatt New Energy Co., Ltd. 4-13/F, Building A, Sino-German(Europe) Industrial Park Hangcheng Ave, Bao'an District, Shenzhen, Guangdong, P.R. China
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	Guangdong Growatt New Energy Co., Ltd. Growatt Industrial Park, No.17 Pingheng Road Pingtan Town, Huiyang District, Huizhou, Guangdong, P.R. China
Ratings and principal characteristics	For model of AXE 15.0~60.0H-1HC-E1: Nominal Capacity: 100Ah For more ratings, refer to the test report.
Trademark / Brand (if any)	GROWATT (logo)
Customer's Testing Facility (CTF) Stage used	N/A
Model / Type Ref.	AXE 15.0H-1HR-E1, AXE 20.0H-1HR-E1, AXE 25.0H-1HR-E1, Additional models on page 2
Additional information (if necessary may also be reported on page 2)	See additional page(s) for further Additional information. For model differences, refer to the test report.
A sample of the product was tested and found to be in conformity with	IEC 62619:2022
As shown in the Test Report Ref. No. which forms part of this Certificate	CN24IDVO 001

This CB Test Certificate is issued by the National Certification Body



Date: 2025-03-03

TÜV Rheinland Japan Ltd.
4-25-2 Kita-Yamata, Tsuzuki-ku
Yokohama 224-0021, Japan
Mail: info@jpn.tuv.com

Signature:


A. Chen

Additional information :

AXE 30.0H-1HR-E1, AXE 35.0H-1HR-E1, AXE 40.0H-1HR-E1,
AXE 45.0H-1HR-E1, AXE 50.0H-1HR-E1, AXE 55.0H-1HR-E1,
AXE 60.0H-1HR-E1

AXE 15.0H-1HC-E1, AXE 20.0H-1HC-E1, AXE 25.0H-1HC-E1,
AXE 30.0H-1HC-E1, AXE 35.0H-1HC-E1, AXE 40.0H-1HC-E1,
AXE 45.0H-1HC-E1, AXE 50.0H-1HC-E1, AXE 55.0H-1HC-E1,
AXE 60.0H-1HC-E1

AXE 50.0H-1HT-S1, AXE 55.0H-1HT-S1, AXE 60.0H-1HT-S1,
AXE 15.0H-2HR-S1, AXE 20.0H-2HR-S1, AXE 25.0H-2HR-S1,
AXE 30.0H-2HR-S1, AXE 35.0H-2HR-S1, AXE 40.0H-2HR-S1,
AXE 45.0H-2HR-S1, AXE 50.0H-2HR-S1, AXE 55.0H-2HR-S1,
AXE 60.0H-2HR-S1

AXE 15.0H-2HC-S1, AXE 20.0H-2HC-S1, AXE 25.0H-2HC-S1,
AXE 30.0H-2HC-S1, AXE 35.0H-2HC-S1, AXE 40.0H-2HC-S1,
AXE 45.0H-2HC-S1, AXE 50.0H-2HC-S1, AXE 55.0H-2HC-S1,
AXE 60.0H-2HC-S1