

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: **21327984 din 20 decembrie 2024**

Obiectul achiziției: **Echipament de iluminat și proiectoare**

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată decătore autoritatea contractantă	Specificarea tehnică deplină propusă decătore ofertant	Standarde de referință
1	2	3	4	5	6	7
1.1. Compact Lighting Console	ChamSys MagicQ MQ70 Compact Console	China	ChamSys	Control your stage, studio, or live entertainment lighting system with the Compact Console. This compact lighting control console can control up to 24 DMX universes and features 12 faders, 8 attribute encoders, and 2 master faders, with support up to 12,288 fixtures. It features a built-in 10.1" multitouch display and Wi-Fi to control the console remotely. Compatible with the existing light console MagicQ General Software Specifications - Max Number of Universes: 24 Max Number of DMX Channels: 12,288 Max Number of Fixtures Supported: 12,288 Max Number of Cues: 5000 Max Number of Cue Stacks: 2000 Max Number of Groups: 5000 Max Number of Palettes: 4096 Number of Media Server Layers Supported: 50 (Each Different Content) Numbers of Shows: Virtually Unlimited USB I/O - 5 x USB-A Female Input/Output Video I/O - 1x HDMI Output Audio I/O - 1x 1/8" / 3.5 mm Input 1x 1/8" / 3.5 mm Output Other I/O - 4 x 5-Pin DMX 3 x RJ45 Ethernet 1 x MIDI Input 1 x MIDI Output 1 x LTC Input 1 x Remote Input Buttons and Controls - Playbacks: 10; Grand Master Fader: 1 Crossfade Master Fader: 1; Attribute Encoders: 8; Wireless - Wi-Fi Power Source - Plug-In Power (Included) AC Input Power - 110 to 240 VAC, 50 / 60 Hz Power Input - 1 x Neutrik powerCON TRUE1 UPS - 12 V Lead-Acid Battery	Control your stage, studio, or live entertainment lighting system with the Compact Console. This compact lighting control console can control up to 24 DMX universes and features 12 faders, 8 attribute encoders, and 2 master faders, with support up to 12,288 fixtures. It features a built-in 10.1" multitouch display and Wi-Fi to control the console remotely. Compatible with the existing light console MagicQ General Software Specifications - Max Number of Universes: 24 Max Number of DMX Channels: 12,288 Max Number of Fixtures Supported: 12,288 Max Number of Cues: 5000 Max Number of Cue Stacks: 2000 Max Number of Groups: 5000 Max Number of Palettes: 4096 Number of Media Server Layers Supported: 50 (Each Different Content) Numbers of Shows: Virtually Unlimited USB I/O - 5 x USB-A Female Input/Output Video I/O - 1x HDMI Output Audio I/O - 1x 1/8" / 3.5 mm Input 1x 1/8" / 3.5 mm Output Other I/O - 4 x 5-Pin DMX 3 x RJ45 Ethernet 1 x MIDI Input 1 x MIDI Output 1 x LTC Input 1 x Remote Input Buttons and Controls - Playbacks: 10; Grand Master Fader: 1 Crossfade Master Fader: 1; Attribute Encoders: 8; Wireless - Wi-Fi Power Source - Plug-In Power (Included) AC Input Power - 110 to 240 VAC, 50 / 60 Hz Power Input - 1 x Neutrik powerCON TRUE1 UPS - 12 V Lead-Acid Battery	

1.2. LED Light	Eurolite LED STP-14 Sunbar	China	Eurolite	<p>3-in-1 LED-Sunbar With warm white beam effects, stroboscope and ambient light 14 Warm white 3W LEDs with 6.5° beam angle for narrow beams 120 Bright RGB LEDs for mood lighting and colour animations 180 Cold white LEDs for fast, dynamic strobe effects Auto, Music, Master/Slave and DMX modes (2, 6, 34 or 37 DMX channels selectable) Music control via built-in microphone with adjustable microphone sensitivity Power-twist mains connection with loop-through output for power supply of up to 8 devices Fanless convection cooling via cooling fins Power supply: 100-240 V AC, 50/60 Hz Total connected load: 95 W Dimensions (L x H x D): 100 x 8.5 x 9 cm Weight: 3.92 kg</p>	<p>3-in-1 LED-Sunbar With warm white beam effects, stroboscope and ambient light 14 Warm white 3W LEDs with 6.5° beam angle for narrow beams 120 Bright RGB LEDs for mood lighting and colour animations 180 Cold white LEDs for fast, dynamic strobe effects Auto, Music, Master/Slave and DMX modes (2, 6, 34 or 37 DMX channels selectable) Music control via built-in microphone with adjustable microphone sensitivity Power-twist mains connection with loop-through output for power supply of up to 8 devices Fanless convection cooling via cooling fins Power supply: 100-240 V AC, 50/60 Hz Total connected load: 95 W Dimensions (L x H x D): 100 x 8.5 x 9 cm Weight: 3.92 kg</p>	
1.3. LED Strobe	Eurolite LED Super Strobe ABL	China	Eurolite	<p>3 Effects in one unit: strobe, blinder and ambient light 216 cool white LEDs (SMD 5730) for fast, dynamic strobe and blinder effects 144 additional RGB LEDs (SMD 5050) provide pleasant mood lighting RGB LEDs and cool white LEDs can be controlled separately RGB LEDs controllable in 1 or 48 segments, depending on choice of DMX mode Auto, music, master/slave and DMX modes 17 Integrated chaser programmes in auto and music mode Flash rate: 20 Hz Stepless RGB colour mixing Dimmer Addressing and settings via control unit with 4-digit LED display Music control via built-in microphone with adjustable microphone sensitivity 7, 13, 22 or 148 DMX channels selectable Flat metal housing with integrated wall bracket Adjustable mounting bracket Power Twist connections for easy series connection of up to 8 units Projection: flicker-free Power supply: 100-240 V AC, 50/60 Hz Power consumption: 130 W DMX input: 3-pin XLR male DMX output: 3-pin XLR female Dimensions (W x H x D): 45.5 x 25.5 x 8 cm Weight: 3.94 kg</p>	<p>3 Effects in one unit: strobe, blinder and ambient light 216 cool white LEDs (SMD 5730) for fast, dynamic strobe and blinder effects 144 additional RGB LEDs (SMD 5050) provide pleasant mood lighting RGB LEDs and cool white LEDs can be controlled separately RGB LEDs controllable in 1 or 48 segments, depending on choice of DMX mode Auto, music, master/slave and DMX modes 17 Integrated chaser programmes in auto and music mode Flash rate: 20 Hz Stepless RGB colour mixing Dimmer Addressing and settings via control unit with 4-digit LED display Music control via built-in microphone with adjustable microphone sensitivity 7, 13, 22 or 148 DMX channels selectable Flat metal housing with integrated wall bracket Adjustable mounting bracket Power Twist connections for easy series connection of up to 8 units Projection: flicker-free Power supply: 100-240 V AC, 50/60 Hz Power consumption: 130 W DMX input: 3-pin XLR male DMX output: 3-pin XLR female Dimensions (W x H x D): 45.5 x 25.5 x 8 cm Weight: 3.94 kg</p>	

1.4. Moving-Head Beam	Eurolite TMH XB-280 Moving-Head-Beam	China	Eurolite	<p>Bright, narrow beam with OSD 10 280W discharge lamp, colour wheel, gobos and prisms</p> <p>Beam angle: 2°</p> <p>Positioning: 540° PAN and 270° TILT (16-bit resolution)</p> <p>Rotating 8- and 24-facet prism, combinable for multi-facet effects, in both directions and at different speeds</p> <p>Frost filter</p> <p>Multi-colour filter</p> <p>Strobe effect with variable speed and random generator</p> <p>Dimmer</p> <p>Motorised focus</p> <p>kCompatible with QuickDMX</p> <p>Phantom-powered USB socket for optional QuickDMX, CRMX and WDMX receivers (available as accessories, not included)</p> <p>Control board with graphic LCD for setting DMX start address, PAN/TILT reverse, reset, lamp switching, hour meter</p> <p>Power Twist mains connection</p> <p>Colour wheel 14 dichroic colours and open</p> <p>Rainbow effect with variable speed in both directions</p> <p>Gobo wheel with static 13 gobos and open, plus shake effect</p> <p>19 CH DMX mode operable</p> <p>Unit is cooled by fan</p> <p>Controllable via DMX, stand-alone, master/slave function</p> <p>Music control via microphone</p> <p>Noise classification: Class 4 (loud noises)</p> <p>Power supply: 100-240 V AC, 50/60 Hz</p> <p>Power consumption: 385 W</p> <p>DMX connection: 3-pin XLR In / Out</p> <p>Dimensions WxDxH: 30 x 21 x 51 cm</p> <p>Weight: 14.80 kg</p>	<p>Bright, narrow beam with OSD 10 280W discharge lamp, colour wheel, gobos and prisms</p> <p>Beam angle: 2°</p> <p>Positioning: 540° PAN and 270° TILT (16-bit resolution)</p> <p>Rotating 8- and 24-facet prism, combinable for multi-facet effects, in both directions and at different speeds</p> <p>Frost filter</p> <p>Multi-colour filter</p> <p>Strobe effect with variable speed and random generator</p> <p>Dimmer</p> <p>Motorised focus</p> <p>kCompatible with QuickDMX</p> <p>Phantom-powered USB socket for optional QuickDMX, CRMX and WDMX receivers (available as accessories, not included)</p> <p>Control board with graphic LCD for setting DMX start address, PAN/TILT reverse, reset, lamp switching, hour meter</p> <p>Power Twist mains connection</p> <p>Colour wheel 14 dichroic colours and open</p> <p>Rainbow effect with variable speed in both directions</p> <p>Gobo wheel with static 13 gobos and open, plus shake effect</p> <p>19 CH DMX mode operable</p> <p>Unit is cooled by fan</p> <p>Controllable via DMX, stand-alone, master/slave function</p> <p>Music control via microphone</p> <p>Noise classification: Class 4 (loud noises)</p> <p>Power supply: 100-240 V AC, 50/60 Hz</p> <p>Power consumption: 385 W</p> <p>DMX connection: 3-pin XLR In / Out</p> <p>Dimensions WxDxH: 30 x 21 x 51 cm</p> <p>Weight: 14.80 kg</p>	
1.5. DMX Cable	EUROLITE DMX Cable 2x0.22 100m bk	Germani a	Eurolite	Cable DMX	Cable DMX	
1.6. Clamp	EUROLITE TPC-10 Coupler, silver	China	Eurolite	<p>Compatible with tubing Ø 48 - 51 mm</p> <p>Machine screw M10 with butterfly nut, split lock washer and washer</p> <p>Shutter: M8 with butterfly nut</p>	<p>Compatible with tubing Ø 48 - 51 mm</p> <p>Machine screw M10 with butterfly nut, split lock washer and washer</p> <p>Shutter: M8 with butterfly nut</p>	
1.7. Connector	Seetronic SCSM3 3pin XLR	China	Seetronic	3-pol XLR Male Connector	3-pol XLR Male Connector	
1.8. Connector	Seetronic SCSF3 3pin XLR	China	Seetronic	3-pol XLR Female Connector	3-pol XLR Female Connector	
1.9. Connector	Rean RCX5M-Z-000-1	China	Eurolite	3-pol XLR Female Connector	3-pol XLR Female Connector	

<p>Lotul nr. 2 Portable/Studio Lights</p>	<p>Aputure LS 300X V-Mount-Kit (EU)</p>	<p>China</p>	<p>Aputure</p>	<p>Bi-Color LED Monolight (V-Mount) Light Fixture Item Type - 1x LED Monolight Lumens - 56,000 Photometrics 105° at 3200K: 5100 Lux at 1 m, 580 Lux at 3 m, 220 Lux at 5 m 105° at 5600K: 6300 Lux at 1 m, 700 Lux at 3 m, 250 Lux at 5 m 3200K: 16,200 Lux at 1 m (with Reflector), 1300 Lux at 3 m (with Reflector), 450 Lux at 5 m (with Reflector) 5600K: 20,500 Lux at 1 m (with Reflector), 1700 Lux at 3 m (with Reflector), 550 Lux at 5 m (with Reflector) Color Temperature - 2700 to 6500K Color Modes - Daylight, Tungsten Color Accuracy Standard - CRI 96, TLCI 96, CQS 95 Dimming - App-Controlled / Controller Included / DMX (Continuous) • 0 to 100% Cooling System - Fan Beam Angle - 105° Front Accessory Mount - Bowens S Power & I/O Inputs/Outputs - Light Fixture 1x XLR 5-Pin Power Input Power Supply/Controller - 1x powerCON Power Input, 1x XLR 5-Pin Power Output, 1x XLR 5-Pin DMX Input, 1x XLR 5-Pin DMX Output Battery Plate Type - 2x V-Mount (Built-In) Input Power - 100 to 240 VAC, 50 / 60 Hz Included Adapter / Cable - 1x USA Type-A/B to powerCON Cable (19.7' / 6 m), 1x XLR 5-Pin Male to XLR 5-Pin Female Cable (3 m) Power Consumption - 350 W</p>	<p>Bi-Color LED Monolight (V-Mount) Light Fixture Item Type - 1x LED Monolight Lumens - 56,000 Photometrics 105° at 3200K: 5100 Lux at 1 m, 580 Lux at 3 m, 220 Lux at 5 m 105° at 5600K: 6300 Lux at 1 m, 700 Lux at 3 m, 250 Lux at 5 m 3200K: 16,200 Lux at 1 m (with Reflector), 1300 Lux at 3 m (with Reflector), 450 Lux at 5 m (with Reflector) 5600K: 20,500 Lux at 1 m (with Reflector), 1700 Lux at 3 m (with Reflector), 550 Lux at 5 m (with Reflector) Color Temperature - 2700 to 6500K Color Modes - Daylight, Tungsten Color Accuracy Standard - CRI 96, TLCI 96, CQS 95 Dimming - App-Controlled / Controller Included / DMX (Continuous) • 0 to 100% Cooling System - Fan Beam Angle - 105° Front Accessory Mount - Bowens S Power & I/O Inputs/Outputs - Light Fixture 1x XLR 5-Pin Power Input Power Supply/Controller - 1x powerCON Power Input, 1x XLR 5-Pin Power Output, 1x XLR 5-Pin DMX Input, 1x XLR 5-Pin DMX Output Battery Plate Type - 2x V-Mount (Built-In) Input Power - 100 to 240 VAC, 50 / 60 Hz Included Adapter / Cable - 1x USA Type-A/B to powerCON Cable (19.7' / 6 m), 1x XLR 5-Pin Male to XLR 5-Pin Female Cable (3 m) Power Consumption - 350 W</p>	
--	---	--------------	----------------	--	--	--

Semnata: Semnat electronic

Nume/prenume: Pantehovschi Vadim

Funcția în cadrul firmei: Director

Ofertantul: SRL "FALENAT"