

Table 5-11 For Omega IV Table (Table continued)

	Omega IV
Horizontal Float Movement	8-way
Horizontal Motorized Movement	NA
Longitudinal Speed	NA
Longitudinal Travel	110 cm (43.3")
Imaging coverage with table panning IGS 520, up to:	127 cm (50")
IGS 530, up to:	NA
IGS 540, up to:	
Transverse Travel	Manual +/-14 cm (+/-5.5")
Transverse Speed	NA
Vertical Travel	30 cm (12")
Vertical Travel above Floor	From 78 cm (30.7") to 108 cm (42.5")
Vertical Speed	2 cm/s (0.8"/s) at 50 Hz 2.5 cm/s (1"/s) at 60 Hz
Table Base	61 cm x 52 cm (24" by 20.5")
Tilt Travel	NA
Tilt Speed	NA
Table Rotation	+/- 180°
Patient Support Type	Cantilevered

Table 5-12 For Omega V Table

	Omega V
Table Top filtration	Less than 0.85 mm aluminium equivalent
Mattress filtration (including slicker if applicable)	less than 0.70 mm aluminium equivalent (1") less than 1.20 mm aluminium equivalent (2")
Mattress thickness (including slicker if applicable)	2.5 cm (1") 5 cm (2")
Maximum Patient Weight	204 kg (450 lb)
Maximum Table Load (including accessories)	304 kg (670 lb)
Maximum weight on table top (including accessories)	204 kg (450 lb)
Maximum weight on fixed table side rails	40 kg
Maximum weight on table end rail	20 kg
Table Top Length	333 cm (131")
Table Top Width	46 cm (18") in Patient Trunk Area - 67 cm (26.4") max
Horizontal Float Movement	8-way
Horizontal Motorized Movement	2-way
Longitudinal Speed	0 to 15 cm/s

Table 5-12 For Omega V Table (Table continued)

	Omega V
Longitudinal Travel	170 cm (67")
Imaging coverage with table panning IGS 520, up to:	187 cm (73")
IGS 530, up to:	195 cm (76")
IGS 540, up to:	201 cm (79")
Transverse Travel	Manual +/-14 cm (+/-5.5")
Transverse Speed	NA
Vertical Travel	30 cm (12")
Vertical Travel above Floor	From 78 cm (30.7") to 108 cm (42.5")
Vertical Speed	2 cm/s (0.8"/s) at 50 Hz 2.5 cm/s (1"/s) at 60 Hz
Table Base	61 cm x 52 cm (24" by 20.5")
Tilt Travel	NA
Tilt Speed	NA
<u>Table Rotation</u>	<u>+/- 180°</u>
Patient Support Type	Cantilevered

Table 5-13 For Innova^{IQ} Table

	Innova^{IQ} Table
Table Top filtration	Less than 0.85 mm aluminium equivalent
Mattress filtration (including slicker if applicable)	less than 1.20 mm aluminium equivalent
Mattress thickness (including slicker if applicable)	5 cm (2")
Maximum Patient Weight	250 kg (551 lb)
Maximum Table Load (including accessories)	320 kg (705 lb)
Maximum weight on table top (including accessories)	275 kg (606 lb)
Maximum weight on fixed table side rails	40 kg (88 lb)
Maximum weight on table end rail	N/A
Table Top Length	333 cm (131")
Table Top Width	46 cm (18") in Patient Trunk Area - 67 cm (26.4") max 53 cm (21") in Patient Trunk Area
Horizontal Float Movement	8-way
Horizontal Motorized Movement	8-way
Longitudinal Speed	0 to 25 cm/s
Longitudinal Travel	170 cm (67")
Imaging coverage with table panning IGS 520, up to:	187 cm (73")
IGS 530, up to:	195 cm (76")
IGS 540, up to:	201 cm (79")
Transverse Travel	Motorized +/-13 cm (+/-5.1")
Transverse Speed	0 to 10 cm/s