


# Auto Leakage Tester SHA-P6

Better care for your scopes



By alerting you to existing leaks in your flexible endoscopes, the SHA-P6 Automatic Leakage Tester helps to avoid costly repairs.





The SHA-P6 Auto Leakage Tester is specifically designed for use with PENTAX Medical flexible endoscopes to avoid costly service interventions.

### Improved operational efficiency

Default pressure setting, automated pressurization cycle, and air release reduce the risk for human error and potential risky variability within the reprocessing process.

#### Space saving and mobile

No need to have large space available in the reprocessing room, due to the handy format of SHA-P6. With the re-chargeable battery, the automatic leakage tester is usable in several stations without power connection need.

#### **Optimized economic outcomes**

Lowers overall repair costs, improves scope utilization and prevents downtime as a result of the optimized, automated process capability

## PENTAX Medical Auto Leakage Tester SHA-P6 Specifications

AC adapter	DC output voltage / current AC input frequency	7.5V, 1.6A 50 to 60Hz
Built - in packaged lithium battery	AC input voltage  Battery capacity	AC100 - 240V 2,600 mAh
Mode of Operation	вашегу сараспу	Continuous Operation
Operating Environment	Ambient temperature	10 to 40 °C (50 to 104°F)
Operating Environment	Relative humidity	30 to 85% BH
	Air pressure	700 to 1,060 hPa (10.2 to 15.4 psl)
Storage Environment	Ambient temperature	-20 to 60 °C (-4 to 140°F)
otolago ziiiii oiii	Relative humidity	10 to 85% BH
	Air pressure	700 to 1,060 hPa (10.2 to 15.4 psl)
Pressurization	,	Automatic (air pump)
Air release		Automatic rapid air release valve
Displayed pressure range		0 to 40 kPa (0 to 5.80 psl)
Pressurization setting range		20 to 30 kPa (in increments of 1kPa) (2.90 to 4.35 psl)
Size		154mm (W) x 63.2mm (H) x 95.6mm (D) (6.06in (W) x 2.49in (H) x 3.76in (D))
Weight		380g (0.84lb) (main unit only)
Electric shock protection Degree of Electric schock protection		Internal power supply equipment and Class II Equipment Type BF (Body Floating)
Electro Magnetic Compatibility		IEC60601 - 1 - 2 : 2007
Electrical Safety		IEC60601 - 1 : 2005 + A1 : 2012
IP Classification		IP22



PENTAX Europe GmbH

Julius-Vosseler-Straße 104 . 22527 Hamburg Tel.: +49 40 / 5 61 92 - 0 . Fax: +49 40 / 5 60 42 13

 $\hbox{E-mail: info.emea@pentaxmedical.com}\ .\ www.pentaxmedical.com$ 

