

Ricardo Generator

JW10GF

MODEL	JW10GF	
Prime Power(50Hz)	10KW	12.5 KVA
Standby Power(50Hz)	11KW	13.75KVA

Standard Features

General Features:

- ◆ Engine (192F Ricardo)
- ◆ Radiator cooling by fresh water
- ◆ 12V charge alternator
- ◆ Alternator: single bearing alternator IP23, insulation class H/H
- ◆ Absorber
- ◆ Dry type air filter, fuel filter, oil filter
- ◆ Main line circuit breaker
- ◆ Standard control panel
- ◆ Ripple flex exhaust pipe, exhaust siphon, flange, muffler
- ◆ Soundproof Enclosure: Painted in an electrostatic field with increased soundproofed, weather-resistant, high-temperature-resistant, and non-flammable
- ◆ Automatic Transfer Switch
- ◆ User manual



Generator Ratings

Voltage(V)		Hz	Phase	P.F ($\cos \phi$)	Prime Amps (A)	Prime Ratings (KW/KVA)	
440	254	50	3	0.8	15.2	10	12.5
415	240	50	3	0.8	16.1	10	12.5
400	230	50	3	0.8	17.1	10	12.5
380	220	50	3	0.8	18.9	10	12.5

●Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

●Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Standard Features

Weifang Junwei Machinery Co., Ltd provides a full line of brand new and high quality products. Each and every generator is strictly factory tested. Warranty is according to our standard conditions: ① 24 months, counted on the day Junwei Machinery sold to the first buyer; ② Two year after installation; ③ 2000 running hours (accumulated); subject to the earlier one. Service and parts are available from Weifang Junwei Machinery Co., Ltd.

Ricardo Generator

JW10GF

Engine Data

Manufacturer / Model: 192F Ricardo

Air Intake System: Naturally intake

Type: Diesel, Four-stroke, Direct injection, 1 Cylinders, Wet cylinder, Water cooling, with a fuel preheater and a low oil level sensor with automatic engine shutdown

Cylinder Type: Water-cooled cylinder liner

Start mode: Electric starting, Batteries, rack and cable

Cooling mode: Closed water cooling

Displacement: 1.35

Bore and Stroke: 110*117(mm)

Compression Ratio: 17.0:1

Rated RPM: 1500rpm

Max. Standby Power: 12KW

Governor Type: Mechanical

Exhaust system

Max Back Pressure: 10kPa

Air Intake System

Max Intake Restriction: 5kPa

Fuel System

100%(Prime Power) Load: 238g/kw.h

Oil System

Total Oil Capacity:4L

Cooling System

Total Coolant Capacity : 5L

Alternator Specification

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34-1, CSA22.2 and AS1359 standards.

Alternator Data

Manufacturer: WEIFANG JUNWEI MACHINERY CO., LTD

Number ofPhase: 3

Connecting Type: 3 phase,"Y" type connecting

Number of bearing: 1

Ricardo Generator

JW10GF

Power factor: 0.8

Protection grade: IP23

Altitude : $\leq 1000\text{m}$

Exciter type: Brushless, self-exciting

Insulation class: H

Telephone influence factor(TIF): ≤ 50 THF:

$\leq 2\%$

Alternator Capacity: 12.5 KVA

Alternator Efficiencies: 85%

Air Cooling Flow: 0.09m³/s

Adjusting rate of stable voltage: $\pm 0.5\%$

Generating Set Data

Voltage Regulation: $\geq \pm 5\%$

Voltage Regulation, Stead State: $\leq \pm 1\%$

Sudden Voltage Warp: $\leq +20\%$

Sudden Voltage Warp: $\leq -15\%$

Voltage Stable Time: $\leq 5\text{S}$

Voltage unbalance: $\leq 1\%$

Frequency Regulation, Stead State: $\leq 5\%$

Frequency Waving: $\leq 0.5\%$

Sudden Frequency Warp: $\leq +10\%$

Transient frequency deviation: $\leq -7\%$

Frequency Recovery Time: $\leq 3\text{S}$

Sockets

3 (1 x 400V 16A; 2 x 230V 16A).

Standard Features

◆ Standard Auto Control System

◆ Starting batteries

◆ Exhaust System

◆ MCCB

◆ Battery switch

◆ Shock pad

◆ Special tool

◆ Oil Drain Valve

◆ Documents

Ricardo Generator

JW10GF

Dimension & Weight



Soundproof Type

Overall Size: 800(mm)×600 (mm) ×600 (mm)

Weight: 200kg

Control Panel



Weifang Junwei Machinery Co., Ltd uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses Smartgen LCD display, optional Chinese and English/ Russian/ Spanish display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability.

Typical Projects

