

# EC CERTIFICATE Production Quality Assurance

Certificate No.: 10000448399-PA-NA-NOR

Project No.: PRJC-519733-2015-MSL-NOR\_MDD Valid Until: 27 May 2024

This is to certify that the quality system of:

Arctiko Oddesundvej 39, Esbjerg N, 6715

Esbjerg N, 6 Denmark

For production and final product inspection/testing of: Blood bank refrigerators

Has been assessed with respect to:

The conformity assessment procedure described in Annex V of Council Directive 93/42/EEC on Medical Devices, as amended

and found to comply

Further details of the product(s) and conditions for certification are given overleaf.

Place and date: Høvik, 20 May 2021



For the issuing office: Notified Body 2460 DNV Product Assurance AS

Mariann Jeremiassen Principal Assessor

Notice: The Certificate is subject to terms and conditions as set out in the Certification Agreement. Failure to comply may render this Certificate invalid. NOTIFIED BODY 2460: DNV Product Assurance AS, Veritasveien 3, 1363 Høvik, Norway, Tel +47 67 57 88 00, <u>www.dnv.com</u>



Certificate No.: 10000448399-PA-NA-NOR Place and date: Høvik, 20 May 2021

#### Jurisdiction

Application of Council Directive 93/42/EEC of 14 June 1993, adopted as "Forskrift om Medisinsk Utstyr" by the Norwegian Ministry of Health and Care Services.

Certificate history:

Revision	Description	Issue Date
0.0	Original Certificate	2021-05-20

#### Products covered by this Certificate:

Product Description	Product Name	Class
Blood bank refrigerators	BBR100, BBR300, BBR500, BBR700, BR1400, BBR100-D, BBR300-D, BBR500-D, BBR700-D, BBR1400-D	lla

The complete list of devices is filed with the Notified Body

#### Sites covered by this certificate

Site Name	Address
Arctiko	Oddesundvej 39, Esbjerg N, 6715 Denmark

NOTIFIED BODY 2460: DNV Product Assurance AS, Veritasveien 3, 1363 Høvik, Norway, Tel +47 67 57 88 00, www.dnv.com



Certificate No.: 10000448399-PA-NA-NOR Place and date: Høvik, 20 May 2021

### **Terms and conditions**

The certificate is subject to the following terms and conditions:

- Any producer (see 2001/95/EC for a precise definition) is liable for damage caused by a defect in his product(s), in accordance with directive 85/374/EEC, as amended, concerning liability of defective products.
- The certificate is only valid for the products and/or manufacturing premises listed above.
- The Manufacturer shall fulfil the obligations arising out of the quality system as approved and uphold it so that it remains adequate and efficient.
- The Manufacturer shall inform the Notified Body of any intended updating of the quality system and the Notified Body will assess the changes and decide if the certificate remains valid.
- Periodical audits will be held, in order to verify that the Manufacturer maintains and applies the quality system. The Notified Body reserves the right, on a spot basis or based on suspicion, to pay unannounced visits.

The following may render this Certificate invalid:

- Changes in the quality system affecting production.
- Periodical audits not held within the allowed time window.

#### Conformity declaration and marking of product

When meeting with the terms and conditions above, the producer may draw up an EC declaration of conformity and legally affix the CE mark followed by the Notified Body identification number.

End of Certificate

Notice: The Certificate is subject to terms and conditions as set out in the Certification Agreement. Failure to comply may render this Certificate invalid.

NOTIFIED BODY 2460: DNV Product Assurance AS, Veritasveien 3, 1363 Høvik, Norway, Tel +47 67 57 88 00, www.dnv.com

**DNV**·GL

## MANAGEMENT SYSTEM CERTIFICATE

Certificate No.: 10000320341-PA-NA-NOR Project No.: PRJC-519733-2015-MSL-NOR

Initial Certification Date: 05 December 2019

Valid Until: 04 December 2022

This is to certify that the management system of:

## Arctiko A/S

Oddesundvej 39, 6715 Esbjerg N, Denmark

Complies with the requirements of: ISO 13485:2016/NS-EN ISO 13485:2016

The Certificate is valid for the following scope: DESIGN, DEVELOPMENT, MANUFACTURING, SALES AND SERVICES OF REFRIGERATORS AND FREEZERS CLASSIFIED AS MEDICAL DEVICES.

Place and date: Høvik, 05 December 2019



**MSYS 018** 

For: **DNV GL PRESAFE AS** Eugenie Winger Husebye

The certificate is digitally verified by blockchain technology. For more info, see www.dnvgl.com/assurance/certificates-in-theblockchain.html



Notice: The Certificate is subject to terms and conditions as set out in the Certification Agreement. Failure to comply may render this Certificate invalid. ACCREDITED UNIT: DNV GL PRESAFE AS, Veritasveien 3, N-1363 Høvik, Norway - Registered Enterprise No: NO 997 067 401 MVA







# LFF 270

SMART FRIDGE AND FREEZER IN ONE CABINET, MAKES IT A PERFECT SOLUTION FOR LABORATORIES WITH LIMITED SPACE DUE TO THE SMALL FOOTPRINT.

With air forced cooling and automatic defrost which will save time to focus on what's most important and store the samples most reliable.







LE IN AIR FORCED

FILTERLESS CONSTRUCTION

## INDEPENDENT & LESS FOOTPRINT

The LFF comes with two controllers allowing you to set and operate them as two independent units. With separate locks and passwords, it provides the ability to restrict access to storage and settings, in case the unit have multiple users. The unit is in effect of two fully independent units each with its own compressor, cooling circuit and controller – allowing to turn off one of the compartments in case that they are not in use for some time.

## STAINLESS STEEL & AUTOMATIC DEFROST

The unit is available with stainless steel AISI 304 Exterior, so that the interior and exterior is made entirely of stainless steel, providing a stronger more resistant unit.


With Arctiko's automatic defrost system it's not required to remove samples prior to defrosting, saving you valuable time to focus on what matter the most and at the same time stores the samples safely.


## EXCEPTIONAL COOLING


Arctiko has combined the high quality cooling performance created by air-forced cooling and automatic defrosting.


The results meet the more stringent requirements for lower power consumption, more precise cooling uniformity, need for temperature and alarm surveillance, documentation and validation, making the LFF 270 the perfect solution for biomedical storage.

## **MAIN DIMENSION FOR LFF 270**









MAIN	SPECIFICATIONS
------	----------------

Item code         DAI 0235 / DAI 0236           Temperature range (°C)         +1/+10 -10/-30           Max. ambient temperature (°C)         32           Capacity (L)         161/161           Exterior dimensions WxDxH (mm)         520x700x1997           Interior dimensions WxDxH (mm)         2x(400x575x700)           Weight (KG)         120           Insulation (mm)         60	
Max. ambient temperature (°C)         32           Capacity (L)         161 / 161           Exterior dimensions WxDxH (mm)         520x700x1997           Interior dimensions WxDxH (mm)         2x(400x575x700)           Weight (KG)         120	
Capacity (L)         161 / 161           Exterior dimensions WxDxH (mm)         520x700x1997           Interior dimensions WxDxH (mm)         2x(400x575x700)           Weight (KG)         120	
Exterior dimensions WxDxH (mm)         520x700x1997           Interior dimensions WxDxH (mm)         2x(400x575x700)           Weight (KG)         120	
Interior dimensions WxDxH (mm)2x(400x575x700)Weight (KG)120	
Insulation (mm) 60	
Cooling technology air forced	
Controller model / probe type G214 / PT1000	
POWER	
Power supply (V) 230*	
Frequency (Hz)         50/60           Power consumption (kWh/24H)         11,4	
AMP (A) 5,8	
Power (Watt) 728	
Horse power (HP) 1/10 + 1/8	
ALARM FUNCTIONS	
Alarm display as text - not codes yes	
Visual / acoustic alarm yes / yes	
Power failure alarm yes	
Adjustable high / low temperature alarm yes / yes	
Open door alarm yes	
Probe failure alarm yes Low battery alarm yes	
Low battery alarm yes Compressor failure alarm no	
Battery backup for alarms (approx. hrs.) 72	
DATA LOGGING & EXTERNAL CONNECTION	
Voltage free contact for remote alarm (e.g. GSM alarm module) yes	
Electronic data logger yes	
RS 485 port yes	
USB port for software update & data download yes	
Temperature chart recorder optional	
DISPLAY FEATURES	
Display type 4,3" with touch buttons	
Number of optional reference probes 2	
Number of optional reference probes     2       Password protection for turning unit on / off     yes	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyes	
Number of optional reference probes     2       Password protection for turning unit on / off     yes       Temperature graph on display     yes       OTHER FEATURES     Version	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyes	
Number of optional reference probes     2       Password protection for turning unit on / off     yes       Temperature graph on display     yes       OTHER FEATURES     yes	
Number of optional reference probes     2       Password protection for turning unit on / off     yes       Temperature graph on display     yes       OTHER FEATURES     yes       Automatic defrost     yes       Antifreeze function     no	
Number of optional reference probes     2       Password protection for turning unit on / off     yes       Temperature graph on display     yes       OTHER FEATURES     yes       Automatic defrost     yes       Antifreeze function     no       Vacuum release port     no       Access port for external probe etc. (int. diameter mm)     optional       Light     no	
Number of optional reference probes       2         Password protection for turning unit on / off       yes         Temperature graph on display       yes         OTHER FEATURES       yes         Automatic defrost       yes         Antifreeze function       no         Vacuum release port       no         Access port for external probe etc. (int. diameter mm)       optional         Light       no         Lock with key       yes	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)no	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)no	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yes	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. load per shelf (kg)30	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. load per shelf (kg)30Adjustable drawers (pcs)optional	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. no. of adjustable drawers (pcs)optionalMax. no. of adjustable drawers (pcs)6	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. no. of adjustable drawers (pcs)6Max. load per adjustable drawers (pcs)30Max. load per adjustable drawer (kg)30	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs)0 / 4Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawer (kg)30REFRIGERATION & CABINET30	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. no. of adjustable drawers (pcs)6Max. load per shelf (kg)30REFRIGERATION & CABINET30Number of compressors2	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)0 / 4Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. load per adjustable drawer (kg)30REFRIGERATION & CABINET30Number of compressors2RefrigerantR290	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)0 / 4Max. no. of adjustable drawers (pcs)6Max. load per shelf (kg)30Adjustable drawers (pcs)6Max. load per adjustable drawer (kg)30REFRIGERATION & CABINET30Number of compressors2RefrigerantR290	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)0 / 4Max. no. of adjustable drawers (pcs)6Max. load per shelf (kg)30Adjustable drawers (pcs)6Max. load per adjustable drawer (kg)30REFRIGERATION & CABINET30Number of compressors2RefrigerantR290Interior cabinet materialstainless steel	Eleine Control Cont
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)0 / 4Max. no. of adjustable drawers (pcs)6Max. load per shelf (kg)30Adjustable drawers (pcs)6Max. load per adjustable drawer (kg)30REFRIGERATION & CABINETNumber of compressorsNumber of compressors2RefrigerantR290Interior cabinet materialstainless steelExterior cabinet materialpainted steel / stainless steel	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)2RefrigerantR290Interior cabinet materialstainless steelExterior cabinet materialpainted steel / stainless steelColour (exterior cabinet)white / stainless steel	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / adjustable shelves (pcs)16 / 8Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. load per adjustable drawer (kg)30REFRIGERATION & CABINETX290Number of compressors2RefrigerantR290Interior cabinet materialstainless steelExterior cabinet materialpainted steel / stainless steelFoam typepolyurethane	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. load per shelf (kg)30Adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. load per adjustable drawers (pcs)2REFRIGERATION & CABINETR290Number of compressors2RefrigerantR290Interior cabinet materialstainless steelExterior cabinet materialpainted steel / stainless steelFoam typepolyurethaneVIP vacuum insulated panelsno	
Number of optional reference probes2Password protection for turning unit on / offyesTemperature graph on displayyesOTHER FEATURESAutomatic defrostyesAntifreeze functionnoVacuum release portnoAccess port for external probe etc. (int. diameter mm)optionalLightnoLock with keyyesCastors (total pcs) / castors with brake (pcs)4 / 2Fixed feet (pcs) / levelling feet (pcs)noSub lids or inner doors (pcs)noReversible door(s)yesFixed shelves (pcs) / adjustable shelves (pcs)0 / 4Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)16 / 8Max. load per shelf (kg)30Adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. no. of adjustable drawers (pcs)6Max. load per adjustable drawers (pcs)2REFRIGERATION & CABINETNumber of compressorsNumber of compressors2RefrigerantR290Interior cabinet materialstainless steelExterior cabinet materialpainted steel / stainless steelFoam typepolyurethaneVIP vacuum insulated panelsnoSHIPPING	

# OPTIONAL ACCESSORIES

GSM alarm module Temperature chart recorder Shelves (perforated, wire stainless steel, plastic coated) Drawers (stainless steel) Modbus adapter Voltage stabilizer Voltage converters LED light





Arctiko A/S info@arctiko.com arctiko.com