


# Neuron MAX 088

Soft Tip, 6F Long Sheath for Neurovascular Support


## Distal flexibility – measuring tip softness

- 3x softer than Competitor A
- 9x softer than Competitor B



## Optimal proximal support

- 75% more support than Competitor A



**Largest lumen in class to deliver the widest range of devices**

Penumbra Neuron MAX	Competitor A	Competitor B <sup>2</sup>
.088"	.087"	.085"

Soft, beveled tip

PX SLIM

Compatible adjunctive device therapy

Penumbra Neuron MAX 088

- Prowler Select Plus
- XT-27
- Marksman
- Hyperform, Hyperglide, TransForm, Ascent, and Sceptre balloons

Penumbra

1. At 50 mm gauge length via 5 mm compression at 10 mm/min rate


2. Based on measurements

## Neuron **MAX 088** Soft Tip, 6F Long Sheath

- Full length stainless steel braid reinforced proximal support zone transitioning to 4 cm distal flexible zone with large .088" inner lumen
- Distal shaft has hydrophilic coating for optimal trackability
- Available in 80 cm and 90 cm lengths with Straight and Multipurpose (MP) tip shape

## 6F Select Catheter

1. Enables primary access and atraumatic placement into desired vessel without an over-the-wire exchange
2. Useful for diagnostic angiogram – .040" lumen
3. Stainless steel braided proximal shaft for support and torque response with a soft polymer distal shaft to enable atraumatic vessel selection



## Ordering Information

### Neuron **MAX 6F 088** Lumen Long Sheath (Crosscut Valve, RHV and Dilator included)

Catalog Number	Description	Tip Shape	Working Length	Distal Flexible Zone	Outer Diameter* Proximal / Distal	Inner Diameter	Wire Compatibility
<b>PNML6F088804</b>	6F 088 Neuron <b>MAX</b> Long Sheath, 80/4 Straight		80 cm	4 cm	8F / 8F	.088"	.035/.038"
<b>PNML6F088804M</b>	6F 088 Neuron <b>MAX</b> Long Sheath, 80/4 MP		80 cm	4 cm	8F / 8F	.088"	.035/.038"
<b>PNML6F088904</b>	6F 088 Neuron <b>MAX</b> Long Sheath, 90/4 Straight		90 cm	4 cm	8F / 8F	.088"	.035/.038"
<b>PNML6F088904M</b>	6F 088 Neuron <b>MAX</b> Long Sheath, 90/4 MP		90 cm	4 cm	8F / 8F	.088"	.035/.038"

### 6F Select Catheter

Catalog Number	Description	Tip Shape	Working Length	Distal Flexible Zone	Outer Diameter* Proximal / Distal	Inner Diameter	Wire Compatibility
<b>PNS6F105BER</b>	6F Select Catheter, 105 BER		105 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"
<b>PNS6F105H1</b>	6F Select Catheter, 105 H1		105 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"
<b>PNS6F125BER</b>	6F Select Catheter, 125 BER		125 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"
<b>PNS6F125SIM - NEW!</b>	6F Select Catheter, 125 SIM	<b>NEW!</b>	125 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"
<b>PNS6F125H1</b>	6F Select Catheter, 125 H1		125 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"
<b>PNS6F125SIMV</b>	6F Select Catheter, 125 SIM-V		125 cm	9 cm	5.6F / 6F / 5F	.040"	.035/.038"

\* A mid outer diameter is only listed if applicable to device.



www.penumbrainc.com

Penumbra, Inc. USA  
One Penumbra Place  
Alameda, CA 94502  
USA  
1.888.272.4606  
T 1.510.748.3200  
F 1.510.748.3232  
order@penumbrainc.com  
info@penumbrainc.com

Penumbra Europe GmbH  
Am Borsigturm 44  
13507 Berlin  
Germany  
T +49 30 2005 676-0  
F +49 30 2005 676-10  
order@penumbrainc.de  
info@penumbrainc.de

Penumbra Neuro Australia Pty Ltd  
Suite 3, Level 5, 1 Oxford Street  
Darlinghurst NSW 2010  
Australia  
T +61-1300 817 025  
F +61-1300 817 026  
order.anz@penumbrainc.com