



**Filter Type** Compact Filter

**EN 779** M6

**Frame** Plastic

**Media** Fiber Glass

**Final PD** 450 Pa

**Operating Temp.** 80°

## Dimensions & Technical Details

Av. Efficiency - EN 779 80% - ISO 16890 ePM2,5 60%

| Filter code      | Width<br>(mm) | Height<br>(mm) | Depth<br>(mm) | Media Area<br>(m <sup>2</sup> ) | Air Volume<br>(m <sup>3</sup> /h) | Initial PD<br>(Pa) |
|------------------|---------------|----------------|---------------|---------------------------------|-----------------------------------|--------------------|
| C-M6-287x592x292 | 287           | 592            | 292           | 7                               | 1700                              | 65                 |
| C-M6-592x592x292 | 592           | 592            | 292           | 14                              | 3400                              | 65                 |

Don bay: Eng. Fatih A Farwati

**5M MUHENDISLIK LTD. STI.**

HOSAB Hasanağa Industrial Area 5th Street No:5

Nilüfer / Bursa / Turkey

[www.5m-muhendislik.com.tr](http://www.5m-muhendislik.com.tr)

t. +90 224 484 29 20

f. +90 224 484 29 40

[info@5m-muhendislik.com.tr](mailto:info@5m-muhendislik.com.tr)