

Marketing Information

Agrofarm 4 / 4E

Stage I / IIIA



New Agrofarm 4 Series Stage I Agrofarm 4E Series Stage IIIA

Agrofarm 4075 | 4090.4 | 4100.4 Stage I

Agrofarm 4065E | 4075E | 4085E | 4080.4E | 4090.4E | 4100.4E Stage IIIA

Treviglio, March 2024



Marketing Information

Agrofarm 4 / 4E

Stage I / IIIA

Tyres combination


Code	Front tyre	Rear tyre	Stage I		Stage IIIA		
			4075	4090.4 4100.4	4065E	4075E 4085E	4080.4E 4090.4E 4100.4E
RF129	6.00 -16"	13.6 -28"	0	-	0	0	0
RF041	7.50 -16"	380/85 R28" (14.9 R28")	0	-	0	0	0
RF151	6.50 -16"	420/70 R24"	0	-	0	0	0
RF039	7.50 -16"	320/85 R36" (12.4 R36")	0	-	-	0	0
RF042	7.50 -16"	380/85 R30" (14.9 R30")	0	-	-	0	0
RF044	7.50 -16"	420/85 R30" (16.9 R30")	0	-	-	0	0
RF677	250/85 R20" (9.5 R20")	340/85 R28" (13.6 R28")	-	-	0	-	-
RF1199	280/70 R20"	420/70 R24"	0	0	0	0	0
RF502	280/85 R20" (11.2 R20")	380/85 R28" (14.9 R28")	0	0	0	0	0
RF597	300/70 R20"	420/70 R24"	0	0	0	0	0
RF1200	320/70 R24"	420/85 R30" (16.9 R30")	0	0	-	0	0
RF1202	280/85 R24" (11.2 R24")	12.4 -36"	0	0	-	0	0
RF510	320/85 R20" (12.4 R20")	380/85 R30" (14.9 R30")	0	0	-	0	0
RF1648	12.4 -24" R1W	16.9 -30" R2	0	0	0	0	0
RF1647	320/85 R24" (12.4 R24")	460/85 R30" (18.4 R30")	-	0	-	-	0

Front mudguards

Front mudguards
for 2 WD (WE004)



Front steering mudguards
for 4 WD (WE003)



NOTE

Marketing Information

Agrofarm 4 / 4E
Stage I / IIIA

Dimensions & Weight



4E Series		4065	4075 -4085	4080.4 - 4100.4
Wheelbase 2WD / 4WD (A)	[mm]	2.041 / 1.976		2.171 / 2.106
Length (B)	[mm]	3.860		3.990
Height (C) (center rear axle - roof with A/C)	[mm]	1.966		
Height (C1) (center rear axle - roof w/o A/C)	[mm]	1.907		
Height (center rear axle - ROPS)	[mm]	1.863		
Weight with cab (2WD / 4WD)	[Kg]	2.650 / 2.950	2.850 / 3.150	2.950 / 3.250
Weight with plat (2WD / 4WD)	[Kg]	2.500 / 2.800	2.700 / 3.000	2.800 / 3.100
Front Admissible Load 2WD / 4WD	[Kg]	1.100 / 2.200		
Rear Admissible Load 2WD / 4WD	[Kg]	2.700 / 3.000		
Total Admissible Load 2WD / 4WD	[Kg]	3.800 / 4.800		

NOTE



Technical sheet

		4065	4075	4085	4080.4	4090.4	4100.4
ENGINE							
Type		1000 Series					
Emission level	Stage	IIIA	I / IIIA	IIIA	IIIA	I / IIIA	I / IIIA
Cyl. / Displ	n°/cc	3 / 3.000			4 / 4.000		
Bore / Stroke	mm	105 / 115,5					
Aspiration		Turbo					
Injection	Type	Direct					
Max. power Stage I	kW/Hp	-	51,5 / 70	-	-	64,1 / 87	69.3 / 94
Max torque Stage I	Nm	-	254	-	-	336	366
Max. power Stage IIIA	kW/Hp	45,6 / 62	53 / 72	60,3 / 82	58,8 / 80	62,5 / 85	70 / 95
Max torque Stage IIIA	Nm	232	265	310	325	348	373
Fuel tank	l	70					
TRANSMISSION							
Transmission	Type	SDF					
Gearbox	n°	5 gears x 3 ranges and splitter					
LS VERSION							
Shuttle	Type	Mechanical with lever under steering wheel					
N° of speed	n°	30 + 15					
PTO							
Mechanical engagement		●	●	●	●	●	●
540/540ECO/Groundspeed		●	●	●	●	●	●
LIFT							
Mechanical rear lift with EasyLift		●	●	●	●	●	●
Rear lifting capacity (STD)	Kg	2.500	3.500	3.500	3.500	3.500	3.500
HYDRAULICS							
Pump flow	l/min	42	42	42	42	42	42
Rear spool valves	n°	2	2	2	3	3	3

NOTE

- Standard
- Option
- Not available

Standard or Optional feature is related to WLD price list



**DEUTZ
FAHR**

DEUTZ-FAHR is a brand of  SDF