



# Canon i-SENSYS LBP6030B Specifications

[Show Now](#)



- [Specification](#)
- [Accessories & Supplies](#)
- [Support](#)

[Left Right](#)

[PRINTER ENGINE](#)



### **Print speed**

18ppm mono (A4)<sup>1</sup>

### **Printing method**

Monochrome laser beam printing

### **Print quality**

Up to 2400 x 600 dpi with Automatic Image Refinement

### **Print resolution**

600 x 600 dpi

### **Warm-up time**

Approx. 1 second from Sleep

10 seconds or less from power on

### **First Page Out Time**

Approx. 7.8 seconds or less

### **Duty cycle**

Max 5,000 pages per month

### **Print margins**

5 mm-top, bottom, left and right

## **MEDIA HANDLING**

### **Paper input (Standard)**

150-sheet multi-purpose tray

### **Paper output**

100-sheet face down

### **Media types**

Plain paper, Heavy Paper, Transparency,

Label, Envelope

### **Media sizes**

A4/B5/A5/LGL/LTR/EXE/16K/Custom size

Env. COM10/Env. Monarch/Env. C5/Env. DL

width 76.2 ~ 216mm x length 188 ~ 356mm

### **Media weights**

Multi-purpose tray:

60 to 163 g/m

## **GENERAL FEATURES**

### **Power requirements**

AC 220-240V (±10%), 50/60Hz (±2Hz)

## Power consumption

Maximum: Approx. 870 W or less

Active: Average approx. 330 W

Standby: Average approx. 1.8 W or less

Sleep: Average approx. 0.8 W or less

Typical Electricity Consumption (TEC): 0.47 kWh/week

Lot26 ([http://www.canon-europe.com/For\\_Work/Lot26/index.aspx](http://www.canon-europe.com/For_Work/Lot26/index.aspx))

## Noise level

Sound power<sup>1</sup>:

Active: 6.34 B or less

Standby: Inaudible

Sound pressure<sup>1</sup>:

Active: 49.2 dB(A)

Standby: Inaudible

## **Dimensions (W x D x H)**

364 mm x 249 mm x 199 mm

## **Weight**

Approx. 5.0 kg

## **Operating environment**

Temperature: 10 ~ 30°C

Humidity: 20 ~ 80%RH (no condensation)

## **Control panel**

2 LED indicators, 2 operation KEY

## **CONTROLLER**

### **Memory**

32 MB

### **Printer languages**

UFR II LT

### **Interface and connectivity**

USB 2.0 Hi-Speed

### **Operating systems compatibility**

Win 8.1(32/64bit)/Win 8(32/64bit)/Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit)/Server 2012(32/64bit)/Server 2012 R2(64bit)/

Server 2008(32/64bit) / Server 2008 R2(64bit)/ 2003 Server(32/64bit)/

Mac OS X 10.6 ~ /Linux<sup>1</sup> /Citrix (FR2)

# CONSUMABLES

## All-in-One cartridges

Standard: Cartridge 725 (1,600 pages<sup>1</sup>)<sup>2</sup>

### Disclaimer

All specifications subject to change without notice

All specifications subject to change without notice

All specifications subject to change without notice

### Footnote

<sup>1</sup> The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed

<sup>1</sup> Declared noise emission in accordance with ISO 9296

<sup>1</sup> Web distribution only

<sup>1</sup> Based on ISO/IEC 19752

<sup>2</sup> Printer ships with 700 pages starter cartridge

<sup>1</sup> The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed

<sup>1</sup> Declared noise emission in accordance with ISO 9296

<sup>1</sup> Web distribution only

<sup>1</sup> Based on ISO/IEC 19752

<sup>2</sup> Printer ships with 700 pages starter cartridge

<sup>1</sup> The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed

<sup>1</sup> Declared noise emission in accordance with ISO 9296

<sup>1</sup> Web distribution only

<sup>1</sup> Based on ISO/IEC 19752

<sup>2</sup> Printer ships with 700 pages starter cartridge

or

