

Material Safety Data Sheet

R600a ISOBUTANE

1.

PRODUCT NAME: ISOBUTANE
CHEMICAL FAMILY: Paraffin Series Hydrocarbon
DISTRIBUTOR: Ningbo Koman's Refrigeration Industry Co.,Ltd
 20 Yong Dinghe RD.,Fine Chemical Zone,Xiapu,Beilun
 Ningbo,China

FOR MORE INFORMATION CALL:
 (Monday-Friday, 9:00am-5:00pm)
 86-574-86910051

IN CASE OF EMERGENCY CALL:
 CHEMTREC: 86-574-86910065

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>% VOLUME</u>	<u>TLV-ACGIH</u>	<u>CAS NUMBER</u>
Liquefied Petroleum Gas	100	1000 ppm	75-28-5

*** Physical Hazard Due to Flammable Nature. Flammable When Combined With Air ***

3. HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE

INGESTION: Aspiration Hazard!

INHALATION: Inhalation of vapor may produce anesthetic effects and feeling of euphoria. Prolonged overexposure can cause rapid breathing, headache, dizziness, narcosis, unconsciousness, and death from asphyxiation, depending on concentration and time of exposure.

SKIN CONTACT: Contact with evaporating liquid can cause frostbite.

EYE CONTACT: Liquid can cause severe irritation, redness, tearing, blurred vision, and possible freeze burns.

4. FIRST AID MEASURES

INGESTION: Do not induce vomiting. Contact a physician immediately.

INHALATION: Remove to fresh air. If breathing has stopped, restore breathing at once. Administer oxygen and get medical help.

SKIN CONTACT: For liquid contact, warm areas gradually and get medical attention if there is evidence of tissue damage. Flush area with plenty of water.

Isobutane

EYE CONTACT: For liquid contact, irrigate with running water for minimum of 15 minutes. Consult physician immediately if frostbite occurs.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT (METHOD): -117 F (Open Cup)
UPPER EXPLOSIVE LIMIT (vol.) gas in air): 8.4%
LOWER EXPLOSIVE LIMIT (vol.) gas in air): 1.8%

EXTINGUISHING MEDIA:

Dry Chemical Extinguisher (B-C), Water

SPECIAL FIRE FIGHTING PROCEDURES:

Stop the release of materials if possible. Cool the vapor space of the storage container with water spray. Avoid accumulation of unburned materials. Remove personnel in general area. Observe maximum isolation when extinguishing fire. Expansion of liquid and change of state from liquid to vapor will allow combustible mixture to encompass a large area.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air and may travel along the ground or may be moved by ventilation systems and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Avoid sources of ignition-Ventilate area. Use water fog to evaporate or ventilate. Protect body against contact with liquid. If confined space – Use self-contained breathing apparatus. Consult local fire authorities.

7. HANDLING AND STORAGE

Comply with state and local regulations covering liquefied petroleum gases.

Comply with NFPA Pamphlet #58.

Store small containers in well-ventilated areas, away from heat or sources of ignition. Prohibit smoking in areas of storage or use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION

Mechanical: Provide as needed to keep concentration in air below TLV and LEL

Local Exhaust: Continuous ventilation recommended

Special: Explosion proof fans and motors

RESPIRATORY PROTECTION: NIOSH approved self-contained breathing apparatus

PROTECTIVE GLOVES: Impervious, insulated gloves recommended

EYE PROTECTION: Face shield or goggles recommended

OTHER: Impervious clothing for prolonged or repeated contact

Isobutane

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR & APPEARANCE	Clear, Colorless liquefied gas with sweet petroleum odor
SOLUBILITY IN WATER @ 70 Deg. F	0.008%
SPECIFIC GRAVITY (H₂O=1.00):	0.564
BOILING RANGE:	10.9 Deg. F
PRESENT VOLATILE BY VOLUME:	100%
VAPOR PRESSURE @ 70 Deg. F:	31 psig
VAPOR DENSITY (air = 1.00):	2.006
EVAPORATION RATE:	> 1 (Ethyl Ether = 1.0)

10. STABILITY AND REACTIVITY

STABILITY:

This product is stable

INCOMPATIBILITY (Material to Avoid):

None

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Volatile Hydrocarbon Vapors

HAZARDOUS POLYMERIZATION:

Can not occur

CONDITIONS TO AVOID:

High Heat, Sparks & Open Flames

11. ECOLOGICAL INFORMATION

No data given

12. DISPOSAL CONSIDERATIONS

- (1) Mechanical recovery
- (2) Flare-Off at safe location (Vapors)
- (3) Exhaust to atmosphere in safe location (No open flames)

OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with federal, state, and local disposal laws.

13. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME:	Petroleum Gases, Liquefied
US DOT HAZARD CLASS:	2.1
US DOT ID NUMBER:	UN 1075
LABELED/PLACARDED	Flammable Gas

Isobutane

14. REGULATORY INFORMATION

The ingredients listed in section 2 are reported/included in the U.S. TSCA inventory and Canadian domestics substance list.

The product is defined by OSHA in 29 CFR 1910.1200c as a flammable gas. Use of this product may require compliance with 29 CFR 1910.119, process safety management of highly hazardous chemicals.

15. OTHER INFORMATION

OTHER INFORMATION: HMIS Classification: Health – 1, Flammability – 4, Reactivity – 0

Ningbo Koman's Refrigeration believes the information and recommendations contained herein (including data and statements are accurate as of the date hereof). NO WARRANTY OF FITNESS OR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of Ningbo Koman's Refrigeration Ningbo Koman expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.