

## VIS-AP4C

2.4GHz/5GHz Conference Access Point



### Features

- Connect with the Wi-fi conference processor VIS-DCP2000-W, or with the switch to extend more conference AP in the same system.
- Typical coverage range 30m
- Each AP can connect up to 50 conference units.
- With scan and diagnose function
- Install on ceiling, wall or with stand rack mount
- 128 bits AES digital encryption technology, with WAP2 secure connection, MAC address filtering, SSID-hiding to prevent wiretapping and unauthorized access from delegate unit

### Functions

- LED indicator for signal/power
- 5GHz dual band communication
- LAN support POE power supply
- RJ45 for LAN connection

### Technical Parameters

RF	
WLAN Standard	IEEE802.11ac, IEEE802.11a, IEEE802.11g, IEEE802.11b
RF Frequency Bands	2.4GHz ISM / 5GHz UNII
RF output power	64mW
Frequency response	80-15kHz
Max Transmission Power	27dBm
Antenna Type	Four built-in 5dBi omnidirectional antennas

<b>POWER</b>	
Supply Type	Power Over Ethernet, 802.3at, DC 12V 1.5A
Supply Voltage(at Power Consumption)	≤13W
<b>NETWORK</b>	
Interface	1×Gigabit WAN/POE Port, 1×Gigabit LAN Port
Link Speed	1200Mbps
Networking Addressing Capability	DHCP or Manual IP address
Cable Length	100m (max)
Cable Type	≥ Cat5e (shielded / unshielded)
Connector Type	1× RJ45
Connector LED	WAN/POE Port (UP LED), LAN Port (Down LED)
<b>USER INTERFACE</b>	
LED Status Indication	Power, Network Audio, Wireless (Yellow / Blue)
Reset	Push button for Factory Reset
<b>MECHANICAL</b>	
Dimensions	220L×220W×45H(mm)
Color	White
Weight	0.3KG
Mounting Type	Ceiling, Wall or Stand Rack

## *Item Model for Order*

VIS-AP4C..... 2.4GHz/5GHz Conference Access Point (White)