



---

# SAVER<sup>®</sup> ONE

Complete AEDs range to save lives

life is a breath,  
...keep it safe with us


[www.amiitalia.com](http://www.amiitalia.com)

## THE IMPORTANCE OF AEDS TO WIN SCA

Sudden cardiac arrest is unpredictable; it can happen anywhere, anytime, at any age and without warning. For each minute that passes by the probability of survival drops of 7/10%. Time is crucial in these situations and using AEDs might be the only effective action. **EACH 2 SECOND SUDDEN CARDIAC ARREST CLAIMS ONE LIFE, TO ANYONE, ANYWHERE.**

**A life-threatening condition that can be reversible just thanks to a timely defibrillation.**

### CHAIN OF SURVIVAL



## THE KEY IS TO ENABLE AVAILABILITY AND EASY ACCESS TO AEDS



### WORKPLACES:

As the chances of surviving a cardiac arrest are increased if the emergency treatment is provided promptly, AED provision is highly recommended to any work places that aim to an healthy and safe environment.



### HOSPITALS:

ERC guidelines says "...staff should be trained to enable achievement of the goal of providing the first shock within 3 minutes of collapse anywhere in the hospital".



### SCHOOLS:

AEDs are easy to use: by following the simple and clear voice prompts bystanders can perform all the crucial steps that can save lives. Furthermore several studies indicate that students without any CPR/AED training can use an AED as instructed.



### SPORT FACILITIES:

Regardless of the discipline performed, AED provision should be mandatory for professional, semi-professional and amateur sport.



### COMMUNITIES:

A lack of confidence in using an AED and the inability to locate a nearby device is a missed opportunity to save lives! Governments should strongly advocate for public access defibrillation programs; every citizen could be trained and then become a potential first responder to a SCA.

**SAVERONE®**

Official Supplier to:



**SAVERONE®**

Chosen by:



Sudden Cardiac Arrest can happen anytime, anywhere and without warning. The person affected has only few precious minutes left for a chance of survival.

**YOUR FIRST AID COULD BE SOMEBODY'S LAST CHANCE**

SAVER ONE AEDs are designed for a public access use and licensed to administer fast and safe rescues. Highly-effective and user-friendly for any lay rescuer, even without minimal training. SAVER ONE Semi and Fully Automatic defibrillators are two dependable members of our AED family. The Fully Automatic administers a defibrillating shock (when appropriate) with no shock button for the user to press whilst the Semi-Automatic administers a shock at the press of a button.

Choose the best portable AED that's right for you to save lives everywhere in any public circumstance (home, office, school, hotel, airport, train, beach, gym, pool, disco, etc.) and before EMS team arrives.

- Automated testing to vouch daily functionality
- A new look complete with all pictograms which light up to guide rescuers step by step
- More alternatives for recording and transfer data: internal memory, removable card, USB
- Slight yet solid with long-lasting battery options to ensure the best portability in any circumstance
- Biphasic technology up to 360J energy
- Unique features combined with available configurations give rise to exclusive devices.



**SEMI-AUTOMATIC**  
two buttons

Meet AHA/ERC 2017 Guidelines

**Maintenance-Free:** Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer. AED runs further tests after each battery insertion as well as every time the device is turned on. A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

**Service Mini-Screen:** The mini LCD screen always displays a battery gauge with its residual percentage charge, error codes in faulty conditions; text prompts in accordance with audible voice instructions helpful in noisy and chaotic environments.

**INFO button:** The "i" button provides valuable device/battery technical information and enable to change the language.

**CPR Coaching:** More instructive voice and text prompts guide user through rescue. A built-in metronome assists responder during the CPR, providing audio cues for the appropriate number and rate of chest compressions.

**Adult/Child capability:** after connecting pads to the patient, flashing icons on the keyboard display which pads are in use (adult/pediatric).

Devices senses when pediatric pads are installed and adjusts to use the appropriate lower energy level (50J).



**FULLY AUTOMATIC**

One button

**MODEL NUMBERS**

- Code SVO-B0001: Semi- Automatic Standard Version at 200J
- Code SVO-B0002: Semi- Automatic Power Version at 360J
- Code SVO-B0847: Fully Automatic Standard Version at 200J
- Code SVO-B0848: Fully Automatic Power Version at 360J

**CONFIGURATION OPTIONS (BOX CONTENT)**

- Conf-Norm: Standard Basic Configuration (adult pads, disposable battery, carrying case)
- Conf-Rech: Rechargeable Configuration (adult pads, accumulator, charger station, carrying case)

**DEFIBRILLATOR**

- Operation: Semi- Automatic Version  
Fully Automatic Version
- Energies: Standard max 200J or Power max 360J
- Waveform: Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance
- Protocols: Various adult shock protocols available on request
- Factory default: Adult Standard escalating 150, 200, 200J  
Adult Power escalating 200, 250, 360J  
Paediatric (Standard or Power) 50J fixed
- Charging time: ≤9 seconds with a new and fully charged battery depleted battery will result in a longer charging time
- Analysis time: IEC/EN 60601-2-4 from 4 to 15 seconds
- Impedance: 20-200 ohms
- Sensitivity: IEC/EN 60601-2-4 (AHADB, MITDB source), 97%
- Specificity: IEC/EN 60601-2-4 (AHADB, MITDB source), 99%
- Controls: 2 buttons for Automatic: ON/OFF, "i" info button  
3 buttons for Semi-Automatic: ON/OFF, "i" info button, shock button
- Flashing Icons: "connect pads to patient"  
"adult/child" informing on pads type use  
"don't touch patient" warning to stay clear  
"touch patient" informing it's safe to touch
- Indicators: Status LED indicator informing on device condition  
Battery gauge with remaining capacity rate  
Audible alerts and text display with service alarms
- Upgradeable: through a USB cable or memory card

**PADS OPTIONS**

- Type: Disposable, pre-gelled and self-adhesive
- Adult: Code SAV-C0846, for patient >8 years or >25 kg
- Paediatric: Code SAV-C0016, for patient <8 years or <25 kg
- Cable length: 120 cm
- Shelf-Life: 30 months

**PHYSICAL**

- Size: 26,5 x 21,5 x 7,5 cm
- Weight: 1,95 kg with disposable battery  
2,00 kg with rechargeable battery

**EVENT RECORDING**

- Internal memory: up to 6 continuous hours of ECG and rescue events
- Optional memory: Removable SD card; length of storage depends on card capacity: a 2GB card records up to 100 hours
- Data recording: "AED1LOG" text file with detailed self-test activity  
"AEDFILES" with complete recorded information
- Event review: "Saver View Express" data manager software

**BATTERY OPTIONS**

- Type: Li-SOCI2 Disposable, code SAV-C0903
- Autonomy: 300 complete rescue cycles (shocks at 200J and CPR) or 200 complete rescue cycles (shocks at 360J and CPR) or 35 hours ECG analysis for a new and fully charged battery (\*) when stored in original packaging 5 years (\*)
- Shelf-Life: 4 years once installed to AED, assuming one battery insertion test and daily self-test but without switching AED on (\*)
- Battery-Life: 4 years once installed to AED, assuming one battery insertion test and daily self-test but without switching AED on (\*)
- Type: Li-ion Accumulator, code SAV-C0011
- Recharging time: 2,5 hours with the charger station code SAV-C0014 (\*) (recommended to charge every 4 months at least)
- Autonomy: 250 shocks at 200J or 160 shocks at 360J or 21 hours in ECG analysis for a new fully charged accumulator (\*)
- Battery-Life: 2 years or 300 charging cycles (\*)

**ENVIROMENTAL**

- Operating temperature: 0°C to 55°C (32°F TO 131°F)
- Storing/Shipping temperature: -40°C to 70°C (-40°F TO 158°F) without battery
- Humidity: 10% to 95% relative humidity non condensing
- Sealing (IP Protection): IEC/EN 60529 class IP54; splash proof, dust protected
- Shock/Drop Abuse Endurance: IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance
- Electrostatic Discharge: IEC/EN 61000-4-2
- Electromagnetic Compatibility: IEC/EN 60601-1-2 Emission, Immunity
- Electrical Protection: IEC/EN 60601-1; Internally Powered Type BF
- Directive 93/42/CEE and 2007/47/CE: Class IIb

(\*)Temperature at 20°C Humidity 45% non-condensing

SAVER ONE D is a rugged, small and lightweight AED with ECG Monitoring capability. Totally reliable for trained users featuring advanced capacities to help improve lifesaving outcomes.

**THE RIGHT CHOICE FOR HARSH, OUTDOOR OR MOBILE USE**

While in AED mode, it allows the user to view the ECG and everything needed to know about the patient and ongoing rescue treatment on a very large (12x8 cm) full-colour display. Additionally the SAVER ONE D can be switched in ECG Monitoring mode, to allow for watch over the rhythm and heart rate while using defibrillation pads or standard ECG electrodes connected to a separate cable.

- Great graphical interface combined with instructive voice prompts to guide rescuers.
- Functionality ensured by automatic daily self-test.
- Slight yet solid with long-lasting battery options to ensure the best portability in any circumstance.
- More alternatives for recording and transfer data: internal memory, removable card, USB, and IrDA Port optional with Print Configuration.
- Biphasic technology up to 360J energy.
- Unique features combined with available configurations give rise to exclusive devices.



**AED  
ECG Monitoring**

Meet AHA/ERC 2017 Guidelines

**Maintenance-Free:** Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer. AED runs further tests after each battery insertion as well as every time the device is turned on. A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

**Service Mini-Screen:** In standby the mini LCD screen displays a check mark confirming AED is ready for use and a battery gauge informing about the residual charge. Error codes will appear in faulty conditions.

**Helpful Menu:** 3 buttons for navigating the software menu to set up device at user leisure: adjust the local date or time, adapt the screen or volume to ambient lights and noises, exclude the microphone while recording events, select a different language, print out the ECG files or simply get information on device and battery.

**CPR Coaching:** More instructive voice and text prompts guide user through rescue. A built-in metronome assists responder during the CPR providing audio cues for the appropriate number and rate of chest compressions.

**Adult / Child Capability:** Can be used on patients of any age with Adult or Pediatric proper electrodes. Device senses when Pediatric pads are installed and automatically adjusts to use a more appropriate lower energy level (50J).

**Monitoring section menu:** a new section has been introduced for the management of technical and physiological alarms and signals, according to IEC/EN 60601-2-27: patient loss, high or low heart rate, audio and visual signal for detection of a shockable rhythm so that the operator can switch/activate the semi-automatic modes to deliver the shock (using the appropriate pads); scaling of the ECG trace on the display (gain x2 or ÷2) reset of the audio or visual alarms.

**DEFIBRILLATOR**

Operation: AED Semi-Automatic; ECG Monitoring capability  
 Energies: Standard max 200J or Power max 360J  
 Waveform: Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance  
 Protocols: Various adult shock protocols available on request  
 Factory default: Adult Standard escalating 150, 200, 200J  
 Adult Power escalating 200, 250, 360J  
 Paediatric (Standard or Power) 50J fixed  
 Charging time: ≤9 seconds with a new and fully charged battery depleted battery will result in a longer charging time  
 Analysis time: IEC/EN 60601-2-4 from 4 to 15 seconds  
 Impedance: 20-200 ohms  
 Sensitivity: IEC/EN 60601-2-4 (AHADB, MITDB source), 97%  
 Specificity: IEC/EN 60601-2-4 (AHADB, MITDB source), 99%  
 Controls: 2 buttons: ON/OFF, shock button, and 3 buttons to surf the menu.  
 Indicators: Status LED indicator informing on device condition  
 Battery gauge with remaining capacity rate  
 Audible alerts and text display with service alarms through a USB cable or memory card  
 Upgradeable: Yes

**ECG MONITORING**

Operations: Through defibrillation pads or standard ECG electrodes attached to a separate 2-Lead patient monitoring reusable cable SAV-C0017  
 Manual setting through the menu  
 ECG size: 25 mm/sec  
 Heart Rate: 30-300 bpm  
 Sweep Speed: IEC/EN 60601-2-27 less than the points 202.6.2.101; 201.12.1.101.12,13; 208.6.6.2.101 not performed for the intended use of the device, as it is not intended for environments such as operating theatres or intensive care units  
 Display: 5,7" TFT colour, 640 x 480 pixel

**PADS OPTIONS**

Type: Disposable, pre-gelled and self-adhesive  
 Adult: Code SAV-C0846, for patient >8 years or >25 kg  
 Paediatric: Code SAV-C0016, for patient <8 years or <25 kg  
 Cable length: 120 cm  
 Shelf-Life: 30 months

**PHYSICAL**

Size: 26,5 x 21,5 x 7,5 cm  
 Weight: 2,08 kg with disposable battery  
 2,13 kg with rechargeable battery

**BATTERY OPTIONS**

Type: Li-SOCI2 Disposable, code SAV-C0903  
 Autonomy: 250 complete rescue cycles (shocks at 200J and CPR) or 160 complete rescue cycles (shocks at 360J and CPR) or 24 hours ECG Monitoring for a new and fully charged battery (\*) when stored in original packaging 5 years (\*)  
 Shelf-Life: 4 years once installed to AED, assuming one battery insertion test and daily self-test but without switching AED on (\*)  
 Battery-Life: 200 shocks at 200J or 110 shocks at 360J or 14 hours in ECG Monitoring for a new fully charged accumulator (\*)  
 Type: Li-ion Accumulator, code SAV-C0011  
 Recharging time: 2,5 hours with the charger station code SAV-C0014 (\*) (recommended to charge every 4 months at least)  
 Autonomy: 200 shocks at 200J or 110 shocks at 360J or 14 hours in ECG Monitoring for a new fully charged accumulator (\*)  
 Battery-Life: 2 years or 300 charging cycles (\*)

**EVENT RECORDING**

Internal memory: up to 6 continuous hours of ECG and rescue events  
 Optional memory: Removable SD card; length of storage depends on card capacity: a 2GB card records up to 100 hours "AED1LOG" text file with detailed self-test activity "AEDFILES" with complete recorded information "Saver View Express" data manager software  
 Data recording: Event review:

**ENVIROMENTAL**

Operating temperature: 0°C to 55°C (32°F TO 131°F)  
 Storing/Shipping temperature: -40°C to 70°C (-40°F TO 158°F) without battery  
 Humidity: 10% to 95% relative humidity non condensing  
 Sealing (IP Protection): IEC/EN 60529 class IP54; splash proof, dust protected  
 Shock/Drop Abuse Endurance: IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance  
 Electrostatic Discharge: IEC/EN 61000-4-2  
 Electromagnetic Compatibility: IEC/EN 60601-1-2 Emission, Immunity  
 Electrical Protection: IEC/EN 60601-1; Internally Powered Type BF/CF  
 Directive 93/42/CEE and 2007/47/CE: Class IIb

(\*)Temperature at 20°C Humidity 45% non-condensing

**MODEL NUMBERS**

Code SVD-B0004: Standard Version with maximum energy at 200J  
 Code SVD-B0005: Power Version with maximum energy at 360J

**CONFIGURATION OPTIONS (BOX CONTENT)**

Conf-Norm: Standard Basic Configuration (adult pads, disposable battery, carrying case)  
 Conf-Rech: Rechargeable Configuration (adult pads, accumulator, charger station, carrying case)  
 Conf-Print: Print Ready Configuration (adult pads, disposable battery, carrying case, IrDA port and thermal printer)  
 Conf-Rech/Print: Rechargeable & Print Ready Configuration (adult pads, accumulator, charger station, carrying case, IrDA port and thermal printer)

**5.7" TFT COLOUR DISPLAY**

**DETAILED AND COMPREHENSIVE SCREEN PROVIDES VALUABLE INFORMATION TO RESCUERS; RUNNING TEXT AND GRAPHICS COMBINED WITH VOICE MESSAGE:**

**ABOUT DEVICE:**  
 battery gauge with residual capacity indicator of available memory for recording notice if the microphone is active or OFF local date, time and alarms



**ABOUT RESCUE:**  
 adult or child protocol in use modality in use (AED, ECG or Manual) fibrillation and shock counts elapsed rescue time heart rate (bpm) impedance (ohms) ECG waveform touch/not touch pictogram charging bar graph if device charges energy level to be delivered (joule) CPR bar graph and cycles countdown



SAVER ONE P is a tough, small and lightweight Defibrillator easy to carry and use anywhere and able to act as an AED or a Manual Defibrillator or a Basic Cardiac Monitoring device.

**HIGHLY FLEXIBLE AND VERSATILE WITH ADVANCED CAPABILITIES**

AED per default, reliable for any BLS rescuer, can be easily switched in a Manual Defibrillator giving to ALS responders the best decision-making control for manual shock timing or an electric cardio version (synchronized shock).

To meet ALS professionals, SAVER ONE P has been designed with all advanced key features to make fast and effective defibrillation everywhere and in any circumstance, even the hardest and has been equipped with a new widely manageable software program which gives users the total control of device to suit their needs. Practical and flexible with Advanced PBLs feature enabling healthcare providers to use the 15:2 CV ratio when performing a Pediatric Basic Life Support, as required by Guidelines if more than one rescuer with a duty to respond.

- Supreme graphical user interface and new tools to have total control of the defibrillator.
- Biphasic escalating energy from 50 to 360J.
- Slight yet solid with long-lasting battery options to ensure the best outdoor and mobile use.
- Functionality guaranteed by daily self-test.
- Wider connectivity with removable card, USB and IrDA Port optional with Print Configuration.
- Unique features combined with available configurations give rise to exclusive devices.



**AED  
ECG Monitoring  
MANUAL Override**

Meet AHA/ERC 2017 Guidelines

**Maintenance-Free:** Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer. AED runs further tests after each battery insertion and every time device is turned on.

A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

**Service Mini-Screen:** In standby the mini LCD screen displays a check mark confirming AED is ready for use and a battery gauge informing about the residual charge. It will run error codes in faulty conditions.

**Entirely Discretionary:** 6 push-buttons allowing users to get the total control of defibrillator while in use: select the best modality, Manual Synchronous or Asynchronous or simply AED, to treat SCA according to events, take decision for shock anytime by choosing the right energy level to be delivered at each shock and get the device charged and ready to shock whenever needed or even disarm it in case defibrillation is not more required. After shocks, the heart rhythm rate can be watched over using the same defibrillation pads or, in case of longer monitoring, by connecting standard ECG electrodes to a separate optional reusable cable. Each step is conducted with the appropriate running features selected and set up in the device software by users.

**Adult / Child Capability:** Can be used on patients of any age with Adult or Pediatric proper electrodes. Device senses when Pediatric pads are installed and automatically adjusts to use a more appropriate lower energy level (50J).

**Monitoring section menu:** a new section has been introduced for the management of technical and physiological alarms and signals, according to IEC/EN 60601-2-27: patient loss, high or low heart rate, audio and visual signal for detection of a shockable rhythm so that the operator can switch/activate one of the available modes to deliver the shock (using the appropriate pads); scaling of the ECG trace on the display (gain x2 or ÷2) reset of the audio or visual alarms.

**DEFIBRILLATOR**

Operation: AED Semi-Automatic (default)  
ECG Monitoring  
Manual Asynchronous or Synchronous (used to convert atrial or ventricular tachyarrhythmia's)  
Energies: Standard max 200J or Power max 360J  
Waveform: Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance  
Energy type: Escalating from 50 to 360J  
AED Protocols: Adult Standard escalating 150, 200, 200J  
Adult Power escalating 200, 250, 360J  
Paediatric (Standard or Power) 50J fixed (AED adult shock protocols can be customized)  
Manual Protocol: Selected by users from 50 to 360J. For electric cardioversion (in Synchronous mode) the shock is synchronised to occur with the R wave of the ECG  
Energy Display: Screen provides the energy to deliver both in Manual mode or AED mode  
Charging time: <math>\leq 9</math> seconds with a new and fully charged battery depleted battery will result in a longer charging time  
Analysis time: IEC/EN 60601-2-4 from 4 to 15 seconds  
Impedance: 20-200 ohms  
Sensitivity: IEC/EN 60601-2-4 (AHADB, MITDB source), 97%  
Specificity: IEC/EN 60601-2-4 (AHADB, MITDB source), 99%  
Controls: 2 buttons: ON/OFF, shock button;  
3 buttons: to surf the menu;  
3 buttons: select energy, charge, disarm the device  
Indicators: Status LED indicator informing on device condition  
Battery gauge with remaining capacity rate  
Audible alerts and text display with service alarms through a USB cable or memory card  
Upgradeable:  
ECG MONITORING

**ECG MONITORING**

Operations: Through defibrillation pads or standard ECG electrodes attached to a separate 2-Lead patient monitoring reusable cable SAV-C0017  
Manual setting through the menu  
ECG size: 30-300 bpm  
Heart Rate: 25 mm/sec  
Sweep Speed: IEC/EN 60601-2-27 less than the points 202.6.2.101; 201.12.1.101.12,13; 208.6.6.2.101 not performed for the intended use of the device, as it is not intended for environments such as operating theatres or intensive care units  
Standard: 5,7" TFT colour, 640 x 480 pixel  
Display:  
PHYSICAL  
Size: 26,5 x 21,5 x 7,5 cm  
Weight: 2,08 kg with disposable battery  
2,13 kg with rechargeable battery

**BATTERY OPTIONS**

Type: Li-SOCI2 Disposable, code SAV-C0903  
Autonomy: 250 complete rescue cycles (shocks at 200J and CPR) or 160 complete rescue cycles (shocks at 360J and CPR) or 24 hours ECG Monitoring for a new and fully charged battery (\*)  
Shelf-Life: when stored in original packaging 5 years (\*)  
Battery-Life: 4years once installed to AED, assuming one battery insertion test and daily self-test but without switching AED on (\*)  
Type: Li-ion Accumulator, code SAV-C0011  
Recharging time: 2,5 hours with the charger station code SAV-C0014 (\*) (recommended to charge every 4 months at least)  
Autonomy: 200 shocks at 200J or 110 shocks at 360J or 14 hours in ECG Monitoring for a new fully charged accumulator (\*)  
2 years or 300 charging cycles (\*)

**PADS OPTIONS**

Type: Disposable, pre-gelled and self-adhesive  
Adult: Code SAV-C0846, for patient >8 years or >25 kg  
Paediatric: Code SAV-C0016, for patient <8 years or <25 kg  
Cable length: 120 cm  
Shelf-Life: 30 months

**EVENT RECORDING**

Internal memory: up to 6 continuous hours of ECG and rescue events  
Optional memory: Removable SD card; length of storage depends on card capacity: a 2GB card records up to 100 hours  
Data recording: "AED1LOG" text file with detailed self-test activity  
"AEDFILES" with complete recorded information  
"Saver View Express" data manager software

**ENVIRONMENTAL**

Operating temperature: 0°C to 55°C (32°F TO 131°F)  
Storing/Shipping temperature: -40°C to 70°C (-40°F TO 158°F) without battery  
Humidity: 10% to 95% relative humidity non condensing  
Sealing (IP Protection): IEC/EN 60529 class IP54; splash proof, dust protected  
Shock/Drop Abuse Endurance: IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance  
Electrostatic Discharge: IEC/EN 61000-4-2  
Electromagnetic Compatibility: IEC/EN 60601-1-2 Emission, Immunity  
Electrical Protection: IEC/EN 60601-1; Internally Powered Type BF/CF  
Directive 93/42/CEE and 2007/47/CE: Class IIb

(\*)Temperature at 20°C Humidity 45% non-condensing

**MODEL NUMBERS**

Code SVP-B0006: Standard Version with maximum energy at 200J      Code SVP-B0007: Power Version with maximum energy at 360J

**CONFIGURATION OPTIONS (BOX CONTENT)**

Conf-Norm: Standard Basic Configuration (adult pads, disposable battery, carrying case)  
Conf-Rech: Rechargeable Configuration (adult pads, accumulator, charger station, carrying case)  
Conf-Print: Print Ready Configuration (adult pads, disposable battery, carrying case, IrDA port and thermal printer)  
Conf-Rech/Print: Rechargeable & Print Ready Configuration (adult pads, accumulator, charger station, carrying case, IrDA port and thermal printer)

**5.7" TFT COLOUR DISPLAY**

**DETAILED AND COMPREHENSIVE SCREEN PROVIDES VALUABLE INFORMATION TO RESCUERS; RUNNING TEXT AND GRAPHICS COMBINED WITH VOICE MESSAGE:**



**ABOUT DEVICE:**  
battery gauge with residual capacity indicator of available memory for recording  
notice if the microphone is active or OFF  
local date, time and alarms

**MANUAL SYNCHRONOUS**  
The shock is synchronised to occur with the R wave of the ECG



**ABOUT RESCUE:**  
adult or child protocol in use  
modality in use (AED, ECG or Manual)  
fibrillation and shock counts  
elapsed rescue time  
heart rate (bpm)  
impedance (ohms)  
ECG waveform  
touch/not touch pictogram  
charging bar graph if device charges  
energy level to be delivered (joule)  
CPR bar graph and cycles countdown

# SAVER ONE AED SERIES

## Supplies and accessories

### TRAINING SOLUTIONS

#### SAVER ONE T CODE SVT – B0959

A smart and easy-to-use AED Trainer providing realistic training for many responders simultaneously.

Designed to meet needs of any instructor, it helps your responders learn to use defibrillators in simulated sudden cardiac arrest episodes for an extremely realistic training experience.

A non-shocking unit that follows the 1, 2, 3-step operations of the Saver One defibrillator and guides responders, with voice prompts in various languages, from ECG analysis until shock and CPR.

It is pre-configured with 10 realistic training scenarios manageable from distance with a wireless remote control and is equipped with a rechargeable battery which allows 20 hours of continuous operating.

SAVER ONE T comes equipped with one set of adult reusable training pads, a remote control, an accumulator with its charger, a quick reference card and a carrying case.



### CPR MANIKIN

#### HALF-BODY TRAINING MANIKIN FOR CPR PRACTICE MAN-B0608/MAN-B1058

With acoustic indicator of the correct deepness of compressions; a knob on the back with three different selection (adult-child-neutral) corresponding to 3 kinds of manikin resistance to compressions.

Content:

- 1 CPR Simulator
- 1 User Manual & FAQ
- 5 Lungs & 2 Valves
- 1 transport bag with mat



#### BABY INFANT TRAINING MANIKIN FOR CPR PRACTICE MAN-B1059/B1060

The most lifelike infant manikin; suitable for performing correct infant CPR, performing realistic breathing and head tilt.

Content:

- 1 Practi-Baby
- 1 User Manual
- 5 Lungs and 2 Valves
- 1 Transport bag



### FAST ACCESS SOLUTIONS



#### NEW OUTDOOR CABINET:

- WITH ALARM
- WITH HEATING & ALARM (SAV-C1051)

Outdoor Wall Cabinet AMI ITALIA in polystyrene and ABS available with alarm or with heater & alarm 100% dust- and waterproof



#### WALL BRACKET (SAV-C0911) CARRYING CASE (SAV-C0916)

Wall Mount Bracket in metal, designed for housing our AEDs in its carrying case. Carrying case made of special shockproof and splash proof material, with adjustable shoulder strap and hook handle.



#### TOTEM STAND SUPPORT

To provide easy access and visibility to our AEDs for outdoor location

**SAV-C1062:** Outdoor Metal Cabinet Yellow with heater and alarm, internal light, digital display for temperature

**SAV-C1063:** Outdoor Metal Cabinet white and green with heater and alarm, internal light, digital display for temperature.

**SAV-C1067:** Column for outdoor cabinet yellow SAV-C1062

**SAV-C1068:** Column for outdoor cabinet



#### NEW INDOOR CABINET:

- WITH ALARM (SAV-C0961)
- WITHOUT ALARM (SAV-C0912)

Indoor AMI ITALIA Wall Cabinet in strong metal, seamless look with or without audible alarm



#### INDOOR CABINET: (SAV-C1064)

Indoor cabinet with customized video display.



white and green SAV-C1063

**INDOOR CABINET: (SAV-C1065/C1066)**  
Indoor cabinet heart shaped with alarm; colour White/Red.



#### AED WALL SIGN - (CODE SAV-C0997)

An AED Wall Sign hanging above a Wall Mount Bracket or Defibrillator Cabinet gives even greater visibility to the defibrillator.

### ECG MONITORING & DATA MANAGEMENT

#### 2-LEAD ECG CABLE (CODE SAV-C0017)

Suitable for SAVER ONE D and SAVER ONE P Defibrillators when used in ECG Monitoring mode. The alternative to pads in case of long-term monitoring to be connected to standard ECG electrodes.

#### 8GB SD CARD (CODE SAV-C0907)

This removable card holds approximately 100 hours of events, ECG information and voice recording.

One card can hold data from multiple cases. A flash data card reader (SAV-C0027) enables data transfer from the card to a personal computer for use with the Saver View Express data management software.

#### THERMAL PRINTER - (CODE SAV-C1070)

Works with SAVER ONE D and SAVER ONE P Defibrillators optioned with the Print Ready Configuration (Conf-Print).

Those are equipped with IrDA Port and therefore are able to communicate with this external thermal printer.

Data saved into device can be selected from the menu and print it out as ECG format complete with case details.



#### SAVER VIEW EXPRESS (CODE SAV-C0019)

Saver View Express is a comprehensive data management tool for the most demanding professional allowing viewing and managing on your PC patient data downloaded from defibrillators. With fully detailed data screen to record every aspect of the treatment, including response times, interventions, and rescuer observations.

#### CONNECTING CABLE (CODE SAV-C0158)

Spare connecting cable for Smart Simulator S 1.

#### SIMULATOR / TESTER

#### SMART SIMULATOR S1 (CODE SSS-B0009)

This equipment can be used for a complete operating test of Saver One Defibrillators. It comes with a dedicated cable to be plugged to any Saver One AED in order to let it run as it was a real lifesaving treatment.

Able to simulate several ECG rhythms (VF, VT, NSR, Asystole, etc.) and display the energy level discharged, up to 360J.





IMQ mark for  
Safety & Quality



**North Italy Office**  
Viale Gran Sasso, 11  
20131 Milano - Italy  
Tel: +39.02.20509246  
Fax: +39.02.29520839

**South Italy Office & Production**  
Via Cupa Reginella, 15/A  
80010 Quarto - Italy  
Tel: +39.081.8060574  
Fax: +39.081.8764769

**Headquarters production site:**  
A.M.I. International kft.  
Közúzó u. 5/A 2000 Szentendre HU  
Hungary  
Tel. +3626302210