



Hospital Care & OPM










MEA Product Summary

Vasofix® Safety – Shielded IV Catheter with injection port

Protects you and your healthcare team against needlestick injuries and related infections.



- Complete portfolio for every vein condition, puncture site and patient age in two material types (FEP + PUR)
- Easy puncture at a wide range of angles because of optimized back cut bevel
- Minimum effort of catheter insertion
- Self-activating clip-technology => covers needle tip automatically after use
- Hygienic injection of medication via injection port without an extra needle or risk of needlestick injury
- PVC-free, latex-free

Color	Size		Vasofix® Safety		Stylet
	G	Ø mm	FEP	PUR (Certon®)	
 yellow	24 x 3/4"	0.7 x 19	—	4269071S-01	—
 blue	22 x 1"	0.9 x 25	4268091S-01	4269098S-01	4215095
 pink/white	20 x 1"	1.1 x 25	—	4269217S-01	4215117
 pink	20 x 1 1/4"	1.1 x 33	4268113S-01	4269110S-01	4219104
 green/white	18 x 1 1/4"	1.3 x 33	4268334S-01	4269330S-01	4219139
 green	18 x 1 3/4"	1.3 x 45	4268130S-01	4269136S-01	4219120
 white	17 x 1 3/4"	1.5 x 45	4268156S-01	4269152S-01	4215150
 grey	16 x 2"	1.7 x 50	4268172S-01	4269179S-01	4219171
 orange	14 x 2"	2.2 x 50	4268210S-01	4269225S-01	4219201

Certofix® Mono – Comprehensive single lumen catheter sets (Seldinger method)



- Catheter made of highly biocompatible polyurethane
 - Opaque, X-ray detectable catheter with length marking
 - Transparent extension line with side clamp
- Soft tip to reduce venous trauma
- Ready-to-use set components provided inside safety bag: Dilator, Safsite® valve, ECG connection cable, 5 ml Omnifix® lock syringe (included in all V-sets)
- Integrated and moveable fixation wing (for all sets with catheter length > 15 cm, except of Mono S 215 and Mono V 215)
- Highly flexible steel guide wire with one J-tip and one straight tip
- Different introducer needles: S = Seldinger needle; V = Valve needle



Code	Needle			Guide wire ø x length mm x cm	Catheter			Sales Unit/ pcs.	Ref. no.
	Type	G	length mm/inch		Size	ø mm	length cm/inch		
Vena jugularis									
S 215	S	20	50/ 2"	0.63 x 50	4F/18G	1.4	15/6"	10	4160185
V 215	V	20	50/ 2"	0.63 x 50	4F/18G	1.4	15/6"	10	4160193
S 315	S	18	70/2 7/8"	0.89 x 50	5F/16G	1.7	15/6"	10	4160223
V 315	V	18	70/2 7/8"	0.89 x 50	5F/16G	1.7	15/6"	10	4160231
S 320	S	18	70/2 7/8"	0.89 x 50	5F/16G	1.7	20/8"	10	4160258
V 320	V	18	70/2 7/8"	0.89 x 50	5F/16G	1.7	20/8"	10	4160266
S 415	S	18	70/2 7/8"	0.89 x 50	6F/14G	2.1	15/6"	10	4160509
V 415	V	18	70/2 7/8"	0.89 x 50	6F/14G	2.1	15/6"	10	4160517
S 420	S	18	70/2 7/8"	0.89 x 50	6F/14G	2.1	20/8"	10	4160304
V 420	V	18	70/2 7/8"	0.89 x 50	6F/14G	2.1	20/8"	10	4160320
Vena subclavia									
S 220	S	20	50/ 2"	0.63 x 50	4F/18G	1.4	20/8"	10	4160207
V 220	V	20	50/ 2"	0.63 x 50	4F/18G	1.4	20/8"	10	4160215
S 330	S	18	70/2 7/8"	0.89 x 70	5F/16G	1.7	30/12"	10	4160282
V 330	V	18	70/2 7/8"	0.89 x 70	5F/16G	1.7	30/12"	10	4160290
S 430	S	18	70/2 7/8"	0.89 x 70	6F/14G	2.1	30/12"	10	4160762
V 430	V	18	70/2 7/8"	0.89 x 70	6F/14G	2.1	30/12"	10	4160789

Certofix® Duo/Trio – Comprehensive multi-lumen catheter sets




Certofix® Duo – Double lumen catheter

- Kink-proof guide wire with unsurpassed flexibility with J-tip and one straight tip
- Catheter made of highly biocompatible polyurethane
 - Opaque, X-ray detectable catheter with length marking
 - Transparent extension line with side clamp
- Ready-to-use set components provided inside safety bag:
 - Dilator, Safsite® valves for each hub, ECG connection cable, scalpel E11 type, 5 ml Omnifix® lock syringe (included in all V-sets)
- Soft tip to reduce venous trauma
- Integrated and moveable fixation wing
- Different introducer needles:
 - S = Seldinger needle; V = Valve needle



Code	Needle		Guide wire ø x length mm x cm	Catheter				Sales Unit/ pcs.	Ref. no.
	ø Type	Length mm/inch		Size	Outer ø mm	Length cm/inch	Channels G		
Certofix® Duo – Double lumen catheter									
S 715	18G S	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	15/6"	16/16	10	4164158
V 715	18G V	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	15/6"	16/16	10	4166159
S720	18G S	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	20/8"	16/16	10	4167385
V 720	18G V	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	20/8"	16/16	10	4161211
S 730	18G S	70/2 7/9"	0.89 x 70 (kink-proof)	7 F	2.4	30/12"	16/16	10	4167394
V 730	18G V	70/2 7/9"	0.89 x 70 (kink-proof)	7 F	2.4	30/12"	16/16	10	4161319
Certofix® Trio – Triple lumen catheter									
S 715	18G S	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	15/6"	16/18/18	10	4161159
V 715	18G V	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	15/6"	16/18/18	10	4162153
S720	18G S	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	20/8"	16/18/18	10	4167408
V 720	18G V	70/2 7/9"	0.89 x 50 (kink-proof)	7 F	2.4	20/8"	16/18/18	10	4163214
S 730	18G S	70/2 7/9"	0.89 x 70 (kink-proof)	7 F	2.4	30/12"	16/18/18	10	4163306
V 730	18G V	70/2 7/9"	0.89 x 70 (kink-proof)	7 F	2.4	30/12"	16/18/18	10	4163311



Perifix® Standard and Soft Tip catheters:

- Excellent shaft stability and kink resistance while still flexible for easy placement and removal
- Crystal clear for easy visualization of fluids
- Fully embedded x-ray lines and easy readable length markings for safe catheter placement

Ref. no.	Article	Perican® Tuohy needle	Epidural filter	8 ml LOR syringe, Luer	Perifix® PinPad	Omnifix® syringes Luer-Lock	Sterican® needles	Sales Unit/ pcs.
<i>Perifix® Standard set with G20 x 40" (0.85 x 1000 mm) catheter, central open tip</i>								
4516206	Perifix® 620	G18 x 3 1/4"	●	●	●	2, 10, 20 ml	G18 x 1 1/2", G21 x 1 1/2", G25 x 5/8"	10
4511000	Perifix® 100	G18 x 3 1/4"	—	—	—	—	—	20
<i>Perifix® Standard set with Perican® G18 (1.3x 80 mm) and G20 x 40" (0.85 x 1000 mm) catheter or Perican® G16 (1.7 x 80 mm) and G19 x 40" (1.05 x 1000 mm) catheter, closed tip with 3 lateral eyes</i>								
4514211	Perifix® 421	G18 x 3 1/4"	●	●	●	2, 20 ml	G18 x 1 1/2", G21 x 1 1/2", G25 x 5/8"	10
4514203	Perifix® 420	G18 x 3 1/4"	●	—	●	2, 10, 20 ml	G18 x 1 1/2", G21 x 1 1/2", G25 x 5/8"	10
4514513	Perifix® 451	G18 x 3 1/4"	●	●	●	—	—	20
4514017	Perifix® 401	G18 x 3 1/4"	●	●	—	—	—	20
4514009	Perifix® 400	G18 x 3 1/4"	●	—	—	—	—	20
4513010	Perifix® 301	G18 x 3 1/4"	—	●	—	—	—	20
4513002	Perifix® 300	G18 x 3 1/4"	—	—	—	—	—	20
4514319	Perifix® 431	G16 x 3 1/4"	●	●	●	2, 20 ml	G18 x 1 1/2", G21 x 1 1/2", G25 x 5/8"	10
4514300	Perifix® 430	G16 x 3 1/4"	●	—	●	2, 10, 20 ml	G18 x 1 1/2", G21 x 1 1/2", G25 x 5/8"	10
4514025	Perifix® 402	G16 x 3 1/4"	●	●	—	—	—	20
4513029	Perifix® 302	G16 x 3 1/4"	—	●	—	—	—	20
4513100	Perifix® 310	G16 x 3 1/4"	—	—	—	—	—	20

Spinocan®, Pencan®, Atraucan® – Needles for spinal anesthesia, diagnostic lumbar puncture and cytologic biopsies

Pencan®

- Total reflection effect
- Pencil point needle tip with lateral opening (like Whitacre® from B-D/Vygon or Sprotte® from Pajunk)
- Distinct feeling of the dural click








Atraucan®

- Special bevel design to reduce post dural puncture headache
- Two-zone atraumatic bevel design

Spinocan®

- With Quinke bevel



Color		Size		Spinocan®	Pencan®	Atraucan®	Sales Unit/ pcs.
		G / inch	mm				
	pink	G18	G18 x 3"	4501373-13			25
			G18 x 3 1/2"	4501390-01			25
	ivory	G19	G19 x 1 1/2"	4501144-13			25
			G19 x 3 1/2"	4501195-13			25
	yellow	G20	G20 x 3"	4509757-13			25
			G20 x 3 1/2"	4509900-01			25
	black	G22	G22 x 1 1/2"	4507401-13			25
			G22 x 3"	4507754-13			25
			G22 x 3 1/2"	4507908-01	4502035-13		25
			G25 x 1"		4502167-13		25
	orange	G25	G25 x 2"		4502159-13		25
			G25 x 3"	4505751-01			25
			G25 x 3 1/2"	4505905-01	4502019-01		25
	brown	G26	G26 x 1"			4504771	25
			G26 x 2"			4504763	25
			G26 x 3 1/2"	4502906-01			25
	grey	G27	G27 x 2"		4502175-13		25
			G27 x 3 1/2"	4503902-01	4502027-01		25

All spinal needles with transparent lock hub and color-coded stylet hub. Whitacre® is a trademark of Becton-Dickinson. and Sprotte® from Pajunk.

Infusomat® Space Lines – For use with Infusomat® Space & Infusomat® fmS



- Sharp, piercing spike
- Bacteria-proof venting with Euro-cap
- Upper drip-chamber segment ideal for attachment of an infusion pump drip sensor
- 15 µm fluid filter
- Roller clamp with piercing-spike covering for safe disposal
- Silicone pump segment
- DEHP-free

Description	Length (cm)	Sales Unit	Ref. no.	Latex free	PVC free
Type "Standard" with injection port for needle access	270	100	8700087SP	●	-
Type "Standard"	300	100	8270350SP	●	-
Type "Standard" with Safeflow needle-free injection port	270	50	8700110SP	●	●
Type „SafeSet“, standard	250	100	8701148SP	●	-
Type „SafeSet“, Neutrapur	250	100	8701149SP	●	●
Type „SafeSet“, with Safeflow needle-free injection port	300	100	8700118SP	●	●
Type "UV-protected" with Safeflow, orange	250	100	8250437SP	●	●
Type "UV-protected", orange	250	100	8700127SP	●	●
Type "Enteral Nutrition Safety" w. Enterofix 1000 ml; PVC	230	25	8250836SP	●	-
Type "Enteral Nutrition Safety" w. Multi connector; PUR	320	40	8250856SP	●	●
Type "Eqidural", Yellow, ProSet	300	100	8700131SP	●	●
Type "Cyto-Set" with 3 needle-free valves	210	20	8250917SP	●	●
Type "Cyto-Set" with 5 needle-free valves	210	20	8250817SP	●	●
Type "Cyto-Set" with 5 needle-free valves and 0.2 µm filter	210	20	8250414SP	●	●
Type "Cyto-Set Mix" with 1 needle-free valve, orange	32	20	A2900N	●	●
Type "Cyto-Set Mix" with 1 needle-free valve and 0.2 µm filter	32	20	A2903N	●	●
Type "Cyto-Set" Mix" with 1 needle-free valve, orange	32	20	A2906N	●	●
Type "Cyto-Set" Line 0.2 µm filter, orange	32	20	A2582NF	●	●
Type "Cyto-Set" Line	32	20	A2581NF	●	●
Type "Piggybacking" with 2 Safeflow needle free injection ports	300	100	8250710SP	●	●
Secondary line for 8250710SP	75	20	4062877	●	●
Type "Transfusion" with 200 µm blood filter	250	100	8270066SP	●	-
Type "Transfusion" with injection port	250	100	8270074SP	●	-
Type "Y-Transfusion"	250	50	4181557SP	●	-
Type "Neutrapur"	250	100	8250731SP	●	●
Type "Neutrapur" with 0.2 µm filter	250	20	8700095SP	●	●
Type "Dosifix®" with Safeflow needle-free injection ports	270	25	8250245SP	●	●
Type "Dosifix®" with SafeSet UV-protected, orange	250	25	8700128P	●	●