

# Nanjing Jingning Quality Inspection Company

## Quality Certificate

Drywall Screw, Coarse/Fine Thread, GRAY phosphate



| Specification                   | Items   | torsion standard | Attack speed | result |
|---------------------------------|---------|------------------|--------------|--------|
| Drywall Screw,<br>Fine Thread   | 3,5x16  | 2.80             | 1S           | Acc.   |
|                                 | 3,5x19  | 2.80             | 1S           | Acc.   |
|                                 | 3,5x25  | 2.80             | 1S           | Acc.   |
|                                 | 3,5x35  | 2.80             | 1S           | Acc.   |
|                                 | 3,5x45  | 2.80             | 1S           | Acc.   |
|                                 | 3,5x55  | 2.80             | 1S           | Acc.   |
|                                 | 4,2x70  | 4.90             | 1S           | Acc.   |
|                                 | 4,8x89  | 4.90             | 1S           | Acc.   |
|                                 | 4,8x102 | 6.80             | 1S           | Acc.   |
| Drywall Screw,<br>Coarse Thread | 3,5x16  | 2.80             | --           | Acc.   |
|                                 | 3,5x19  | 2.80             | --           | Acc.   |
|                                 | 3,5x25  | 2.80             | --           | Acc.   |
|                                 | 3,5x32  | 2.80             | --           | Acc.   |
|                                 | 3,5x35  | 2.80             | --           | Acc.   |
|                                 | 3,5x41  | 2.80             | --           | Acc.   |
|                                 | 3,5x45  | 2.80             | --           | Acc.   |
|                                 | 3,5x51  | 2.80             | --           | Acc.   |
|                                 | 3,5x55  | 2.80             | --           | Acc.   |
|                                 | 3,8x64  | 3.40             | --           | Acc.   |
|                                 | 4,2x70  | 4.90             | --           | Acc.   |
|                                 | 4,2x76  | 4.90             | --           | Acc.   |
|                                 | 4,8x89  | 6.80             | --           | Acc.   |
|                                 | 4,8x95  | 6.80             | --           | Acc.   |
|                                 | 4,8x102 | 6.80             | --           | Acc.   |
|                                 | 4,8x120 | 6.80             | --           | Acc.   |
|                                 | 4,8x152 | 6.80             | --           | Acc.   |

Remark: Acc. Stands for acceptable

|                                                |            |     |     |                        |     |                        |
|------------------------------------------------|------------|-----|-----|------------------------|-----|------------------------|
| Steel grade: SWRCH22A                          |            |     |     |                        |     |                        |
| Specification: Q/ASB 234-2015                  |            |     |     |                        |     |                        |
| Chemical composition & Technical specification |            |     |     |                        |     |                        |
| Element                                        | C%         | Si% | Mn% | P%                     | S%  | Cr%                    |
| Ratio                                          | 21         | 8   | 78  | 1.7                    | 0.7 | 2                      |
|                                                | Elongation |     |     | Contraction Percentage |     | Tensile Strength (Mpa) |
| Ratio                                          | 28%        |     |     | 64%                    |     | 498                    |

Inspection date: 2016.1.20

Inspector:Li Jun

