

CERTIFICATE OF ANALYSIS

Product : Lamination

Product Description : BİFLEX SPUNBOND BLUE NONWOVEN FABRIC ROLLS
 Raw Material : 34 gr/m2 sb ,20 gr/m2 pe film ,2 gr/m2 adhesive
 Application on Fabric : SB+PE FİLM
 Treatment :
 Fabric Colour : BLUE
 Customer Name :
 Weight : **56 GSM**
 Width :
 Packing : PE BAG WITH LABEL

PROPERTIES	TEST METHOD	UNIT	TARGET
WEIGHT	NWSP 130.1.R0 (15)	gsm	56
THICKNESS	NWSP 120.1.R0 (15)	mm	0,22
TENSILE STRENGTH	MD	N/5 cm	114,0
			57,5
ELONGATION AT BREAK	MD	%	111,3
			94,8
HYDROSTATIC HEAD	NWSP 080.6.R0(15)	mm	
AIR PERMEABILITY	NWSP 070.1.R0 (15)	l/m ² /s(200 pa)	
ABSORPTION	WATER	%	
	OIL		

Tolerances For The Avarage Results

Weight	± 5 %
Thickness	± 10 %
Tensile Strenght	± 15 %
Elongation	± 15 %
Hydrostatic Head	± 15 %
Air Permeability	± 20 %
Absorption	± 20 %

Roll Tolerance

Length : - 0 / +5% against target / ordered lenght

Width : Up to 150 cm in width = -0mm/+5mm Over 150 cm in width = - 0mm/+ 10

Splice : Maxium five splices per roll

The product is wound onto cardboard cores and then wrapped in polyethylen film. Bar code labels with product code, description and lot details are applied to the outside of each pack and a small label is applied to each roll. Suitable sized rolls may be palletised and the pallet load cling-wrapped

Preperation Date

30.03.2018

QUALITY CONTROL APPROVED

VE SAĞLIK ÜRÜNLERİ SAN. VE TİC. LTD.ŞTİ.

Mahmutbey Mah. 2567 Sk. No:115 Yeri No:11,21

Bağcılar / İSTANBUL / TÜRKİYE

Tel: 0212 445 45 25 Tlc.Sic.No: 794704

Güneşli YD.: 997 067 1942