

# BCS-P-NVR0902-A-4K(5)

Index: **12652** GTIN13/EAN13: 5904890714564

URL: <https://bcs.pl/gb/8-channel/4327-bcs-p-nvr0902-a-4k5-5904890714564.html>



## BCS-P-NVR0902-A-4K(5)

## Product Details

<b>Product</b>	BCS-P-NVR0902-A-4K(5)
<b>Brand</b>	BCS POINT
<b>NDAA</b>	National Defense Authorization Act
<b>System</b>	IP
<b>Pentaplex function</b>	Live view / recording / playback / archiving / remote access
<b>Channels</b>	9
<b>HDD support</b>	2
<b>HDD capacity</b>	16 TB
<b>RAID type</b>	1
<b>ANR</b>	Automatic synchronization of recordings from the camera's microSD card after the connection is lost and restored.
<b>Max recording resolution</b>	16 Mpx
<b>Incoming bandwidth</b>	320Mbps(160Mbps Ai)
<b>Outgoing bandwidth</b>	160Mbps
<b>Display efficiency</b>	2x16MP@30 2x12MP@30 4x4K@30 8x4MP@30 9x3MP@30 9x1080P@30 Ai: 2x12MP@30 2x4K@30 6x4MP@30 8x3MP@30 9x1080P@30
<b>Recording resolutions</b>	16M / 12M / 8M / 6M / 5M / 4M / 3M / 2M / 960p / 720p / D1 / 2CIF / CIF
<b>Video compression</b>	H.265+ / H265 / H.264
<b>HDMI out</b>	HDMI4K
<b>VGA out</b>	VGA
<b>HDMI display resolutions</b>	3840×2160 / 1920×1080 / 1600×1200 / 1280×1024 / 1280×720 / 1024×768
<b>VGA display resolutions</b>	1920×1080 / 1600×1200 / 1280×1024 / 1280×720 / 1024×768
<b>Display split</b>	1/4/6/8/9 (3/4/5/7/9 corridor mode)
<b>Synchronous playback</b>	1/4/8/9
<b>Archiving</b>	Possibility to download material to external media such as USB FLASH, USB HDD
<b>User connections</b>	128
<b>Interfaces</b>	2×USB2.0, 1×USB3.0
<b>Serial port</b>	RS485
<b>Audio in</b>	1
<b>Audio out</b>	1
<b>Audio compression</b>	G.711A / G.711U
<b>Alarm in</b>	8
<b>Alarm out</b>	2
<b>Support</b>	Local, Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
<b>Network</b>	2×RJ-45 10/100/1000Mbps
<b>Compatibility</b>	ONVIF(S/G/T), support third party cameras
<b>Protocols</b>	TCP/IP, P2P, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS, RTSP, IPv6, IPv4
<b>Power supply</b>	12V DC
<b>Power consumption (without HDD)</b>	max 12W
<b>Working environment</b>	-10°C~+50°C max 90% RH
<b>Casing</b>	1U
<b>Dimensions (W×D×H)</b>	380×315×53mm
<b>Weight (without HDD)</b>	2 kg

<b>POS</b>	Yes
<b>Ai - Intelligent functions from recorder</b>	Face Detection, Face Comparison, Smart Intrusion Prevention (SIP), Ultra Motion Detection (UMD)
<b>Ai - Intelligent functions from camera</b>	Face Detection/Comparison, Vehicle Detection, SIP(Intrusion/Cross Line, Enter/Leave Area), Ultra Motion Detection(UMD), Temperature(Fire/Smoking/M Measurement/Smoke/Fire Detection), People Counting(People Flow, Crowd Density), Video Metadata, Traffic