

## Eaton 5PX2200IRTNG2



Imaginile sunt doar cu titlu informativ

Eaton 5PX Gen2 UPS, 2200 VA, 2200 W,  
Input: C20, Output: (8) C13, (2) C19,  
Rack/tower, 2U, Network card included

### General specifications

<b>PRODUCT NAME</b>	Eaton 5PX Gen2 UPS
<b>CATALOG NUMBER</b>	5PX2200IRTNG2
<b>UPC</b>	743172104847
<b>PRODUCT LENGTH/DEPTH</b>	603 mm
<b>PRODUCT HEIGHT</b>	85.5 mm
<b>PRODUCT WIDTH</b>	438 mm
<b>PRODUCT WEIGHT</b>	28.2 kg
<b>COMPLIANCES</b>	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 RoHS Compliant REACH UL 1778 CSA 22.2
<b>CERTIFICATIONS</b>	CE cTUVus EAC Cm UKCA Ukr KCC ENERGY STAR certified
<b>MODEL CODE</b>	Eaton 5PX 2200i RT2U Netpack G2

## Additional information

<b>AUTO SHUTDOWN FUNCTION</b>	Yes
<b>COLOR</b>	Black/silver
<b>CONSTRUCTION TYPE</b>	482.6 mm (19 inch) device
<b>EFFICIENCY AT MAX. LOAD</b>	98

### PACKAGE CONTENTS

- Network Management Card
- Input cable
- Rack-mounting kit
- (2) Supports for tower mounting
- Cable locking system
- USB cable
- Serial cable
- (2) IEC-IEC cables
- Quickstart guide
- Safety instructions

<b>PHASE (INPUT)</b>	1
<b>PHASE (OUTPUT)</b>	1
<b>RACK MOUNTING KIT</b>	Yes

## Battery specifications

<b>BATTERY MANAGEMENT</b>	ABM & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, automatic recognition of external battery units
<b>BATTERY QUANTITY</b>	6
<b>BATTERY RATING</b>	12 V / 7 Ah
<b>BATTERY REPLACEMENT</b>	User replaceable
<b>BATTERY TYPE</b>	Lead-acid maintenance-free (replaceable)
<b>EXTENDED BATTERY CAPABILITY</b>	Yes
<b>RUNTIME GRAPH</b>	\$row.attributeValue.cdata

## Communication

### COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini-terminal block for remote On/Off and Remote Power Off
- Mini-terminal block for output relay
- Dry contacts (3 outputs, 1 input, optocoupler, DB9)

<b>EXPANSION SLOTS</b>	One slot, network card included
------------------------	---------------------------------

<b>INCLUDES NETWORK CARD</b>	Yes
------------------------------	-----

<b>POTENTIAL FREE SWITCH CONTACT</b>	Yes
--------------------------------------	-----

<b>SOFTWARE COMPATIBILITY</b>	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
-------------------------------	--

<b>TYPE OF INTERFACE</b>	Other
--------------------------	-------

<b>USER INTERFACE</b>	Multilingual graphical LCD display
-----------------------	------------------------------------

## Electrical output

<b>FEED TYPE</b>	1
------------------	---

<b>OUTPUT NOMINAL VOLTAGE</b>	230V default (200/208/220/230/240V)
-------------------------------	-------------------------------------

<b>OUTPUT POWER FACTOR</b>	1
----------------------------	---

<b>OUTPUT VOLTAGE RANGE</b>	230 V (+6%/-10%)
-----------------------------	------------------

<b>OUTPUT WAVEFORM</b>	Sine wave
------------------------	-----------

<b>RECEPTACLE</b>	(8) C13, (2) C19
-------------------	------------------

<b>TOPOLOGY</b>	Line-interactive
-----------------	------------------

<b>VA RATING</b>	2200 VA
------------------	---------

<b>VOLTAGE</b>	230V
----------------	------

<b>VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX</b>	0
--	---

<b>WATTAGE</b>	2200 W
----------------	--------

## Electrical input

<b>INPUT CONNECTION</b>	C20
-------------------------	-----

<b>INPUT CORD LENGTH</b>	1.8m
--------------------------	------

<b>INPUT FREQUENCY RANGE</b>	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode
------------------------------	---

<b>INPUT NOMINAL VOLTAGE</b>	230V default (200/208/220/230/240V)
------------------------------	-------------------------------------

<b>INPUT VOLTAGE RANGE</b>	160-294 V (adjustable to 150 V-294 V)
----------------------------	---------------------------------------

<b>NOMINAL FREQUENCY</b>	50-60 Hz
--------------------------	----------

## Environmental

<b>ALTITUDE</b>	3000 m
-----------------	--------

<b>NOISE LEVEL</b>	<40 dB at 1 meter
--------------------	-------------------

<b>RELATIVE HUMIDITY</b>	0-90% non-condensing
--------------------------	----------------------

<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F), batteries recommended max. 25°C (77°F)
--------------------------	---

## Resurse

COMPLIANCE  
INFORMATION [Eaton 5PX Gen2 - EU  
Declaration of Conformity](#)

GHIDURI DE UTILIZARE [Eaton 5PX Gen2 -  
Quickstart guide](#)

---

**DENUMIREA PROIECTULUI:**

**NUMĂRUL PROIECTULUI:**

**PREGĂTIT DE:**

**DATA:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Irlanda  
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare  
pentru a obține cele mai noi  
informații despre produse și  
asistență.

