

## MEDICAL GRADE SILICONE TUBES FOR EXTERNAL USE



**SILICONE TUBES for external medical use - silicone 100%**  
 Suitable for autoclaving (135°C - 2.2-2.5 bar) and Gamma Sterilization. Resistant to hot air up to 200°C.  
 Infra-red vulcanization.  
 Hours treatment at 200°C temperature in special oven.  
 Anti-adherent, avoid incrustation and coagulation.  
 Medical Grade - Transparent - Odourless

### TECHNICAL SPECIFICATIONS

Raw material: HTV-R-401/60 S - WACKER (D)  
 Colour: translucent  
 Hardness: 60° ±5% Shore - DIN 53505  
 Density: 1.17 g/ccm - DIN 53479A  
 Tensility: 10.8 N/mm<sup>2</sup> - DIN 53504 S1  
 Stretch: 490/530% - DIN 53504S1  
 Tear resistance: 34-35 N/mm - ASTM D 624 B  
 Reverse pull elasticity: 51% - DIN 53512  
 Compression set: (22h/175°C): 30-15% - DIN 53517

Made in European Union according to: US PHARMACOPOEIA XXI  
 EUROPEAN PHARMACOPEA DIN 58367 - DIN 58362 - DIN  
 13098- FDA 177.2600 - BGA XV part A and B - BGA IX part B

GIMA code	Internal diameter x external diameter	Thickness mm	Minimum order
25450	1x3 mm	1 mm	roll of 100 m
25451	2x4 mm	1 mm	roll of 100 m
25452	3x5 mm	1 mm	roll of 100 m
25453	4x6 mm	1 mm	roll of 100 m
25455	6x8 mm	1 mm	roll of 30 m
25458	3x6 mm	1.5 mm	roll of 30 m
25459	4x7 mm	1.5 mm	roll of 30 m
25460	5x8 mm	1.5 mm	roll of 30 m
25461	6x9 mm	1.5 mm	roll of 30 m
25462	7x10 mm	1.5 mm	roll of 30 m
25466	4x8 mm	2 mm	roll of 30 m
25467	5x9 mm	2 mm	roll of 30 m
25468	6x10 mm	2 mm	roll of 30 m
25469	8x12 mm	2 mm	roll of 30 m
25470	10x14 mm	2 mm	roll of 30 m
25474	5x10 mm	2.5 mm	roll of 30 m
25475	7x12 mm	2.5 mm	roll of 30 m
25476	8x13 mm	2.5 mm	roll of 30 m
25477	10x15 mm	2.5 mm	roll of 30 m
25480	6x12 mm	3 mm	roll of 30 m
25481	7x13 mm	3 mm	roll of 30 m
25482	8x14 mm	3 mm	roll of 30 m
25483	9x15 mm	3 mm	roll of 30 m
25484	10x16 mm	3 mm	roll of 30 m
25485	12x18 mm	3 mm	roll of 30 m
25488	8x15 mm	3.5 mm	roll of 30 m
25491	10x20 mm	5 mm	roll of 30 m
25495		made to order	500 m

**MADE TO ORDER SILICONE TUBES**  
 We can manufacture any size  
 (minimum order 500 m - delivery 30 days)

## ACCESSORIES FOR ANY SUCTION ASPIRATOR



GIMA code	STAINLESS STEEL ASPIRATION TUBES
28262	S/S Bierer Aspiration tube Ø 8 mm
28264	S/S Bierer Aspiration tube Ø 12 mm
	Supplied with removable connection cannula
28260	Set of 7 uterine aspiration cannulas for abortion: 4 cannulas with side suction end (Ø 5, 6, 8, 9 mm), 3 cannulas with front suction end (Ø 7, 10, 11 mm) and one handle

- SILICONE VACUUM SUCTION  
See page 172
- SUCTION CATHETER  
See page 43
- S/S FRAIZER SUCTION CANNULA  
See page 34
- S/S ROSEN SUCTION CANNULA  
See page 34
- S/S NOVAK SUCTION CANNULA  
See page 33

## BREAST PUMP - MAMILAT GIMA

• **28148 MAMILAT - BREAST PUMP - 230 V - 50 Hz**  
 Easily transportable from one maternity ward to another, or for use at home. To be used for mother's milk suction. Made of highly heat-resistant, electrically insulated plastic material in conformity with the latest European safety standards. Supplied with 2 polycarbonate milk bottles (150 cc and 250 cc) antibacterial and hydrofobic filter, set of tubes 6x10 mm, breast shield, PVC air tube. Suction adjustment knob. Working time: 20 minutes ON, 40 OFF.

• **28229 HYDROPHOBIC ANTIBACTERIAL FILTER - spare**

• **28149 SPARE KIT**

Includes two plastic bottles (125 cc and 250 cc) nipple shield, filter and tubes.

### TECHNICAL SPECIFICATIONS

Regulator for suction intensity - max suction -0.33 bar  
 Operating voltage: 220-230 V - 50/60 Hz - available on request 110 V - 60 Hz  
 Max flow (air litres/min): 14 l/min  
 Power consumption: 184 VA  
 Size: 235x190x165 mm Weight: 2.2 kg  
 Norms: CEI 62-5 (IEC601-1). Made in Italy

Supplied with anti-bacterial filter

5 languages manual:  
 IT, GB, ES, FR, DE.



28148