Xerox[®] AltaLink[®] Color Multifunction Printers

Xerox[™]

C8130/C8135/C8145/C8155/C8170



Xerox[®] AltaLink[®] C8100 Series Color Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Speed ¹					
Color/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm
Monthly Duty Cycle ²	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ Option	nal: 500 GB HDD/Intel Atom® Q	uad Core 1.91 GHz/4 GB system	memory (8 GB system memory a	AltaLink® C8170)
Connectivity	Ethernet 10/100/1000 Base-T	, High-speed USB 2.0 direct prin	t, NFC, Optional: WiFi/WiFi Dire	ct with Xerox® Dual Band Wirele	ss Kit, Bluetooth (iBeacon)
Controller Features	Unified Address Book, Remote	Control Panel, Configuration Cla	oning, Fleet Orchestrator, Configu	ration Watchdog	
Optional Controller	Xerox® EX-c C8100 Print Server	Powered by Fiery®			
Copy and Print					
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Pri	int: Up to 1200 x 2400 dpi			
First-Print-Out Time (as fast as)	5.7 seconds color/4.2 seconds	black-and-white	4.9 seconds color/3.8 seconds black-and-white	4.5 seconds color/3.2 seconds black-and-white	3.8 seconds color/3.0 seconds black-and-white
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.1 seconds color/4.5 seconds black-and-white		5.5 seconds color/4.4 seconds black-and-white	4.7 seconds color/3.7 seconds black-and-white	4.0 seconds color/3.2 seconds black-and-white
Page Description Language	Adobe® PostScript® 3™, Adobe	® PDF, PCL® 5c/PCL® 6			
Print Features	Identification, Booklet Layout, Printing (as default), Hold All Jo	Store and Recall Driver Settings obs, Long Sheet (Banner) Printin	Orive, and Google Drive), Encryp , Bi-directional Real-time Status, S g, Print Around, Print on Alternat can to Xerox® DocuShare® Go co	Scaling, Job Monitoring, Applicat e Paper; Imaging Security with A	ion Defaults, Two-sided
Mobile and Cloud Ready					
Mobile Connectivity	Near Field Communication (NF	FC); Optional: Wi-Fi Direct, Wi-F	i (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon (Bluetooth)	
Mobile Printing	Mopria® Scan, Apple AirPrint™, including iBeacon (Bluetooth)	Xerox® Print Service (Android),	@PrintByXerox App; Optional: Xe	erox® Workplace Mobile App (iO	5/Android), AirPrint™ (iOS)
Mobile Scanning	Mopria® Scan, Apple AirPrint™,	Optional: Xerox® Workplace M	obile App (iOS/Android)		
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)				
Xerox® Workplace Central Platform	cloud-based workflows you car with a wider audience, turn ha	Dee-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases			

Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure
Scan	
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support, Touchless Workflow Accelerators, Imaging Security with AltaLink's proprietary marking and infrared detection technology
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, Firmware Verification, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager, LogRhythm SIEM, Splunk SIEM, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2.User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Job Level Encryption via HTTPS and Drivers, Signed Email, Common Criteria Certification (ISO 15408), Encrypted Secure Print, Imaging Security (copy, print, scan, email) with AltaLink's proprietary marking and infrared detection technology
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with multi-pass Image Overwrite³, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



USER INTERFACE



INNOVATIVE TECHNOLOGIES

Intuitive Tablet-like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

Xerox® Integrated RFID Card

90 access cards.

with the MFP.

Reader (optional) adds card-based authentication with support for over

Near Field Communication (NFC)

Tap-to-Pair allows users to tap their mobile devices to the AltaLink® C8100 Series user panel and quickly connect

Smart Proximity Sensor detects

when users are nearby. It conserves

energy during inactive periods and automatically activates the device when a user approaches.

PAPER INPUT⁴

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four Tray Module Configuration

(available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.



Feeder (optional) holds 3,000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.





Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1.320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50-sheets of 20 lb./75 gsm media.

Device Specification					
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic				
Accessories					
Optional	BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Booklet Maker for Office Finisher Bluetooth Kit Convenience Stapler (includes Work Surface ⁵) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and of High Capacity Feeder 3000 A4/Letter Hole Punch (273, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® C8130, C8135, C8145, C8155) Long Sheet Feed Kit (banner printing) McAfee® Integrity Control Enablement Kit Multi-feed Detection Kit (AltaLink® C8170 only) Office Finisher Smart Card Enablement Kit USB Keyboard/Shelf Kit Unicode Font Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Xerox® EX-c C8100 Print Server Powered by Fiery® Xerox® Integrated RFID Card Reader Kit 500GB HDD				
Electrical Requirements	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C				
North America		-127 VAC +/- 10 % 50/60 Hz +/- 3 % ,			
Europe		-240 VAC +/- 10 % 50/60 Hz +/- 3 % ,			

Device Specification (continued)					
Power Consumption	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Running (Average)	115V: 576 watts 230V: 586 watts	115V: 600.3 watts 230V: 595.8 watts	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts
Standby Mode	115V: 67 watts 230V: 71 watts	115V: 64 watts 230V: 70 watts	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts
Auto Off/Sleep Mode	115V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 8.5 seconds				
Recovery from Sleep	As fast as 4.5 seconds				
Operating Environment					
Required Temperature Range	50 to 82° F/10 to 28° C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 4.0/4.0 dB(A)		Operating: 65.2/67.3 dB(A) Standby: 4.3/4.3 dB(A)		Operating: 70.4 dB(A) Standby: 4.3 dB(A)
Dimensions and Weight					
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 316 lb./143.1 kg				Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 352.1 lb./159.7 kg
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 32.2 in./819 mm Depth: 28.5 in./723 mm Height: 44.55 in./1,130 mm Weight: 340 lb./154.2 kg				N/A
With Office Finisher (with Booklet Maker)	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 402.3 lb./182.5 kg				Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 439 lb./199 kg
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 412.3 lb/187 kg				Width: 55 in./1,395 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 448.4 lb./203.4 kg
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 449.7 lb./204 kg				Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 486.3 lb./220.6 kg
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 560.6 lb./254.3 kg				Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 597.2 lb./270.9 kg
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 628.8 lb./285.2 kg				Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 665.8 lb./302 kg
System Certifications/Regulo	atory Compliance				
Certifications	To view the latest list of certific	ations, go to xerox.com/Office	Certifications		

Paper Handling	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)	'		<u>'</u>	
Capacity ⁴	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and o 141 ipm black-and-white and				135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85	5 x 125 mm to 297 x 432 m	m		
Weights	16 to 32 lb. bond/60 to 128 g	sm			
Bypass Tray (Standard)					
Capacity ⁴	100 sheets				
Sizes	Custom Sizes: 3.5 x 3.9 in. to	12.6 x 52 in./89 x 98 mm to	320 x 1320 mm (SEF); Optior	nal: Long Sheet Feed Kit (Banner	Printing)
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm, Long sheets/	'banners (>19 in./483 mm): 28	lb Bond - 120lb Index/106 - 220	gsm
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Long Sheets/Banners: Card Stock Card Stock Reloaded Lightweight Card Stock	ck ck Reloaded ded			
Trans 1 and 2 (Chandrad)	Lightweight Card Stock Reload	ded			
Trays 1 and 2 (Standard)	F20 sh sats as sh				
Capacity ⁴ Sizes	520 sheets each	7 in to 11 7 v 17 in /1//0 v 1	82 mm to 297 x 432 mm (SEF)		
Sizes	Tray 2: Custom Sizes: 5.5 x 7.2				
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm			
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded			

Paper Handling (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Four Tray Module (Trays 3 a	nd 4) (Available on C8130/C81	135)					
Capacity ⁴	Tray 4: 520 sheets Tray 4: 520 sheets						
Sizes	Trays 3 and 4: 5.5 x 7.2 in. to	Trays 3 and 4: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 mm (SEF)					
Weights	16 lb. bond to 110 lb. cover/52	to 300 gsm					
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Lightweight Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	k k Reloaded ed					
High Capacity Tandem Tray	(Available with all models)						
Capacity ⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets						
Sizes	8.5 x 11 in./A4, JIS B5, Executiv	ve (7.25 x 10.5 in) LEF					
Weights	16 lb. bond to 110 lb. cover/52	! to 300 gsm					
Mediα Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted						
Envelope Tray (Optional - Re	places Tray 1)						
Capacity ⁴	Up to 60 envelopes						
Sizes	#10 Commercial (9.25 x 4.125 Custom Sizes: 3.9 x 5.8 in. to 6.		62 x 241 mm				
Weights	20 lb. to 24 lb. bond/75 to 90 g	gsm					
High Capacity Feeder (HCF)	(Optional with all models)						
Capacity ⁴	3,000 sheets						
Sizes	Standard Sizes: 8.5 x 11 in. or 7	7.25 x 10.5 in./A4 or B5 LEF					
Weights	16 lb. bond to 110 lb. cover/52	16 lb. bond to 110 lb. cover/52 to 300 gsm					
Total Capacity							
Device Total Capacity ⁴	Four Tray Module: 2,180 sheet: Four Tray Module with High Ca High Capacity Tandem Tray M High Capacity Tandem Tray M	spacity Feeder: 5,180 sheets odule: 3,140 sheets	eder: 6,140 sheets				

Finishing	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C8170
	l ual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)
Stacking Tray Capacity ⁴	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to 100 sheets
Integrated Office Finisher (C	Dptional with AltaLink® C8130/C8135/C8145/C8155)
Stacking Tray Capacity ⁴	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)
Top Tray Capacity ⁴	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm
Score/Crease	1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm
Business Ready (BR) Finishe	r (Optional) (Requires Horizontal Transport Kit)
Capacity ⁴	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)
Capacity ⁴	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported

Finishing (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170			
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Bool	with BR Finisher and BR Booklet Maker Finisher)						
Types	C-fold, Z-fold, and Z-half-fold							
Capacity ⁴	40 sheets							
Sizes	C-fold and Z-fold: Letter – 8.5 Z-half-fold: Tabloid – 11 x 17 i							
Weights	16 lb. to 24 lb. bond/64 to 90	gsm						
Output Trays	Envelope Tray: C-fold, Z-fold, c Stacker Tray or Top Tray: Z-hal							
Convenience Stapler (Option	nal - Includes Work Surface ⁵)							
Capacity ⁴	50-sheet stapling 5,000 staples Requires separate power outle	et.						
Сору	AltaLink® C8130	AltαLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170			
First-Copy-Out Time (from platen/warmed up Color/Black-and-White)	As fast as 6.1 seconds/ As fast as 4.5 seconds		As fast as 5.5 seconds/ As fast as 4.4 seconds	As fast as 4.7 seconds/ As fast as 3.7 seconds	As fast as 4.0 seconds/ As fast as 3.2 seconds			
Sides (input-output)	1-1, 1-2, 2-2, 2-1							
Quantity	1 to 9,999							
Resolution (max)	Up to 600 x 600 dpi							
Reduction/Enlargement	Variable zoom from 25% to 4	00% in 1% increments						
Concurrency	Program-ahead to allow job to	o be queued while initial job is p	processed (Copy, Print, Fax, and	Scan)				
Copy Features	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan) Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e., Color Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Touchless Workflow Accelerators							

Print	AltaLink® C8130	AltαLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Resolution (up to)	1200 x 2400 dpi				
Print Features	Delay Print (specific time) U Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Saver Imaging Security Job Identification (Print ID of LAN Fax (requires optional F Layout/Watermark Long Sheet/Banner N-up (up to 16 pages per sh Paper Selection by Attribute Print From Cloud Repositoric Saved Job (color jobs can be Secure Print with Timed Del Special Pages (exception pa Store and Recall Driver Setti	r By Words) Bi-directional Real- ser Permissions r, Resolution (Standard, Enhance or Banner, Print ID in margins of fax Kit) seet) Sample Set es (Dropbox, OneDrive, and God e printed as monochrome) etion ge programming: covers, insertings pox® Earth Smart Settings, Duple	ed, High)) n first page only or all pages) ogle Drive) s, exception pages)	rint ID, Smart Sample Set, Hold	All Jobs)
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white				
Operating Systems	Windows Server 2008 SP2 (Windows Server 2008 R2 (6 Windows Server 2012 and R Windows Server 2019 (64-b Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 10 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®	4-bit) 12 (64-bit) it) it) t)			
Network Protocols	TCP/IP: HTTP/HTTPS, Intern Microsoft Windows Network Bonjour®/AirPrint™ IPv6 Most protocols not in use co	S	aw Socket Printing/Port 9100, 1	Pv4/IPv6, WSD	
Font Capability	PCL: 93 scalable fonts, line p	orinter, and bitmap font (includ	ing Cyrillic font support) PostSc	ript 3: 173 Type 1 fonts, 2 Multip	ple Master fonts
Xerox® Global Print Driver®				Devices and non-Xerox devices implifying print services manage	es from a single driver. It provides a ement. Support for
Xerox [®] Pull Print Driver	driver. The Xerox® Pull Print I		oss a broad range of printing a	ssets. IT administrators no long	nent. Uses a single queue and single er need to manage and configure
Unified Address Book for Fax	, Internet Fax, Email, and Sc	can to			
Features	Services supported: Fax, Inte Maximum contacts: 5,000 Contacts: Supports 1 or mor Favorites for quick access of	e destinations			

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
Concurrency	Scan while the system is print concurrent jobs)	ting, copying, or while it is trar	ısferring scan to network or fax j	obs (priority is for return of scannec	l originals and printing	
Input Speed (up to)	82 ppm black-and-white and color (simplex) 141 ipm black-and-white and color (duplex) 142 ipm black-and-white and color (duplex) 145 ppm black-and-white and color (simplex) 150 ipm black-and-white color (duplex)					
Resolution	72 x 72 dpi to 600 x 600 dpi					
Bit Depth	1-bit (black-and-white), 8-bit	(grayscale), 24-bit (color)				
Maximum Scan Area	11 x 17 in./A3					
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® 1	S scan templates and share v	a device cloning to other multifu	unction printers' confirmation sheet	options	
Network Protocols	SFTP, FTP, SMB, HTTP, HTTP:	5				
File Compression		l, G4 MMR compression – sing F/A-1b (MRC, JPEG, G3 MH, G		Arithmetic Compression, Deflate (fo	r black-and-white and within	
Document Management Fields (Metadata)	1 to 6 user programmable name, default value, and of	•	•	ed fields within the template – Met	adata field consists of field	
Scan Features	Auto Background and Shado Bound Originals Compression Quality/File Size Edge Erase Imaging Security Mixed Size Originals Scan Bu Original Type (Photo and Tex Reduction/Enlargement Scan Preview Single Touch Scan buttons (u Size for Size (for mixed size o Touchless Workflow Acceleral TWAIN Support/WIA 2.0 Sup	e Control ild Job t, Photo, Text, Map, Newspape p to 10) riginals) Lors	er/Magazine)			
Scan to Email (Standard)						
Scan Features	Auto send to self Email signatures (6 lines ec Email signing (requires Small Signing (requires Small Signing Small Signing Signin	art Card option) Tyption	ail message body (user configur	able), email Embedded Web Server	confirmation sheet options	
Directory Access	Address list via LDAP (Windo	ws Active Directory, Exchange	, Notes, Domino), Device Addres	s Book		
Scan To						
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secu Scan to Network Folder (usin Scan to PC/Server Client (SM Scan to USB	g Secure FTP/HTTP/HTTPS)				
Optional Features	Native Scan to Cloud Reposit	ories (Dropbox, OneDrive, and	l Google Drive) ³			
Workflow Scanning (Option	ıl features)					
Scanning Software	Autostore v7 eCopy ScanStation v5.2 ecopy ShareScan v5.2					
Scanning Apps and Xerox App Gallery		ve, Microsoft OneDrive, Micro Ible in the Xerox App Gallery: >		kplace Mobile App (iOS/Android)		

Security	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Features	Audit Log						
		Engine (ISE) compatible		,			
	Configuration Watchdo 802.1x	g (Monitors and remediates 75	security settings in the following	g areas):			
	- Admin Password Rese	t					
	- Audit Log						
	- Automatic Software l	Jpgrade					
	- Email Alerts - FIPS 140-2						
	- Hold All Jobs						
	- Immediate Job Overv	vrite ⁹					
	 Installation Policies McAfee® Embedded (Cantural					
	- McAlees Embedded (COULLO					
	- PostScript Passwords						
	- Remote Services Enab						
	Remote Start (Mopria Remote Start (TWAIN						
	- Remote Start (TWAIN - Reprint Saved Jobs	1)					
	- Scan to Mailbox (Inte						
	- Scheduled Disk Overwrite ⁹						
	- Secure Passcode Length - Secure Print Device Policies						
	- Secure Print Device Policies - SIFM						
	- SNMP						
	- System Timeout						
	- USB (Print from USB) - USB (Scan to USB)						
	- USB Port Management						
	- User Data Encryption						
	Expanded Authentication						
	- Digitally signed PDF (when using Smart Card authentication) - Encrypted and authentication to SMTP server for Scan to Email						
		Protected PDF (when using Emai		only)			
		ard Disk Encryption, TLS 1.1/1.2/		3			
	- Immediate Image Overwrite/Securely delete jobs using approved algorithms ⁹						
	- Local Authentication (internal database) - Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008,						
), NDS, LDAP authentication			,		
		Overwrite (Scheduled, Manual), ir					
	- Smart Card authentic - Secure Data	ation – 144k CAC/PIV Card Sup	port (2048 bit certificate key)/.N	NE I			
		digit PIN or Network Authentic	ation)				
	Expanded Authorization	n					
	- Authorization per use						
	SA access based on n Secure Network Access						
			atures (e.g., color access, or time	e restrictions) reflects in the print	driver		
		riteria certified by NIAP under H	D Protection Profile for Hardcop	y Devices v1.0 (HCD-PP v1.0)			
	Hide Print Job Names Imaging Security						
		S V1.0, V1.2, V1.3, SNMP V1/V2	/V3, HTTPs, 802.1X. SFTP				
		ontrol (whitelisting), McAfee® Int					
	Port disablement include						
	Security Information ar	nd Event Management (SIEM) si	upport for McAfee® Enterprise S	ecurity Manager, LogRhythm, ar	d Splunk		
Xerox® Integrated RFID			ding additional security; with em	nbedded multifunction printer co	rd readers in		
Card Reader (Optional Kit)	the multifunction printer	panel					
(Optional Kit)							

Fax	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Network Server Fax Features							
Compatibility	ITU (CCITT) group 3; Various X	Kerox® Business Innovation Pa	rtner Solutions				
Maximum Scan Area	11 x 17 in./A3						
Fax Send Features	Add to Send List (200 numbers	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)					
Fax Print Features	One- or Two-sided Printing, Sta	ple, Secure Print					
Transmission Resolution	Superfine: 400 x 200 dpi (Scan Fine: 200 x 200 dpi Standard: 200 x 100 dpi	at 600 x 600 dpi)					
Internet Fax Features							
Compatibility	Direct print-ready document to Reception and automatic print						
Directory Access	Utilizes the Unified Address Bo	ok					
Send/Receive	Send: Multi-page TIFF, PDF, PD Receive: TIFF, MTIFF, PDF, PDF						
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-whi	te)					
Network Protocols	SMTP (send), POP3 (receive)						
Compliance	ITU-T T.37 compliant						
Walk-up Fax Features (Option	nal; Customer-Installable – 1 a	nd 2 lines)					
Compatibility	ITU (CCITT) Group 3						
Speed/Modems	One or Two V.34 modems: 33,6	500 bps. Less than 4 seconds p	oer page transmission time				
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBI	IG/SG3					
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: Receive: Accepts all sizes	600 x 600 dpi					
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reductic Page-by-page Job Status at the Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory cap Device Address Book (up to 5,0 Touchless Workflow Accelerato	e Machine s pacity) 100 contacts)					
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (Output Tray Selection Up to 200 Password-protected Secure Receive Receive Timestamp Auto Answer Delay		uto				
Fax Forward	Forward to Email or SMB Locat Fax Forward on Receive Only	ion					
Fax Reports	Activity, Dial Directory, Group [Broadcast Report	Directory, Transmission Confirr	mation, Pending Fax, Options	Report, On Demand Overwrite ⁹ R	eport, Mailbox Report,		
Directory Access	Utilizes the Unified Address Bo Group fax available	ok					
Auto Redial	Up to 14 attempts (per country 1 to 25 minute intervals	y requirements)					
Auto Resend	Up to 5 attempts						

Device Management				
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog			
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install			
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install			
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server			
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure			
Novell NDPS/NEPS	Server gateway application: centralized management tool			
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions			
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions			
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device				
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel			
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)			
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator			
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x			
Support	Install print/scan drivers and online support available via support.xerox.com			
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic			
Remote Services				
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time			
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory			

Accounting				
Xerox® Standard Accounting (Standard)				
Tracking	Copy, Print, Fax, Scan, and Email usage			
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)			
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file 			
Accounting Options – Network Accounting (Allows central server to manage all accounting)				
	Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface			
Xerox® EX-c C8100 Print Server Powered by Fiery® (Optional)				
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache			
Memory (ESS)	2 GB			
System Disk	500 GB HDD			
Page Description Language	PostScript v 3020			
Features	Access Controls Automatic two-sided printing Booklet Maker – booklet wizard to create booklets Calibration Digitally Signed Software Updates Expert Color Settings: Profile, Rendering, and Simulation Encryption of critical information Fiery API Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery drivers for Mac and Windows Fiery FreeForm Create to create personalized files for free Image Enhance IP Fittering Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps, and more Job Preview Job Preview Job Preview Job Preview PANTONE® Color Enabled Print from USB flash drive PostScript Security Port Blocking Secure Erase Secure Printing Spool-RIP-Print simultaneously Standard support for long sheet banners User Authentication Watermarks			
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet			
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Color Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network			

Supplies	Description	Yield		
Toner Cartridge ⁶	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages		
Transfer Belt Cleaner	1 Assembly	160,000 pages		
Second Bias Transfer Roll	1 Assembly	200,000 pages		
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge		
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge		
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge		
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton)	5,000 each refill		
Fan Filter	1 Assembly (AltaLink® C8170)	500,000 pages		
Xerox® Smart Kit®				
Drum Cartridge ⁷	1 Cartridge per Color	180,000 pages		
Waste Toner Container w/o Suction Filter ⁸	1 Cartridge (AltaLink® C8130/35/45/55)	69,000 pages		
Waste Toner Container with Suction Filter ⁹	1 Cartridge (AltaLink® C8170)	69,000 pages		

¹ Declared in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.



 $^{^{2}\,}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Not available in all geographies.

Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁵ Sold separately in some geographies.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 35% color/65% black-and-white pages.

⁸ Waste Toner Container yield will vary depending on type of image, area coverage %, and Job run length.

⁹ With optional hard drive.