



Customer pos. no.:
 Inquiry date: 2026-02-09
 Inquiry no.: P Circulatie - SI 21555427 TE rev
 Quantity: 1
 Quantity: 1

Number: 4005994231 - 419
 Line: 000600
 Date: 2026-02-05
 Page: 32 / 44

Etabloc 065-040-160 GG
 ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2

Operating point 1 Dimensioning operating point

Operating conditions (purchaser requirements)

Target flow rate	35 m³/h
Target head	30 m
Fluid	Water, heating water
Fluid variant	Heating water up to 100°C (max.), acc. to VDI 2035
Specified fluid temperature	20 °C
Density Fluid handled	998 kg/m³
Kinematic viscosity Fluid handled	1 mm²/s

Vapour pressure determined	0.02337 bar.a
Minimum inlet pressure required	-0.3 bar.r
Specified ambient temperature	20 °C
Installation altitude above sea level	1,000 m

Operating conditions (performance)

Flow rate	35 m³/h
Minimum permissible flow rate	6.471 m³/h
Maximum permissible flow rate	60.92 m³/h
Pump set	
Maximum permissible flow rate	60.92 m³/h
Head	30 m
Maximum pressure determined at duty point	2.936 bar.r
Shut-off head	32.45 m
Efficiency Pump	74.34 %
NPSH required	1.98 m

Maximum power input at duty point	3.84 kW
Maximum power input / curve	5.226 kW
Pump speed	2,502 1/min
Shut-off pressure	3.176 bar.r

Design data pump

Scope of supply Pump supplied by KSB	Pump + motor
Pump standard	EN 733
Shaft axis position	Horizontal
Pump design	Close-coupled
Pump system design	Single-pump system
Pump direction of rotation, viewed from casing side	Counterclockwise
Hydraulic impeller diameter	174 mm
Impeller type	Radial, closed, multi-channel
Free passage	11.5 mm
Support foot	No

Mains voltage	400 V
Mains frequency	50 Hz
Minimum efficiency index MEI	0.7
Minimum permissible fluid temperature	0 °C
Maximum permissible fluid temperature	110 °C
Quantity Stages, single-entry	1
Casing wear ring design suction-side	Casing wear ring flat
Casing wear ring design discharge-side	Casing wear ring flat
Installation chamber Casing cover	Conical (A-type cover)
Bearing bracket size / shaft unit	25
Pump directive	CE

Technical Datasheet



Customer pos. no.:
Inquiry date: 2026-02-09
Inquiry no.: P Circulatie - SI 21555427 TE rev
Quantity: 1
Quantity: 1

Number: 4005994231 - 419
Line: 000600
Date: 2026-02-05
Page: 33 / 44

Etabloc 065-040-160 GG
ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2

Nozzle connections pump

Nominal diameter Suction nozzle	DN 65	Nominal diameter Discharge nozzle	DN 40
Nominal pressure Suction nozzle	PN 16	Nominal pressure Discharge nozzle	PN 16
Suction nozzle position	Axial	Discharge nozzle position	0 deg
Suction nozzle design acc.to	EN1092-2	Discharge nozzle design acc.to	EN1092-2
Suction flange bolt hole pattern as per standard	EN1092-2	Discharge flange bolt hole pattern as per standard	EN1092-2
Flange facing type Inlet	Raised face (B,RF)		
Flange facing type Outlet	Raised face (B,RF)		

Auxiliary connections pump

1M Pressure gauge Discharge nozzle	G 1/4 Pressure sensor	5B Venting and drain	G 1/4 Drilled and plugged
1M Pressure gauge Suction nozzle	G 1/4 Pressure sensor		
6B Fluid Drain	G 1/4 Drilled and plugged		
6D Fluid Filling and venting	G 1/4 Drilled and plugged		

Shaft sealing

Shaft seal type	Single mechanical seal; seal chamber can be vented (A-type casing cover) - AV	Shaft seal code	Code 11
Operating mode of mechanical seal (function)	API plan 03	Shaft seal manufacturer inboard	KSB's choice
Determined pressure Seal chamber	-0.11 bar.r	Mechanical seal type inboard	KSB's choice
		Material Shaft seal inboard	BQEGG DW001



Customer pos. no.:
 Inquiry date: 2026-02-09
 Inquiry no.: P Circulatie - SI 21555427 TE rev
 Quantity: 1
 Quantity: 1

Number: 4005994231 - 419
 Line: 000600
 Date: 2026-02-05
 Page: 34 / 44

Etabloc 065-040-160 GG
 ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2

Materials

Material Volute casing (102)	EN-GJL-250/A48 CL 35B	Material Bolts/Screws Volute casing (902.01)	8.8
Material Casing cover (161)	EN-GJL-250/A48 CL 35B	Material Nut Impeller fastening (920.95)	(ST)
Material Shaft	C45+N		
Material Impeller (230)	EN-GJL-250/A48 CL 35B		
Material Casing wear ring suction-side (502.01)	JL/LAMELLAR GRAPHITE CAST IRON		
Material Casing wear ring discharge-side (502.02)	JL/LAMELLAR GRAPHITE CAST IRON		
Material Shaft protecting sleeve (523)	(CRNIMO ST INT)		
Material Static seal Discharge cover	DPAF DW001		
Material Drive lantern	EN-GJL-250/A48 CL 35B		

Driver

Electric motor, asynchronous	Yes	Rated speed Motor	2,935 1/min
Drive concept	Electric actuator	Number of motor poles	2
Drive standard, mechanical	IEC	Rated power Motor	7.5 kW
Drive standard electric	IEC	Motor power reserve determined	61.3 %
Motor bearing, insulated	No	Rated voltage Motor	400 V
Motor manufacturer	KSB's choice	Motor winding	400 / 690 V
Customer supply Drive	No	Rated frequency Motor	50Hz
Motor construction type	IM V15 (IM2011) IEC 60034-7	Motor switching type	Delta
Motor size	132S	Rated current Motor	14.6 A
Efficiency class	IE3 (Premium)	Starting current ratio Ia/In	8.9
Material motor housing	AL	Cos phi at 4/4 load	0.83
Enclosure Motor	IP55 (TEFC)	Motor efficiency at 4/4 load	90.1 %
Thermal class	155 (F) according to IEC 60085	Limit value Maximum humidity Motor	30 g/m ³
Temperature sensor motor	3 PTC thermistors	Marking according to directive Drive	CE
Terminal box position of motor (looking at the motor shaft)	360 °	The values indicated are regarded as guaranteed values. They are applied to motors with a sinusoidal power supply within the permissible tolerances specified by IEC 60034-1. The values given on the name plate may be different.	
Motor housing feet position (looking at the motor shaft)	180° (below)		
Operation on a frequency inverter permitted	Yes (acc to motor manufact)		
Earthing connection 31M Drive	No		
Sound pressure level Motor	71 dBa		
Type series Motor manufacturer	Acc. to motor manufacturer (IEC, IE3)		

Technical Datasheet



Customer pos. no.:
Inquiry date: 2026-02-09
Inquiry no.: P Circulatie - SI 21555427 TE rev
Quantity: 1
Quantity: 1

Number: 4005994231 - 419
Line: 000600
Date: 2026-02-05
Page: 35 / 44

Etabloc 065-040-160 GG
ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2

Coating

Aggregate

Surface preparation	Free from dirt, grease, rust
Properties Primer coat	Hydro dip primer, water-dilutable
Thickness Primer coat	60 µm
Properties Top coat	Acrylate dispersion water-thinned
Thickness Top coat	40 µm
Colour Top coat	RAL5002 Ultramarine Blue
Colour Top coat Drive	RAL5002 Ultramarine Blue

Energy cost and Environmental Impact

Result

Estimated Product Carbon Footprint (cradle-to-gate) (CO₂eq) 625 kg

*

*is based on the product weight assuming typical material proportions. The conversion rate between product weight and CO₂ emissions is based on several life cycle analyses in acc. with ISO 14040 / 44 of sample products from the same series. The objective and scope of these LCAs was limited to the manufacturing phase (cradle-to-gate). With regard to the 'inputs', all materials, energy and auxiliary materials were taken into account; with regard to the 'outputs', emissions, scrap and waste were considered. The influence of outgoing logistics is not covered. The input variables of the analyses cover at least 95% of the total weight. The analysis focusses on the global warming potential (EF3.0 Climate Change - total).

Packaging

Suitable for transport	Truck transport
Suitable for storage	Indoor storage
Packaging category	Wooden crate (A07)
IPPC Standard ISPM 15	Yes

Order related documents

Detail drawing Mechanical seal	No
--------------------------------	----

Performance Curve (Pump)




Customer pos. no.:
 Inquiry date: 2026-02-09
 Inquiry no.: P Circulatie - SI 21555427 TE rev
 Quantity: 1
 Quantity: 1

Number: 4005994231 - 419
 Line: 000600
 Date: 2026-02-05
 Page: 36 / 44

Etabloc 065-040-160 GG
 ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2



Curve Data

Pump speed	2,502 1/min	Efficiency Pump	74.3 %
Density Fluid handled	998 kg/m³	Minimum efficiency index MEI	0.7
Kinematic viscosity Fluid handled	1 mm²/s	Maximum power input at duty point	3.84 kW
Flow rate	35 m³/h	NPSH required	1.98 m
Maximum permissible flow rate	60.9 m³/h	Hydraulic impeller diameter	174 mm
Head	30 m	Hydraulic values according to	EN ISO 9906
Maximum pressure determined at duty point	2.94 bar.r	Class 3B	

Speed Curve




Customer pos. no.:
Inquiry date: 2026-02-09
Inquiry no.: P Circulatie - SI 21555427 TE rev
Quantity: 1
Quantity: 1

Number: 4005994231 - 419
Line: 000600
Date: 2026-02-05
Page: 37 / 44

Etabloc 065-040-160 GG
ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2



Curve Data

Density Fluid handled
Kinematic viscosity Fluid handled
Flow rate

998 kg/m³
1 mm²/s
35 m³/h

Head
Minimum efficiency index MEI
Hydraulic impeller diameter

30 m
0.7
174 mm

Installation plan




Customer pos. no.:
Inquiry date: 2026-02-09
Inquiry no.: P Circulatie - SI 21555427 TE rev
Quantity: 1
Quantity: 1

Number: 4005994231 - 419
Line: 000600
Date: 2026-02-05
Page: 38 / 44

Etabloc 065-040-160 GG
ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2



Drawing is not to scale.

Dimensions are given in mm

Motor

Motor manufacturer	KSB's choice
Motor size	132S
Rated power Motor	7.5 kW
Number of motor poles	2
Rated speed Motor	2,935 1/min
Terminal box position of motor (looking at the motor shaft)	360 °
Motor housing feet position (looking at the motor shaft)	180° (below)

Connections

Nominal diameter Suction nozzle	DN 65
Suction flange bolt hole pattern as per standard	EN1092-2
Nominal diameter Discharge nozzle	DN 40
Discharge flange bolt hole pattern as per standard	EN1092-2
Nominal pressure Suction nozzle	PN 16
Nominal pressure Discharge nozzle	PN 16

Installation plan



Customer pos. no.:
Inquiry date: 2026-02-09
Inquiry no.: P Circulatie - SI 21555427 TE rev
Quantity: 1
Quantity: 1

Number: 4005994231 - 419
Line: 000600
Date: 2026-02-05
Page: 39 / 44

Etabloc 065-040-160 GG
ETB 065-040-160-GGSBV11 WSEDN2HCB

Version No.: 2

Net weight

Total weight Pump	30 kg
Total weight Drive	71 kg
Total weight Control unit	10.71 kg
Total weight Pump set	113.3 kg
Total weight Assembly/transport aids	2.4 kg

Connect pipelines stress-free

Dimensional tolerances for shaft axis height: DIN 747
Dimensions without tolerances, middle tolerances to: ISO 2768-m
Connection dimensions for pumps: EN735
Dimensions without tolerances - welded parts: ISO 13920-B
Dimensions without tolerances - gray cast iron parts: ISO 8062-CT9

Plan for additional connections see extra drawing