

EN Certified Biological Safety Cabinet



E-mail: export@biobase.com
http://www.biobase.com



ADVANTAGE

1. 7-inch large touch color display: touch operation, real-time and clearer display of various values of the safety cabinet, dynamic air flow pattern diagram, fault alarm sound and light prompt.
2. The power-on password can be set to prevent mis-operation by irrelevant personnel.
3. Automatically adjust the wind speed.
4. Power off automatically, remind the state before power-off, and have a visual reminder to alarm.
5. Side windows on both sides for easy observation.
6. The operation area is integrally formed, which is easy to disassemble and clean.
7. A breeze speed sensor is equipped at the working area and the outer exhaust air outlet to detect the wind speed in real time.
8. It can be used both manually and electrically, and the glass door can be pulled down to close the front window when the power is off.
9. The cabinet is sealed from the top. The height of the adjustable feet can be customized.
10. Interlocking function: UV lamp and front door; UV lamp and fan; LED lamp, fan, and front window.
11. It has an appointment timing function, which can automatically set the timing of turning on, turning off and the running time of the UV lamp, fan, and socket.
12. The closing of the front window can double trigger the signal, so that the sterilization and disinfection function of the UV lamp can be turned on automatically.
13. The cabinet is designed with a 10° inclination angle, which conforms to the principle of ergonomics, has a larger viewing angle, is easy to operate and is more user-friendly.
14. Anti-paper dust structure at the air inlet to prevent paper dust from entering the air cavity.
15. Split countertop is easier to clean.
16. One button front window lifting function.

TECHNICAL PARAMETERS

Model	BSC-3FA2-HA	BSC-4FA2-HA
External Size(W*D*H)	1067*800*2260mm	1383*800*2260mm
Internal Size(W*D*H)	980*500*650mm	1280*600*650mm
Work Surface Height	750mm	
Max Opening	500mm	
Tested Opening	200mm	
Airflow	Inflow 370m³/h(218cfm)	490m³/h(280cfm)
Volume	Down flow 65%: 650 m³/h(408cfm)	65%: 910 m³/h(538cfm)
	Exhaust 35%: 370m³/h(218cfm)	35%: 490m³/h(280cfm)
Front Window	Manual and electric, glass thickness> 5mm, anti-ultraviolet	
ULPA Filter	2pcs, filtration efficiency for 0.12μm particles>99.999%	
Illumination	≥1000Lum	
Noise	EN12469≤65dB	
Display	Color Touch Screen	
European Standard Socket	230V, 3A	
Power Supply	AC 230V, 50/60Hz	
Rated Power	1100W	1200W
Alarm	Alarm for abnormal wind speed, alarm for glass door not at safe height, alarm for abnormal power failure	
Motor	AC motor, 230V acceptable, adjustable speed, high efficiency, low power	
Material	Working Area: 304 stainless steel, side window glass: Frame and decorative plate: cold-rolled steel with anti-bacteria powder coating	
LED Lamp	12W*2	14W*2
UV Lamp	20W	30W
Standard Accessory	Cabinet*1, Base stand*1, LED lamp*2, UV lamp*2, S.S. water tap*1, S.S. gas tap*1, Drain ball valve*1, European Standard Socket*2, Remote control	
Optional Accessory	Arm rest, Formalin fumigation sterilizer, Infrared sterilizer, Electric height adjustable base stand, S.S. water tap*1, S.S. gas tap*1, Foot switch	
Package Size (W*D*H)	1240*1060*1880mm	1530*1060*1880mm
Gross Weight	270kg	345kg