GPC GPC Medical Ltd.

fix*LOCK* INSTRUMENT SET

fixLOCK Self-Tapping Screw, 5.0 mm

Thread dia.	5.0 mm
Head dia.	6.7 mm
Core dia.	4.4 mm
Lengths	20 – 100 mm
Drill bit used	4.3 mm



fixLOCK Cancellous Screw,

6.5 mm- Fully Threaded



Thread dia.6.5 mmHead dia.8.0 mmCore dia.3.0 mmLengths25 - 120 mmDrill bit used4.3 mm

(Item Code: 701)

(Item Code: 767)



GOS1439L	Instrument set for Large Fragment with Aluminium Graphic Box	
BTD1130.32	Drill Bit 3.2 mm, Length 195/170 mm	2
BTD1130.45	Drill Bit 4.5 mm, Length 195/170 mm	2
C-ILBS736.43	Locking Drill Bit, 4.3 mm with stop, Length 221 mm	2
IBS700.04	Counter Sink 4.5 mm	1
C-IBS762.45	Bone Tap 4.5 mm Q.C.	2
C-IBS762.65	Bone Tap 6.5 mm Cancellous Q.C.	1
IBS765	Quick Coupling Handle	1
IBS720.32	Insert Drill Sleeve 4.5/3.2 mm, length 80 mm	1
IBS735.45	Drill & Tap sleeve Combined 3.2/4.5 mm	1
IBS735.65	Drill & Tap sleeve Combined 3.2/6.5 mm	1
ILBS746.35	Large Screw Driver Shaft 4.5 mm	1
SH.35	Large Screw Holder	1
ILBS786.50	Torque Screwdriver for Large Screws 5.0 mm	1
IBS708	Depth Gauge Large 4.5 mm	1
ILBS716.50	Locking Drill Sleeve 5.0 mm	2
ILBS716.65	Locking Drill Sleeve 6.5 mm	2
IBS777	Large Neutral Eccentric Drill Guide 3.2/4.5 mm	1
REH1064.18.235L	Hohman Retractor 18 mm	1
REH1064.22.250	Hohman Retractor 22 mm	1
REH1068.14S	Periosteal Elevator 14 mm with fibre handle	1
BHF1248.24	Reduction Forceps 240 mm	2
ILBS739-L	Threaded Plate Holder Large	1
IBP630	Plate Bender Large	1
IBP637.45	Bone & Bone Plate Holding Forceps 4.5 mm	1
AGC1439L	Graphic Container Aluminium	1

fix*LOCK* Self Tapping Cancellous Screw, 5.0 mm- Fully Threaded

Thread dia.	5.0 mm
Head dia.	8.0 mm
Core dia.	2.70 mm
Lengths	25 - 120 mm
Drill bit used	4.3 mm

All the screws are available in stainless steel & titanium.

For Titanium, please affix 'T' after code number.

• www.indianorthopaedic.com