

Technical Data Sheet

Favorit Turbo M10ДМ-M API CD



Packages: 5L, 20L, 60L, 208L

Meets the requirements and specifications:
API CD
SAE 30

[EN] Favorit Turbo M10ДM-M API CD mineral-based monograde oil designed for use in summer period of highly accelerated turbo-charged diesel engines of freight trucks, logging trucks, large dump trucks, industrial tractors of domestic and foreign production, operating at extreme loads. It has excellent antioxidant, anti-corrosion and anti-wear characteristics, has good detergent-dispersant properties. Viscosity grade SAE 30.

[RU] Favorit Turbo M10ДМ-М API CD масло сезонное на минеральной основе, предназначенное для эксплуатации высокофорсированных дизелей турбонаддувом магистральных тягачей, лесовозов, большегрузных самосвалов, промышленных тракторов отечественного и импортного производства, работающих в тяжелых условиях. Имеет отличные антиокислительные, антикоррозионные и противоизносные характеристики, обладает хорошими моюще-диспергирующими свойствами. Класс вязкости SAE 30.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30° C to $+30^{\circ}$ C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	98,88
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	11,16
Viscosity index	STB 1797	97,94
Flash poin, °C	GOST 4333	
Pour point, °C	GOST 20287	
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m3	GOST 3900	890

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range. Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные. Показатели могут варьироваться в пределах допустимой нормы.