

Specificații tehnice

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1724398934057 din 23.08.2024
Obiectul achiziției: Echipamente IT necesare în cadrul Proiectului Erasmus+ KA2 RE-GRAD — 101128817 – „REFORMING UNDERGRADUATE EDUCATION FOR GREEN AND SUSTAINABLE DEVELOPMENT IN ARMENIA AND MOLDOVA”

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri/servicii						
LOT 6 Video and Audio-Conferencing System						
Lotul 6. Video conferencing equipment	Rally Plus Video Conferencing Camera System	China	Logitech	<p>Video conferencing equipment - Black with Mounting Kit (PTZ camera with ceiling installations) and 2x Mic ceiling Mount.</p> <p>Compatible software: Video noise reduction, Low-light saturation optimization, Renders natural skin tones for each participant on camera, Human figure detection, Auto-frame participants at meeting, Auto-reframe participants during meetings, able to distinguish human speech from other sounds, Acoustic Echo Cancellation, Voice Activity Detector,</p>	<p>Rally Plus Video Conferencing Camera System (960-001224) Black +RALLY MOUNTING KIT (939-001644)</p> <p>+ 2 x RALLY MIC POD MOUNT (952-000020)</p> <p>Compatible software: Video noise reduction, Low-light saturation optimization, Renders natural skin tones for each participant on camera, Human figure detection, Auto-frame participants at meeting, Auto-</p>	

				<p>Background noise suppression, Auto-level loud and soft voices, low distortion.</p> <p>Camera: 1xCamera, PTZ imaging system, USB 3.0 Type-C cable min. 2m, Power adapter with regional plugs, Power splitter & case, Camera mount with mounting hardware, supports: 4K, 1440p, 1080p.</p> <p>Slow motorized tilt, turn and zoom: min. turn $\pm 90^\circ$, min. Tilt: $+50^\circ / -90^\circ$, min. 15X HD zoom, min. 90° field of view.</p> <p>Automatic inversion detection to correct image orientation and camera controls when mounted upside down, Autofocus, min. 3 camera presets.</p> <p>Microphone: min. 2x Microphones with cable connection.</p> <p>Pickup Range: min. 4 m diameter, omnidirectional microphones, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Mute button with LED status indicator.</p> <p>Speaker: min. 2x Speaker</p> <p>High-performance, suspension system that eliminates camera shake from vibrations and audio interference, min. 7.5W.</p> <p>Accessories: Mount kit.</p> <p>All components compatible from the same manufacturer and sold as a set from the manufacturer</p> <p>Warranty: Complete for 3 years.</p>	<p>reframe participants during meetings, able to distinguish human speech from other sounds, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Auto-level loud and soft voices, low distortion.</p> <p>Camera: 1xCamera, PTZ imaging system</p> <p>Camera to Display Hub</p> <p>2 m USB 3.1 Type C to USB Type C 3.1</p> <p>-Conference Room Computer to Display or Table Hub</p> <p>2 m USB 3.1 Type A to USB Type B</p> <p>-Display Hub to Table Hub</p> <p>5 m CAT6A Ethernet cable (supports customer-supplied cables up to 50 m</p> <p>-Display Hub to Speaker (x2)</p> <p>2.95 m Mini XLR (supports customer-supplied extension cables up to 3 m</p> <p>-Conference Room Computer to Displays (x2)</p> <p>2 m HDMI A</p> <p>-Mic Pod</p> <p>2.95 m: Hardwired with 12 pin connector</p> <p>-Power Outlets to Power Supplies (x2): 1 m</p> <p>1 m</p> <p>-Power Supplies to Table Hub / Display Hub (x2)</p> <p>1.5 m</p>	
--	--	--	--	---	--	--

					<p>Rally Camera Zoom: 15x HD zoom (5x optical + 3x digital) Pan: 180° (±90°) Tilt: 140° (+50° / -90°) Field of View Diagonal: 90° Horizontal: 82° Vertical: 52° Total Room Coverage: 262° wide x 192° tall (field of view + pan and tilt) Resolutions @ 30fps: 4K Ultra HD, 1440p, 1080p, 900p, 720p, and SD Resolutions @ 60fps: 1080p, 720p RightLight Technologies: Wide Dynamic Range (WDR), low-light compensation, video noise reduction, low-light saturation optimization Privacy: Lens parks at -90° in sleep mode for assured privacy</p> <p>Rally Mic Pod (2) Pickup Range: 7 m diameter Four omnidirectional microphones forming eight acoustic beams AEC: Acoustic Echo Cancellation VAD: Voice Activity Detector Background noise suppression Mute button with LED status indicator Captive 2.95 m 12-pin cable Daisy chain up to 7 Rally Mic Pods</p>	
--	--	--	--	--	--	--

					<p>Frequency Response: 90Hz – 16kHz Sensitivity: >-27 dB +/-1dB @ 1Pa Microphone data rate: 48 kHz Rally Speaker High-performance 76 mm driver with rare-earth magnet Patent-pending suspension system eliminates vibration-induced camera shake and audio interference Mini XLR cable connects to Rally Display Hub for both signal and power Speaker volume 95dB SPL @1W, 100dB SPL @7.5W, both +/-2dB at ½ meter Sensitivity: 95+/-2 dB SPL at ½ meter Distortion: 200Hz–300Hz <2.5%, 300Hz–10kHz < 1% @7.5W Sampling rate: 48 kHz Accessories: Mount kit. Warranty: Complete for 3 years.</p>
--	--	--	--	--	---

Semnat: _____
Ofertantul: TrioMAC SRL

Numele, Prenumele: Constantin Alexandru
Adresa: Orhei, str Stefan cel Mare 3, of 16

În calitate de: director