



Art & Science of Amazing Protection

DATA SHEET

PRO X-TENDED LATEX

POWDER FREE
EXAMINATION GLOVES



PRO X-TENDED LATEX POWDER FREE EXAMINATION GLOVES

Features

Extra protection

Longer cuffs provide further insurance against harmful chemicals and physical damage to the Hands and the forearms.

Rolldown prevention

Unintentional roll-downs are prevented through added stability from the beaded cuff which also eases donning.

Latex

ASAP's X-Tended Latex gloves offer a close fit giving a very comfortable wrap around the hands for prolonged usage.

Durable

Gloves are rated to withstand extended use and is resistant against abrasion.

Textured grip

Textured surface on strategic areas of the gloves provide excellent grip in all operating conditions.

Powder free

The powder free design minimizes the chances for allergic reactions and irritations linked to glove use.

Application

ASAP Pro X-Tended Latex Powder Free gloves are recommended to be used in industries that require:

- Hand and wrist protection for sectors such as Veterinary Care
- Splash protection when handling harmful chemicals
- Overall extra coverage protection

Industry icons:



Vet Care (VC)



Research & Development (R&D)



Service & Repair (S&R)



Hygiene Matters

At ASAP, we are committed to hygiene control and quality assurance. Proper hygiene standard is practiced throughout the development of all ASAP products – from raw materials handling, processing, production, inspection, to our finished product to deliver high quality products while limiting the risk of cross contamination.

Look for the Hygiene Matters logo, quality and hygiene you can trust.

Technical Specification Sheet

Product Information

Series Number	10110
Description	Latex, Powder Free, Examination Gloves
Material	100% Latex Powder
Design	Ambidextrous, Textured & Beaded Cuff
Color	Natural
Quality Assurance	ISO 9001 ISO 13485 ISO 14001
Quality Control	EN 455-1:2000 EN 455-2:2015 EN 455-3:2015 EN 455-4:2009
Food Safe	Tested in accordance with EU standard EN 1186 under Food Commission Regulation 10/2011
Acceptable Quality Level (AQL)	1.5
Packaging	100 pcs per box, 10 boxes per carton
Handling & Storage	Keep out of direct sunlight; store in a cool and dry place
Country of Origin	Malaysia

Physical Properties Specification

Dimension Specification

Test	Particular		Specification
Dimension (mm)	Palm Width	Extra Small	75—82
		Small	83—92
		Medium	93—102
		Large	103—112
		Extra Large	113—122
		Double Extra Large	123—132
	Length		Min. 395
		Cuff (25 ± 5 from bead)	Min. 0.10
	Thickness (Single wall)	Palm (centre of palm)	Min. 0.13
		Finger (13 ± 3 from tip)	Min. 0.18
Physical Properties	Force at break (N)	Before Aging	Min. 6.0
		After Aging	Min. 6.0
Physical Appearance	Rolled beaded cuff Natural Latex Colour Textured Surface Ambidextrous		

Packaging Dimensions

Inner	290 x 140 x 70 mm
Carton	376 x 290 x 296 mm



Product Size Codes

Small	Medium	Large	Extra Large
10112	10113	10114	10115

Instructions for Use

Use

This guideline is to be used in combination with the specific information that is mentioned on each packaging. These gloves are designed as single and transient use gloves and should be disposed of after use. The gloves are liquid proof, and can therefore be used for splash protection against certain chemicals. Kindly ensure the gloves are used for the designated purposes only.

Precautions

This product contains latex rubber which may cause an allergic reaction in some individuals. Do not expose these gloves to any person with a known or suspected sensitivity to nitrile rubber. If allergic reaction occurs, discontinue use immediately and consult a physician. These gloves should not be used for thermal or harsh chemical protection. They are not intended for application involving prolonged direct exposure to harsh chemical where heavy-duty industrial gloves are required.

Variability in material thickness, gloves integrity, chemical concentration, temperature, and length of exposure to chemicals may affect performance. User is responsible for determining glove suitability for individual application. Before usage, inspect the gloves for any faults or deficiencies. If the gloves are ripped or punctured during use, dispose them immediately.

Storage

Store in a dry place at room temperature. Open product should be shielded from exposure to direct sunlight, intense artificial light, x-ray machines, and other sources of zone.

Disposal

Dispose according to Local Authority Regulations. Landfill or incinerate under controlled conditions.

ASAP INTERNATIONAL SDN BHD

No. 1, Jalan Sitar 33/6, Seksyen 33,
40400 Shah Alam, Selangor, Malaysia.

T : +603 5191 0166

E : info@whyasap.com

W : www.whyasap.com

ASAP INNOVATIONS LTD

UNIT 7, Fonthill Business Park, THE
COURTYARD, Fonthill Rd, Ballyowen,
Dublin, D22 XA07, Ireland

T : +353 1 4661660

E : info@whyasap.ie

W : www.whyasap.ie

ASAP INNOVATIONS UK LTD

Atterbury Lakes, Fairbourne Drive,
Milton Keynes, MK10 9RG, United
Kingdom

T : +44 (0)1908 909146

E : info@whyasap.co.uk

W : www.whyasap.co.uk