

Single Speed Mini Centrifuge



Application:

The mini centrifuge is used for serum extraction from whole blood, supernate extraction from different samples, micro blood cell separation, bio-sample treatment, samples quick sedimentation and PCR sample treatment.

Features:

- * Rotor with 8 position & rotor for PCR strip tube
- * Unique rotor clip design, easy to install and replace
- * Long life, reliable motor, low noise, stable running
- * Humanization design, switch control for cover
- * Unibody casing looks wonderful



Technical Parameters:

Model	Mini-12	Mini-7	Mini-5
Max Speed	12000rpm	7000 rpm	5000 rpm
Max RCF	7776×g	2650×g	1350×g
Capacity	0.2/0.5/1.5/2.0ml*8; 8*4*0.2ml (PCR tube)		
Rotor	8*2/1.5ml rotor (With 0.2ml and 0.5ml adapter); 8*4*0.2ml PCR tube		
Power	110VAC 60Hz; 220VAC 50/60Hz	AC110V-265V, 50/60Hz	
Consumption	30W	20W	
Noise	65dB(A)	≤45dB(A)	
External Size	178*178*115mm		
Package Size	320*250*210 mm		
Net Weight	1.3kg	1kg	
Gross Weight	2.4kg	2kg	

Mini High Speed Centrifuge



Features:

- * Speed up to 15000rpm (15100×g)
- * Brushless DC motor drive quickly to the target speed
- * Quiet working, Low noise ≤54dB
- * Cast iron chassis, low center of gravity, vacuum suction cup feet, double safety guarantee.
- * Wide voltage design, the speed is not affected by voltage fluctuations, and the speed accuracy is high.

Technical Parameters:

Model	D2012 plus
Max. Speed	15000rpm(500-15000rpm)increment:100rpm
Max. RCF	15100×g, increment: 100×g
Speed Accuracy	±20rpm
Rotor Capacity	2mL*12
Run Time	30sec-99min/Continuous
Acceleration/Braking Time	11s/9s↓
Driving Motor	Brushless DC motor
Safety Devices	Door interlock; Over-speed detection; Over-temperature detection; Automatic internal diagnosis
Power	Single-phase, AC100V-240V; 50Hz/60Hz, 3A; 100W
Noise Level	≤54dB
Dimension (D*W*H)	255*245*140mm
Package Size (D*W*H)	455*345*250mm
Gross Weight	6.54kg
Other Functions	Speed/RCF switch; Short-time run function; Sound-alert function; Running process display

Standard Outfit:

Adapted Rotor

Model	A12-2P(19400010)
Max.Speed	15000rpm
Max.RCF	15100×g
Rotor Capacity	2mL*12
Rotor Material	High strength plastic
Adapted Rotor Adapter	A02P2,A05P2

Optional Accessories:

Adapted Adapter

Model	A02P2(19500001)	A05P2(19500002)
Descriptions	0.2ml rotor adapter for A12-2,A12-2P, AS24-2 andA24-2P rotors,24pcs/pk	0.5ml rotor adapter for A12-2,A12-2P, AS24-2 andA24-2P rotors,24pcs/pk

Mixer

Vortex Mixer



Application:

Used for liquid, liquid-solid, solid (powder) mixing, the vortex mixer can mix any liquid and powder in the form of whirlpool. The mixing speed is fast, uniform, thorough. Widely used in environmental monitoring, medical and health, petrochemical, food, metallurgy, PCR laboratory, scientific research and production enterprises laboratory, laboratory, for mixing, extraction and biological, biochemical, cell, strain and other sample oscillation culture.

- Features:**
- * The shell is white and gray, beautiful and atmospheric.
 - * New type of DC brushless motor, stepless adjustment, low noise and long effect.
 - * Digital display to ensure the accuracy of time and speed.
 - * Time and speed adjustment response is fast, saving experiment time.
 - * Solid and reliable workmanship, excellent shock absorption, suitable for high-speed operation.
 - * A variety of models and accessories are available.

Technical Parameters:

Model	BJPX-VW
Speed/Accuracy	200-3000rpm/ ±5rpm
Timing	0-9999 min/s
Amplitude Range	4mm
Oscillation Mode	Circular motion
Working Mode	Point vibration, continuous
Control Form	Pressure sensing
Power	35W
Power Supply	100-240V, 50/60Hz
Packing Size	280mm*230mm*210mm
Gross Weight	7.1kg

Accessories Technical Parameters:

Type	Item No.	Mode	Max Speed	Max Test Tube Size	Pictures	Standard/Optional
Test tube platform	XW001	Point vibration, continuous	3000rpm	Suitable for test tubes of different sizes		Standard
Flat bottom container platform	XW002	Point vibration, continuous	2000rpm	Container bottom size≤Φ80mm		Optional
Test tube holder: 19*10mm	XW003	Continuous	2000rpm	Applicable to 19 test tubes with an outer diameter of 10mm		Optional
Test tube holder: 13*12mm	XW004	Continuous	1600rpm	Suitable for 13 test tubes with an outer diameter of 12mm		Optional
Test tube holder: 12*15mm	XW005	Continuous	1600rpm	Suitable for 12 test tubes with outer diameter of 15mm		Optional
Test tube holder: 7*20mm	XW006	Continuous	1200rpm	Applicable for 7 test tubes of 20mm outer diameter		Optional
Test tube holder: 4*26mm	XW007	Continuous	1000rpm	Suitable for 4 test tubes with outer diameter of 26mm		Optional