

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 3, 4, 5, 7, iar de către autoritatea contractantă – în coloanele 1, 2, 6, 8]

Numărul procedurii de achiziție ocde-b3wdp1-MD-1558004101070 din 16 mai 2019
Denumirea procedurii de achiziție: Echipament și accesorii pentru computer

Cod CPV	Denumirea bunurilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
	Lotul 3						
30200000-1	Smart Board (Se aplică cota zero a TVA)	MX275	China	SMART Technologies	.Interactive touch display 75” with fast & accurate touch technology (20-point touch, finger and pen) DISPLAY SPECIFICATIONS Display technology Liquid Crystal Display (LCD) with DirectLED lighting Panel active screen area 1650.0 x 927.9 mm 64.96” x 36.54” Display aspect ratio 16:9 Display native resolution 3840 x 2160 pixels - 4K Ultra High Definition Brightness 330 cd/m² Contrast ratio 1200:1 Viewing angle 178° / 178° Colour depth 1.073 billion colors (10 bit) Response time (typ.) 8 ms Refresh rate 60 Hz (@ UHD) Pixel pitch 0.372 x 0.372 mm	DISPLAY-75" Resolution- 4K Ultra HD (3840 × 2160) Refresh rate-60 Hz Aspect ratio-16:9 Back lighting-DLED LED lifespan-Commercial-grade – 50,000 hours LCD quality-Grade A Contrast ratio-1600:1 Brightness-≥350 cd/m² Response time-8 ms Glass-Fully heat-tempered, anti-glare Ambient light sensor TOUCH AND DIGITAL INK	

				Supported orientation Landscape Glass 4 mm Hardened Anti-Reflection Safety Glass Life time 30,000 hours CONNECTIVITY Digital audio-video inputs 2x HDMI 2.0 Digital audio-video output 1x HDMI 2.0 Analogue audio-video input 1x VGA (DE-15 male) + audio jack (3.5 mm TRS connector) Analogue video output 1x AV (TRRS connector) Analogue audio output audio output 1x audio jack (TRS connector) Digital audio output audio output 1x digital coax (RCA connector) USB data ports 2x USB 3.0 2x USB 2.0 Integrated PC slot OPS-PC slot (JAE TX24 connector) Control input 1x COM DE-9 (RS-232 standard) Network LAN: RJ-45 connector (100 Mbit/sec) Wi-Fi: 2.4 / 5 GHz (802.11 a/b/g/n/ac) Bluetooth: 4.0 Integrated loudspeakers 2 x 12 Watt OPERATIONAL FEATURES Operating System Android™ >=7.0 Architecture CPU: ARM CORTEX Dual Core A73 (2.8 GHz) GPU: ARM MALI-450 RAM: >=2 GB ROM: >=16 GB Interactive touch Technology: V-Sense Infrared Touch recognition Input Detection: 20 touch inputs Touch Connection: 1x USB-B Recognition: Finger or passive stylus (size ≥ 3 mm) Response time: < 4 ms (regular touch), < 25 ms (max touch inputs)	Touch technology-Distributed IR Simultaneous Tool Differentiation Object awareness SMART Ink Silktouch Simultaneous touch points-10 – Windows & Mac Tools included-2 pens IQ APPLIANCE Model-MX275: AM40 MX375: AM50 Operating system-Android 7.1 Nougat Processor-RK3399, Dual-core A72 + Quad-core A53, 64 bits, 2GHz Memory-4 GB Storage-32 GB Wireless technology-Bluetooth 4.1 802.11A/B/G/N/Ac Connectors-HDMI 1.4 out USB 3.0 Type-A (x2) RJ45 Gigabit Ethernet CONNECTIVITY Wired-RJ45 (x2) Wi-Fi-IEEE 802.11A/B/G/N/Ac with 2 × 2 MIMO (both 2.4 and 5 GHz bands) Bluetooth-4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR) Remote control INPUTS/OUTPUTS Front control and connector panels- Power, input select, menu, freeze frame, mute, volume, USB-A (x2), USB-B, HDMI in	
--	--	--	--	--	---	--

					Accuracy: ± 1 mm Supported Compatibility Windows, Android, Macintosh OS X, Linux, Chrome OS Maximum operating hours 18 hours / day Languages English, French, German, Romanian, Russian PHYSICAL PROPERTIES Product dimensions 1763 x 1016 x 100 mm 69.41" x 40.00" x 3.94" Mounting Pattern 800 x 400 Accessories: Power cable, USB cable (> 5m), HDMI cable (> 5m), Remocon + Battery, PEN 2 x, User Manual, Wall mount, Wifi dongle, Floor lift on wheels for Interactive touch display 75" VESA Mount: 800 x 400 WARRANTY Standard warranty 5 years Analog: i3Tech E1075R Interactive display 75" 4K 20 touch + Floorlift on wheels 02 (https://assets.touchboards.com/assets/1/26/i3-Technologies-i3Touch-E1075R-Data-Sheet.pdf)	Video-HDMI 1.4 (x3), HDMI out (HDCP-compliant), VGA Audio-Stereo 3.5 mm in, stereo 3.5 mm out, S/PDIF out USB-Type-A (x4), Type-B (touch) (x2) Other-OPS slot, RS-232 in Speakers-10 W integrated speakers (x2) POWER Power consumption (display only) ENERGY STAR certified INSTALLATION Dimensions-68 13/16" x 42" x 4 3/8" (174.6 cm x 106.4 cm x 11.2 cm) Weight-133 lb. (60 kg) VESA mounting points-600 mm x 400 mm CERTIFICATION AND COMPLIANCE Regulatory certifications-UL (U.S./Canada), FCC, IC, CE, EAC, RCM, NRCS, SABS, CITC, TRA, CCC Environmental complianceEU: REACH, RoHS, Battery, WEEE and Packaging; U.S.: CONEG Packaging, California Proposition 65 and Conflict Minerals	
--	--	--	--	--	---	--	--

Numele, Prenumele:Dodon Ivan În calitate de:Director

Ofertantul:TRIDIMENSIONAL TEC Adresa: mun. Chişinău, str. Uzinelor 11, of. 401

Specificații de preț (F4.2)

[Acest tabel va fi completat de către ofertant în coloanele 5,6,7,8, iar de către autoritatea contractantă – în coloanele 1,2,3,4,9,10]

Numărul procedurii de achiziție ocds-b3wdp1-MD-1553773420168 din 31 mai 2019
Denumirea procedurii de achiziție: Echipament informatic

Cod CPV	Denumirea bunurilor	Unitate a de măsură	Cantitatea	Preț unitar (fără TVA)	Preț unitar (cu TVA)	Suma fără TVA	Suma cu TVA	Termen de livrare	Clasificație bugetară (IBAN)
1	2	3	4	5	6	7	8	9	10
	Bunuri								
	Lotul 3							30 de zile	
30200000-1	Interactive touch display 75”	buc	1	76000-00	91200-00	76000-00	91200-00	30 de zile	
	TOTAL			76000-00	91200-00	76000-00	91200-00		

Numele, Prenumele:Dodon Ivan În calitate de:Director

Ofertantul:TRIDIMENSIONAL TEC Adresa: mun. Chișinău, str. Uzinelor 11, of. 401