

## CONNECTING TUBINGS (1200PSI)

### Features

- Protects against microbiological infect
- ganoid; smooth-faced
- succinct design
- High pressure resistant
- Easy operation

Product No.	Description
42.02.20000	25 cm Female Luer Lock to Male Rotator
42.02.20001	50 cm Female Luer Lock to Male Rotator
42.02.20002	75 cm Female Luer Lock to Male Rotator
42.02.20003	120 cm Female Luer Lock to Male Rotator
42.02.20004	150 cm Female Luer Lock to Male Rotator
42.02.20005	180 cm Female Luer Lock to Male Rotator

## CONNECTING TUBINGS (500PSI)

### Features

- Clear PVC Tubing (DEHP Free)
- High durometer for accurate measurements
- bore high pressure extension line suitable for high pressure monitoring

Product No.	Description	Product No.	Description
42.02.10006	25 cm Female to Male Luer Lock	42.02.10009	120 cm Female to Male Luer Lock
42.02.10000	25 cm Female Luer Lock to Male Rotator	42.02.10003	120 cm Female Luer Lock to Male Rotator
42.02.10007	50 cm Female to Male Luer Lock	42.02.10010	150 cm Female to Male Luer Lock
42.02.10001	50 cm Female Luer Lock to Male Rotator	42.02.10004	150 cm Female Luer Lock to Male Rotator
42.02.10008	75 cm Female to Male Luer Lock	42.02.10011	180 cm Female to Male Luer Lock
42.02.10002	75 cm Female Luer Lock to Male Rotator	42.02.10005	180 cm Female Luer Lock to Male Rotator

## INTRODUCER NEEDLES



Product No.	Description	Product No.	Description	Product No.	Description	Product No.	Description
42.19.10009	Green Hub 18Ga x 6.5 cm	42.19.10002	Clear Hub 18Ga x 6.5 cm	42.19.10008	Green Hub 20 Ga x 3.8 cm	42.19.10006	Y type Pink Hub 18 Ga x 6.5 cm
42.19.10010	Green Hub 18Ga x 7.0 cm	42.19.10003	Clear Hub 18Ga x 7.0 cm	42.19.10005	Clear Hub 20 Ga x 3.8 cm	42.19.10007	Y type Pink Hub 18 Ga x 7.0 cm