

513.3257**SURFACE MOUNTING SOCKET**

32A 3P+N+E 6h 346-415V 60Hz 50Hz

Screw terminals



EN 60309-2/A1 (2007)

EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA-BASE Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M32X1,5

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
Catalogue notes	Rubber threaded cable sleeve included