General Information

Product Name: xr450p / xr450m

Manufacturer: Runner Srl

Via G. di Vittorio, 391 41032 Cavezzo (MO)

Italy

Distributed by: Cardioline S.p.A.

Registered Office and Factory:

Via Linz, 151 38121 Trento

Italy

xr450

xr450 is a treadmill designed to guarantee high performances, comfort and security for the patient. It has gradual-compression foot plates, able to adapt to the patient's stride, so drastically reducing articular impact to ankles, knees and back.

xr450 is an ideal instrument for use in combination with CARDIOLINE exercise test systems: silent and reliable, also at high speed, it has a wide tread surface being an extremely compact and light unit.

The **xr**450 treadmill is available in three different versions, all equipped with a wide colour LCD touch-screen display and with different functionalities, as described in the technical specifications section. The **xr**450 treadmill can be upgraded with lateral hand rails.

Intended use

xr450 is treadmill for the execution of exercise tests and cardiovascular rehabilitation. It can be used both as an independent unit, configured with optional console (model **xr**450**m**, **xr**450**p**), or in connection with a digital electrocardiograph equipped with an RS232 interface.

Correct use of the unit is in a medical environment. Use of this device is at the responsibility of qualified and suitably trained personnel, and must conform to the instructions contained in the User's Manual.

The unit must be handled with care and with every care to avoid bumps, vibration, heat sources, liquids and anything else that could cause it damage.

The **xr**450 treadmill can be used both on adult and pediatric patients in hospital or in the doctor's office.

xr450m - xr450p

sp_xr450m-p_08_eng_01 06/03/2023 1/4

Technical specifications

Width	70 cm
Length	188 cm
Height	142 cm
Weight	
Max. working speed	20.0 km/h constant;
Min. working speed	0.1 km/h constant;
Max inclination	
Min. inclination	0 %
Walking surface	140 x 48 cm
Toroidal transformer of isolation	1900VA;
Engine power (peak)	2 HP (AC)
Inverter	
	220/240 V – 50/60 Hz – 10 amp
Auxiliary circuit power supply for	·
inclination	low tension 18 V ac
Auxiliary circuit power supply for	
console/motor electric card	low tension 12 V dc
Absorbed power at max. speed	2000 VA
Nominal absorbed power	
Noise	
User's max. weight	

Damped board
Self-centring belt system
Self-oiling belt system
Acoustic warning to the pressure of the keys
Cardio recording with chest belt
EEC 93/42 certification (medical device)
Serial interface with Trackmaster protocol
Push button and pull rope stop emergency
Console with colour LCD touch-screen display for all the versins (R, M, P)
Electronic variation of inclination and speed

xr450m - xr450p

sp_xr450m-p_08_eng_01 06/03/2023 2/4

Features

Console functions (M)	- liquid crystal display shows heart beats, speed, time, distance and
Programmable console functions (P)	- liquid crystal display shows heart beats, speed, time, distance and
PROFILES	with speed, inclination and time independent setting;50 free profiles with time, inclination
	and speed setting; training at constant pulsations (until 80% of max. theoretical own heart rate) with machine self-adjustment of the speed to
FAT BURNING	keep heart rate within max. set value; training at constant pulsations (until 65% of max. theoretical own heart rate) with machine self-adjustment of the inclination to keep heart rate within max. set value;
FOUR TESTS	two auto tests, CHR (Constant Heart Rate) and CWL (Constant Work Level), let making a constant heart rate or load exercise. The third, RUNNER TEST, lets making an increasing load exercise with 1 km/h rising speed per minute. The fourth, COOPER TEST, lets making a 12 minutes exercise to achieve the maximum distance;
PERSONAL DATA	setting of user's personal data (age and weight);
	decreasing setting of exercise timing.

xr450m - xr450p

sp_xr450m-p_08_eng_01 06/03/2023 3/4

Models

model/operation	remote controlled	stand alone manual	stand alone automatic
xr 450 m ref 67019385	Х	Х	
xr 450 p ref 67019386	X	X	X

Standard Accessories

Description	Quantity
Power supply cable	1
RS232 connection cable to PC	1
User manual	1

Accessories and consumables

Code	Description
63090686	RS232 connection cable
67010036	Fall prevention support
67010021	Power supply cable
67010037	Polar belt receiver
67019310	Long lateral support bars
67010039	Underam kit
67010040	Can of lubricant
67019311	Access ramp
67019312	Lateral pediatric support bars



xr450m - xr450p

sp_xr450m-p_08_eng_01 06/03/2023 4/4