

COMPANY
BOLLARD
UP&DOWN
BULKHEAD
FLOODLIGHT
IN-GROUND
BRICKLIGHT
GARDEN
URBAN CLASSIC
URBAN MODERN
HIGH-BAY
POST
LAMPS
REFERENCES

VIVI 500 GX53 LED

GRAND SIZE




Modern luminaries made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Suitable for post top, wall and hanging installation. Equipped with TÜV approved, long-life and efficient **GX53 LED modular system** in different wattages. Designed according to the international regulations against light pollution (standard UNI 10819). Insulation class II, Protection rating IP65.

Diffusore moderno realizzato in resina antiurto, stabilizzato ai raggi UV, inattaccabile da ruggine e corrosione. Idoneo per il montaggio a palo, a sospensione o a parete. Provvisto di sistema modulare a LED GX53 approvato TÜV di lunga durata ed alta efficienza disponibile in diverse potenze. Progettato in ottemperanza alle norme internazionali contro l'inquinamento luminoso (standard UNI 10819). Classe di isolamento II, grado di protezione IP65.



V60.000.D9L





VIVI 500 GX53 LED - COMPONENTS

IP65



ROOF made of shockproof resin material one piece only, UV-rays stabilized, rust and corrosion-free.

TETTO in un unico pezzo, realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.



DIFFUSER made of UV-rays stabilized polymethylmethacrylate (PMMA), one piece only, available in clear or opal colour.

DIFFUSORE realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV, disponibile in colore trasparente o opale.



Decorative connection **RING** to be fixed on the luminaries diffuser.

ANELLO decorativo di connessione da fissare sul diffusore dell'apparecchio.

VIVI 500 GX53 LED

V60.000 *



Dimensions and weight

Height: 600 mm
Diameter: 600 mm
Weight: 7,7 Kg
Junction to support: diameter 60 mm
Area expose to wind pressure:
CxS = m² 0,1932

Moulded colours:

Black White Grey

Diffuser PMMA:

Clear Opal

GX53 LED



- **COST SAVING:** long-life and efficient LED light sources.
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **SUITABLE FOR OUTDOOR USE:** built-in driver fully protected against heat and humidity by silicone paste.

*ADD. SUFFIX

Luminaries supplied with white resin CEILING provided with TÜV approved, long-life and efficient 9x GX53 LED lamps included. Each lamp can be quickly and easily replaced individually, making the luminaries maintenance very simple.



9x 7W
63W

7200 Lm

4000 K .C9L

3000 K .C9R

9x 10W
90W




10800 Lm

4000 K .D9L

3000 K .D9R

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

PHOTOMETRIC DATA SAMPLE - VIVI 500 GX53 LED



SAVE -45%

9x10W GX53 LED
90W
(power consumption)

Area: 10x10mt
Height: 5mt
34 lux



HQI 150W
165W
(power consumption)

Area: 10x10mt
Height: 5mt
35 lux

COMPANY
BOLLARD
UP&DOWN
BULKHEAD
FLOODLIGHT
IN-GROUND
BRICKLIGHT
GARDEN
URBAN CLASSIC
URBAN MODERN
HIGH-BAY
POST
LAMPS
REFERENCES

VIVI 500

GRAND SIZE



V60.384.P10.D9L



V60.253




V60.129.D9L



V60.115.D9L





VIVI 500
V60.000

Pcs 1
Kg 7,7
mc 0,10

NEW LOT/VIVI500
V60.115

Pcs 1
Kg 8,7
mc 0,13

MARIO/VIVI500
V60.129

Pcs 1
Kg 7,1
mc 0,11

PILAR/VIVI500
V60.253

Pcs 1
Kg 9,7
mc 0,15

EKTOR 6000 PILAR/VIVI500 2L
V60.384.P20

Pcs 1
Kg 94,6
mc 1,46

EKTOR 6000 PILAR/VIVI500 1L
V60.384.P10


Pcs 1
Kg 86,2
mc 1,36

VIVI 500

GRAND SIZE



MADE IN
ITALY



EKTOR 5000 PILAR/VIVI500 1L V60.377.P10	AKILLE 5000 PILAR/VIVI500 1L V60.427.P10
Pcs 1 Kg 55,7 mc 0,43	
EKTOR 4500 PILAR/VIVI500 1L V60.374.P10	AKILLE 4500 PILAR/VIVI500 1L V60.424.P10
Pcs 1 Kg 50,2 mc 0,40	
EKTOR 4000 PILAR/VIVI500 1L V60.371.P10	AKILLE 4000 PILAR/VIVI500 1L V60.421.P10
Pcs 1 Kg 44,7 mc 0,37	

EKTOR 5000 PILAR/VIVI500 2L V60.377.P20	AKILLE 5000 PILAR/VIVI500 2L V60.427.P20
Pcs 1 Kg 65,1 mc 0,60	
EKTOR 4500 PILAR/VIVI500 2L V60.374.P20	AKILLE 4500 PILAR/VIVI500 2L V60.424.P20
Pcs 1 Kg 59,6 mc 0,57	
EKTOR 4000 PILAR/VIVI500 2L V60.371.P20	AKILLE 4000 PILAR/VIVI500 2L V60.421.P20
Pcs 1 Kg 54,1 mc 0,54	