



Radifocus® Guide wire M Non-Vascular type – Guide wires



[Enlarge image](#)

Radifocus® Guide wire M Non-Vascular type are standard and stiff Nitinol hydrophilic guide wires covered with polyurethane and hydrophilic coating for non-vascular procedures (endourology).

Indicated for use for non-vascular procedures such as Endoscopic and Urologic applications (drainage, endoprosthesis placement, and embolization), catheterization and exchange procedures in normal, tortuous and narrow, and tight and stenotic ducts (bile and pancreatic ducts).

Product Characteristics

- Extra flexible & non traumatic tapered tip: increased flexibility, smooth and safe navigation through ducts.
- Extra hydrophilic ("M" polymer coating): smooth navigation through both catheters and ducts, providing time savings to user.
- Polyurethane radiopaque jacket: smooth surface to minimize adhesion to the wire, soft and atraumatic navigation. Includes tungsten for higher visibility.
- Super elastic Nitinol alloy core: excellent shape memory, greater flexibility, increased control in difficult cases. Prevents kinking for an easier and faster catheter placement.
- One-piece construction: improved steering control, true one-to-one torque transmission, easier, faster and safer navigation through both catheter and ducts.
- Rounded end: decreased likelihood of duct trauma, smoother wire insertion.

General Specifications

Core material	Standard or stiff Nitinol
Radiopaque jacket	Polyurethane layer containing tungsten
Hydrophilic coating	"M" polymer
Guide wire diameters	0.020" (0.51 mm) / 0.025" (0.64 mm) / 0.032" (0.81 mm) / 0.035" (0.89 mm)
Guide wire lengths	150 cm / 260 cm / 400 cm / 450 cm
Distal flexible length	30 mm
Distal curves	Straight / 45° angled
Units per box	5

Item Specifications

Shaft	Outer diameter	Length	Flexible length	Distal curve	Item reference
Standard	0.035" / 0.89 mm	150 cm	30 mm	Angled	NV-GA35153M
Standard	0.035" / 0.89 mm	150 cm	30 mm	Straight	NV-GS35153M
Stiff	0.035" / 0.89 mm	150 cm	30 mm	Angled	NV-PA35153M
Stiff	0.035" / 0.89 mm	150 cm	30 mm	Straight	NV-PS35153M
Standard	0.032" / 0.81 mm	260 cm	30 mm	Angled	NV-GA32263M
Standard	0.035" / 0.89 mm	400 cm	30 mm	Angled	NV-GA35403M
Standard	0.032" / 0.81 mm	400 cm	30 mm	Angled	NV-GA32403M
Standard	0.035" / 0.89 mm	260 cm	30 mm	Angled	NV-GA35263M
Standard	0.035" / 0.89 mm	450 cm	30 mm	Angled	NV-GA35453M
Standard	0.032" / 0.81 mm	260 cm	30 mm	Straight	NV-GS32263M
Standard	0.032" / 0.81 mm	400 cm	30 mm	Straight	NV-GS32403M
Standard	0.035" / 0.89 mm	260 cm	30 mm	Straight	NV-GS35263M
Standard	0.035" / 0.89 mm	400 cm	30 mm	Straight	NV-GS35403M
Standard	0.035" / 0.89 mm	450 cm	30 mm	Straight	NV-GS35453M
Stiff	0.020" / 0.51 mm	450 cm	30 mm	Angled	NV-PA18453M
Stiff	0.025" / 0.64 mm	450 cm	30 mm	Angled	NV-PA25453M
Stiff	0.035" / 0.89 mm	260 cm	30 mm	Angled	NV-PA35263M
Stiff	0.035" / 0.89 mm	400 cm	30 mm	Angled	NV-PA35403M
Stiff	0.020" / 0.51 mm	450 cm	30 mm	Straight	NV-PS18453M
Stiff	0.025" / 0.64 mm	450 cm	30 mm	Straight	NV-PS25453M
Stiff	0.035" / 0.89 mm	260 cm	30 mm	Straight	NV-PS35263M
Stiff	0.035" / 0.89 mm	400 cm	30 mm	Straight	NV-PS35403M

Please quote above item reference codes when placing an order.

Other code numbers are available on special demand. For any further information, please contact your local [Terumo representative](#).