


ARIETTA V60



- · ARIETTA and 4Dshading are registered trademarks or trademarks of Hitachi Aloka Medical, Ltd. in Japan and other countries.
- Real-time Tissue Elastography is a registered trademark or trademark of Hitachi Medical Corporation in Japan and other countries.
- IPS-Pro is a registered trademark or trademark of Japan Display Inc.
- The specifications, shape and color of this product are subject to change without notice.
- The standard components and optional items vary depending on the country.





ALOKA illuminate the change



Usability of ARIETTA V60, a solution for comfort

High-performance features normally reserved for premium systems are packed into its compact housing. ARIETTA V60, almost 25% lighter in weight than conventional systems (Hitachi Aloka Medical's in-house comparison), can be moved around with little effort and operated easily in confined spaces.

Palm rest

10.4" touch screen panel

Multi-rotary encoder

17" IPS-Pro high-resolution monitor

Gel warmer

Transducer connectors

One-step caster lock mechanism

The benefit of "comfortable" is for everyone.

Side pocket for storage

Ergonomic Design

ARIETTA V60 is ergonomically designed to allow the examiner to scan in comfort irrespective of the type of patient or clinical examination. The adjustment of the panel height between 70 and 100 cm is one of the key contributory elements.



IPS-Pro (In-Plane Switching) LCD panel technology

ARIETTA V60 is fitted with an IPS-Pro monitor, giving a high quality display of the images from a wide viewing angle.



Console design

The console layout is arranged to provide intuitively smooth operation, with a large palm rest provided centrally to give optimum wrist support.



Multiple auto-adjust functions

Optimization in real-time: In B-mode, the image brightness is continuously monitored, so that the adjusted value is tuned to the user's preference and the speed of sound is corrected for different tissues automatically bringing all areas of the image into sharper focus. In Doppler mode, the velocity range and baseline position are instantly optimized with just a single key stroke.

Dependable results provided by high-definition image quality


ARIETTA V60 offers imaging solutions from diagnosis through to treatment, in a wide variety of clinical fields.

To complement the high-definition image quality, a broad range of transducers and advanced functionality offer increased diagnostic confidence.



High Resolution B-mode

ARIETTA V60 provides an image quality that excels in both lateral and axial resolution.





High Resolution eFlow


The high spatial resolution of eFLOW produces an accurate display of blood flow confined within the vessel walls even in fine vessels.

Real-time Tissue Elastography (RTE)

Hitachi's Real-time Tissue Elastography assesses tissue strain in real time and displays the measured differences in tissue stiffness as a color map. Its application has been validated in a wide variety of clinical fields: for the breast, thyroid gland, urinary structures, and many more.








Strain Graph

The strain graph analyses the main strain in the chosen area of interest and provides feedback to the user for selection of the optimum frame that will provide robust information on tissue stiffness.




Assist Strain Ratio

Assist Strain Ratio provides automatic identification of both the border of a designated breast lesion and a reference area in the fat tissue. The two ROIs are automatically positioned and the strain ratio of the lesion to the fat tissue is calculated.

Contrast enhanced ultrasound – from detection to differential diagnosis

Contrast enhanced ultrasound, a technique widely used in clinical diagnosis, is also realized in this compact system. It delivers homogeneous enhancement throughout the field of view.



Accumulation Imaging


Variety of transducers that support intraoperative examinations.

The importance of intraoperative ultrasound is increasing in the quest to improve the safety of surgery. Choosing the best transducer to suit the procedure can lead to a more definitive diagnosis.


T-shaped convex intraoperative transducer

Held between fingers, this transducer provides stability for scanning. Contrast enhanced ultrasound and Hitachi's Real-time Tissue Elastography modes complement the high-definition B-mode and high-sensitivity Color Flow Doppler.









Support for early detection and diagnosis – from the heart to systemic blood vessels

Even with its compact size, ARIETTA V60 features advanced tools that contribute to early detection and diagnosis of lesions in the heart and systemic blood vessels.

Vascular system evaluation



Early assessment of atherosclerosis (eTracking) eTracking analyses changes in blood vessel diameter in real time by tracking the RF signals. It determines parameters that measure the degree of atherosclerosis.



long-axi

AP NO. 7172 AND TO SERVICE STATE STATE STATE STATE STATE STATE WITH STATE ST

Automatic measurement of Intima-media Thickness (IMT)
The maximum and mean IMT is automatically
calculated following the placement of the ROI on a
long-axis section of the blood vessel.

Dual CF
Dual CF is a simultaneous side by side display of the color Doppler and B-mode images, enabling the observation of both the intravascular lumen and the blood flow together in real time.





eFLOW
eFlow is a blood flow mapping display with high
spatial resolution that reduces color overlapping of
small vessel walls.




Trapezoidal scan

Trapezoidal scan offers a wider field of view with the linear transducers, enhancing the visualization of vessels and organs and the tissues around them.


Cardiac function evaluation

B- and CW-modes can be realized with less patient-dependent variability. Clarity of imaging contributes to reduced examination time and improved workflow.






Functions that reduce exam time




Dynamic Slow-motion Display (DSD)
Display of the real-time image and its
slow-motion counterpart side by side on one
screen. Rapid valve movements can be observed
in detail.



The M-mode can be displayed using any cursor orientation in real time or reconstructed from the data in the cine memory after freeze. In this way, the wall motion or valve excursion can be compared from multiple angles in the same heartbeat.

Advanced functions for cardiac examinations



Two-dimensional Tissue Tracking
Two-dimensional Tissue Tracking (2DTT) can be
used to quantify the movement of the entire left
ventricle or a local movement of the cardiac
muscle. This speckle tracking technique provides
precise and accurate analysis of the movement of
the cardiac muscle.



Dual Gate Doppler

Dual Gate Doppler can display Doppler waveforms from two sampling points simultaneously, shortening exam time. A combination of Tissue Doppler Imaging and Pulsed Wave Doppler (TDI/PW) allow simultaneous evaluation of wall motion and hemodynamics and enables measurement of E/e'.

Variety of Transesophageal Transducers

The form of the TE probes is designed to reduce patient discomfort while providing high imaging performance.

- •Rotary plane transducer
- •Electronic transesophageal transducer



An earlier, more accurate diagnosis of maternal and fetal well-being provides reassurance

Diagnostic ultrasound plays a role in connecting a mother with her fetus. Early observation and accurate diagnosis provide support that can guide the optimum course of the pregnancy.





High-resolution B-mode Imaging

High-resolution B-mode imaging is recognized as the key requirement for observation of potential morphological abnormalities in fetal organs, such as the heart and brain. ARIETTA V60's high contrast resolution allows detailed observation.





Accurate diagnosis in the 2nd & 3rd Trimesters

Various functions support the observation of the fetal heart. They can streamline the examination as well as improve the accuracy of diagnosis.



eFlow

eFlow is a blood flow mapping display with high spatial resolution that reduces color overlapping of the wall of small vessels.



STIC

STIC displays 3D images using volume data constructed by collecting image frames at the same time phase from multiple heartbeats. It is possible to observe the motion of the fetal heart in any arbitrary cross section.



Dual Gate Doppler

Dual Gate Doppler allows observation of Doppler waveforms from two different locations during the same heart cycle. Simple measurements from the two different waveforms can be useful in the diagnosis of fetal arrhythmia.

Reassurance for patients

Real-time 3D

Three- and four-dimensional imaging can play a role in connecting a mother with her fetus.

4Dshading is a rendering technology that simulates different positions of a virtual light source giving a more realistic appearance to the 3D reconstructed image







ARIETTA

3D (Fetus)

4Dshading

Supporting Women's Health

The compact size of ARIETTA V60 allows positioning in confined spaces and close to the examination table.

Our focus is to improve women's quality of life by making full use of technology to contribute to the early detection and prevention of diseases.

Transvaginal transducer

The transvaginal transducer is designed for patient comfort with a small insertion tip and thin shaft. At the same time, the handle is easy to grip and the transducer light in weight ensuring operator well-being when scanning for long periods.







11