

Nanjing Jingning Quality Inspection Company

Quality Certificate

Sleeve Anchors Hex Flange Nuts, yellow zinc plated



Items	Standard				result
	diameter x cone outer diameter x diameter (±0.2)	length of bolt (±1.0)	length of sleeve (±1.0)	working length	
8x40	7.8x7.8x5.8	45	34	40	Acc.
8x65	7.8x7.8x5.8	70	59	65	Acc.
8x85	7.8x7.8x5.8	90	79	85	Acc.
8x100	7.8x7.8x5.8	105	94	100	Acc.
10x60	9.8x9.8x7.7	65	52	60	Acc.
10x77	9.8x9.8x7.7	82	69	77	Acc.
10x97	9.8x9.8x7.7	102	89	97	Acc.
10x125	9.8x9.8x7.7	130	117	125	Acc.
10x150	9.8x9.8x7.7	155	142	150	Acc.
12x75	11.8x11.8x9.7	82	66	75	Acc.
12x100	11.8x11.8x9.7	107	89	100	Acc.
12x129	11.8x11.8x9.7	136	117	129	Acc.
12x150	11.8x11.8x9.7	157	138	150	Acc.
12x180	11.8x11.8x9.7	187	168	180	Acc.
12x200	11.8x11.8x9.7	207	188	200	Acc.
14x120	13.8x13.8x9.6	127	108	120	Acc.
14x150	13.8x13.8x9.6	157	138	150	Acc.
14x200	13.8x13.8x9.6	207	188	200	Acc.
16x150	15.8x15.8x11.5	157	135	150	Acc.
16x200	15.8x15.8x11.5	210	188	200	Acc.
16x250	15.8x15.8x11.5	260	238	250	Acc.
20x200	19.8x19.8x15.5	210	185	200	Acc.
20x250	19.8x19.8x15.5	260	235	250	Acc.

Remark: Acc. Stands for acceptable

Material: Q195						
Chemical composition & Technical specification						
Element	C%	Si%	Mn%	P%	S%	Tensile Strength (Mpa)
Ratio	8.00	10.00	34.00	2.00	2.70	368~392

Inspection date: 2016.2.15

Inspector:Li Jun

