

No. AJFS1805004270FF

Date: MAR.25, 2018

Page 1 of 5

JINAN HENGSHENG NEW BUILDING MATERIALS CO., LTD

ROOM601, TOWER D, BINHE BUSINESS CENTER, TIANQIAO DISTRICT, JINAN CITY

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description: PVC PROFILE SGS Ref No.: QDIN1805002468SC

Specification: HANDRAIL, WALL PROTECTOR, CORNER GUARD, TACTILE TILE, STAIR NOSING,

SHOWER SEAT

Buyer: JINAN HENGSHENG NEW BUILDING MATERIALS CO., LTD

Manufacturer: SHANDONG HENGSHENG PROTECTION PRODUCTS CO., LTD

Test Requested:

BS 476 Part 7:1997 *Incorporating Corrigendum No.1:2014* "Fire tests on building materials and structures Part 7: Method of test to determine the classification of the surface spread of flame of products".

Test Results: -- See attached sheet -

Test Period:

Sample Receiving Date

: MAY.08, 2018

Test Performing Date

: MAY.08, 2018 TO MAY.15, 2018

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou

Technical Manager





No. AJFS1805004270FF

Date: MAR.25, 2018

Page 2 of 5

I. Test conducted

This test was performed in accordance with the procedure specified in BS 476 Part 7:1997 *Incorporating Corrigendum No.1:2014* "Fire tests on building materials and structures Part 7. Method of test to determine the classification of the surface spread of flame of products".

II. Sample details

Sample description	PVC profile
Thickness	About 1.8mm
Color	White
Specimen size	885mm×270mm

III. Test details

Conditioning of specimens:	Prior to testing, the sample was conditioned to constant mass at a temperature of 23 \pm 2 °C, and a relative humidity of 50 \pm 10 %, and maintained in this condition until required for testing.
Exposed Face:	White surface

Irradiance along horizontal reference line on the calibration board

Distance along reference line from inside edge of specimen holder	Irradiance kW/m²		
mm	Specified	Min.	Max.
75	32.5	32.0	33.0
225	21.0	20.5	21.5
375	14.5	14.0	15.0
525	10.0	9.5	10.5
675	7.0	6.5	7.5
825	5.0	4.5	5.5

To be continued....



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sqs.com/en/Tems-and-Conditions, sapy, and, for electronic Dracture at http://www.sqs.com/en/Tems-and-Conditions.appy and, for electronic Dracture at http://www.sqs.com/en/Tems-and-Conditions/Terms-e-Document.appy attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits or Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a speciation from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the sul, Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention.To check the authenticity of testing / inspection report & certificate, please contact the telephone (68-758) 8302.

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Ariji County, Zhejiang Province, China 313300 t (修6-572) 5018825 f (修6-572) 5018829 www.sgsgroup.com.cn 中国·斯江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (修6-572) 5018825 f (修6-572) 5018829 e sgs.china@sgs.com



No. AJFS1805004270FF

Date: MAR.25, 2018

Page 3 of 5

IV. Test results

SPECIMEN No.	1	2	3	4	5	6
Distance (mm)	Time to travel to indicated distance (minutes :seconds)					
75	0:28	0:25	0:25	0:26	0:25	0:24
165	1:35	1:23	1:22	1:29	1:28	1:30
190	2:12	2:05	2:03	2:05	2:08	2:15
215						·
240						
265						
290						
375						
455						
500						
520						
600						
675						
710						
750						
785						
825						
Maximum distance traveled at 1.5 minutes (mm)	175	180	170	168	168	160
Maximum distance traveled during the whole test (mm)	185	187	178	170	172	168
Time to reach maximum distance traveled	10min	10min	10min	10min	10min	10min

Note: 1. "--" Not reached the reference line

2. Six specimens are usually tested. If the test on any specimen is deemed to be invalid, as defined in the standard, it is permissible for up to a maximum of nine specimens to be tested in order to obtain the six valid test results.

The classification limits specified in BS 476 Part 7:1997 *Incorporating Corrigendum No.1:2014* are given in Appendix 1.

Observations during test: None

To be continued....



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printee verleaf, available on request or accessible at http://www.ags.com/en/Ferms-and-Conditions.agsy and, foretcomic format documents ubject to Terms and Conditions for Electronic Documents at http://www.ags.com/en/Ferms-and-Conditions/Ferms-e-Document.agsy taken to Terms and Conditions for Electronic Documents at <a href="http://www.ags.com/en/Ferms-and-Conditions/Ferms-e-Document.agsy (advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits or lient to the state of the second of the second of the state of the second o

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (%5-572) 5018825 f (%5-572) 5018825 www.sgsgroup.com.cn 中国・浙江・安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (%5-572) 5018825 f (%5-572) 5018825 e sgs.china@sgs.com



No. AJFS1805004270FF

Date: MAR.25, 2018

Page 4 of 5

Criteria for classification:

If the prefix "D" or suffix "R" or "Y" is included in the classification, this indicates that the results should be treated with caution. An explanation of the reason for prefix and suffixes is given in Appendix 2

Appendix 1 Classification of spread of flame

	Spread	of flame at 1.5 min	Final spread of flame		
Classification	Limit (mm)	Limit for one specimen in sample(mm)	Limit (mm)	Limit for one specimen in sample(mm)	
Class 1	165	165+25	165	165+25	
Class 2	215	215+25	455	455+45	
Class 3	265	265+25	710	710+75	
Class 4	Exceeding the limits for class 3				

Appendix 2 Explanation of prefix and suffixes which may be added to the classification

- 1. A suffix R is added to the classification if more than six specimens are required in order to obtain six valid test results (e.g. class 2R).
- 2. A prefix D is added to the classification of any product which does not conform to the surface characteristics specified in the standard and has therefore been tested in a modified form (e.g. class D3).
- 3. A suffix Y shall be added to the classification if any softening and/or other behaviour that may affect the flame spread occurs.

<u>Classification</u>: In accordance with the class definitions given in BS 476 Part 7:1997 *Incorporating Corrigendum No.1:2014*, the tested sample is classified as <u>Class 1</u>.

Statements:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test. They are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

The test results relate only to the specimens of the product in the form in which were tested. Small differences in the composition or thickness of the product may significantly affect the performance during the test and may therefore invalidate the test results. Care should be taken to ensure that any product, which is supplied or used, is fully represented by the specimens, which were tested.

To be continued....



inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer vertified, and an object of the Company subject to the Company subject to the Company subject to the Company subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-p-Document.aspx ubject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-p-Document.aspx ubject to Terms-and-Conditions/Terms-p-Document.aspx ubject to Terms-and-Conditions/Te




No. AJFS1805004270FF

Date: MAR.25, 2018

Page 5 of 5

Photo Appendix:



SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-C

Attention:To check the authenticity of teating / inspection report & certificate, please contact us at telephone:(86-75) 8307 1443, or email: CN. Doccheck@egs.com
|No 301, suright Road, 2 Block, Suright Industry Zone, Arj County, Zhejang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgegroup.com.cn
| 中国・浙江・安吉县阳光工业园二区阳光大道301号 鄭錦:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com