

Specificații tehnice

Numărul procedurii de achiziție : **ocds-b3wdp1-MD-1717767302670** din **07 iunie 2024**

Obiectul achiziției: **Materiale electrotehnice (repetat) .Achiziții cu costuri mici . CPV : 31500000-1 - Aparatură de iluminat și lămpi electrice**

Denumirea bunurilor	Denumirea modelului bunului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
<i>Materiale electrotehnice (repetat)</i>						
Lotul nr. 5 Conectori și Accesorii						
5.1. Conector de criptare	NBNC75BFG7	Liechtenstein	Neutrik	BNC Connector: -Compatible for HD-SDI digital video -For inner conductor of 0.6 mm and insulated diameter up 4.6 mm - Connector: BNC male - Impedance: 75Ω - Options: Crimp	Title NBNC75BFG7 Connection Type BNC 75 Ω -Compatible for HD-SDI digital video -For inner conductor of 0.6 mm and insulated diameter up 4.6 mm - Connector: BNC male - Impedance: 75Ω - Options: Crimp Gender male Electrical Contact resistance ≤ 3mΩ (inner) Contact resistance ≤ 2mΩ (outer) Dielectric strength 1,5kVdc Impedance 75 Ω	

					<p>Insulation resistance > 5 GΩ Rated voltage < 50 V VSWR ≤ 1.050 / > 32 dB up to 1 GHz ≤ 1.065 / > 30 dB up to 2 GHz ≤ 1.100 / > 26 dB up to 3 GHz Mechanical Cable O.D. 4.7 mm Cable retention > 30 N (Center) Crimp size 5 Hex crimp (shield) acc. MIL22520/5-43(B) Crimp size (pin) 1,6 Square crimp (pin) acc. IEC 60803 (die designation 2) Insertion force < 25 N Lifetime > 1000 mating cycles Garanție : 12 luni</p>	
5.2. Conector	NC3FXX	Liechtenstein	Neutrik	<p>Conectori XLR, male 3-pole - Chuck type strain relief - Protective rubber sleeve - Solder contacts - Ergonomic design - Improved screening when plugging</p>	<p>Conectori XLR, male 3-pole - Chuck type strain relief - Protective rubber sleeve - Solder contacts - Ergonomic design - Improved screening when plugging Garanție : 12 luni</p>	
5.3. Conector	NC3FXX	Liechtenstein	Neutrik	<p>Conectori XLR, female 3-pole - Chuck type strain relief - Protective rubber sleeve - Solder contacts - Ergonomic design - Improved ground contact - Improved pin contact with a solder stop</p>	<p>Conectori XLR, female 3-pole - Chuck type strain relief - Protective rubber sleeve - Solder contacts - Ergonomic design - Improved ground contact - Improved pin contact with a solder stop Garanție : 12 luni</p>	
5.4. Cablu video digital	SDI cable HD-SDI - digital video cable 0.6/2.8 AF - FRNC - Eca	Germania	Klotz	<p>HD-SDI - digital video cable: Construction: -inner conductor - solid bare copper, Ø 0.60 mm -insulation - Foam-Skin PE, gas injected, Ø 2.8 mm -shielding - AL/PET/AL double-layer foil + tinned copper braid (92% coverage)</p>	<p>HD-SDI - digital video cable: Construction: -inner conductor - solid bare copper, Ø 0.60 mm -insulation - Foam-Skin PE, gas injected, Ø 2.8 mm -shielding - AL/PET/AL double-layer foil + tinned copper braid (92% coverage)</p>	

				-outer jacket - FRNC -overall diameter - 4.5 mm -working temperature -30°C / +70°C -min. bending radius - 25 mm -characteristic impedance - 75 Ω ± 1% -application – HD-SDI 3.0G -hd-sdi transmission length for 1080i – min. 68m	-outer jacket - FRNC -overall diameter - 4.5 mm -working temperature -30°C / +70°C -min. bending radius - 25 mm -characteristic impedance - 75 Ω ± 1% -application – HD-SDI 3.0G -hd-sdi transmission length for 1080i – min. 68m Garanție : 12 luni	
5.5. Cablu audio	Cablu de Microfon MY206SW	Germania	Klotz	Professional Microphone Cable balanced patch and microphone cable high screen – PVC Shielded	Conductor : fir litat din cupru, 28 x 0.10 mm Diametru conductor : 0.22 mm ² Izolatie ș polietilena (PE) Aranjament fire ș 2 conductori + fire de bumbac, rasucite Ecranaj ș spirala din cupru Manson exterior : PVC, mat Diametru total : 6.15 mm Raza minima de indoire : 30 mm Temperatura de lucru ș -20 °C / +70°C Rezistenta conductor : <85Ω/km Cond./Cond. : 60pF/m Cond./Shield : 110pF/m Rezistenta izolatie : > 0.1 GΩ x km Garanție : 12 luni	
5.6. Cablu video	CC-HDMI14	PRC	Gembrid	Cablu HDMI- HDMI 10 m	Cablu HDMI la HDMI male-male Conector 1 : HDMI Tip Conector 1 : Male Conector 2 : HDMI Tip Conector 2 : Male Lungimea : 10 m Garanție : 12 luni	
5.7. Cablu video	HDMI-HDMI V1.4	PRC	Cablexpert/ Gembrid	Cablu HDMI- HDMI 5 m	Cablu HDMI la HDMI male-male Conector 1 : HDMI Tip Conector 1 : Male Conector 2 : HDMI Tip Conector 2 : Male Lungimea : 5 m Garanție : 12 luni	
5.8. Cablu video	CC-HDMI14	PRC	Cablexpert/ Gembrid	Cablu HDMI- HDMI 1 m	Cablu HDMI la HDMI male-male Conector 1 : HDMI	

					Tip Conector 1 : Male Conector 2 : HDMI Tip Conector 2 : Male Lungimea : 1 m Garanție : 12 luni	
5.9. Cablu video	CC-DP-HDMI-3M, DisplayPort (M) - HDMI (M), 3m, Negru	PRC	Cablexpert	Cablu Display Port - HDMI 3m	Interfață Video : DisplayPort to HDMI Conector 1 : DisplayPort (M) Conector 2 : HDMI (M) Lungimea : 3m Garanție : 12 luni	
5.10. Cablu video	CC-HDMI-DVI-10, HDMI (M) - DVI-I (M), 3m, Negru	PRC	Cablexpert	Cablu HDMI-DVI 3m	Interfață Video : HDMI to DVI Conector 1 : DVI-I (M) Conector 2 : HDMI (M) Lungimea : 3m Garanție : 12 luni	
5.11 Fibra optica	Fiber optic patch cords, Multimode OM4, LC-LC Duplex, 3M	PRC	APC	Fiber optic patch cords, Multimode OM4, LC-LC Duplex, 3M	Fiber optic patch cords, Multimode OM4, LC-LC Duplex, 3M Garanție : 12 luni	

Semnat: _____ Numele, Prenumele: Cîrlig Ion În calitate de: director

Ofertantul: WEST BUY SRL Adresa: mun.Chisinau bd.Mirecea cel Batrin 39 ap 143

Data : 16.06.2024