

## TECHNICAL DATA

Volume (L):	120.00
Curb weight approx. (kg):	8.00
Permissible total weight max. (kg):	60.00
Material:	HDPE, UV-stabilized
Wheels:	2 rubber wheels Ø 200 mm corrosion free steel axle
Lid / Container:	2 hinge pins continuous handle: approx. Ø 27 mm Lid with continuous lip handle and additional bow handles
Certification:	EN 840, RAL GZ 951/1


## OPTIONS

- Locking versions
- Lid apertures
- Hood apertures
- Security insert / CD insert
- Markings / Identification
- Clip-Variants
- Noise reduction
- Volume reduction
- Bio features
- Special features / Accessories


The products do not contain any substances on the SVHC list of the European Chemicals Agency (ECHA).

## Options


### Locking versions



Gravity Lock 2/4W



Preparation for  
Padlock




Triangular Lock 2/4W


### Lid apertures




Packaging 155x255  
rubber ring 2W CL SL




Small LiL rectangular  
2W



Glass 152 rubber ring  
2W CL SL



Glass 152 rubber 2W  
CL SL



Small LiL Glass 2W

### Hood apertures



Paper Hood 2W

### Security insert / CD insert




CD insert 2W



Security Insert 2W



### Markings / Identification



### Clip-Variants



### Noise reduction



### Volume reduction



### Bio features



### Special features / Accessories

