

Vipoil Drivetronic ATF DX III

Ulei de transmisie automata

DESCRIERE

Vipoil Drivetronic ATF DX III este un ulei de transmisie automata multifunctional, formulat din uleiuri de baza sintetice si un pachet de aditivi atent selectionati, care ofera o lubrifiere superioara, reduc frecarea, ofera tranzitii fara intreruperi intre trepte imbunatatind confortul general la conducere, protejeaza impotriva formarii de namol si lac, asigurand totodata nivelul de performanta Dexron III H.

SPECIFICATII

GM Dexron III H,G,F
Caterpillar TO-2
Allison TES-389
MB 236.9
MAN 339 V1, Z1, Z2
Ford MERCON M931220, WSS-M2C922-A1
VOITH H55.6336.xx
ZF TE-ML 03D/05L/14A/16L/17C/20B/25B
VOLVO 1161521, 1161621, TO 97341
VOITH G607

APLICATII

Este recomandata utilizarea la transmisiile automate, sistemele de servodirectie si alte sisteme hidraulice ale autovehiculelor, autoutilitarelor care solicita acest tip de ulei.

BENEFICII

- Stabilitate foarte buna impotriva oxidarii
- Stabilitate foarte buna impotriva depunerilor
- Durata de exploatare extinsa (LongLife)
- Pornire usoara la temperature scazute

PROPRIETATI TIPICE

Caracteristici	Metoda de test	Valori
Densitate la 15°C, g/cm ³ , max.	ASTM D4052	0.850
Viscozitate cinematica la +40°C, mm ² /s ⁻¹ .	ASTM D445	34.0
Viscozitate cinematica la +100°C, mm ² /s ⁻¹ .	ASTM D445	7.1
Indice de viscozitate, min.	ASTM D2270	178
Punct de inflamabilitate °C, min.	ASTM D92	220
Punct de curgere °C, min.	ASTM D97	-48

* These values are informative. Variations of these characteristics may occur.

This lubricant does not present a particular danger if it is used according to our recommendations and according to the purpose for which it was produced. The security sheet according to the European legislation in force can be obtained on request.