



Labculture® Plus LA2-E-EU G4



Labculture® Plus LA2-S-EU G4

# Labculture® PLUS G4

## Class II Biological Safety Cabinets

*Energy-efficient, Safe, and Ergonomic  
Biosafety Cabinet in the World*



# LABCULTURE® PLUS G4 (LA2-EU G4) CLASS II BIOSAFETY




## USB Port

- Export Data Logging
- Software Update
- Wired data transaction to BMS



## Zero Volt Relay Contact

- Free Relay Contact
- Exhaust Free Relay Contact




## Airflow Sensor

- Monitors real-time airflow for safety
- Alert the user if airflow is insufficient




## Centurion 7" Capacitive Touchscreen Controller

- Displays all safety information on one large screen
- Shows cabinet parameters with intuitive 3D illustration
- Easy to use menu, similar to Smart Phone Apps
- Large buttons, easy to operate when wearing gloves
- Self-guidance to users to deal with specific situations
- Centered and angled down for easy reach and viewing
- Optional: 21 CFR Part 11 Compliance



## Motorized Window

- Aerosol tight window seal
- Window automatically stops at safe operating height
- Conveniently move the window by fingertip
- Tilttable Sash for easy glass cleaning



## Unique Stainless Steel and Glass Hybrid Wall (E-Series)

- Large corner radius for easy cleaning
- Easy to reach service fixture and outlets
- Stainless steel side wall is available (S-Series)
- Hole-free side glass for increased safety

## User-friendly Work Tray

- Largest useable area in the market
- Available in two variants:
  - Single-piece, recessed work tray to contain spillage (S-series)
  - Autoclavable, multi-piece work tray (E-series)
- Sloped perimeter for easy cleaning
- Easy-to-lift tray
  - Large, easy-to-clean tray handles (S-series)
  - Seamless hole to lift a tray segment (E-series)
- V-shaped grill allowing efficient inflow



## Raised Arm Rest

- Prevent grille blocking
- Comfortable working posture
- Durable stainless steel construction



## Ergonomic Work Zone

- 10° angle to optimize user comfort, reduce glare, and maximize reach into the work area
- Brightly illuminated with >1200 lux
- Industry-leading dimmable LED for optimum work comfort
- Airtight seal port for cable/tube exit protected by a negative pressure side wall



Esco Labculture® Plus G4 Class II Biosafety Cabinet  
Available in 0.9 m, 1.2 m, 1.5 m, and 1.8 m models.





Certified by TÜV NORD, Germany  
for compliance to DIN EN 12469

# CABINET, FEATURING ADVANCED TOUCHSCREEN CONTROLLER

## Dual Energy-efficient DC ECM Blower

- The leading energy efficient Class II Biosafety Cabinet in the world with 70% energy savings compared to AC motor
- Stable airflow despite building voltage fluctuations and filter loading
- Standby mode to further reduce power consumption by 80%



Labculture  
Class II Biosafety Cabinet

## Advance Filtration System

- 10x Filtration efficiency of HEPA filter
- Creates ISO Class 3 work zone instead of Industry-standard ISO Class 5
- Same 10 years filter life and replacement cost as HEPA filters



## Dimmable LED

- Save energy and optimize work comfort

## Removable Paper Catch

- Prevent objects from being pulled into blower plenum
- Removable for easy cleaning
- Optional pre-filter can be fitted



## User Modified Pass-Through / Cable Port

- 3" Port with 1/4" hole on rubber membrane inside
- NSF-approved. Surrounded by negative pressure
- Allows cables and tubes to exit with fully closed sash




## Tray Support Beams

- Support work tray evenly for less vibration
- Cleaning holder to easily wipe the drain pan

## ISOCIDE™ Powder Coat

- Silver-ion impregnated powder coat
  - Inhibits microbial growth to improve safety
- Prevents the plenum from becoming biohazard landfill




## Certification


	Performance	Air Quality	Filtration	Electrical Safety	Electromagnetic Compatibility (EMC)
<b>Standards Compliance</b>	EN 12469, TUV Nord, Germany	ISO 14644.1, Class 3, Worldwide, US Fed Std 209E, Class 1 USA JIS B9920, Class 3, Japan	EN-1822 (H14), Europe IEST-RP-CC001, USA	EN-61010-1, Europe IEC61010-1, Worldwide	EN IEC 61326-1 Group 1 / Class B

## Dynamic Chamber™

- Blower plenum and side walls are surrounded by negative pressure
- Prevent contaminants from escaping outside

■ Positive Pressure  
■ Negative Pressure






## Cabinet Filtration System


- Ambient air is pulled through front grille to create inflow, without going into the work surface. Inflow is joined by half of the downflow, to create front air curtain that is fine-tuned to create a large performance envelope. The combined air stream travels through the back air column towards the blower.
- Approximately 1/3 of the air in the common plenum is exhausted through the ULPA filter to the room. The remaining 2/3 of the air is passed through the downflow ULPA filter and into the work area as a vertical laminar flow air to create ISO Class 3 work surface and prevents cross contamination.
- Near the work surface, the downflow splits. About half goes to the front grille, and half goes to the rear grille. A small portion enters the side capture zones to prevent dead air corners (small blue arrows).
- The design was optimized to give large performance envelope, that provides operator and product protection at wide Inflow and Downflow variation from the Nominal point.

## Performance Envelope Test of LA2-EU G4



- Nominal Airflow
- Personnel / Product Protection
- Area of Personnel / Product Protection
- ▲ No Personnel / Product Protection
- Area of no Personnel / Product Protection

## Engineering Drawing



1. Exhaust Airflow Sensor
2. Power Inlet
3. Zero Volt Relay Contact
4. USB Port
5. Centurion Touchscreen Controller
6. Angled Sash Glass Window

7. Maximum Sash Opening
8. Single-piece Stainless Steel Back Wall
9. Single-piece Stainless Steel Work Tray
10. Electrical Panel
11. Dimmable LED Lamp
12. IV Bar Retrofit Kit Provision

13. Electrical Outlet Provision
14. Service Fixture Retrofit Kit Provision
15. VHP Port In (Optional)
16. Tempered Side Glass
17. Stainless Steel Arm Rest
18. Exhaust Collar (optional)

19. Exhaust Filter
20. DC-ECM Exhaust Blower
21. DC-ECM Downflow Blower
22. Downflow Filter
23. UV Lamp Provision
24. Cable Port (right side only)

## TECHNICAL SPECIFICATIONS

Labculture® Plus Class II 220-240 VAC, 50/60 Hz	Glass Side Walls	LA2-3E8-EU G4 2011742	LA2-4E8-EU G4 2011743	LA2-5E8-EU G4 22011744	LA2-6E8-EU G4 2011745	
	Stainless Steel Side Walls	LA2-3S8-EU G4 2011738	LA2-4S8-EU G4 2011739	LA2-5S8-EU G4 2011740	LA2-6S8-EU G4 2011741	
Nominal Size		0.9 meter	1.2 meter	1.5 meter	1.8 meter	
External Dimensions (W x D x H)	Without Optional Base Stand	1035 x 858 x 1570 mm	1340 x 858 x 1570 mm	1645 x 858 x 1570 mm	1950 x 858 x 1570 mm	
Internal Dimensions (W x D x H)		915 x 623 x 720 mm	1220 x 623 x 720 mm	1525 x 623 x 720 mm	1830 x 623 x 720 mm	
Usable Work Area		0.45 m <sup>2</sup>	0.62 m <sup>2</sup>	0.76 m <sup>2</sup>	0.93 m <sup>2</sup>	
Sash opening		200 mm				
Maximum Sash Opening		470 mm				
Average Airflow Velocity	Inflow	0.45 m/s				
	Downflow	0.32 m/s				
Average Airflow Volume	Inflow	415 cmh	564 cmh	750 cmh	846 cmh	
	Downflow	726 cmh	971 cmh	1214 cmh	1457 cmh	
	Exhaust	415 cmh	564 cmh	750 cmh	846 cmh	
ULPA Filter Typical Efficiency		99.999% efficiency at 0.3 to 0.1 µm				
Sound Emission*		54.8 dBA	55.0 dBA	57.5 dBA	58.0 dBA	
Light Intensity	LED Lamp	1390 lux	1250 lux	1480 lux	1381 lux	
	UV Lamp	253.7 nm				
Electrical Requirements**	Nominal Power Consumption	167 W	178 W	285 W	315 W	
	Heat Load	570 BTU/ Hr	607 BTU/ Hr	972 BTU/ Hr	1075 BTU/ Hr	
	Full Load Amps	10 A				
Cabinet Construction	Main body	Electro-galvanized steel with white oven-baked epoxy-polyester Isocide™ antimicrobial powder-coated finish, 1.5 mm / 16 gauge thick				
	Work Zone	Stainless steel Type 304 with No.4 finish, 1.5 mm / 16 gauge thick				
	Side Walls	E Series	UV-absorbing tempered glass, 6 mm, colorless and transparent			
		S Series	1.5 mm 16 gauge stainless steel, type 304, with 4B finish			
Sash Window	UV-absorbing tempered glass, 6 mm, colorless and transparent					
Net Weight		274 kg	330 kg	370 kg	460 kg	
Shipping Weight		302 kg	365 kg	450 kg	489 kg	
Shipping Dimensions, Maximum (W x D x H)		1300 x 960 x 2120 mm	1520 x 960 x 2120 mm	1950 x 960 x 2120 mm	2200 x 960 x 2120 mm	
Shipping Volume Dimensions (W x D x H)		2.3 m <sup>3</sup>	2.8 m <sup>3</sup>	3.5 m <sup>3</sup>	4.0 m <sup>3</sup>	

Disclaimer: Technical Specifications may be subjected to further changes without prior notice.

\*Noise reading in open field condition / anechoic chamber. Noise reading in normal room varies by room size, layout, and background noise, but may reach roughly 3-4 dBA above these values.

\*\*Electrical power consumption is a measurement of new unit with clean filter operated within nominal setpoint. Result per unit may vary.

## Options and Accessories

Anti-blowback Valve	EG Powder Coated	ABBV-10P 5170352	ABBV-10P 5170352	ABBV-10P 5170352	ABBV-10P 5170352
	304 Stainless Steel	ABBV-10S 5170354	ABBV-10S 5170354	ABBV-10S 5170354	ABBV-10S 5170354
Exhaust Collar		ECO-F-LA2EU-3FT G4 517186	ECO-F-LA2EU-4FT G4 517187	ECO-F-LA2EU-5FT G4 517188	ECO-F-LA2EU-6FT G4 517189
Top Box with VHP Out		Top Box, LA2-3-EU G4 with VHP-Out 5171302	Top Box, LA2-4-EU G4 with VHP-Out 5171303	Top Box, LA2-5-EU G4 with VHP-Out 5171304	Top Box, LA2-6-EU G4 with VHP-Out 5171305
Exhaust Collar with VHP Out Port		ECO-LA2-3-EU G4 with VHP-Out 5171311	ECO-LA2-3-EU G4 with VHP-Out 5171312	ECO-LA2-3-EU G4 with VHP-Out 5171313	ECO-LA2-3-EU G4 with VHP-Out 5171314
VHP In Port		VHP-IN Port 5170552	VHP-IN Port 5170552	VHP-IN Port 5170552	VHP-IN Port 5170552
Manual Volumetric Exhaust Damper		B2-Damper 5170104	B2-Damper 5170104	B2-Damper 5170104	B2-Damper 5170104
UV Lamp		UV-15A-L 5170251	UV-30A-L 5170255	UV-30A-L 5170255	UV-30A-L 5170255
IV Bar		IV-910 5170499	IV-1215 5170231	IV-1520 5170500	IV-1825 5170501
Prefilter		PF-41 5090061	PF-42 5090062	PF-43 5090063	PF-44 5090064
Electrical Outlet	Direct Mounted	EO-HC 5170035			
Service Fixtures	EU SF-Gas-20 mm	SF-1G20 5170410			
	Solenoid Valve	SOLENOID VALVE FITTING FOR LA2-EU 5075239			
	EU SF-Vacuum-20 mm	SF-1V20 5170457			
	EU SF-Air-20 mm	SF-1A20 5170502			
	EU SF-Nitrogen-20 mm	SF-1N20 5170503			
	EU SF-Water-20 mm	SF-1W20 5170458			
	US SF-Universal-20 mm	SF-2U22 5170504			
	Copper Piping for SF	CU-Pipe 5170026			
	SPEU-A & SPEU-B	Support Stand 71 cm Height	SPEU-3A0 5131343	SPEU-4A0 5131344	SPEU-5A0 5131455
Support Stand 91 cm Height		SPEU-3B0 5131457	SPEU-4B0 5131458	SPEU-5B0 5131459	SPEU-6B0 5131460
Stainless Steel Pipette Storage Shelf	5260327				
Arm Rest Padding	MEWREST 5170127				
Foot Rest	FT-REST 5170492				
Laboratory Chair	ME-LD-AR360 1150006				
IQQQ Protocol	9010179				



# ESCO

LIFESCIENCES GROUP

*Improving Lives through Science*

## ESCO SCIENTIFIC



- Animal Research Workstation
- Biological Safety Cabinet
- CO<sub>2</sub> Incubator
- Ducted Fume Hood
- Ductless Fume Hood
- Filtered Storage Cabinet
- Laboratory Centrifuge
- Laboratory Oven and Incubator
- Laboratory Refrigerator and Freezer
- Laboratory Shaker
- Laminar Flow Cabinet
- PCR Cabinet
- Powder Weighing Balance Enclosure
- Thermal Cycler
- Ultra-low Temperature Freezer

## ESCO MEDICAL



- Time-Lapse Incubator
- Benchtop Incubator
- ART Workstation
- CO<sub>2</sub> Incubator
- Anti-Vibration Table
- Gas Analyser

## ESCO Healthcare

"Discovery to Delivery"



Pharmaceutical Manufacturing, Pharmacy Compounding, and Bioprocessing Tools


## ESCO ASTER



CRDMO Services

# ESCO LIFESCIENCES GROUP

42 LOCATIONS IN 21 COUNTRIES ALL OVER THE WORLD



- 📍 Global Offices
- 📍 Licensee
- 📍 Distributors
- 📍 Factories
- 📍 R&D Centers
- 📍 Regional Distribution Centers

Follow us on social media, download our apps,  
and scan the QR code for more info.



@EscoLifesciences



@EscoLifesciences



@EscoLifesci



@Esco



@EscoLifesciences



@EscoLifesciences



Esco Lifesciences



Esco Lifesciences

# ESCO

LIFESCIENCES GROUP

Esco Micro Pte. Ltd. • 19 Changi South Street 1 • Singapore 486779  
Tel +65 6542 0833 • mail@escolifesciences.com  
www.escolifesciences.com

Esco Technologies, Inc. • 903 Sheehy Drive, Suite F, Horsham, PA 19044, USA  
Tel: +1 215-441-9661 • eti.admin@escolifesciences.com

Esco Lifesciences Group Offices: Bangladesh | China | Denmark | Germany | Hong Kong | India | Indonesia | Italy | Japan | Lithuania  
| Malaysia | Myanmar | Philippines | Russia | Singapore | South Africa | South Korea | Taiwan | Thailand | UAE | UK | USA | Vietnam

9010627\_1A2-EU\_Labculture Plus Gen 4-BSC-A4\_VA\_071624

Esco can accept no responsibility for possible errors in catalogues, brochures and other printed materials. Esco reserves the right to alter its products and specifications without notice. All trademarks and logotypes in this material are the property of Esco and the respective companies.